

# OASIS LegalXML Member Section Electronic Court Filing Technical Committee DRAFT Electronic Court Filing 1.1 Proposed Standard

## Document Number

12072002CF1.1r1

## Current Version Date

12 July 2002

## Previous Version(s)

## Workgroup Information

Workgroup Name: JTC/OASIS LegalXML Member Section Electronic Court Filing Technical Committee

Workgroup Co-Chairs: John Greacen, Mary McQueen

Workgroup Mailing List: [legalxml-court filing@lists.oasis-open.org](mailto:legalxml-court filing@lists.oasis-open.org)

Workgroup Mailing List Archive: None

## Document Author(s)

Marty Halvorson ([martyh@nmcourts.com](mailto:martyh@nmcourts.com))

## Document Editor(s)

Roger Winters ([roger.winters@metrokc.gov](mailto:roger.winters@metrokc.gov))

Robin Gibson ([robin\\_gibson@osca.state.mo.us](mailto:robin_gibson@osca.state.mo.us))

## Short Statement of Status

Draft being recommended for Proposed Standard status.

## Abstract

This Draft Specification provides the XML DTD required for Court Filing updated in light of agreements specified in "Principles of XML Development for Justice and Public Safety," August 28, 2001, and as is detailed in the "LegalXML Standards Development Project: Horizontal Elements Draft Standard," [November 28, 2001,

<http://www.jointcourtxmlstandard.org/xml/JjntXmlStandard.nsf/516c7664fda1528a862565ec00504473/dfd5bf88d59c73bd86256b1400536399?OpenDocument>].

## Status of Document

This is an OASIS LegalXML Member Section Electronic Court Filing Technical Committee Draft Specification for submission and review by the JTC and interested members.

Table of Contents

1 Introduction..... 2

1.1 Conventions..... 3

1.1.1 Visual Indicators ..... 3

1.2 Document Description..... 3

1.3 Assumptions and Requirements ..... 3

1.4 Terminology..... 4

1.5 Date and Time Format..... 5

1.6 Authentication..... 6

1.7 White Space Treatment..... 6

1.8 Extensions ..... 6

2 DTD..... 6

2.1 Transmission Encapsulation..... 6

2.1.1 Elements Particular to legalEnvelope ..... 7

2.2 courtFiling ..... 8

2.2.1 filing ..... 8

2.2.2 confirmation..... 10

2.2.3 query ..... 11

2.2.4 response..... 12

2.3 Common to courtFiling..... 12

2.4 Horizontal to Legal ..... 14

2.4.1 Elements Common to Law, Safety, and Justice XML..... 14

2.4.2 Elements Common to Legal XML..... 27

2.5 Elements for specific case types ..... 29

3 Appendices..... 30

3.1 Statement of Intent..... 30

3.2 Examples ..... 31

3.3 Query and Response..... 31

3.4 User Descriptions ..... 31

3.4.1 Attorneys ..... 31

3.4.2 Judicial Officer and Staff ..... 31

3.4.3 Clerk of Court ..... 31

3.4.4 Clerk Staff ..... 31

3.4.5 Super User..... 31

4 Change History ..... 32

5 Attachment I—Electronic Court Filing 1.1 DTD..... 33

**1 Introduction**

This document is intended to describe the information required for electronic court filing and the structure of that information. No information regarding the content of any pleading or other legal devices (e.g., contracts, orders, judgments) is included, other than what is required to accomplish the intended task.

This document is a Proposed Standard collaboratively developed by the COSCA/NACM<sup>1</sup> Joint Technology Committee and the OASIS LegalXML Member Section Electronic Court Filing Technical Committee. Portions of this document were derived from the “Court Filing Straw Man,” collaboratively developed by the U.S. District Court for the District of New Mexico, New Mexico Administrative Office of the Courts, SCT Global Government Solutions, Inc., and West Group.

This specification is the product of a consensus process. Many items covered by the standard attracted valuable inputs from multiple viewpoints. The views about items were often not identical. When resolution of items needed to be reached, discussion on proposed resolutions were closed only when the question “Is there anyone cannot live with this?” was answered in the negative.

---

<sup>1</sup> Conference of State Court Administrators/National Association for Court Management.

## 1.1 Conventions

Within this document the term "shall" is used to describe mandatory items. The term "may" is used to describe optional items.

This proposed standard conforms to the XML 1.0 Specification (<http://www.w3.org/TR/REC-xml.html>).

### 1.1.1 Visual Indicators

In the following sections, different fonts are used to identify the meaning of the term. Except within the Document Type Definition (DTD), the font size is 10 point.

The Arial font identifies the names of elements and attributes.

A **Bold** font, whether in **Arial** or **Times New Roman**, is used for emphasis or to identify the beginning of a definition.

`Courier New` identifies DTD text. It is also used, when enclosed in quotation marks, to indicate user-supplied attribute values or other strings, including attribute values. The font size for the entirety of the DTD is reduced to 8 point.

## 1.2 Document Description

This document includes a DTD to be used to validate the syntax of XML documents used for court filing. Annotations appearing inside the DTD, which add further definition and specification, shall be binding.

Appendices are non-normative and may contain well-formed, validated examples. Where conflict arises between an example and the DTD or the body of this document, the body or DTD shall be deemed normative and ruling.

An additional non-normative appendix shall be added to this specification prior to its reaching the status of a recommendation. It shall contain minority opinions for any items where there was significant disagreement. Links to and from the affected sections within this specification may be created and maintained. This is to support future developers and maintainers by giving them insight into the different viewpoints that were involved in reaching this consensus.

## 1.3 Assumptions and Requirements

1. The three-tier application model is assumed, including three cooperating applications: A) The application on the user's desk, known as the Electronic Filing Provider (EFP), the client; B) the Electronic Filing Manager (EFM), the server; and C) the Case Management System (CMS).
2. This document, with a few exceptions, does not specify how any of the three cooperating applications would function. Rather, it defines the data elements and data tags for use in such applications.
3. Any EFM application shall have the capability to return an electronic acknowledgment to a filer.
4. The DTD is intended to support both the filing of a pleading initiating a new case and the filing of one or more documents in existing cases.
5. The DTD is designed to include all data elements needed by any court. However, any court, as a matter of local policy, may limit the data it will accept in an electronic filing. In particular, a court may refuse to accept:
  - more than one filing in a single envelope,
  - a pleading or other document that initiates a case,
  - payments associated with a filing, or
  - hypertext links to documents residing elsewhere.
6. This document differentiates between docketing and filing of received documents, whether pleadings, orders, or notices (see 1.4 Terminology, pages 4 and 5).
7. There is no state maintained at the server between requests for a particular user connection, i.e., data is not kept by the server between transactions.

8. There will exist a method by which the user identity can be verified.
9. Extraneous data is discouraged. That is, only the information required for successful completion of the filing transactions should be included.
10. Certain XML document elements are assumed to have their content protected from public view. Other protected data shall be explicitly marked.
11. Tags have been chosen to provide a neutral name where the definition of what some might consider a more appropriate term could vary. For example, in some courts the "filer" is the attorney, in others the "filer" is a party to the case.
12. The DTD is designed to support the inclusion of multiple filings in a single submission for the same case.
13. There is no intent to require multiple packets per individual task. For example, a user asking the system to provide a list of all cases with which the user is associated, in order to choose the case for which a pleading is going to be submitted, would require a single exchange of packets: one packet to make the request, the second packet to supply the answer.

## **1.4 Terminology**

### **1. application**

A generic term used to identify a cooperating system (e.g., EFP, or EFM, or CMS).

### **2. authentication**

The process of verifying the identity of the user or filer. This process may reside in either the EFP or the EFM. In either case, authentication data is to be included in every envelope.

### **3. binary document**

A document that contains binary characters. Binary documents are often in a proprietary format (e.g., PDF file, Word document, WordPerfect document). This may also be called a "BLOB" (Binary Large Object). It may include XML that is non-normative (to this standard).

### **4. CMS (Case Management System)**

Software that records and manages court cases, records, calendars, financial transactions, and other information. Depending on the implementation, this could include more than one application.

### **5. CMS/DMS**

Case Management System with an embedded Document Management System. Depending on the implementation, this could be a single application.

### **6. document**

- a. An XML document instance.
- b. One or more electronic pleadings or other court devices that can be contained within an XML document or XML envelope.

### **7. docket entry**

The recording in a docket or register of actions of a filing, event, or activity that the court makes part of its official record.

### **8. docketing**

The process invoked when a CMS receives a pleading, order, or notice, when no errors in transmission or in presence of required content have occurred, and when the pleading, order, or notice is recorded as a part of the official record.

### **9. DMS (Document Management System)**

A DMS manages, retrieves, and stores documents electronically.

### **10. DTD (Document Type Definition)**

A DTD is used to define the structure (elements and attributes) of an XML document. For a complete overview, see the XML 1.0 Specification (<http://www.w3.org/TR/REC-xml.html>).

### **11. EFM (Electronic Filing Manager)**

An Electronic Filing Manager (or Management system) is middleware that receives, presents, and manages electronic filings; the EFM is also considered a server in the electronic filing process.

**12. EFP (Electronic Filing Provider)**

An EFP is a front-end application that prepares and submits filings. The EFP is the application on the filer's side of the electronic filing architecture, and it is also called the client.

**13. electronic filing**

Documents and data submitted to the court electronically by means of an XML based protocol.

**14. filing**

The set of electronic documents and associated metadata included in a submission intended to be docketed by the court. This document or collection of documents is either accepted or rejected by the court. It should be noted that, in some courts, "filing" means acceptance of a packet of associated documents. "Filing" is understood as opposed to "docketing," which is the recording in a docket or register of actions of a filing, event, or activity that the court makes part of its official record

**15. filing data**

All data that is necessary to provide a useful and complete electronic filing and to support electronic access.

**16. filing metadata**

Data about the documents within a filing. For every electronic submission, metadata flows from an EFP into a CMS/DMS.

**17. party**

For the purposes of this document, "party" refers only to those persons directly affected by the outcome of the court case: defendants, plaintiffs, etc. In particular, judges and attorneys representing the parties are not considered parties to the case.

**18. place holder**

An element name reserved for future expansion of the standard.

**19. submission**

A filing or group of filings delivered to the court.

**20. user**

The person sitting at the keyboard of the remote machine, i.e., who is preparing and submitting a filing.

**1.5 Date and Time Format**

In the specifications for date and time, optional parts are denoted by square brackets ('[' and ']'). Options may nest such that, e.g., date can be any of CCYY, CCYY-MM, or CCYY-MM-DD. Specifically, the form CCYY-DD is not allowed.

Document times and dates follow the standards set by ISO 8601 (the ISO standard for numerical date/time interchange formats). Specifically, dates shall be expressed using the Gregorian Calendar and the form "CCYY[-MM[-DD]]". For example, "1999-01-02" represents "2 January 1999". All components shall be zero-padded to two digits.

Times shall be expressed in local time only, using the one of the following forms:

hh[:mm[:ss[.ttt]]]-hh[:mm]  
hh[:mm[:ss[.ttt]]]-hh[:mm]  
hh[:mm[:ss[.ttt]]].

All components shall be zero-padded to two digits.

For example, "22:04:38.015-07" represents "thirty-eight and 15 thousands seconds after 10:04 PM Mountain Standard Time".

Periods of time will conform to ISO 8601. Duration shall be expressed in one of the following ways:

a) As a period delimited by a specific start and end times. :

A solidus (aka slash, "/" ) shall be used to separate the start time from the end time. Start time and end time shall conform to the ISO 8601 form shown above.

For example, "14:00/16:00" indicates a period of two hours beginning at 2:00 PM local time.

b) As a quantity, expressed as follows:

PnYnMnWnDTnHnMnS - The format is interpreted as follows: "P" introduces the string as a quantity of time, "T" introduces a time period (i.e., a number of hours, minutes, and seconds), and "n" in all uses denotes a number. "Y" denotes years, "M" denotes months, "W" denotes weeks of the year, "D" denotes days, "H" denotes hours, "M" denotes minutes, and "S" denotes seconds. The first week of a new year is the week that has the majority of its days in the new year. All elements of the period are optional with the exception of the leading "P".

Examples are:

"P2Y10M15DT5H12M" is a period of 2 years, 10 months, 15 days, 5 hours, and 12 minutes.

"PT2H30M" is a period of 2 hours and 30 minutes.

## 1.6 Authentication

Authentication is shown with place holders only.

It is assumed that HTTP basic authentication is provided, and therefore, username and password data elements are provided.

## 1.7 White Space Treatment

It is often convenient to use "white space" (spaces, tabs, and blank lines) to set apart the markup for greater readability.

Court filing XML processors may:

1. Discard leading and trailing white space contained within any element content returned to the sender in a confirmation message, e.g., the `messageID`.
2. Convert strings of white space characters into a single space character (#x20) contained within any element or attribute content returned to the sender in a confirmation message.

Court filing XML processors shall discard leading and trailing white space contained within any attribute content returned to the sender in a confirmation message, e.g., `refersTo`.

## 1.8 Extensions

Extensions are allowed to this standard. All extensions shall be readily identifiable by conforming applications. Conforming applications that do not understand the extension may ignore the extended element and its content.

Extensions shall be identified by the appearance of an underscore character, "\_", at the end of the new element name. Following the underscore, there shall be a series of characters identifying the individual or organization creating the extension.

For example, `goodKarma_NMAOC` has an element name `goodKarma`, and the creating organization is the New Mexico Administrative Office of the Courts (NMAOC).

## 2 DTD

The DTD has made available at the end of this document in Attachment I.

### 2.1 Transmission Encapsulation

Each filing, confirmation, query, or response is encapsulated in a standard "shell" called a `legalEnvelope`. This shell includes such information as the identity of the sender, the recipient, the time and date the message was created, and the `messageIdentification`.

The receiving application may discard all of the parent elements and any child elements of the `legalEnvelope` element, with the exception of the `legal` element and its children. That is, the receiver may discard the transmission encapsulation.

### 2.1.1 Elements Particular to `legalEnvelope`

**legalEnvelope** is the root element of Electronic Court Filing XML for the purpose of transmission. This element has an attribute specifying the version number as 1.1. If this attribute is present, it must be 1.1. If absent, is assumed to be 1.1 (for the version described in this document).

```
<!ELEMENT legalEnvelope (messageIdentification, to, from, cc?, bcc?,
    replyTo?, memo*, creation, dataIntegrity?, paymentInformation?,
    authentication?, legal)>
<!ATTLIST legalEnvelope version CDATA #FIXED "1.1">
```

**messageIdentification** is a string used by the sending application to identify the message.

`messageIdentification` shall have the same value in a `confirmation` or `response` message as in the corresponding `filing` or `query` message.

```
<!ELEMENT messageIdentification (#PCDATA)>
```

**to** identifies the recipient of this transmission.

Courts may specify that **to** does not satisfy the requirement for a certificate of service.

```
<!ELEMENT to (addressee+)>
```

**from** identifies the sender, and may provide the information needed to send a `confirmation` or `response`.

```
<!ELEMENT from (sender)>
```

**replyto** supplies the information of where to send the `confirmation` or `response`. If not present, the `from` element shall be used to send the `confirmation` or `response`.

```
<!ELEMENT replyTo (sender)>
```

**cc** identifies others receiving this transmission. This is a courtesy copy (also called a “carbon copy”) only and no official action is required or expected. The `addressee` will appear on the distribution list.

```
<!ELEMENT cc (addressee+)>
```

**bcc** identifies others receiving this transmission. This is a blind courtesy copy only and no official action is required or expected. The `addressee` for the blind courtesy copy will not appear on the distribution list.

```
<!ELEMENT bcc (addressee+)>
```

The **addressee** element supplies information necessary to identify receivers, their respective delivery addresses, and the corresponding delivery methods.

```
<!ELEMENT addressee ((personName | entity)?,(postalAddress | email | fax |
    uri))>
```

The **sender** element supplies information necessary to identify senders, their respective return addresses, and the corresponding delivery methods.

```
<!ELEMENT sender ((personName | entity)?,(postalAddress | email | fax |
    uri))>
```

**creation** identifies the date and time this envelope was created.

```
<!ELEMENT creation (dateTime)>
```

**dataIntegrity** is a place holder for the method used to validate the integrity of a message’s content.

```
<!ELEMENT dataIntegrity ANY>
```

**legal** is a generic tag preceding all legal-related XML. In other legal DTDs, **legal** will have a different content model.

```
<!ELEMENT legal (courtFiling)>
```

## 2.2 courtFiling

**courtFiling** allows multiple filings. Each filing consists of a single lead document for one case in one court, with any number of attached documents. **courtFiling** allows, but does not require, multiple confirmations in response to a single filing. Each confirmation represents the response to one filing.

In version 1.1, **courtInformation** and **caseInformation** shall be the same in each filing included within a single **legalEnvelope**.

A court's policy (as expressed in its "Court Policy XML") may limit a **courtFiling** to one filing element per **legalEnvelope**.

```
<!ELEMENT courtFiling (filing+ | confirmation+ | query | response)>
```

### 2.2.1 filing

**filing** specifies one filing for one case in one court with multiple documents. The attribute **privacy** may be used as a request to the court, or as an assignment made by the court.

The sender assigns ID attribute values within a **filing**. The receiving application shall return all applicable IDs with the confirmation message that is to be sent as a result of the filing.

```
<!ELEMENT filing (actor+, filingInformation, leadDocument)>
  <!ATTLIST filing privacy CDATA #IMPLIED>
```

**filingInformation** contains all information not necessarily expected to be found in the document. The **id** attribute shall be returned in the confirmation message sent as a result of this transmission. The **privacy** attribute has the same meaning as in **filing**.

```
<!ELEMENT filingInformation (specialHandling?, paymentInformation*,
  authentication*, courtInformation, caseInformation, actor*,
  courtEvent*, memo?)>
  <!ATTLIST filingInformation id ID #REQUIRED
    filingInformation privacy CDATA #IMPLIED>
```

A sender may use **specialHandling** to request user intervention by the receiving court.

```
<!ELEMENT specialHandling (#PCDATA)>
```

**leadDocument** is the single document that comprises the lead document (e.g., a Motion, Order) of a single filing. Each lead document may have multiple attached documents. The **id** attribute shall be returned in any confirmation message sent as a result of this transmission.

```
<!ELEMENT leadDocument (documentInformation, documentContent, attachment*,
  authentication*)>
  <!ATTLIST leadDocument id ID #REQUIRED>
```

**documentInformation** contains the same information that is normally included in the text of the document being filed.

Information appearing in both **filingInformation** and **documentInformation** shall be by reference only. The preferred location for content to reside is **filingInformation**. A reference pointing from **documentInformation** to an **id** in **filingInformation** shall be the preferred markup and offers the largest opportunity for reuse. A reference from **filingInformation** to an **id** in **documentInformation** is also allowed but not recommended. A deprecated use, but not an error, occurs if content is included in both places.

That is to say, this implements the "where practical" model.

## Electronic Court Filing Draft Specification

```
<!ELEMENT documentInformation (actor+, submitted, documentDescription,  
    (administrativeLaw | appeals | bankruptcy | civil | criminal |  
    domesticRelations | juvenile | probate | smallClaims | traffic)?,  
    matter*, causeOfAction*)>
```

**submitted** supplies the date and time the author created the document being filed.

Note that this **date** and **time** are not necessarily the same as those specified in the **creation** element.

```
<!ELEMENT submitted (dateTime)>
```

**documentDescription** provides the title of the document assigned by the author, and the court-specified type of document.

```
<!ELEMENT documentDescription (documentTitle, documentType*)>
```

**documentTitle** is the name given to the document by the author.

```
<!ELEMENT documentTitle (#PCDATA)>
```

**documentType** is the court specified name assigned by the court specified in **courtInformation**. Those courts that don't want to do a reverse look-up on the textual **documentType** to retrieve an event code may require the **documentCode** attribute.

```
<!ELEMENT documentType (#PCDATA)>  
    <!ATTLIST documentType documentCode CDATA #IMPLIED>
```

All of the following elements, which deal with the specific requirements of a particular type of case, are place holders. It is expected that the various working groups will define the content model for each element.

In 2.3 Common to courtFiling (page 12) and in 2.5 Elements for specific case types (page 29), a number of elements have been defined that may be used inside these case types. Where a court identifies a requirement for one of these elements, the elements defined in "Common to courtFiling" or "Elements for specific case types" shall be used. Where a court identifies a requirement not included in these elements, the court may itself define an element to support that requirement. It must be understood that the Electronic Court Filing Technical Committee will provide a full set of elements intended to meet requirements that are not now defined.

```
<!ELEMENT administrativeLaw ANY>  
<!ELEMENT appeals ANY>  
<!ELEMENT bankruptcy ANY>  
<!ELEMENT civil ANY>  
<!ELEMENT domesticRelations ANY>  
<!ELEMENT probate ANY>  
<!ELEMENT smallClaims ANY>  
<!ELEMENT traffic ANY>
```

The **criminal** and **juvenile** case types include information related to the identification of the accused person, the charge(s) against that person, whether bail has been posted, where the booking occurred, whether that person is in custody, and what incident precipitated the apprehension of that person.

```
<!ELEMENT criminal (identification, charge+, bail?, booking?, custody?,  
    incident*)>  
<!ELEMENT juvenile (identification, charge+, bail?, booking?, custody?,  
    incident*)>
```

**documentContent** can be a hyperlink, text, or a Base 64 encoded "Binary Large Object" (BLOB). It may be divided into parts, using the **part** element.

A given court's policy (see "Court Policy XML") may prohibit the use of hyperlinked documents.

The **id** attribute shall be referenced in the confirmation of this filing. The **size** attribute may be used to indicate the size, in bytes, of the encapsulated “BLOB.” The **mimeType** attribute specifies how the contents of the decoded PCDATA are to be interpreted (e.g., `application/PDF`). All binary code in version 1.1 of this standard shall be Base 64 encoded. The attribute **contentEncoding** allows for future revisions. The **href** attribute specifies the location of a hyperlinked document.

```
<!ELEMENT documentContent (#PCDATA | part)*>
  <!ATTLIST documentContent id ID #REQUIRED
    size CDATA #IMPLIED
    mimeType CDATA #REQUIRED
    contentEncoding (Base64) #IMPLIED
    href CDATA #IMPLIED>
```

The **part** element is used to divide document content into multiple parts. The **number** attribute provides an index, or ordering, to the various pieces of `documentContent`.

```
<!ELEMENT part (#PCDATA)>
  <!ATTLIST part number CDATA #REQUIRED>
```

An **attachment** may have additional attached documents. The **id** shall be referenced in the confirmation of this filing.

```
<!ELEMENT attachment (attachmentDocumentInformation, documentContent,
  authentication*, attachment*)>
  <!ATTLIST attachment id ID #REQUIRED>
```

The only difference between an **attachmentDocumentInformation** and a `documentInformation` is that **actor** becomes zero or more instances, i.e., **actor\***. This allows **actor** to span the entire set of documents included within a single `leadDocument`.

```
<!ELEMENT attachmentDocumentInformation (actor*, submitted,
  documentDescription, (administrativeLaw | appeals | bankruptcy |
  civil | criminal | domesticRelations | juvenile | probate |
  smallClaims | traffic)?, matter*, causeOfAction*)>
```

## 2.2.2 confirmation

**confirmation** shall be used to return the confirmation of a filing to the sender. It is not an error for a conforming EFM to send multiple confirmation messages in response to a single filing message, e.g., the first **confirmation** indicates a lead document disposition of **deferred** followed by a second confirmation message with a lead document disposition of **accepted**.

```
<!ELEMENT confirmation (actor*, timeStamp, confirmationInformation)>
```

**confirmationInformation** corresponds to `filingInformation` in the received filing. The attribute **refersTo** shall be identical to the `filingInformation` id.

The attribute **filingDisposition** enumerated values are defined as follows:

**“transmissionError”**: The terminating element for the transmission, i.e., `</legalEnvelope>`, was not received. The transmission was incomplete or the network transport layer reported an error in transmission.

**“acknowledged”**: Transmission was received with no errors in transmission. No action relating to the message has been taken.

```
<!ELEMENT confirmationInformation (fee*, courtInformation?,
  caseInformation?, actor*, leadDocumentDisposition+, courtEvent*)>
  <!ATTLIST confirmationInformation refersTo CDATA #REQUIRED
    filingDisposition (transmissionError | acknowledged) #REQUIRED>
```

**leadDocumentDisposition** corresponds to the leadDocument submitted. The attribute **refersTo** shall be identical to the leadDocument id.

The attribute **filingDisposition** enumerated values are defined as follows:

**"transmissionError"**: The terminating element for the transmission, i.e., `</legalEnvelope>`, was not received. The transmission was incomplete or the network transport layer reported an error in transmission.

**"acknowledged"**: Transmission was received with no errors in transmission. No action relating to the message has been taken.

**"received"**: Filed. The transmission was received without error and a time stamp was generated for the filing. This corresponds to the manual system of the court clerk stamping the document at the court counter.

**"accepted"**: Docketed. The transmission was received without error, a time stamp was generated, and the filing was recorded in the case docket. This corresponds to the action of the clerk of court recording filing information into the official record, that is, what many call a "docket entry." See Terminology, page 4, for the definition.

**"partial"**: Part of filing was docketed. The leadDocument was docketed but one or more of the attachments were not, due to a conformance error.

**"deferred"**: Transmission was received OK, errors were checked, the filing was validated against the DTD, but no further action was taken. The formal response will be included in a separate later transmission.

**"rejected"**: The court refused to accept the filing.

```
<!ELEMENT leadDocumentDisposition (timeStamp, courtDocumentReference,
    memo?, attachmentDisposition*)>
    <!ATTLIST leadDocumentDisposition refersTo CDATA #REQUIRED>
    <!ATTLIST leadDocumentDisposition filingDisposition (transmissionError |
        acknowledged | received | accepted | partial | deferred |
        rejected) #REQUIRED>
```

**courtDocumentReference** is the court specified document reference. The court may use the attribute **href** to return the location of the electronically filed document.

```
<!ELEMENT courtDocumentReference (#PCDATA)>
    <!ATTLIST courtDocumentReference href CDATA #IMPLIED>
```

**attachmentDisposition** corresponds to any attachments submitted with the filing. The attribute **refersTo** shall be identical to the id of the attachment element in the submitted filing.

The attribute **disposition** enumerated values are defined as follows:

**"received"**: Filed. The transmission was received without error and a time stamp was generated for the filing. This corresponds to the manual system of the court clerk stamping the document at the court counter.

**"accepted"**: Docketed. The transmission was received without error, a time stamp was generated, and the filing was recorded in the case docket. This corresponds to the action of the clerk of court recording filing information into the official record, that is, what many call a "docket entry." See Terminology, page 4, for the definition.

**"rejected"**: The court refused to accept the filing.

```
<!ELEMENT attachmentDisposition (courtDocumentReference)>
    <!ATTLIST attachmentDisposition refersTo CDATA #REQUIRED>
    <!ATTLIST attachmentDisposition disposition (received | accepted |
        rejected) #REQUIRED>
```

### 2.2.3 query

**query** is defined in a separate document. Thus, **query** is a place holder. **query** shall be used to request court specific policy and allowable values of court supplied information.

```
<!ELEMENT query ANY>
```

## 2.2.4 response

**response** is defined in a separate document. Thus, **response** is a place holder. **response** shall be used to return information requested by a **query** message.

```
<!ELEMENT response ANY>
```

## 2.3 Common to courtFiling

All the elements in **actor** are optional to allow for EMPTY **actor** elements that reference a complete **actor** element that appears earlier in the document. The same actor may be mentioned many times within a filing. To eliminate redundancy, the content of the first **actor** element for a particular actor shall have a fully defined content. This fully defined **actor** shall occur in filing. Subsequent references to this **actor** shall use an empty **actor** element with a **reference** attribute pointing to the id of the fully defined **actor** element. The attribute **refersTo** shall be used when the element being referred to is not contained within the particular filing transmission, e.g., **refersTo** when sent as part of a **confirmation** would refer to the **actor** attribute **id** as already specified by the sender in the **filing**. There can be more than one **actor** in a given document or filing. Where more than one **actor** is possible, the element will be shown as **actor+** or **actor\***. Each **actor** will be defined individually according to these principles.

The attribute **privacy** may be used as a request to the court, or as a court assignment.

**designation** within **actor** is used for disambiguating, i.e., establishing a single grammatical or semantic interpretation for, persons with the same or similar names, and to identify uniquely an entity upon initiation of a case.

```
<!ELEMENT actor (title?, name?, postalAddress*, telephone*, email*, group*,
  personDescription*, designation*, role*, characteristic*)>
  <!ATTLIST actor id ID #IMPLIED
    reference IDREF #IMPLIED>
    refersTo CDATA #IMPLIED>
    privacy CDATA #IMPLIED>
```

This actor's **title**.

```
<!ELEMENT title (#PCDATA)>
```

The **role** played by this actor in this filing.

```
<!ELEMENT role (roleName, roleWith*)>
```

The **roleName**.

```
<!ELEMENT roleName (#PCDATA)>
```

**roleWith** is an EMPTY element used to supply references to other actors and matters. The attribute **actorID** shall be used to match this **actor** with another **actor** within this filing transaction. For example, the attorney/client roles would be defined in this way. The attribute **matterID** shall be used to match this **actor** with a **matter** within this transmission.

```
<!ELEMENT roleWith EMPTY>
  <!ATTLIST roleWith actorID IDREF #IMPLIED>
  <!ATTLIST roleWith matterID IDREF #IMPLIED>
```

**characteristic**, and its children, **characteristicName** and **characteristicValue**, provide a mechanism to define the characteristics of this **actor** that are not defined elsewhere in this document. (NOTE: **personDescription** provides descriptive characteristics that should not be redundantly provided as values for **characteristic**.)

```
<!ELEMENT characteristic (characteristicName, characteristicValue)>
  <!ELEMENT characteristicName (#PCDATA)>
  <!ELEMENT characteristicValue (#PCDATA)>
```

**authentication** shall be used for authenticating the sender or for some other element containing a digital signature.

```
<!ELEMENT authentication ((userIdentification, password?) | signature)>
```

**userIdentification** is the user name or logon identifier being authenticated by the password.

```
<!ELEMENT userIdentification (#PCDATA)>
```

**password** is the secret word known to the user who is identified by **userIdentification**.

```
<!ELEMENT password (#PCDATA)>
```

**caseInformation** includes all the information about the case this filing applies to.

**fullCaseNumber**, and **caseTitle** are optional, so that case initiation could proceed without there having been a prior assignment of a case number. The attribute **id** may be referred to by **lineageCaseNumber** or **filersCaseNumber**. The attribute **newCase** defaults to "false".

The Court Policy may limit **newCase** to "false" if filings that initiate new cases are not accepted as electronic filings.

```
<!ELEMENT caseInformation (fullCaseNumber?, caseTitle?, caseCategory?,
    caseYear?, lineageCaseNumber*, filersCaseNumber?)>
```

```
<!ATTLIST caseInformation id ID #IMPLIED
    newCase (true | false) "false">
```

**fullCaseNumber** includes all qualifiers necessary to completely specify the case within its venue, to fix the court type, court location, category, year, number, etc.

```
<!ELEMENT fullCaseNumber (#PCDATA)>
```

**caseTitle** is court-generated for the case.

```
<!ELEMENT caseTitle (#PCDATA)>
```

**caseCategory** is court-generated: civil, criminal, etc.

```
<!ELEMENT caseCategory (#PCDATA)>
```

**caseYear** identifies the year the case was created. It may be specified either as two or four characters, corresponding to YY or CCYY.

```
<!ELEMENT caseYear (#PCDATA)>
```

**lineageCaseNumber** is a previous case number. It may be used to supply the case number of a case being appealed. The **id** attribute may be used to identify this case elsewhere in the filing. The attribute **referenceCase** shall refer to the encapsulating **caseInformation** id.

```
<!ELEMENT lineageCaseNumber (fullCaseNumber?, caseTitle?, caseCategory?,
    caseYear?, courtInformation?, lineageCaseNumber*)>
```

```
<!ATTLIST lineageCaseNumber id ID #IMPLIED
    referenceCase IDREF #REQUIRED>
```

**filersCaseNumber** is a string used by the originator of the filing to identify the case in the originator's application. The attribute **referenceCase** shall refer to the encapsulating **caseInformation** id.

If present in a filing, **filersCaseNumber** shall be returned in the associated confirmation.

This is most useful in a filing initiating a new case because the court-generated case number is not yet assigned; it is returned in the **confirmation**, that is, as part of an event after the case has been opened.

```
<!ELEMENT filersCaseNumber (#PCDATA)>
```

```
<!ATTLIST filersCaseNumber referenceCase IDREF #IMPLIED>
```

**causeOfAction** is a place holder. The **id** attribute may be used as a referent.

```
<!ELEMENT causeOfAction (#PCDATA)>
```

```
<!ATTLIST causeOfAction id IDREF #REQUIRED>
```

**courtEvent** is used to identify court events, e.g., hearings, appearances, trials. It may be used for when the filer is scheduling the event, e.g., a traffic officer, or when the court is scheduling the event, e.g., a hearing on a motion. The attribute **eventID** may be used to identify the **courtEvent**.

```
<!ELEMENT courtEvent (courtEventType, courtEventReason*,
    courtEventSession+)>
```

```
<!ATTLIST courtEvent eventID CDATA #IMPLIED>
```

**courtEventType**, **courtEventReason** provide definition of the event. For example, **courtEventType** could be "Hearing", and **courtEventReason** could be "Consider plaintiff's motion for summary judgment".

```
<!ELEMENT courtEventType (#PCDATA)>
```

```
<!ELEMENT courtEventReason (#PCDATA)>
```

**courtEventSession** provides the date and time, the expected duration, the actor+ (attendees), and the location of the **courtEvent**.

The attribute **eventID** may be used to identify which **courtEvent** if there is more than one **courtEventSession**.

```
<!ELEMENT courtEventSession (dateTime, duration?, actor+,
    courtInformation)>
```

```
<!ATTLIST courtEventSession eventID CDATA #IMPLIED>
```

**courtInformation**, and its children, **courtType** and **courtName**, provide the court's identifying information. **courtType** is specified by the court. **courtName** is a sender-assigned value. Courts may ignore the content of **courtName**.

```
<!ELEMENT courtInformation (physicalLocation, courtType, courtName?)>
```

```
<!ELEMENT courtType (#PCDATA)>
```

```
<!ELEMENT courtName (#PCDATA)>
```

**matter** is a place holder. The **id** attribute may be used as a referent.

```
<!ELEMENT matter ANY>
```

```
<!ATTLIST matter id ID #IMPLIED>
```

**memo** provides human readable text, ignored by applications.

```
<!ELEMENT memo (#PCDATA)>
```

**timeStamp** contains the date and time a filing was received by a court.

```
<!ELEMENT timeStamp (dateTime)>
```

## 2.4 Horizontal to Legal

The elements described in this section are considered applicable across, or "horizontal" to, all types of legal documents, including court filings.

When discrepancies between element content models in this standard and the "Horizontal" standard element content models exist, this standard applies.

### 2.4.1 Elements Common to Law, Safety, and Justice XML

These elements are the result of the Department of Justice effort to reconcile XML standards in the justice area. The results, documented in the "Horizontal Elements Draft Standard," are included, with some appropriate and necessary changes, in this Electronic Court Filing Standard, Version 1.1.

Not all elements specified by the reconciliation effort have been included in Electronic Court Filing 1.1. Some of the elements specified in the draft horizontal standard have been modified to meet Court Filing requirements. These modifications are noted where this has occurred.

### 2.4.1.1 Common attributes

All elements defined as common to law, safety, and justice applications have seven attributes in common. They are: **id**, **type**, **status**, **referenceDate**, **codeValue**, **codeSource**, and **codeLiteral**. The common attributes are not shown in the DTD content models provided for the descriptions below.

The common to law, safety, and justice elements each have specific content models. As provided for in the approved data dictionary of these elements, specific applications may have different content models than those contained in the data dictionary. There are a number of elements in Electronic Court Filing 1.1 that are different than those in the common to law, safety, and justice data dictionary.

With some exceptions, as noted, the attributes are all CDATA with IMPLIED content. That is, in all but a few cases these attributes are optional (#IMPLIED) and not required. The places where the attributes are required are noted by the notation #REQUIRED, or, where a default value exists, the attribute default value replaces the notation for optional. Where common attributes are shown in the specification, it is usually the case that not all common attributes are shown. In these cases, the trailing angle bracket (“>”), required by XML rules, may or may not be shown. **id** provides a means to identify a specific element in an XML document.

**type** provides a means to describe the type of information being described, e.g., for **agencyID**, the **type** attribute describes the type of agency.

**status** provides a place to describe the status of this information, e.g., for **residence**, the **status** attribute describes whether this is a current or previous address.

**referenceDate** identifies the date on which the status was known to be accurate, e.g., a **residence** status of “current” and a **referenceDate** of “1998-11-01” would mean the residence information was known to be accurate three years ago. It shall conform to the date format specified in this document.

**codeSource**, **codeValue**, and **codeLiteral** are used to identify the appropriate source, along with both the coded and literal forms of the data conforming to their usage in appropriate other standards. The **codeSource** attribute defaults to the name of the appropriate standard for those elements that are making use of values obtained from that external standard. For example, the element **hairColor** requires the use of the literal form of values defined by the NCIC-2000 Code Manual. Thus, **codeSource** in this case is “NCIC-2000”.

**codeValue** would be the code specified by NCIC-2000 Code Manual. Since the element is required to contain a literal value from the NCIC-2000 Code Manual, the **codeLiteral** attribute would not be needed.

### 2.4.1.2 Element Content Models

#### 2.4.1.2.1 Elements for Locations and Addresses

**postalAddress** is a postal location to which paper mail could be directed. The attribute **type** identifies the type of mailing address, e.g., “home”, “business”, “school”. The attribute **status** indicates the address’s status, e.g., “current”, “last”, “previous”. The attribute **referenceDate** indicates the last date the address was (is) considered to be valid.

```
<!ELEMENT postalAddress (addressLine*, city?, county?, state?, postalCode?,
country?, addressFull?)>
```

**addressLine** provides text address lines, and may include alternative text for locations that don't have a postal address system. **addressLine** elements shall be sequenced in the order they would appear on an address label. The attribute **type** may be used to identify context of the address line, e.g., a firm name, an organization name.

```
<!ELEMENT addressLine (#PCDATA)>
```

**city** contains the name of a city, town, or township.

```
<!ELEMENT city (#PCDATA)>
```

**county** the name of a county.

```
<!ELEMENT county (#PCDATA)>
```

**state** contains one of three options identifying a state or province. The option used is specified in the **codeSource** attribute. The three options are: (1) U.S. Postal Service ("USPS") two-character state codes are the preferred option. (2) "FBI" standard state codes are the second choice. (3) The "literal" name of the state or province may be used for legacy data that cannot be converted to one of the preferred codes. For this standard, the United States Postal Codes ("USPS") are the default selection.

```
<!ELEMENT state (#PCDATA)>
```

```
<!ATTLIST state codeSource (USPS | FBI | literal) "USPS">
```

**postalCode** provides the zip or postal code.

```
<!ELEMENT postalCode (#PCDATA)>
```

**country** provides the address country. The attribute **codeSource** is defaulted to "ISO 3166" to indicate the required source for the allowed values of this element. The three-character codes shall be used, e.g., "USA".

```
<!ELEMENT country (#PCDATA)>
```

```
<!ATTLIST country codeSource CDATA "ISO 3166"
```

**addressFull** provides an element to contain the full address.

```
<!ELEMENT addressFull (#PCDATA)>
```

**email** provides an electronic mail address. The attribute **type** identifies the type of email address, e.g., "home", "business", "school". The attribute **status** indicates the address's status, e.g., "current", "last", "previous". The attribute **referenceDate** indicates the last date the address was (is) considered to be valid.

```
<!ELEMENT email (#PCDATA)>
```

The element **fax** provides the address for a facsimile telephone number. The attribute **type** identifies the type of fax address, e.g., "home", "business", "school". The attribute **status** indicates the address's status, e.g., "current", "last", "previous". The attribute **referenceDate** indicates the last date the address was (is) considered to be valid.

```
<!ELEMENT fax (telephone)>
```

**physicalLocation** is used to identify physical locations.

```
<!ELEMENT physicalLocation (locationText*, postalAddress?,
    relatedLocation?, locationType?)>
```

**locationText** element holds a textual description of a location. It contains mixed content.

```
<!ELEMENT locationText (#PCDATA | streetNumber | streetName | streetType |
    streetDirection | apartmentNumber | suite | privateMailBox |
    postOfficeBox | buildingName | latitude | longitude)*>
```

For the various parts of the mixed content of **locationText**, the following are the values used in the examples:

```
Nomads
P.O. Box 274
207 North Shelby Street, suite 100
N35.69
W105.94
```

**streetNumber** contains the numeric part of an address, e.g., "207".

```
<!ELEMENT streetNumber (#PCDATA)>
```

**streetName** contains the name of the street, e.g., "Shelby".

## Electronic Court Filing Draft Specification

<!ELEMENT streetName (#PCDATA)>

**streetType** contains the street designation, e.g., "Street", "Drive", "Road".

<!ELEMENT streetType (#PCDATA)>

**streetDirection** contains the orientation or quadrant of the street, e.g., "North", "Southwest".

<!ELEMENT streetDirection (#PCDATA)>

**apartmentNumber** contains an apartment number, e.g., "100".

<!ELEMENT apartmentNumber (#PCDATA)>

**suite** contains a suite number, e.g., "100".

<!ELEMENT suite (#PCDATA)>

**privateMailBox** contains a private mail box number, e.g., "100".

<!ELEMENT privateMailBox (#PCDATA)>

**postOfficeBox** contains a post office box number, e.g., "274".

<!ELEMENT postOfficeBox (#PCDATA)>

**buildingName** contains the name of a building, e.g., "Nomads".

<!ELEMENT buildingName (#PCDATA)>

**latitude** contains the latitude of the location. Use decimal notation to specify latitude, i.e., not minutes and seconds. For example, use "N35.69".

<!ELEMENT latitude (#PCDATA)>

**longitude** contains the longitude of the location. Use decimal notation to specify longitude, i.e., not minutes and seconds. For example, use "W105.94".

<!ELEMENT longitude (#PCDATA)>

The **physicalLocation** child element **locationType** is a coded field that defines locations or facilities. Courts may define acceptable values. When using court-defined values, the attribute **codeSource** shall identify the court defining the value used.

<!ELEMENT locationType (#PCDATA)>

The element **relatedLocation** contains information regarding related locations or facilities. The court may specify acceptable values. When using court-defined values, the attribute **codeSource** shall identify the court defining the value used.

<!ELEMENT relatedLocation (#PCDATA)>

**residence** contains the physical location, with the telephone number, where a person resides.

<!ELEMENT residence (physicalLocation\*, telephone?)>

The **vehicleOwnerAddress** element supplies the address of an owner of a vehicle.

<!ELEMENT vehicleOwnerAddress (physicalLocation)>

The **telephone** element contains the address for a telephone number. The attribute **type** identifies the type of address, e.g., "home", "business", "school". The attribute **status** indicates the address's status, e.g., "current", "last", "previous". The attribute **referenceDate** indicates the last date the address was (is) considered to be valid.

<!ELEMENT telephone (telephonePrefix, telephoneNumber, telephoneSuffix?)>

**telephonePrefix** contains the prefix information related to a telephone number, e.g., a country and city code, or an area code. This is a choice element requiring either two sub-elements or one sub-element.

```
<!ELEMENT telephonePrefix ((telephoneCountryCode?, telephoneCityCode?) |
    areaCode?)>
```

**telephoneCityCode** contains the city code when this is an international number.

```
<!ELEMENT telephoneCityCode (#PCDATA)>
```

**telephoneCountryCode** contains the country code when this is an international number.

```
<!ELEMENT telephoneCountryCode (#PCDATA)>
```

**areaCode** contains the area code for a telephone number.

```
<!ELEMENT areaCode (#PCDATA)>
```

**telephoneNumber** contains a telephone number. This element has one additional attribute, **format**, which is used to define the format of the digits comprising the telephone number. Format information includes: the hash (“#”) character to indicate the position of a telephone keypad digit, and white space characters to specify the position for optional white space; all other characters must be included as shown.

```
<!ELEMENT telephoneNumber (#PCDATA)>
    <!ATTLIST telephoneNumber format CDATA #IMPLIED
```

**telephoneSuffix** contains suffix information, e.g., an extension number.

```
<!ELEMENT telephoneSuffix (#PCDATA)>
```

**birthPlace** provides information about a person’s place of birth.

```
<!ELEMENT birthPlace (physicalLocation?, birthPlaceData?)>
```

**birthPlaceData** contains information identifying a birthplace. It uses values from the IAFIS manual. The attribute **codeSource** is defaulted to “IAFIS”.

```
<!ELEMENT birthPlaceData (#PCDATA)>
    <!ATTLIST birthPlaceData codeSource CDATA "IAFIS"
```

#### 2.4.1.2.2 Elements for Names and Identifications

The **agencyID** element provides identification information for an agency.

```
<!ELEMENT agencyID (entityName?, entityAbbreviatedName?, entityAcronym?,
    ori?, name*)>
```

The **organizationID** element provides information identical to that provided in **agencyID**. These elements serve to differentiate between official entities (**agencyID**), e.g., a police department, and social organizations (**organizationID**), e.g., a gang.

```
<!ELEMENT organizationID (entityName?, entityAbbreviatedName?,
    entityAcronym?, ori?, name*)>
```

The **originatingJurisdiction** element identifies a jurisdiction originating a charge or a case.

```
<!ELEMENT originatingJurisdiction (agencyID)>
```

**entityName** is the full legal name of an entity.

```
<!ELEMENT entityName (#PCDATA)>
```

**entityAbbreviatedName** provides the common abbreviation for an entity’s name.

```
<!ELEMENT entityAbbreviatedName (#PCDATA)>
```

**entityAcronym** provides any common acronym by which the entity is known, e.g., “FBI”.

```
<!ELEMENT entityAcronym (#PCDATA)>
```

## Electronic Court Filing Draft Specification

The **ori** element contains the “Originating Agency” code assigned to a law enforcement agency or court. This is assigned by a system operator (e.g., by a database or network operator) and is used to track usage within that system.

```
<!ELEMENT ori (#PCDATA)>
```

The **group** element describes a group and its children, specifying membership in a collection of actors, e.g., members of a judge’s staff. The attribute **type** defines the group. Courts may define acceptable values for the attribute **type**. The attribute **status** defines the status of the group, e.g., “Active”, “Inactive”.

```
<!ELEMENT group (entity, groupRelationship?, physicalLocation?)>
```

**groupRelationship** provides the relationship between this and other groups.

```
<!ELEMENT groupRelationship (#PCDATA)>
```

The **personName** element provides name information specific to a human being, i.e., identifies a natural person.

```
<!ELEMENT personName (namePrefix?, firstName?, middleName?, lastName?,  
nameSuffix?, fullName?, designation?, name*)>
```

**namePrefix** contains any formal prefix that is used with this name, e.g., “The Honorable”, “Mr.”, “Ms”.

```
<!ELEMENT namePrefix (#PCDATA)>
```

**firstName** contains the first, or given, name of a person.

```
<!ELEMENT firstName (#PCDATA)>
```

**middleName** provides an element to contain a person’s middle name, initials, or multiple initials. For persons with more than one name between their first and last names, one may put all of those names into the single element **middleName**.

```
<!ELEMENT middleName (#PCDATA)>
```

**lastName** contains the family name, or surname, of a person.

```
<!ELEMENT lastName (#PCDATA)>
```

**nameSuffix** provides a name suffix, such as “Jr.”, “PhD”, or “III”.

```
<!ELEMENT nameSuffix (#PCDATA)>
```

**fullName** contains the entire, or complete name of a person; it includes all name elements, i.e., **prefix**, **firstName**, **middleName**, **lastName**, and **suffix**.

```
<!ELEMENT fullName (#PCDATA)>
```

The **identification** element provides identifying information about an individual.

```
<!ELEMENT identification (personName*, personDescription*, palmPrint?,  
photo?, dna?, employment*, residence?, cautionInformation*,  
firearmSalesDisqualified?, offenderNoticeInformation?,  
commentInformation?)>
```

The **dna** element contains DNA information

```
<!ELEMENT dna (agencyID?, dnaLocus+, commentInformation*)>
```

The **dnaLocus** element contains the specification of the data contained within DNA. The **type** attribute identifies the locus type.

```
<!ELEMENT dnaLocus (locusValue+)>  
  
<!ATTLIST dnaLocus type (CSF1PO | D13S317 | D16S539 | D18S51 | D21S11 |  
D3S1358 | D5S818 | D7S820 | D8S1179 | FGA | TH01 | TPOX | vWA)  
#REQUIRED >
```

The **locusValue** element contains DNA values.

```
<!ELEMENT locusValue (#PCDATA)>
```

The **employment** element provides employment information about an individual.

```
<!ELEMENT employment (occupation?, physicalLocation?, employer?)>
```

**occupation** contains a person's occupation.

```
<!ELEMENT occupation (#PCDATA)>
```

**employer** contains the name of a person's employer.

```
<!ELEMENT employer (#PCDATA)>
```

The **palmPrint** element contains an image of a palm print.

```
<!ELEMENT palmPrint (agencyID?, imageData, commentInformation?)>
```

The **fingerprint** element contains an image of a fingerprint.

```
<!ELEMENT fingerprint (agencyID?, imageData, commentInformation?)>
```

**firearmSalesDisqualified** specifies whether the identified person is allowed to purchase firearms. It is limited to the values, "cleared", "disqualified", "unknown".

```
<!ELEMENT firearmSalesDisqualified (#PCDATA)>
```

#### 2.4.1.2.2.1 *personDescription*

The **personDescription** element contains descriptive characteristics of a person.

```
<!ELEMENT personDescription (sex*, height*, weight*, eyeColor*, hairColor*,
    scarsMarksTattoos*, birthDate*, birthPlace*, ethnicity*, race*,
    citizenship*, maritalStatus*, religion*, personalIDNumber*,
    fingerprintPattern*, skinTone*, bloodType?, medicalCondition*)>
```

The **sex** element contains a person's physiological gender. Required data values are: "male", "female", "other", "unknown". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT sex (#PCDATA)>
```

```
<!ATTLIST sex codeSource CDATA "NCIC-2000"
```

The **height** element contains a person's height. This element has an attribute of **units** in addition to the normal seven attributes. The **units** attribute specifies the measurement units that were used in collecting the element data. The default for **units** is "inches".

```
<!ELEMENT height (#PCDATA)>
```

```
<!ATTLIST height units (centimeters | meters | inches | feet |
    feetInches) "inches"
```

The **weight** element contains a person's weight. This element has an attribute of **units** in addition to the normal seven attributes. The **units** attribute specifies the measurement units that were used in collecting the element data. If not specified, the default for **units** is "pounds".

```
<!ELEMENT weight (#PCDATA)>
```

```
<!ATTLIST weight units (pounds | kilograms | grams) "pounds"
```

The **eyeColor** element contains the color of a person's eyes. Required data values are: "black", "blue", "brown", "gray", "green", "hazel", "maroon", "multicolored", "pink", "unknown". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT eyeColor (#PCDATA)>
```

```
<!ATTLIST eyeColor codeSource CDATA "NCIC-2000"
```

The **hairColor** element contains the color of a person's hair. Required data values are: "black", "blond", "blue", "brown", "gray", "green", "orange", "pink", "purple", "red", "sandy", "white", "bald", "unknown". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT hairColor (#PCDATA)>
  <!ATTLIST hairColor codeSource CDATA "NCIC-2000"
```

The **scarsMarksTattoos** element contains information on a person's scars, marks, and tattoos. The **agencyID** child element specifies the origination of the description of the scar, mark, or tattoo.

```
<!ELEMENT scarsMarksTattoos (agencyID, scarsMarksTattoosDescription,
  image)>
```

The **scarsMarksTattoosDescription** element contains a description of a person's scars, marks, and tattoos, including location on the person and type.

```
<!ELEMENT scarsMarksTattoosDescription (#PCDATA)>
```

The **ethnicity** element contains a person's ethnicity, e.g., "Norwegian", "Mexican".

```
<!ELEMENT ethnicity (#PCDATA)>
```

The **race** element describes a person's race. Required data values are: "white", "black", "asian", "nativeAmerican", "unknown". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT race (#PCDATA)>
  <!ATTLIST race codeSource CDATA "NCIC-2000"
```

The **citizenship** element identifies the citizenship held by a person. It is the same as the **country** element. The attribute **codeSource** is defaulted to "ISO 3166" to indicate the required source for the allowed values of this element. The three-character codes shall be used, e.g., "USA".

```
<!ELEMENT citizenship (#PCDATA)>
  <!ATTLIST country codeSource CDATA "ISO 3166"
```

The **maritalStatus** element contains the marital status of a person. Required data values are: "married", "widowed", "divorced", "separated", "neverMarried", "unmarriedPartner", "unknown". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT maritalStatus (#PCDATA)>
  <!ATTLIST maritalStatus codeSource CDATA "NCIC-2000"
```

The **religion** element identifies a person's religious preference or affiliation.

```
<!ELEMENT religion (#PCDATA)>
```

The **personalIDNumber** element contains identifiers assigned by various agencies and organizations. The **type** attribute shall be used to identify the kind of ID assigned, e.g., "Social Security", "driver's license", "NCIC". This element has an additional attribute: **issuingAuthority** shall contain the name of the issuing organization or state for this identification number.

```
<!ELEMENT personalIDNumber (#PCDATA)>
  <!ATTLIST personalIDNumber issuingAuthority CDATA #IMPLIED>
```

The **fingerprintPattern** element contains FBI defined fingerprint pattern information. The **codeSource** attribute defaults to "FBI" as the source of the data values.

```
<!ELEMENT fingerprintPattern (#PCDATA)>
  <!ATTLIST fingerprintPattern codeSource CDATA "FBI">
```

The **skinTone** element contains a description of a person's skin color or tone. Required data values are: "albino", "black", "dark", "darkBrown", "fair", "light", "lightBrown", "medium", "mediumBrown", "olive", "ruddy", "sallow", "yellow", "unknown". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT skinTone (#PCDATA)>
  <!ATTLIST skinTone codeSource CDATA "NCIC-2000"
```

The **bloodType** element contains NCIC 2000 Code Manual defined information on a person's blood type. The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT bloodType (#PCDATA)>
  <!ATTLIST bloodType codeSource CDATA "NCIC-2000"
```

The **medicalCondition** element contains NCIC 2000 Code Manual defined information on a person's medical condition. The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT medicalCondition (#PCDATA)>
  <!ATTLIST medicalCondition codeSource CDATA "NCIC-2000"
```

#### 2.4.1.2.2.2 *vehicle*

The **vehicle** element provides contains identification information for a vehicle. Vehicles include boats, automobiles, etc.

```
<!ELEMENT vehicle (vehicleType?, vehicleStyle?, vehicleMake?,
  vehicleModel?, vehicleBrand?, vehicleModelYear?, vehicleEnginePower?,
  vehicleVisibleID?, vehicleSerialNumber?, vehicleRegistrationNumber?,
  vehicleRegistrationExpiration?, state?, vehicleColor?, vin? ,
  vehicleOwner?, vehicleOwnerAddress?, vehicleLeased?,
  vehicleOwnerAppliedName?, vehicleDescription?)>
```

The **vehicleType** element contains NCIC 2000 Code Manual defined information identifying the type of vehicle, e.g., "aircraft", "automobile", "bicycle". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT vehicleType (#PCDATA)>
  <!ATTLIST vehicleType codeSource CDATA "NCIC-2000"
```

The **vehicleStyle** element contains NCIC 2000 Code Manual defined information identifying the vehicle style, e.g., an aircraft can be "Single-Engine", "Blimp", an automobile can be "Ambulance", "Roadster". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT vehicleStyle (#PCDATA)>
  <!ATTLIST vehicleStyle codeSource CDATA "NCIC-2000"
```

The **vehicleMake** element contains NCIC 2000 Code Manual defined information identifying the vehicle make, e.g., "Audi", "Hudson". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT vehicleMake (#PCDATA)>
  <!ATTLIST vehicleMake codeSource CDATA "NCIC-2000"
```

The **vehicleModel** element contains NCIC 2000 Code Manual defined information identifying the vehicle model, e.g., vehicleMake "Hudson" has vehicleModel "commodore". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT vehicleModel (#PCDATA)>
```

```
<!ATTLIST vehicleModel codeSource CDATA "NCIC-2000"
```

The **vehicleBrand** element contains NCIC 2000 Code Manual defined information identifying the vehicle brand, e.g., "Audi", "Hudson". This content is the same as the content of **vehicleMake**. NCIC 2000 values are the same for both elements. For example, in an NCIC "stolen vehicle" record, one sees the **vehicleMake** field. In a "stolen vehicle part" record, one sees the **vehicleBrand** field. The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT vehicleBrand (#PCDATA)>
```

```
<!ATTLIST vehicleBrand codeSource CDATA "NCIC-2000"
```

The **vehicleModelYear** element contains the manufacturer's assigned model year, e.g., a 2002 Audi could be manufactured in 2001. The content format is CCYY, and is based on ISO 8601.

```
<!ELEMENT vehicleModelYear (#PCDATA)>
```

The **vehicleEnginePower** element contains NCIC 2000 Code Manual defined information identifying the vehicle engine power, e.g., "165 Horsepower", "2.6 Liter". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the textual part, e.g., "Horsepower", of the element values.

```
<!ELEMENT vehicleEnginePower (#PCDATA)>
```

```
<!ATTLIST vehicleEnginePower codeSource CDATA "NCIC-2000"
```

The **vehicleVisibleID** element contains the visible vehicle identification number. In the case of automobiles, this would be the license plate, for airplanes it would be the tail number, etc.

```
<!ELEMENT vehicleVisibleID (#PCDATA)>
```

The **vehicleSerialNumber** element contains the registration tag serial number information.

```
<!ELEMENT vehicleSerialNumber (#PCDATA)>
```

The **vehicleRegistrationExpiration** element contains the year, and month, if applicable, the vehicle's registration expires. The content format is CCYY[-MM], and is based on ISO 8601.

```
<!ELEMENT vehicleRegistrationExpiration (#PCDATA)>
```

The **vehicleColor** element contains NCIC 2000 Code Manual defined information identifying the vehicle's color, e.g., "Copper", "Mauve (purple)/Ivory". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT vehicleColor (#PCDATA)>
```

```
<!ATTLIST vehicleColor codeSource CDATA "NCIC-2000"
```

The **vin** element contains the Vehicle Identification Number imprinted by the manufacturer.

```
<!ELEMENT vin (#PCDATA)>
```

The **vehicleOwner** element identifies the owner of a vehicle.

```
<!ELEMENT vehicleOwner (name)>
```

The **vehicleOwnerAddress** element supplies the address of an owner of a vehicle.

```
<!ELEMENT vehicleOwnerAddress (physicalLocation)>
```

The **vehicleLeased** element contains information on whether the vehicle is leased or not.

```
<!ELEMENT vehicleLeased (#PCDATA)>
```

The **vehicleOwnerAppliedName** contains any name applied to the vehicle by the owner, e.g., "Barbara's Dream".

```
<!ELEMENT vehicleOwnerAppliedName (#PCDATA)>
```

The **vehicleDescription** element contains a textual description of the vehicle, e.g., "Ugly, beat-up, badly sun-faded, station wagon with collision damage on the left rear".

```
<!ELEMENT vehicleDescription (#PCDATA)>
```

#### 2.4.1.2.2.3 *weapon*

The **weapon** element contains descriptive information that identifies a weapon.

```
<!ELEMENT weapon (weaponType?, weaponMake?, weaponModel?, weaponID?,
  weaponFinish?, barrel?, caliber?, weaponDescription?)>
```

The **weaponType** element contains NCIC 2000 Code Manual defined information identifying the weapon type, e.g., "Shotgun, Double-Barrel", "Rocket Launcher". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT weaponType (#PCDATA)>
  <!ATTLIST weaponType codeSource CDATA "NCIC-2000"
```

The **weaponMake** element contains NCIC 2000 Code Manual defined information identifying the weapon manufacturer, e.g., "USA", "A. Zoli/Antonio Zoli". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT weaponMake (#PCDATA)>
  <!ATTLIST weaponMake codeSource CDATA "NCIC-2000"
```

The **weaponModel** element contains NCIC 2000 Code Manual defined information identifying the weapon model, e.g., "U.S. Revolvers, M1917", "Ace". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT weaponModel (#PCDATA)>
  <!ATTLIST weaponModel codeSource CDATA "NCIC-2000"
```

The **weaponID** element contains the weapon serial number.

```
<!ELEMENT weaponID (#PCDATA)>
```

The **weaponFinish** element contains NCIC 2000 Code Manual defined information identifying the weapon finish, e.g., "Stainless Steel", "Blue, Dark". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT weaponFinish (#PCDATA)>
  <!ATTLIST weaponFinish codeSource CDATA "NCIC-2000"
```

The **barrel** element contains NCIC 2000 Code Manual defined information identifying the firearm barrel size, see caliber for examples. The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT barrel (#PCDATA)>
  <!ATTLIST barrel codeSource CDATA "NCIC-2000"
```

The **caliber** element contains the same information as barrel, e.g., ".240 Weatherby Magnum", "13 mm Gyrojet rocket pistol/carbine". The **codeSource** attribute defaults to the NCIC Code Manual reference as the source of the element values.

```
<!ELEMENT caliber (#PCDATA)>
  <!ATTLIST caliber codeSource CDATA "NCIC-2000"
```

The **weaponDescription** element contains a textual description of the weapon.

```
<!ELEMENT weaponDescription (#PCDATA)>
```

### 2.4.1.2.3 Date and Time elements

All elements containing date and time information shall conform to the format specified in 1.5 Date and Time Format (page 5).

The **date** element contains a date. The required format is: CCYY[-MM[-DD]], and is based on ISO 8601.

```
<!ELEMENT date (#PCDATA)>
```

The **birthDate** element contains the birth date of an actor. It is in the same format as **date**.

```
<!ELEMENT birthDate (#PCDATA)>
```

The **time** element contains a time. All times are local times. The three allowed formats are: hh[:mm[:ss[.d...d]]]-hh[:mm], hh[:mm[:ss[.d...d]]]+hh[:mm], and hh[:mm[:ss[.d...d]]].

```
<!ELEMENT time (#PCDATA)>
```

### 2.4.1.2.4 Miscellaneous Elements

The **cautionInformation** provides cautionary messages about an individual. The **agencyID** sub-element identifies the origin of the information.

```
<!ELEMENT cautionInformation (agencyID?, caution?)>
```

The **caution** element contains the text for **cautionInformation**.

```
<!ELEMENT caution (#PCDATA)>
```

The **caveatInformation** element provides information regarding caveats, qualifiers, or restrictions about an individual's, entity's, or thing's history. The **agencyID** sub-element identifies the origin of the information.

```
<!ELEMENT caveatInformation (agencyID?, caveat?)>
```

The **caveat** element contains the text for **caveatInformation**.

```
<!ELEMENT caveat (#PCDATA)>
```

The **commentInformation** element contains other information about an actor for which no other element is appropriate. The **agencyID** sub-element identifies the origin of the information.

```
<!ELEMENT commentInformation (agencyID?, comment*)>
```

The **comment** element contains the text for **commentInformation**.

```
<!ELEMENT comment (#PCDATA)>
```

The **image** element provides an image.

```
<!ELEMENT image (agencyID?, imageData, commentInformation?)>
```

The **imageData** element contains the bits comprising an image. It has four additional attributes.

**contentEncoding** specifies the means by which the binary image data has been encoded for transmission as characters, for which the default value is base-64 encoding. **href** supplies a URL or URI where the actual image data may be located. **size** is a hint about the size, in bytes, of the encoded image. **mimeType** specifies the application required to view or process the decoded image.

```
<!ELEMENT imageData (#PCDATA)>
<!ATTLIST imageData
  contentEncoding CDATA "base64"
  href CDATA #IMPLIED
  size CDATA #IMPLIED
  mimeType CDATA #REQUIRED
```

The **photo** element contains a photographic image.

```
<!ELEMENT photo (agencyID?, imageData, commentInformation?)>
```

The **offenderNoticeInformation** element is used to contain other information about cautions, caveats, or notices relating to an offender. The **agencyID** element identifies the origin of the information.

```
<!ELEMENT offenderNoticeInformation (agencyID?, offenderNotice?)>
```

The **offenderNotice** element contains the textual information of an **offenderNoticeInformation** element.

```
<!ELEMENT offenderNotice (#PCDATA)>
```

#### 2.4.1.2.4.1 *charge*

**charge** is the identification of a criminal activity. This element has an additional attribute, **against**, which connects this **charge** with an **actor**.

```
<!ELEMENT charge (chargeNumber?, chargeSequenceNumber?,
    chargeTrackingNumber?, originatingJurisdiction?, offenseDate?,
    chargeName?, chargeStatute*, offenseCode?, numberOfIdenticalCharges?,
    chargeSeverity?, inchoateCharge?, chargeEnhancingFactor*,
    chargeReducingFactor*, chargeDisposition?, commentInformation*)>
```

```
<!ATTLIST charge against IDREF #REQUIRED
```

The **chargeNumber** element contains a sequentially assigned number for linking multiple charges against an **actor** through arrest, prosecution, and court disposition.

```
<!ELEMENT chargeNumber (#PCDATA)>
```

The **chargeSequenceNumber** element contains a sequentially assigned number for charge tracking purposes. For example, the first charge under an arrest might be assigned **chargeSequenceNumber** "1". As the charge changes for prosecution, conviction, etc, the sequence number would increase.

```
<!ELEMENT chargeSequenceNumber (#PCDATA)>
```

The **chargeTrackingNumber** element contains a unique identifying number assigned to the particular charge for case management purposes.

```
<!ELEMENT chargeTrackingNumber (#PCDATA)>
```

The **offenseDate** contains the date of the alleged offense. It is in the same format as **date**.

```
<!ELEMENT offenseDate (#PCDATA)>
```

The **chargeName** element contains text describing the charge.

```
<!ELEMENT chargeName (#PCDATA)>
```

The **chargeStatute** element contains the statute justifying the charge.

```
<!ELEMENT chargeStatute (#PCDATA)>
```

The **offenseCode** contains the offense code for the charge.

```
<!ELEMENT offenseCode (#PCDATA)>
```

The **numberOfIdenticalCharges** element contains the number of times an **actor** is charged with the same offense at a particular time.

```
<!ELEMENT numberOfIdenticalCharges (#PCDATA)>
```

The **chargeSeverity** element indicates the severity of a charge. The required data values are: "felony", "misdemeanor", "localOrdinance", "other", "unknown".

```
<!ELEMENT chargeSeverity (#PCDATA)>
```

The **inchoateCharge** element contains information relating to any inchoate charges. The required data values are: "solicitation", "conspiracy", "attempt", "accomplice".

```
<!ELEMENT inchoateCharge (#PCDATA)>
```

The **chargeEnhancingFactor** element contains information on factors that make a charge more serious, e.g., "armed", "against the elderly", "hate crime".

```
<!ELEMENT chargeEnhancingFactor (#PCDATA)>
```

The **chargeReducingFactor** element contains information on factors that may make a charge less serious or limit the penalty, e.g., violations observed by "photo-radar" stations in some states.

```
<!ELEMENT chargeReducingFactor (#PCDATA)>
```

The **chargeDisposition** element contains a free-text description of a law enforcement agency action, e.g., "custody only", "turned over to another agency", "not referred for prosecution", "referred for prosecution".

```
<!ELEMENT chargeDisposition (#PCDATA)>
```

## 2.4.2 Elements Common to Legal XML

The **barMembershipInformation** element, and its children, **barNumber**, **licenseAuthority**, **yearAdmitted**, and **barStatus**, identify members of the Bar in a particular state or province.

```
<!ELEMENT barMembershipInformation (barNumber, licenseAuthority,
    yearAdmitted?, barStatus?)>
```

Licensing state, or other authority.

```
<!ELEMENT licenseAuthority (#PCDATA)>
```

```
<!ELEMENT barNumber (#PCDATA)>
```

```
<!ELEMENT yearAdmitted (#PCDATA)>
```

```
<!ELEMENT barStatus (#PCDATA)>
```

Date and time are represented by a single element, **dateTime**.

```
<!ELEMENT dateTime (date, time)>
```

The **duration** element is used to specify a period of time. It shall conform to ISO 8601 as shown in paragraph 1.5.

```
<!ELEMENT duration (#PCDATA)>
```

The **entity** element identifies legal persons. The attribute **type** identifies the type of entity, e.g., "Corporation".

```
<!ELEMENT entity (agencyID | organizationID | originatingJurisdiction)>
    <!ATTLIST entity type CDATA #REQUIRED>
```

**fee** is a court-imposed payment, differentiated from **paymentInformation**, which is supplied by the filer of the filing. The attribute **type** specifies the type of fee being assessed.

```
<!ELEMENT fee (#PCDATA)>
```

```
<!ATTLIST fee type CDATA #REQUIRED>
```

**name** identifies the names of people, entities, and things. The **id** attribute shall be used for alias matching. The attribute **type** identifies the type of name, e.g., "dba" (doing business as). When the **name** is an alias, the **type** attribute is required. The court may specify acceptable values for **type**. The attribute **matchWith** is used when the **name** is an alias, and contains a reference to an **id** attribute of a different **name** element. The attribute **matchWith** is required when **name** is an alias.

```
<!ELEMENT name (personName | entity | thing)>
```

```
<!ATTLIST name id ID #IMPLIED
    type CDATA #IMPLIED
    matchWith IDREF #IMPLIED>
```

**paymentInformation**, and its children, **credit**, **debit**, **account**, **cash**, **check**, and **negotiableInstrument** are sent by the filer and identify how the filer intends to pay, is paying, or has paid any court fees.

A court may refuse to accept **paymentInformation**.

```
<!ELEMENT paymentInformation (credit | debit | account | cash | check |
    negotiableInstrument)>
```

**credit** refers to credit card or other credit token information, e.g., a "smart card".

```
<!ELEMENT credit (amount, accountNumber, expiration, cardHolder?)>
```

**debit** refers to debit card or other debit token information, e.g., a "smart card".

```
<!ELEMENT debit (amount, accountNumber, expiration, cardHolder?)>
```

**account** refers to a prepaid or billable account that has been established at the receiving court.

```
<!ELEMENT account (amount, accountNumber, cardHolder?)>
```

**cardHolder** indicates the owner of the credit, debit, or account and is linked with their billing address.

```
<!ELEMENT cardHolder ((personName | entity)?,(postalAddress | email | fax |
    uri))>
```

**expiration** is the expiration date.

```
<!ELEMENT expiration (date)>
```

**cash** and **amount** provide information on a payment. The data contains the amount of the payment.

```
<!ELEMENT cash (#PCDATA)>
```

```
<!ELEMENT amount (#PCDATA)>
```

The **check** element contains check information. The attribute **sequenceNumber** provides a place to indicate the imprinted number of the check. The attribute **business** indicates whether the checking account belongs to a business or a person.

```
<!ELEMENT check (amount, financialInstitution, routingNumber,
    accountNumber, payee, signer)>
```

```
<!ATTLIST check
    sequenceNumber CDATA #IMPLIED
    business ("Yes" | "No") "No">
```

**negotiableInstrument** provides information about any other instrument that can be used for fee payments. The attribute **type** specifies the type of negotiable instrument being presented. The attribute **value** contains the value of the instrument if different from the amount.

```
<!ELEMENT negotiableInstrument (amount, financialInstitution,
    instrumentNumber, payee, signer)>
```

```
<!ATTLIST negotiableInstrument
    type CDATA #IMPLIED
    value CDATA #IMPLIED>
```

The **accountNumber**, and **instrumentNumber** element contain numbers assigned by the issuer to identify credit cards, debit cards, checks, and negotiable instruments. The **format** attribute may be used to define the format of the number.

**format** uses the hash character (" # ") to specify a position occupied by a number digit, the "x" character to specify a position occupied by an alphabetic character, a white space character (any of the characters tab, space, new line, etc.) to specify the position of optional white space. All other non-alphanumeric characters in a format definition must appear as shown.

```
<!ELEMENT accountNumber (#PCDATA)>
```

```
<!ATTLIST accountNumber format CDATA #IMPLIED>
<!ELEMENT instrumentNumber (#PCDATA)>
```

```
<!ATTLIST instrumentNumber format CDATA #IMPLIED>
```

**financialInstitution** identifies the issuing financial institution for the check or negotiableInstrument.

```
<!ELEMENT financialInstitution (entity)>
```

**routingNumber** identifies the issuing financial institution routing number for the check.

```
<!ELEMENT routingNumber (#PCDATA)>
```

The **payee** element supplies information necessary to identify the recipient of the value represented by a check or negotiableInstrument, their respective delivery addresses, and the corresponding delivery methods.

```
<!ELEMENT payee ((personName | entity)?,(postalAddress | email | fax |
uri))>
```

The **signer** element supplies information necessary to identify the signer of the check or negotiableInstrument, their respective delivery addresses, and the corresponding delivery methods.

```
<!ELEMENT signer ((personName | entity)?,(postalAddress | email | fax |
uri))>
```

**designation** identifies persons having the same name in different generations, different persons with the same name in an actor list, or an attorney bar number. The sender assigns the content for this element. For a Court Filing confirmation message, designation shall be the same as in the corresponding filing.

```
<!ELEMENT designation (#PCDATA | barMembershipInformation)*>
```

**signature** is a place holder.

```
<!ELEMENT signature ANY>
```

The **thing** element identifies property or other items that are related to a case. **vehicle** and **weapon** provide information on those items.

```
<!ELEMENT thing (#PCDATA | vehicle | weapon)*>
```

The **uri** element contains either a Universal Resource Identifier (URI) or a Universal Resource Locator (URL).

```
<!ELEMENT uri (#PCDATA)>
```

## 2.5 Elements for specific case types

These elements have been proposed as useful for various specific case types.

The **custody** element provides information on where, when, and whether the defendant is locked up. The attribute **status** indicates whether the defendant is jailed or not. The **defendantID** points to an actor element containing information about the defendant.

```
<!ELEMENT custody (date, physicalLocation)>
<!ATTLIST custody status CDATA #REQUIRED
defendantID IDREF #REQUIRED>
```

The **incident** element provides information about when and where the alleged crime was committed. **clockedSpeed** and **speedLimit** are for completeness. The attribute **chargeID** is used to connect the incident to the charge.

```
<!ELEMENT incident (date, physicalLocation, clockedSpeed?, speedLimit?)>
<!ATTLIST incident chargeID IDREF #REQUIRED>
```

The elements **clockedSpeed** and **speedLimit** are provided for traffic offenses.

```
<!ELEMENT clockedSpeed (#PCDATA)>
```

```
<!ELEMENT speedLimit (#PCDATA)>
```

The **bail** element contains the information concerning the bail. The **chargeID** attribute is used to identify the charge for which bail is made. The **type** attribute identifies the type of bail. The **referenceDate** attribute identifies the date on which bail was made.

```
<!ELEMENT bail (paymentInformation)>
  <!ATTLIST bail chargeID IDREF #REQUIRED
    type CDATA #IMPLIED
    referenceDate CDATA #REQUIRED>
```

The **booking** element serves to identify when the defendant was booked. The **chargeID** attribute is used to connect the booking to a charge. The **agencyID** attribute is used to identify the booking agency. The **referenceDate** attribute identifies the date on which the booking occurred. It shall conform to the date format specified in this document.

```
<!ELEMENT booking (fingerprint)>
  <!ATTLIST booking chargeID IDREF #REQUIRED
    agencyID IDREF #REQUIRED
    referenceDate IDREF #REQUIRED>
```

The **caseDisposition** element contains the information concerning case disposition status and source. The **codeValue** attribute is used to identify the status of the disposition. The **codeSource** attribute is used to identify the source of the status information.

```
<!ELEMENT caseDisposition (#PCDATA)>
  <!ATTLIST caseDisposition codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED>
```

### 3 Appendices

Information contained in appendices is not binding on conforming applications.

#### 3.1 *Statement of Intent*

With the release of Electronic Court Filing 1.1 as a proposed standard, Electronic Court Filing Technical Committee has reached an important milestone. Electronic Court Filing 1.1 should enable courts and Electronic Filing Service Providers to engage in standards-based e-filing without delay.

The work of the OASIS LegalXML Member Section Electronic Court Filing Technical Committee is ongoing. Electronic Court Filing 1.1 is based upon a Document Type Definition (DTD). DTDs are currently being replaced by W3C schemas, which are a more recent and robust way of defining XML documents. Therefore, Electronic Court Filing 2.0 is anticipated to address schema in addition to an updated DTD. In addition, the W3C on February 14, 2002 made the XML Signature Standard a W3C Recommendation (and approved for Draft Standard Publication) and Exclusive Canonicalization (a companion work) should follow soon. This development makes the possibility of digitally signing Electronic Court Filing documents using W3C standards a present reality. In addition, SOAP extensions to Electronic Court Filing schemas offer a way to standardize the parsing of Electronic Court Filing transmissions without the need to develop unique tools to perform the parsing. This could increase costs, reliance upon proprietary solutions, and isolation of the OASIS LegalXML Member Section from the efforts of other XML standards bodies. These points, which were raised in a comment posted by John Messing on January 1, 2002., are by this Appendix acknowledged to be requirements of the Electronic Court Filing Technical Committee in the development of Electronic Court Filing 2.0. As a result, Electronic Court Filing 1.1 is based upon group consensus without dissent.

## **3.2 Examples**

Examples have been removed from this version pending the creation of new examples using the latest DTD.

## **3.3 Query and Response**

Examples for the query and response data elements are not included. The Query and Response specification is separate from this document, and examples are contained in that document.

## **3.4 User Descriptions**

### **3.4.1 Attorneys**

Attorneys

- File pleadings
- Receive notifications
- Review pleadings, orders, and notices of individual cases
- Open civil cases

District Attorneys

- Open criminal cases

Pro Se (also called “Pro Per”) are defendants or plaintiffs (that is, parties) in a court case who are representing themselves.

- Limited to specific cases involving self-represented litigants

### **3.4.2 Judicial Officer and Staff**

Judicial Officer

- Limited in jurisdiction
- Files orders
- Receives notifications
- Annotates notifications for processing by support staff
- Reviews pleadings, orders, and notices of individual cases

Judicial Support Staff

- Acts for the judge

### **3.4.3 Clerk of Court**

- Limited to specific court jurisdiction
- Files orders and notices within court
- Receives notifications
- Reviews pleadings, orders, and notices of individual cases
- Keeps the court files, including sealed, confidential records
- Provides access to court files

### **3.4.4 Clerk Staff**

- Limited to specific court jurisdiction
- Receives, indexes, and files pleadings, orders, and notices for litigants, attorneys, judges, and clerk of court
- Reviews queued entries prior to docketing
- Reviews pleadings, orders, and notices of individual cases

### **3.4.5 Super User**

- Limited to one associated court
- Maintains (adds, deletes, modifies) user lists
- Maintains database

## **4 Change History**

This is a new version of created by the OASIS LegalXML Member Section Electronic Court Filing Technical Committee.

*Copyright (C) The Organization for the Advancement of Structured Information Standards [OASIS] (date). All Rights Reserved.*

## **5 Attachment I—Electronic Court Filing 1.1 DTD**

The Electronic Court Filing 1.1 DTD is provided in the following pages.

Electronic Court Filing Draft Specification

```
<?xml version='1.0' encoding='utf-8'?>
<!-- Copyright (C) The Organization for the Advancement of Structured
Information Standards [OASIS] 2002. All Rights Reserved.
-->

<!-- Envelope content -->
<!ELEMENT legalEnvelope (messageIdentification, to, from, cc?, bcc?,
replyTo?,
memo*, creation, dataIntegrity?, paymentInformation?, authentication?,
legal)>
  <!ATTLIST legalEnvelope version CDATA #FIXED "1.1">
  <!ELEMENT messageIdentification (#PCDATA)>
  <!ELEMENT to (addressee+)>
  <!ELEMENT from (sender)>
  <!ELEMENT replyTo (sender)>
  <!ELEMENT cc (addressee+)>
  <!ELEMENT bcc (addressee+)>
  <!ELEMENT addressee ((personName | entity)?,(postalAddress | email | fax |
uri))>
  <!ELEMENT sender ((personName | entity)?,(postalAddress | email | fax |
uri))>
  <!ELEMENT creation (dateTime)>
  <!ELEMENT dataIntegrity ANY> <!-- place holder -->

<!-- Court Filing content -->
<!ELEMENT legal (courtFiling)>
<!ELEMENT courtFiling (filing+ | confirmation+ | query | response)>
<!ELEMENT filing (actor+, filingInformation, leadDocument)>
  <!ATTLIST filing privacy CDATA #IMPLIED>
<!ELEMENT filingInformation (specialHandling?, paymentInformation*,
authentication*, courtInformation, caseInformation, actor*, courtEvent*,
memo?)>
  <!ATTLIST filingInformation id ID #REQUIRED
                                privacy CDATA #IMPLIED>
  <!ELEMENT specialHandling (#PCDATA)>
<!ELEMENT leadDocument (documentInformation, documentContent, attachment*,
authentication*)>
  <!ATTLIST leadDocument id ID #REQUIRED>
<!ELEMENT documentInformation (actor+, submitted, documentDescription,
(administrativeLaw | appeals | bankruptcy | civil | criminal
| domesticRelations | juvenile | probate | smallClaims | traffic)?,
matter*, causeOfAction*)>
  <!ELEMENT submitted (dateTime)>
  <!ELEMENT documentDescription (documentTitle, documentType*)>
    <!ELEMENT documentTitle (#PCDATA)>
    <!ELEMENT documentType (#PCDATA)>
    <!ATTLIST documentType documentCode CDATA #IMPLIED>
  <!ELEMENT administrativeLaw ANY>
  <!ELEMENT appeals ANY>
  <!ELEMENT bankruptcy ANY>
  <!ELEMENT civil ANY>
  <!ELEMENT domesticRelations ANY>
  <!ELEMENT probate ANY>
  <!ELEMENT smallClaims ANY>
  <!ELEMENT traffic ANY>
```

## Electronic Court Filing Draft Specification

```
<!ELEMENT criminal (identification, charge+, bail?, booking?, custody?,
incident*)>
<!ELEMENT juvenile (identification, charge+, bail?, booking?, custody?,
incident*)>
<!ELEMENT documentContent (#PCDATA | part)*>
  <!ATTLIST documentContent id ID #REQUIRED
    size CDATA #IMPLIED
    mimeType CDATA #REQUIRED
    contentEncoding (Base64) #IMPLIED
    href CDATA #IMPLIED>
  <!ELEMENT part (#PCDATA)>
    <!ATTLIST part number CDATA #REQUIRED>
<!ELEMENT attachment (attachmentDocumentInformation, documentContent,
authentication*, attachment*)>
  <!ATTLIST attachment id ID #REQUIRED>
  <!ELEMENT attachmentDocumentInformation (actor*, submitted,
documentDescription, (administrativeLaw | appeals | bankruptcy | civil
| criminal | domesticRelations | juvenile | probate | smallClaims
| traffic)?, matter*, causeOfAction*)>

<!-- Confirmation elements -->
<!ELEMENT confirmation (actor*, timeStamp, confirmationInformation)>
<!ELEMENT confirmationInformation (fee*, courtInformation?,
caseInformation?, actor*, leadDocumentDisposition+, courtEvent*)>
  <!ATTLIST confirmationInformation refersTo CDATA #REQUIRED
    filingDisposition (transmissionError |
acknowledged) #REQUIRED>
  <!ELEMENT leadDocumentDisposition (timeStamp, courtDocumentReference,
memo?,
attachmentDisposition*)>
    <!ATTLIST leadDocumentDisposition refersTo CDATA #REQUIRED
      filingDisposition (transmissionError |
acknowledged | received
| accepted | partial | deferred |
rejected) #REQUIRED>
    <!ELEMENT courtDocumentReference (#PCDATA)>
      <!ATTLIST courtDocumentReference href CDATA #IMPLIED>
    <!ELEMENT attachmentDisposition (courtDocumentReference)>
      <!ATTLIST attachmentDisposition refersTo CDATA #REQUIRED
        disposition (received | accepted |
rejected) #REQUIRED>
<!ELEMENT query ANY> <!-- place holder -->
<!ELEMENT response ANY> <!-- place holder -->

<!-- Court Filing common elements -->
<!ELEMENT actor (title?, name?, postalAddress*, telephone*, email*, group*,
personDescription*, designation*, role*, characteristic*)>
  <!ATTLIST actor id ID #IMPLIED
    reference IDREF #IMPLIED
    refersTo CDATA #IMPLIED
    privacy CDATA #IMPLIED>
  <!ELEMENT title (#PCDATA)>
  <!ELEMENT role (roleName, roleWith*)>
    <!ELEMENT roleName (#PCDATA)>
    <!ELEMENT roleWith EMPTY>
    <!ATTLIST roleWith actorID IDREF #IMPLIED
      matterID IDREF #IMPLIED>
```

## Electronic Court Filing Draft Specification

```
<!ELEMENT characteristic (characteristicName, characteristicValue)>
  <!ELEMENT characteristicName (#PCDATA)>
  <!ELEMENT characteristicValue (#PCDATA)>
<!ELEMENT authentication ((userIdentification, password?) | signature)>
  <!ELEMENT userIdentification (#PCDATA)>
  <!ELEMENT password (#PCDATA)>
<!ELEMENT caseInformation (fullCaseNumber?, caseTitle?, caseCategory?,
caseYear?, lineageCaseNumber*, filersCaseNumber?)>
  <!ATTLIST caseInformation id ID #IMPLIED
                                newCase (true | false) "false">
  <!ELEMENT fullCaseNumber (#PCDATA)>
  <!ELEMENT caseTitle (#PCDATA)>
  <!ELEMENT caseCategory (#PCDATA)>
  <!ELEMENT caseYear (#PCDATA)>
  <!ELEMENT lineageCaseNumber (fullCaseNumber?, caseTitle?,
caseCategory?, caseYear?, courtInformation?, lineageCaseNumber*)>
  <!ATTLIST lineageCaseNumber id ID #IMPLIED
                                referenceCase IDREF #REQUIRED>
  <!ELEMENT filersCaseNumber (#PCDATA)>
  <!ATTLIST filersCaseNumber referenceCase IDREF #IMPLIED>
<!ELEMENT causeOfAction (#PCDATA)>
  <!ATTLIST causeOfAction id IDREF #REQUIRED>
<!ELEMENT courtEvent (courtEventType, courtEventReason*, courtEventSession+)>
  <!ATTLIST courtEvent eventID CDATA #IMPLIED>
<!ELEMENT courtEventType (#PCDATA)>
<!ELEMENT courtEventReason (#PCDATA)>
<!ELEMENT courtEventSession (dateTime, duration?, actor+, courtInformation)>
  <!ATTLIST courtEventSession eventID CDATA #IMPLIED>
<!ELEMENT courtInformation (physicalLocation, courtType, courtName?)>
  <!ELEMENT courtType (#PCDATA)>
  <!ELEMENT courtName (#PCDATA)>
<!ELEMENT matter ANY> <!-- place holder -->
<!ATTLIST matter id ID #IMPLIED>
<!ELEMENT memo (#PCDATA)>
<!ELEMENT timeStamp (dateTime)>

<!-- Common Horizontal elements -->
<!--
  All of the following common horizontal elements have seven (7) common
  attributes.
  In all but a few cases these attributes are optional (#IMPLIED) and not
  required.
  The places where the attributes are required are noted by the notation
  #REQUIRED,
  or, where a default value exists, the attribute default value replaces
  the notation
  for optional.
-->
<!ELEMENT agencyID (entityName?, entityAbbreviatedName?, entityAcronym?,
ori?, name*)>
  <!ATTLIST agencyID
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
```

## Electronic Court Filing Draft Specification

```
        codeLiteral CDATA #IMPLIED>
<!ELEMENT birthPlace (physicalLocation?, birthPlaceData?)>
  <!ATTLIST birthPlace
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT cautionInformation (agencyID?, caution?)>
  <!ATTLIST cautionInformation
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT caveatInformation (agencyID?, caveat?)>
  <!ATTLIST caveatInformation
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT charge
(chargeNumber?, chargeSequenceNumber?, chargeTrackingNumber?,
originatingJurisdiction?, offenseDate?, chargeName?, chargeStatute*,
offenseCode?, numberOfIdenticalCharges?, chargeSeverity?, inchoateCharge?,
chargeEnhancingFactor*, chargeReducingFactor*, chargeDisposition?,
commentInformation*)>
  <!ATTLIST charge
    against IDREF #REQUIRED
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT commentInformation (agencyID?, comment*)>
  <!ATTLIST commentInformation
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT dna (agencyID?, dnaLocus+, commentInformation*)>
  <!ATTLIST dna
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
```

Electronic Court Filing Draft Specification

```
referenceDate CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA #IMPLIED
codeLiteral CDATA #IMPLIED>
<!ELEMENT dnaLocus (locusValue+)>
<!ATTLIST dnaLocus
type (CSF1PO | D13S317 | D16S539 | D18S51 | D21S11 | D3S1358 | D5S818 |
D7S820 | D8S1179 | FGA | TH01 | TPOX | vWA) #REQUIRED
id ID #IMPLIED
status CDATA #IMPLIED
referenceDate CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA #IMPLIED
codeLiteral CDATA #IMPLIED>
<!ELEMENT employment (occupation?, physicalLocation?, employer?)>
<!ATTLIST employment
id ID #IMPLIED
type CDATA #IMPLIED
status CDATA #IMPLIED
referenceDate CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA #IMPLIED
codeLiteral CDATA #IMPLIED>
<!ELEMENT fax (telephone)>
<!ATTLIST fax
id ID #IMPLIED
type CDATA #IMPLIED
status CDATA #IMPLIED
referenceDate CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA #IMPLIED
codeLiteral CDATA #IMPLIED>
<!ELEMENT group (entity, groupRelationship?, physicalLocation?)>
<!ATTLIST group
id ID #REQUIRED
qualifier CDATA #REQUIRED
status CDATA #REQUIRED
referenceDate CDATA #REQUIRED
referenceDateQualifier CDATA #IMPLIED
type CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA #IMPLIED
codeLiteral CDATA #IMPLIED>
<!ELEMENT identification
(personName*, personDescription*, palmPrint?, photo?, dna?,
employment*,
residence?, cautionInformation*, firearmSalesDisqualified?,
offenderNoticeInformation?,
commentInformation?)>
<!ATTLIST identification
id ID #IMPLIED
type CDATA #IMPLIED
status CDATA #IMPLIED
referenceDate CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA #IMPLIED
codeLiteral CDATA #IMPLIED>
```

Electronic Court Filing Draft Specification

```
<!ELEMENT image (agencyID?, imageData, commentInformation?)>
  <!ATTLIST image
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT locationText
  (#PCDATA | streetNumber | streetName | streetType | streetDirection
  |
  apartmentNumber | suite | privateMailBox | postOfficeBox |
buildingName | latitude | longitude)*>
  <!ATTLIST locationText
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT offenderNoticeInformation (agencyID?, offenderNotice?)>
  <!ATTLIST offenderNoticeInformation
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT organizationID (entityName?, entityAbbreviatedName?,
entityAcronym?, ori?, name*)>
  <!ATTLIST organizationID
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT originatingJurisdiction (agencyID)>
  <!ATTLIST originatingJurisdiction
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT palmPrint (agencyID?, imageData, commentInformation?)>
  <!ATTLIST palmPrint
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
```

## Electronic Court Filing Draft Specification

```
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT fingerprint (agencyID?, imageData, commentInformation?)>
  <!ATTLIST fingerprint
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT personDescription
  (sex*, height*, weight*, eyeColor*, hairColor*, scarsMarksTattoos*,
  birthDate*, birthPlace*, ethnicity*, race*, citizenship*, maritalStatus*,
  religion*, personalIDNumber*, fingerprintPattern*, skinTone*, bloodType?,
  medicalCondition*)>
  <!ATTLIST personDescription
    issuingAuthority CDATA #IMPLIED
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT personName (namePrefix?, firstName?, middleName?, lastName?,
  nameSuffix?, fullName?, designation?, name*)>
  <!ATTLIST personName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT photo (agencyID?, imageData, commentInformation?)>
  <!ATTLIST photo
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT physicalLocation (locationText*, postalAddress?, relatedLocation?,
  locationType?)>
  <!ATTLIST physicalLocation
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT postalAddress (addressLine*, city?, county?, state?, postalCode?,
  country?, addressFull?)>
  <!ATTLIST postalAddress
```

## Electronic Court Filing Draft Specification

```
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT rapSheetRequest (personalIDNumber*, fullName?, purposeCode?,
attention?)>
    <!ATTLIST rapSheetRequest
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT residence (physicalLocation?, telephone?)>
    <!ATTLIST residence
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT scarsMarksTattoos (agencyID, scarsMarksTattoosDescription, image)>
    <!ATTLIST scarsMarksTattoos
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT telephone (telephonePrefix?, telephoneNumber, telephoneSuffix?)>
    <!ATTLIST telephone
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT telephonePrefix ((telephoneCountryCode?, telephoneCityCode?) |
areaCode?)>
    <!ATTLIST telephonePrefix
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleOwner (name)>
    <!ATTLIST vehicleOwner
        id ID #IMPLIED
```

Electronic Court Filing Draft Specification

```
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleOwnerAddress (physicalLocation)>
  <!ATTLIST vehicleOwnerAddress
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicle
  (vehicleType?, vehicleStyle?, vehicleMake?, vehicleModel?,
  vehicleBrand?, vehicleModelYear?, vehicleEnginePower?, vehicleVisibleID?,
  vehicleSerialNumber?, vehicleRegistrationNumber?,
  vehicleRegistrationExpiration?, state?, vehicleColor?, vin? , vehicleOwner?,
  vehicleOwnerAddress?, vehicleLeased?, vehicleOwnerAppliedName?,
  vehicleDescription?)>
  <!ATTLIST vehicle
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT weapon
  (weaponType?, weaponMake?, weaponModel?, weaponID?, weaponFinish?,
  barrel?, caliber?, weaponDescription?)>
  <!ATTLIST weapon
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT addressFull (#PCDATA)>
  <!ATTLIST addressFull
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT addressLine (#PCDATA)>
  <!ATTLIST addressLine
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
```

Electronic Court Filing Draft Specification

```
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT apartmentNumber (#PCDATA)>
  <!ATTLIST apartmentNumber
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT suite (#PCDATA)>
  <!ATTLIST suite
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT privateMailBox (#PCDATA)>
  <!ATTLIST privateMailBox
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT areaCode (#PCDATA)>
  <!ATTLIST areaCode
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT attention (#PCDATA)>
  <!ATTLIST attention
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT barrel (#PCDATA)>
  <!ATTLIST barrel
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT birthDate (#PCDATA)>
```

Electronic Court Filing Draft Specification

```
<!-- Same format as date -->
  <!ATTLIST birthDate
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT birthPlaceData (#PCDATA)>
  <!ATTLIST birthPlaceData
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "IAFIS"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT bloodType (#PCDATA)>
  <!ATTLIST bloodType
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT buildingName (#PCDATA)>
  <!ATTLIST buildingName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT caliber (#PCDATA)>
  <!ATTLIST caliber
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT caution (#PCDATA)>
  <!ATTLIST caution
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT caveat (#PCDATA)>
  <!ATTLIST caveat
    id ID #IMPLIED
```

Electronic Court Filing Draft Specification

```
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeDisposition (#PCDATA)>
  <!ATTLIST chargeDisposition
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeEnhancingFactor (#PCDATA)>
  <!ATTLIST chargeEnhancingFactor
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeName (#PCDATA)>
  <!ATTLIST chargeName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeNumber (#PCDATA)>
  <!ATTLIST chargeNumber
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeReducingFactor (#PCDATA)>
  <!ATTLIST chargeReducingFactor
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeSequenceNumber (#PCDATA)>
  <!ATTLIST chargeSequenceNumber
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
```

Electronic Court Filing Draft Specification

```
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeSeverity (#PCDATA)>
  <!-- Required to be from the list:
        "felony", "misdemeanor", "localOrdinance", "other", "unknown"
  -->
  <!ATTLIST chargeSeverity
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeStatute (#PCDATA)>
  <!ATTLIST chargeStatute
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT chargeTrackingNumber (#PCDATA)>
  <!ATTLIST chargeTrackingNumber
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT citizenship (#PCDATA)>
<!-- Same format as country -->
  <!ATTLIST citizenship
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA "ISO 3166"
        codeLiteral CDATA #IMPLIED>
<!ELEMENT city (#PCDATA)>
  <!ATTLIST city
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT comment (#PCDATA)>
  <!ATTLIST comment
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
```

Electronic Court Filing Draft Specification

```
referenceDate CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA #IMPLIED
codeLiteral CDATA #IMPLIED>
<!ELEMENT country (#PCDATA)>
  <!ATTLIST country
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "ISO 3166"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT county (#PCDATA)>
  <!ATTLIST county
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT date (#PCDATA)>
  <!-- Use ISO 8601 dashed format, i.e., CCYY[-MM[-DD]] -->
  <!ATTLIST date
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "ISO 8601"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT email (#PCDATA)>
  <!ATTLIST email
    format CDATA #IMPLIED
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT employer (#PCDATA)>
  <!ATTLIST employer
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT entityAbbreviatedName (#PCDATA)>
  <!ATTLIST entityAbbreviatedName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
```

Electronic Court Filing Draft Specification

```
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT entityAcronym (#PCDATA)>
  <!ATTLIST entityAcronym
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT entityName (#PCDATA)>
  <!ATTLIST entityName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT ethnicity (#PCDATA)>
  <!ATTLIST ethnicity
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT eyeColor (#PCDATA)>
  <!-- Required to be from the list
    "black", "blue", "brown", "gray", "green", "hazel",
    "maroon", "multicolored", "pink", "unknown"
-->
  <!ATTLIST eyeColor
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT fingerprintPattern (#PCDATA)>
  <!ATTLIST fingerprintPattern
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "FBI"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT firearmSalesDisqualified (#PCDATA)>
  <!-- Required to be from the list, "cleared", "disqualified", "unknown" -->
  <!ATTLIST firearmSalesDisqualified
    id ID #IMPLIED
    type CDATA #IMPLIED
```

## Electronic Court Filing Draft Specification

```
status CDATA #IMPLIED
referenceDate CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA #IMPLIED
codeLiteral CDATA #IMPLIED>
<!ELEMENT firstName (#PCDATA)>
  <!ATTLIST firstName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT fullName (#PCDATA)>
  <!ATTLIST fullName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT groupRelationship (#PCDATA)>
  <!ATTLIST groupRelationship
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT hairColor (#PCDATA)>
  <!-- Required to be from the list
    "black", "blond", "blue", "brown", "gray", "green", "orange",
    "pink", "purple", "red", "sandy", "white", "bald", "unknown"
  -->
  <!ATTLIST hairColor
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT height (#PCDATA)>
  <!ATTLIST height
    units (centimeters | meters | inches | feet | feetinches)
    "inches"
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT imageData (#PCDATA)>
```

Electronic Court Filing Draft Specification

```
<!ATTLIST imageData
    contentEncoding CDATA "base64"
    href CDATA #IMPLIED
    size CDATA #IMPLIED
    mimeType CDATA #REQUIRED
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT inchoateCharge (#PCDATA)>
  <!-- Required to be from the list
        "solicitation", "conspiracy", "attempt", "accomplice"
  -->
  <!ATTLIST inchoateCharge
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT lastName (#PCDATA)>
  <!ATTLIST lastName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT latitude (#PCDATA)>
  <!--
        Use decimal notation
  -->
  <!ATTLIST latitude
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT locationType (#PCDATA)>
  <!ATTLIST locationType
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT longitude (#PCDATA)>
  <!--
        Use decimal notation
```

Electronic Court Filing Draft Specification

```
-->
<!ATTLIST longitude
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT locusValue (#PCDATA)>
    <!ATTLIST locusValue
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT maritalStatus (#PCDATA)>
    <!-- required to be from the list
        "married", "widowed", "divorced", "separated",
        "nevermarried", "unmarriedpartner", "unknown"
    -->
    <!ATTLIST maritalStatus
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA "NCIC-2000"
        codeLiteral CDATA #IMPLIED>
<!ELEMENT medicalCondition (#PCDATA)>
    <!ATTLIST medicalCondition
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA "NCIC-2000"
        codeLiteral CDATA #IMPLIED>
<!ELEMENT middleName (#PCDATA)>
    <!ATTLIST middleName
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT namePrefix (#PCDATA)>
    <!ATTLIST namePrefix
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
```

Electronic Court Filing Draft Specification

```
        codeLiteral CDATA #IMPLIED>
<!ELEMENT nameSuffix (#PCDATA)>
  <!ATTLIST nameSuffix
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT numberOfIdenticalCharges (#PCDATA)>
  <!ATTLIST numberOfIdenticalCharges
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT occupation (#PCDATA)>
  <!ATTLIST occupation
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT offenderNotice (#PCDATA)>
  <!ATTLIST offenderNotice
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT offenseCode (#PCDATA)>
  <!ATTLIST offenseCode
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT offenseDate (#PCDATA)>
  <!-- Same format as date -->
  <!ATTLIST offenseDate
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "ISO 8601"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT ori (#PCDATA)>
```

Electronic Court Filing Draft Specification

```
<!ATTLIST ori
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT personalIDNumber (#PCDATA)>
    <!ATTLIST personalIDNumber
        issuingAuthority CDATA #IMPLIED
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT postalCode (#PCDATA)>
    <!ATTLIST postalCode
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT postOfficeBox (#PCDATA)>
    <!ATTLIST postOfficeBox
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT purposeCode (#PCDATA)>
<!-- Limited to the characters, 'A', 'C', 'D', 'F', 'H', 'I', 'J', 'S', 'V',
'X' -->
    <!ATTLIST purposeCode
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT race (#PCDATA)>
    <!-- Required to be from the list
        "white", "black", "asian", "nativeAmerican", "unknown"
-->
    <!ATTLIST race
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
```

Electronic Court Filing Draft Specification

```
        codeSource CDATA "NCIC-2000"
        codeLiteral CDATA #IMPLIED>
<!ELEMENT relatedLocation (#PCDATA)>
  <!ATTLIST relatedLocation
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT religion (#PCDATA)>
  <!ATTLIST religion
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT scarsMarksTattoosDescription (#PCDATA)>
  <!ATTLIST scarsMarksTattoosDescription
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT sex (#PCDATA)>
  <!-- Required to be from the list
    "male", "female", "other", "unknown"
  -->
  <!ATTLIST sex
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT skinTone (#PCDATA)>
  <!-- Required to be from the list
    "albino", "black", "dark", "darkBrown", "fair", "light",
    "lightBrown", "medium", "mediumBrown", "olive", "ruddy",
    "sallow", "yellow", "unknown"
  -->
  <!ATTLIST skinTone
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT state (#PCDATA)>
  <!-- Use either the US Postal Service 2 character ("USPS") codes
```

## Electronic Court Filing Draft Specification

for states and provinces, the FBI standard codes, or, for legacy data that can not be converted, use a literal.

```
-->
<!ATTLIST state
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource (USPS | FBI | Literal) "USPS"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT streetDirection (#PCDATA)>
    <!ATTLIST streetDirection
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT streetName (#PCDATA)>
    <!ATTLIST streetName
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT streetNumber (#PCDATA)>
    <!ATTLIST streetNumber
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT streetType (#PCDATA)>
    <!ATTLIST streetType
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT telephoneCityCode (#PCDATA)>
    <!ATTLIST telephoneCityCode
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT telephoneCountryCode (#PCDATA)>
```

Electronic Court Filing Draft Specification

```
<!ATTLIST telephoneCountryCode
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT telephoneNumber (#PCDATA)>
    <!ATTLIST telephoneNumber
        format CDATA #IMPLIED
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT telephoneSuffix (#PCDATA)>
    <!ATTLIST telephoneSuffix
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT time (#PCDATA)>
<!-- Use ISO 8601 based format for local times only, i.e.,
hh[:mm[:ss[.d...d]]]-hh[:mm]
hh[:mm[:ss[.d...d]]]+h[:mm]
hh[:mm[:ss[.d...d]]]
-->
    <!ATTLIST time
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleBrand (#PCDATA)>
    <!ATTLIST vehicleBrand
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA "NCIC-2000"
        codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleColor (#PCDATA)>
    <!ATTLIST vehicleColor
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
```

Electronic Court Filing Draft Specification

```
        codeSource CDATA "NCIC-2000"
        codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleDescription (#PCDATA)>
  <!ATTLIST vehicleDescription
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleEnginePower (#PCDATA)>
  <!ATTLIST vehicleEnginePower
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleLeased (#PCDATA)>
  <!ATTLIST vehicleLeased
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleMake (#PCDATA)>
  <!ATTLIST vehicleMake
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleModel (#PCDATA)>
  <!ATTLIST vehicleModel
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleModelYear (#PCDATA)>
<!-- Required format CCYY -->
  <!ATTLIST vehicleModelYear
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
```

Electronic Court Filing Draft Specification

```
<!ELEMENT vehicleOwnerAppliedName (#PCDATA)>
  <!ATTLIST vehicleOwnerAppliedName
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleRegistrationExpiration (#PCDATA)>
<!-- Required format CCYY[-MM] -->
  <!ATTLIST vehicleRegistrationExpiration
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleRegistrationNumber (#PCDATA)>
  <!ATTLIST vehicleRegistrationNumber
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleSerialNumber (#PCDATA)>
  <!ATTLIST vehicleSerialNumber
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleStyle (#PCDATA)>
  <!ATTLIST vehicleStyle
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleType (#PCDATA)>
  <!ATTLIST vehicleType
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT vehicleVisibleID (#PCDATA)>
  <!ATTLIST vehicleVisibleID
```

Electronic Court Filing Draft Specification

```
        id ID #IMPLIED
        type CDATA #IMPLIED
        status CDATA #IMPLIED
        referenceDate CDATA #IMPLIED
        codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED
        codeLiteral CDATA #IMPLIED>
<!ELEMENT vin (#PCDATA)>
  <!ATTLIST vin
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT weaponDescription (#PCDATA)>
  <!ATTLIST weaponDescription
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT weaponFinish (#PCDATA)>
  <!ATTLIST weaponFinish
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT weaponID (#PCDATA)>
  <!ATTLIST weaponID
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>
<!ELEMENT weaponMake (#PCDATA)>
  <!ATTLIST weaponMake
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT weaponModel (#PCDATA)>
  <!ATTLIST weaponModel
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
```

## Electronic Court Filing Draft Specification

```
referenceDate CDATA #IMPLIED
codeValue CDATA #IMPLIED
codeSource CDATA "NCIC-2000"
codeLiteral CDATA #IMPLIED>
<!ELEMENT weaponType (#PCDATA)>
  <!ATTLIST weaponType
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA "NCIC-2000"
    codeLiteral CDATA #IMPLIED>
<!ELEMENT weight (#PCDATA)>
  <!ATTLIST weight
    units (Pounds | Kilograms | Grams) "Pounds"
    id ID #IMPLIED
    type CDATA #IMPLIED
    status CDATA #IMPLIED
    referenceDate CDATA #IMPLIED
    codeValue CDATA #IMPLIED
    codeSource CDATA #IMPLIED
    codeLiteral CDATA #IMPLIED>

<!-- Court Filing Horizontal Elements -->
<!ELEMENT barMembershipInformation (barNumber, licenseAuthority,
yearAdmitted?, barStatus?)>
  <!ELEMENT licenseAuthority (#PCDATA)>
  <!ELEMENT barNumber (#PCDATA)>
  <!ELEMENT yearAdmitted (#PCDATA)>
  <!ELEMENT barStatus (#PCDATA)>
<!ELEMENT dateTime (date, time)>
<!ELEMENT duration (#PCDATA)>
<!ELEMENT entity (agencyID | organizationID | originatingJurisdiction)>
  <!ATTLIST entity type CDATA #REQUIRED>
<!ELEMENT fee (#PCDATA)>
  <!ATTLIST fee type CDATA #REQUIRED>
<!ELEMENT name (personName | entity | thing)>
  <!ATTLIST name id ID #IMPLIED
    type CDATA #IMPLIED
    matchWith CDATA #IMPLIED>
<!ELEMENT paymentInformation (credit | debit | account | cash | check |
negotiableInstrument)>
  <!ELEMENT credit (amount, accountNumber, expiration, cardHolder?)>
  <!ELEMENT debit (amount, accountNumber, expiration, cardHolder?)>
  <!ELEMENT account (amount, accountNumber, cardHolder?)>
  <!ELEMENT cardHolder ((personName | entity)?,(postalAddress | email |
fax | uri))>
  <!ELEMENT expiration (date)>
  <!ELEMENT cash (#PCDATA)>
  <!ELEMENT amount (#PCDATA)>
  <!ELEMENT check (amount, financialInstitution, routingNumber,
accountNumber, payee, signer)>
    <!ATTLIST check sequenceNumber CDATA #IMPLIED
      business (Yes | No) "No">
  <!ELEMENT negotiableInstrument (amount, financialInstitution,
instrumentNumber, payee, signer)>
```

## Electronic Court Filing Draft Specification

```
<!ATTLIST negotiableInstrument type CDATA #IMPLIED
        value CDATA #IMPLIED>
<!ELEMENT accountNumber (#PCDATA)>
    <!ATTLIST accountNumber format CDATA #IMPLIED>
<!ELEMENT instrumentNumber (#PCDATA)>
    <!ATTLIST instrumentNumber format CDATA #IMPLIED>
<!ELEMENT financialInstitution (entity)>
<!ELEMENT routingNumber (#PCDATA)>
<!ELEMENT payee ((personName | entity)?,(postalAddress | email | fax |
uri))>
    <!ELEMENT signer ((personName | entity)?,(postalAddress | email | fax |
uri))>
<!ELEMENT designation (#PCDATA | barMembershipInformation)*>
<!ELEMENT signature ANY>
<!ELEMENT thing (#PCDATA | vehicle | weapon)*>
<!ELEMENT uri (#PCDATA)>

<!-- Specific Case Type elements -->
<!ELEMENT custody (date, physicalLocation)>
    <!ATTLIST custody status CDATA #REQUIRED
        defendantID IDREF #REQUIRED>
<!ELEMENT incident (date, physicalLocation, clockedSpeed?, speedLimit?)>
    <!ATTLIST incident chargeID IDREF #REQUIRED>
    <!ELEMENT clockedSpeed (#PCDATA)>
    <!ELEMENT speedLimit (#PCDATA)>
<!ELEMENT bail (paymentInformation)>
    <!ATTLIST bail chargeID IDREF #REQUIRED
        type CDATA #IMPLIED
        referenceDate CDATA #REQUIRED>
<!ELEMENT booking (fingerprint)>
    <!ATTLIST booking chargeID IDREF #REQUIRED
        agencyID IDREF #REQUIRED
        referenceDate IDREF #REQUIRED>
<!ELEMENT caseDisposition (#PCDATA)>
<!ATTLIST caseDisposition codeValue CDATA #IMPLIED
        codeSource CDATA #IMPLIED>
```