



# Web Services Reliable Messaging Policy Assertion (WS-RM Policy) Version 1.1

## Committee Specification

11 April 2007

### Specification URIs:

#### This Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cs-01.pdf>  
<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cs-01.html>  
<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cs-01.doc>

#### Previous Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-09.pdf>  
<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-09.html>  
<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-09.doc>

#### Latest Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/v1.1/wsrmp.pdf>  
<http://docs.oasis-open.org/ws-rx/wsrmp/v1.1/wsrmp.html>  
<http://docs.oasis-open.org/ws-rx/wsrmp/v1.1/wsrmp.doc>

### Technical Committee:

OASIS Web Services Reliable Exchange (WS-RX) TC

### Chairs:

Paul Fremantle <[paul@wso2.com](mailto:paul@wso2.com)>  
Sanjay Patil <[sanjay.patil@sap.com](mailto:sanjay.patil@sap.com)>

### Editors:

Doug Davis, IBM <[dug@us.ibm.com](mailto:dug@us.ibm.com)>  
Anish Karmarkar, Oracle <[Anish.Karmarkar@oracle.com](mailto:Anish.Karmarkar@oracle.com)>  
Gilbert Pilz, BEA <[gpilz@bea.com](mailto:gpilz@bea.com)>  
Ümit Yalçınalp, SAP <[umit.yalcinalp@sap.com](mailto:umit.yalcinalp@sap.com)>

### Related Work:

This specification replaces or supercedes:

- WS-ReliableMessaging Policy v1.0

### Declared XML Namespaces:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702>

### Abstract:

This specification describes a domain-specific policy assertion for WS-ReliableMessaging [WS-RM] that that can be specified within a policy alternative as defined in WS-Policy Framework [WS-Policy].

By using the XML [XML], SOAP [SOAP 1.1], [SOAP 1.2] and WSDL [WSDL 1.1] extensibility models, the WS\* specifications are designed to be composed with each other to provide a rich Web services environment. This by itself does not provide a negotiation solution for Web services. This is a building block that is used in conjunction with other Web service and application-specific protocols to accommodate a wide variety of policy exchange models.

43 **Status:**

44 This document was last revised or approved by the WS-RX Technical Committee on the above  
45 date. The level of approval is also listed above. Check the "Latest Version" or "Latest Approved  
46 Version" location noted above for possible later revisions of this document.

47 Technical Committee members should send comments on this specification to the Technical  
48 Committee's email list. Others should send comments to the Technical Committee by using the  
49 "Send A Comment" button on the Technical Committee's web page at [http://www.oasis-  
open.org/committees/ws-rx/](http://www.oasis-<br/>50 open.org/committees/ws-rx/).

51 For information on whether any patents have been disclosed that may be essential to  
52 implementing this specification, and any offers of patent licensing terms, please refer to the  
53 Intellectual Property Rights section of the Technical Committee web page ([http://www.oasis-  
open.org/committees/ws-rx/ipr.php](http://www.oasis-<br/>54 open.org/committees/ws-rx/ipr.php)).

55 The non-normative errata page for this specification is located at [http://www.oasis-  
open.org/committees/ws-rx/](http://www.oasis-<br/>56 open.org/committees/ws-rx/).

---

## 57 Notices

58 Copyright © OASIS® 1993–2007. All Rights Reserved. OASIS trademark, IPR and other policies apply.

59 All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual  
60 Property Rights Policy (the "OASIS IPR Policy"). The full Policy may be found at the OASIS website.

61 This document and translations of it may be copied and furnished to others, and derivative works that  
62 comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and  
63 distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and  
64 this section are included on all such copies and derivative works. However, this document itself may not be  
65 modified in any way, including by removing the copyright notice or references to OASIS, except as needed  
66 for the purpose of developing any document or deliverable produced by an OASIS Technical Committee  
67 (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or  
68 as required to translate it into languages other than English.

69 The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors  
70 or assigns.

71 This document and the information contained herein is provided on an "AS IS" basis and OASIS  
72 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY  
73 WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY  
74 OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A  
75 PARTICULAR PURPOSE.

76 OASIS requests that any OASIS Party or any other party that believes it has patent claims that would  
77 necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to  
78 notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such  
79 patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced  
80 this specification.

81 OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any  
82 patent claims that would necessarily be infringed by implementations of this specification by a patent  
83 holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR  
84 Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims  
85 on its website, but disclaims any obligation to do so.

86 OASIS takes no position regarding the validity or scope of any intellectual property or other rights that  
87 might be claimed to pertain to the implementation or use of the technology described in this document or  
88 the extent to which any license under such rights might or might not be available; neither does it represent  
89 that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to  
90 rights in any document or deliverable produced by an OASIS Technical Committee can be found on the  
91 OASIS website. Copies of claims of rights made available for publication and any assurances of licenses  
92 to be made available, or the result of an attempt made to obtain a general license or permission for the use  
93 of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS  
94 Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any  
95 information or list of intellectual property rights will at any time be complete, or that any claims in such list  
96 are, in fact, Essential Claims.

97 The name "OASIS", WS-ReliableMessaging Policy, WS-ReliableMessaging, WSRMP, WSRM, WS-RX are  
98 trademarks of OASIS, the owner and developer of this specification, and should be used only to refer to  
99 the organization and its official outputs. OASIS welcomes reference to, and implementation and use of,  
100 specifications, while reserving the right to enforce its marks against misleading uses. Please see  
101 <http://www.oasis-open.org/who/trademark.php> for above guidance.

---

## 102 Table of Contents

103	1	Introduction .....	5
104	1.1	Terminology .....	5
105	1.2	Normative .....	5
106	1.3	Non Normative .....	6
107	1.4	Namespace .....	7
108	1.5	Conformance .....	7
109	2	RM Policy Assertions .....	8
110	2.1	Assertion Model .....	8
111	2.2	Normative Outline .....	8
112	2.3	Assertion Attachment .....	9
113	2.4	Assertion Example .....	11
114	2.5	Sequence Security Policy .....	11
115	3	Security Considerations .....	13
116		Appendix A. Schema .....	14
117		Appendix B. Acknowledgments .....	16
118			

---

# 119 1 Introduction

120 This specification defines a domain-specific policy assertion for reliable messaging for use with WS-Policy  
121 and WS-ReliableMessaging.

## 122 1.1 Terminology

123 The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD  
124 NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described  
125 in RFC 2119 [[KEYWORDS](#)].

126 This specification uses the following syntax to define normative outlines for messages:

- 127 • The syntax appears as an XML instance, but values in italics indicate data types instead of values.
- 128 • Characters are appended to elements and attributes to indicate cardinality:
  - 129 ○ "?" (0 or 1)
  - 130 ○ "\*" (0 or more)
  - 131 ○ "+" (1 or more)
- 132 • The character "|" is used to indicate a choice between alternatives.
- 133 • The characters "[" and "]" are used to indicate that contained items are to be treated as a group  
134 with respect to cardinality or choice.
- 135 • An ellipsis (i.e. "...") indicates a point of extensibility that allows other child, or attribute, content.  
136 Additional children and/or attributes MAY be added at the indicated extension points but MUST  
137 NOT contradict the semantics of the parent and/or owner, respectively. If an extension is not  
138 recognized it SHOULD be ignored.
- 139 • XML namespace prefixes (see section 1.4) are used to indicate the namespace of the element  
140 being defined.

141 Elements and Attributes defined by this specification are referred to in the text of this document using  
142 XPath 1.0 [[XPATH 1.0](#)] expressions. Extensibility points are referred to using an extended version of this  
143 syntax:

- 144 • An element extensibility point is referred to using {any} in place of the element name. This  
145 indicates that any element name can be used, from any namespace other than the wsrn:  
146 namespace.
- 147 • An attribute extensibility point is referred to using @{any} in place of the attribute name. This  
148 indicates that any attribute name can be used, from any namespace other than the wsrn:  
149 namespace.

## 150 1.2 Normative

151 **[KEYWORDS]** S. Bradner, "[Key words for use in RFCs to Indicate Requirement Levels](#)," RFC  
152 2119, Harvard University, March 1997.  
153 <http://www.ietf.org/rfc/rfc2119.txt>

154 **[SOAP 1.1]** W3C Note, "[SOAP: Simple Object Access Protocol 1.1](#)" 08 May 2000.  
155 <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

156	<b>[SOAP 1.2]</b>	W3C Recommendation, "SOAP Version 1.2 Part 1: Messaging Framework" June 2003. <a href="http://www.w3.org/TR/2003/REC-soap12-part1-20030624/">http://www.w3.org/TR/2003/REC-soap12-part1-20030624/</a>
157		
158		
159	<b>[URI]</b>	T. Berners-Lee, R. Fielding, L. Masinter, "Uniform Resource Identifiers (URI): Generic Syntax," RFC 3986, MIT/LCS, U.C. Irvine, Xerox Corporation, January 2005. <a href="http://ietf.org/rfc/rfc3986">http://ietf.org/rfc/rfc3986</a>
160		
161		
162		
163	<b>[WS-RM]</b>	OASIS WS-RX Technical Committee Specification, "Web Services Reliable Messaging (WS-ReliableMessaging)," April 2007. <a href="http://docs.oasis-open.org/ws-rx/wsrn/v1.1/wsrn.pdf">http://docs.oasis-open.org/ws-rx/wsrn/v1.1/wsrn.pdf</a>
164		
165		
166	<b>[WSDL 1.1]</b>	W3C Note, "Web Services Description Language (WSDL 1.1)," 15 March 2001. <a href="http://www.w3.org/TR/2001/NOTE-wsdl-20010315">http://www.w3.org/TR/2001/NOTE-wsdl-20010315</a>
167		
168	<b>[XML]</b>	W3C Recommendation, "Extensible Markup Language (XML) 1.0 (Fourth Edition)," September 2006. <a href="http://www.w3.org/TR/REC-xml/">http://www.w3.org/TR/REC-xml/</a>
169		
170		
171	<b>[XML-ns]</b>	W3C Recommendation, "Namespaces in XML," 14 January 1999. <a href="http://www.w3.org/TR/1999/REC-xml-names-19990114/">http://www.w3.org/TR/1999/REC-xml-names-19990114/</a>
172		
173	<b>[XML-Schema Part1]</b>	W3C Recommendation, "XML Schema Part 1: Structures," October 2004. <a href="http://www.w3.org/TR/xmlschema-1/">http://www.w3.org/TR/xmlschema-1/</a>
174		
175	<b>[XML-Schema Part2]</b>	W3C Recommendation, "XML Schema Part 2: Datatypes," October 2004. <a href="http://www.w3.org/TR/xmlschema-2/">http://www.w3.org/TR/xmlschema-2/</a>
176		
177	<b>[XPATH 1.0]</b>	W3C Recommendation, "XML Path Language (XPath) Version 1.0," 16 November 1999. <a href="http://www.w3.org/TR/xpath">http://www.w3.org/TR/xpath</a>
178		
179		

### 180 **1.3 Non Normative**

181	<b>[RDDL 2.0]</b>	Jonathan Borden, Tim Bray, eds. "Resource Directory Description Language (RDDL) 2.0," January 2004 <a href="http://www.openhealth.org/RDDL/20040118/rddl-20040118.html">http://www.openhealth.org/RDDL/20040118/rddl-20040118.html</a>
182		
183		
184	<b>[SecurityPolicy]</b>	G. Della-Libra, et. al. "Web Services Security Policy Language (WS-SecurityPolicy)," July 2005 <a href="http://specs.xmlsoap.org/ws/2005/07/securitypolicy/ws-securitypolicy.pdf">http://specs.xmlsoap.org/ws/2005/07/securitypolicy/ws-securitypolicy.pdf</a>
185		
186		
187	<b>[WS-Policy]</b>	W3C Member Submission "Web Services Policy 1.2 - Framework", April 2006 <a href="http://www.w3.org/Submission/2006/SUBM-WS-Policy-20060425/">http://www.w3.org/Submission/2006/SUBM-WS-Policy-20060425/</a>
188		
189		
190		W3C Candidate Recommendation, "Web Services Policy 1.5 - Framework,"
191		February 2007.
192		<a href="http://www.w3.org/TR/2007/CR-ws-policy-20070228">http://www.w3.org/TR/2007/CR-ws-policy-20070228</a>
193	<b>[WS-PolicyAttachment]</b>	W3C Member Submission "Web Services Policy 1.2 - Attachment", April 2006 <a href="http://www.w3.org/Submission/2006/SUBM-WS-PolicyAttachment-20060425/">http://www.w3.org/Submission/2006/SUBM-WS-PolicyAttachment-20060425/</a>
194		
195		
196		
197		W3C Candidate Recommendation, "Web Services Policy 1.5 - Attachment,"
198		February 2007.
199		<a href="http://www.w3.org/TR/2007/CR-ws-policy-attach-20070228">http://www.w3.org/TR/2007/CR-ws-policy-attach-20070228</a>
200	<b>[WS-Security]</b>	Anthony Nadalin, Chris Kaler, Phillip Hallam-Baker, Ronald Monzillo, eds. "OASIS Web Services Security: SOAP Message Security 1.0 (WS-Security 2004)", OASIS Standard 200401, March 2004. <a href="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf">http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf</a>
201		
202		
203		
204		

205  
206  
207  
208  
209

Anthony Nadalin, Chris Kaler, Phillip Hallam-Baker, Ronald Monzillo, eds. "OASIS Web Services Security: SOAP Message Security 1.1 (WS-Security 2004)", OASIS Standard 200602, February 2006.  
<http://docs.oasis-open.org/wss/v1.1/wss-v1.1-spec-os-SOAPMessageSecurity.pdf>

## 210 1.4 Namespace

211 The XML namespace [XML-ns] URI that MUST be used by implementations of this specification is:

212 <http://docs.oasis-open.org/ws-rx/wsrmp/200702>

213 Dereferencing the above URI will produce the Resource Directory Description Language [RDDL 2.0]  
214 document that describes this namespace.

215 Table 1 lists the XML namespaces that are used in this specification. The choice of any namespace prefix  
216 is arbitrary and not semantically significant. The assertions defined within this specification have been  
217 designed to work independently of a specific version of WS-Policy. At the time of the publication of this  
218 specification the versions of WS-Policy known to correctly compose with this specification are WS-Policy  
219 1.2 and 1.5. Within this specification the use of the namespace prefix wsp refers generically to the WS-  
220 Policy namespace, not a specific version.

221 Table 1

Prefix	Namespace	Specification
wSDL	<a href="http://schemas.xmlsoap.org/wSDL/">http://schemas.xmlsoap.org/wSDL/</a>	[WSDL 1.1]
wsrmp	<a href="http://docs.oasis-open.org/ws-rx/wsrmp/200702">http://docs.oasis-open.org/ws-rx/wsrmp/200702</a>	This specification.
wsu	<a href="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd</a>	WS-Security-Utility Schema

222 The normative schema for WS-ReliableMessaging can be found linked from the namespace document that  
223 is located at the namespace URI specified above.

224 All sections explicitly noted as examples are informational and are not to be considered normative.

## 225 1.5 Conformance

226 An implementation is not compliant with this specification if it fails to satisfy one or more of the MUST or  
227 REQUIRED level requirements defined herein. A SOAP Node MUST NOT use the XML namespace  
228 identifier for this specification (listed in section 1.4) within SOAP Envelopes unless it is compliant with this  
229 specification.

230 Normative text within this specification takes precedence over normative outlines, which in turn take  
231 precedence over the XML Schema [XML-Schema Part1, XML-Schema Part2] descriptions.

---

## 232 2 RM Policy Assertions

233 WS-Policy Framework and WS-Policy Attachment [WS-PolicyAttachment] collectively define a framework,  
234 model and grammar for expressing the requirements, and general characteristics of entities in an XML  
235 Web services-based system. To enable an RM Destination and an RM Source to describe their  
236 requirements for a given Sequence, this specification defines a single RM policy assertion that leverages  
237 the WS-Policy framework.

### 238 2.1 Assertion Model

239 The RM policy assertion indicates that the RM Source and RM Destination **MUST** use WS-  
240 ReliableMessaging to ensure reliable delivery of messages. Specifically, the WS-ReliableMessaging  
241 protocol determines invariants maintained by the reliable messaging endpoints and the directives used to  
242 track and manage the delivery of a Sequence of messages.

### 243 2.2 Normative Outline

244 The normative outline for the RM assertion is:

```
245 <wsrmp:RMAssertion [wsp:Optional="true"]? ... >  
246   <wsp:Policy>  
247     [ <wsrmp:SequenceSTR/> |  
248       <wsrmp:SequenceTransportSecurity/> ] ?  
249     <wsrmp:DeliveryAssurance>  
250       <wsp:Policy>  
251         [ <wsrmp:ExactlyOnce/> |  
252           <wsrmp:AtLeastOnce/> |  
253             <wsrmp:AtMostOnce/> ]  
254         <wsrmp:InOrder/> ?  
255       </wsp:Policy>  
256     </wsrmp:DeliveryAssurance> ?  
257   </wsp:Policy>  
258   ...  
259 </wsrmp:RMAssertion>
```

260 The following describes the content model of the `RMAssertion` element.

261 `/wsrmp:RMAssertion`

262     A policy assertion that specifies that WS-ReliableMessaging protocol **MUST** be used when  
263     sending messages.

264 `/wsrmp:RMAssertion/@wsp:Optional="true"`

265     Per WS-Policy, this is compact notation for two policy alternatives, one with and one without the  
266     assertion. The intuition is that the behavior indicated by the assertion is optional, or in this case,  
267     that WS-ReliableMessaging **MAY** be used.

268 `/wsrmp:RMAssertion/wsp:Policy`

269     This required element allows for the inclusion of nested policy assertions.

270 `/wsrmp:RMAssertion/wsp:Policy/wsrmp:SequenceSTR`

271     When present, this assertion defines the requirement that an RM Sequence **MUST** be bound to an  
272     explicit token that is referenced from a `wsse:SecurityTokenReference` in the  
273     `CreateSequence` message. See section 2.5.1.



274 /wsrmp:RMAssertion/wsp:Policy/wsrmp:SequenceTransportSecurity

275       When present, this assertion defines the requirement that an RM Sequence MUST be bound to

276       the session(s) of the underlying transport-level protocol used to carry the `CreateSequence` and

277       `CreateSequenceResponse` message. When present, this assertion MUST be used in

278       conjunction with the `sp:TransportBinding` assertion, see section 2.5.2.

279 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance

280       This expression, which may be omitted, describes the message delivery quality of service between

281       the RM and application layer. When used by an RM Destination it expresses the delivery

282       assurance in effect between the RM Destination and its corresponding application destination, and

283       it also indicates requirements on any RM Source that transmits messages to this RM destination.

284       Conversely when used by an RM Source it expresses the delivery assurance in effect between the

285       RM Source and its corresponding application source, as well as indicating requirements on any

286       RM Destination that receives messages from this RM Source. In either case the delivery

287       assurance does not affect the messages transmitted on the wire. Absence of this expression from

288       a `wsrmp:RMAssertion` policy assertion simply means that the endpoint has chosen not to

289       advertise its delivery assurance characteristics.

290       Note that when there are multiple policy alternatives of the RM Assertion, the Delivery Assurance

291       on each MUST NOT conflict.

292 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy

293       This required element identifies additional requirements for the use of the

294       `wsrmp:DeliveryAssurance`.

295 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:ExactlyOnce

296       This expresses the ExactlyOnce Delivery Assurance defined in [WS-RM].

297 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:AtLeastOnce

298       This expresses the AtLeastOnce Delivery Assurance defined in [WS-RM].

299 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:AtMostOnce

300       This expresses the AtMostOnce Delivery Assurance defined in [WS-RM].

301 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:InOrder

302       This expresses the InOrder Delivery Assurance defined in [WS-RM].

303 /wsrmp:RMAssertion/{any}

304       This is an extensibility mechanism to allow different (extensible) types of information, based on a

305       schema, to be passed.

306 /wsrmp:RMAssertion/@{any}

307       This is an extensibility mechanism to allow different (extensible) types of information, based on a

308       schema, to be passed.

### 309 **2.3 Assertion Attachment**

310 The RM policy assertion is allowed to have the following Policy Subjects [WS-PolicyAttachment]:

- 311       • Endpoint Policy Subject
- 312       • Message Policy Subject

313 WS-PolicyAttachment defines a set of WSDL/1.1 policy attachment points for each of the above Policy  
314 Subjects. Since an RM policy assertion specifies a concrete behavior, it MUST NOT be attached to the  
315 abstract WSDL policy attachment points.

316 The following is the list of WSDL/1.1 elements whose scope contains the Policy Subjects allowed for an  
317 RM policy assertion but which MUST NOT have RM policy assertions attached:

- 318 • wsdl:message
- 319 • wsdl:portType/wsdl:operation/wsdl:input
- 320 • wsdl:portType/wsdl:operation/wsdl:output
- 321 • wsdl:portType/wsdl:operation/wsdl:fault
- 322 • wsdl:portType

323 The following is the list of WSDL/1.1 elements whose scope contains the Policy Subjects allowed for an  
324 RM policy assertion and which MAY have RM policy assertions attached:

- 325 • wsdl:port
- 326 • wsdl:binding
- 327 • wsdl:binding/wsdl:operation/wsdl:input
- 328 • wsdl:binding/wsdl:operation/wsdl:output
- 329 • wsdl:binding/wsdl:operation/wsdl:fault

330 If an RM policy assertion is attached to any of:

- 331 • wsdl:binding/wsdl:operation/wsdl:input
- 332 • wsdl:binding/wsdl:operation/wsdl:output
- 333 • wsdl:binding/wsdl:operation/wsdl:fault

334 then an RM policy assertion, specifying `wsp:Optional="true"` MUST be attached to the corresponding  
335 `wsdl:binding` or `wsdl:port`, indicating that the endpoint supports WS-RM. Any messages, regardless  
336 of whether they have an attached Message Policy Subject RM policy assertion, MAY be sent to that  
337 endpoint using WS-RM. Additionally, the receiving endpoint MUST NOT reject any message belonging to  
338 a Sequence, simply because there was no Message Policy Subject RM policy assertion attached to that  
339 message. There might be certain RM implementations that are incapable of applying RM Quality of  
340 Service (QoS) semantics on a per-message basis. In order to ensure the broadest interoperability, when  
341 an endpoint decorates its WSDL with RM policy assertions using Message Policy Subject, it MUST also be  
342 prepared to accept that all messages sent to that endpoint might be sent within the context of an RM  
343 Sequence, regardless of whether the corresponding `wsdl:input`, `wsdl:output` or `wsdl:fault` had an attached  
344 RM policy assertion.

345 Rather than turn away messages that were unnecessarily sent with RM semantics, the receiving endpoint  
346 described by the WSDL MUST accept these messages.

347 By attaching an RM policy assertion that specifies `wsp:Optional="true"` to the corresponding endpoint  
348 that has attached RM policy assertions at the Message Policy Subject level, the endpoint is describing the  
349 above constraint in policy.

350 In the case where an optional RM Assertion applies to an output message, there is no requirement on the  
351 client to support an RM Destination implementation

## 352 2.4 Assertion Example

353 Table 2 lists an example use of the RM policy assertion.

354 Table 2: Example policy with RM policy assertion

```
355 (01) <wsdl:definitions
356 (02)   targetNamespace="example.com"
357 (03)   xmlns:tns="example.com"
358 (04)   xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
359 (05)   xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
360 (06)   xmlns:wsrmp="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
361 (07)   xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
362 wssecurity-utility-1.0.xsd">
363 (08)
364 (09) <wsp:UsingPolicy wsdl:required="true" />
365 (10)
366 (11) <wsp:Policy wsu:Id="MyPolicy" >
367 (12)   <wsrmp:RMAssertion>
368 (13)     <wsp:Policy/>
369 (14)   </wsrmp:RMAssertion>
370 (15)   <!-- omitted assertions -->
371 (16) </wsp:Policy>
372 (17)
373 (18) <!-- omitted elements -->
374 (19)
375 (20) <wsdl:binding name="MyBinding" type="tns:MyPortType" >
376 (21)   <wsp:PolicyReference URI="#MyPolicy" />
377 (22)   <!-- omitted elements -->
378 (23) </wsdl:binding>
379 (24)
380 (25) </wsdl:definitions>
```

381 Line (09) in Table 2 indicates that WS-Policy is in use as a required extension.

382 Lines (11-16) are a policy expression that includes a RM policy assertion (lines 12-14) to indicate that WS-  
383 ReliableMessaging must be used.

384 Lines (20-23) are a WSDL binding. Line (21) indicates that the policy in lines (11-16) applies to this  
385 binding, specifically indicating that WS-ReliableMessaging must be used over all the messages in the  
386 binding.

## 387 2.5 Sequence Security Policy

388 WS-SecurityPolicy [[SecurityPolicy](#)] provides a framework and grammar for expressing the security  
389 requirements and characteristics of entities in a XML web services based system. The following assertions  
390 MAY be used in conjunction with WS-SecurityPolicy to express additional security requirements particular  
391 to RM Sequences.

### 392 2.5.1 RM Assertion with Sequence STR Assertion

393 This version of the RM assertion includes the requirement that an RM Sequence MUST be bound to an  
394 explicit token that is referenced from a `wsse:SecurityTokenReference` in the `CreateSequence`  
395 message.

396 This assertion MUST apply to [Endpoint Policy Subject]. The normative outline for this form of the  
397 Sequence STR Assertion is:

```
398 <wsrmp:RMAssertion [wsp:Optional="true"]? ...>
399   <wsp:Policy>
```

```
400     <wsrmp:SequenceSTR/>
401     <wsp:Policy>
402 </wsrmp:RMAssertion>
```

403 The following describes the content model of the `SequenceSTR` element.

404 `/wsrmp:SequenceSTR`

405 A policy assertion that specifies security requirements which MUST be used with an RM Sequence  
406 that are particular to WS-RM and beyond what can be expressed in WS-SecurityPolicy.

## 407 **2.5.2 RM Assertion with Sequence Transport Security Assertion**

408 This version of the RM assertion includes the requirement that an RM Sequence MUST be bound to the  
409 session(s) of the underlying transport-level security protocol (e.g. SSL/TLS) used to carry the  
410 `CreateSequence` and `CreateSequenceResponse` messages.

411 This assertion MUST apply to [Endpoint Policy Subject]. This assertion MUST be used in conjunction with  
412 the `sp:TransportBinding` assertion that requires the use of some transport-level security mechanism  
413 (e.g. `sp:HttpsToken`).

414 The normative outline for this form of the RM Assertion with the Sequence Transport Security Assertion is:

```
415     <wsp:Policy>
416     <wsp:ExactlyOne>
417     <wsp:All>
418     <wsrm:RMAssertion [wsp:Optional="true"]> ...>
419     <wsp:Policy>
420     <wsrmp:SequenceTransportSecurity/>
421     </wsp:Policy>
422     </wsrm:RMAssertion>
423     <sp:TransportBinding ...>
424     ...
425     </sp:TransportBinding>
426     </wsp:All>
427     </wsp:ExactlyOne>
428 </wsp:Policy>
```

429 The following describes the content model of the `SequenceTransportSecurity` element.

430 `/wsrmp:SequenceTransportSecurity`

431 A policy assertion that specifies that any Sequences targeted to the indicated endpoint MUST be  
432 bound to the underlying session(s) of the transport-level security used to carry messages related to the  
433 Sequence.

434 This form of the RM Assertion says that an endpoint MAY have RM as an option but always requires  
435 HTTPS to be used. All the `SequenceTransportSecurity` assertion indicates is that RM's rules for protecting  
436 the Sequence over TLS are followed.

---

## 437 **3 Security Considerations**

438 It is strongly RECOMMENDED that policies and assertions be signed to prevent tampering.

439 It is RECOMMENDED that policies SHOULD NOT be accepted unless they are signed and have an  
440 associated security token to specify the signer has proper claims for the given policy. That is, a relying  
441 party shouldn't rely on a policy unless the policy is signed and presented with sufficient claims to pass the  
442 relying parties acceptance criteria.

443 It should be noted that the mechanisms described in this document could be secured as part of a SOAP  
444 message using WS-Security [[WS-Security](#)] or embedded within other objects using object-specific security  
445 mechanisms.

---

## 446 Appendix A. Schema

447 A normative copy of the XML Schema [XML-Schema Part1, XML-Schema Part2] description for this  
448 specification may be retrieved from the following address:

449 <http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-schema-200702.xsd>

450 The following copy is provided for reference.

```
451 <?xml version="1.0" encoding="UTF-8"?>
452 <!-- Copyright (C) OASIS (R) 1993-2007. All Rights Reserved.
453      OASIS trademark, IPR and other policies apply. -->
454 <xs:schema xmlns:tns="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
455   xmlns:xs="http://www.w3.org/2001/XMLSchema" targetNamespace="http://docs.oasis-
456   open.org/ws-rx/wsrmp/200702" elementFormDefault="qualified"
457   attributeFormDefault="unqualified">
458   <xs:element name="RMAssertion">
459     <xs:complexType>
460       <xs:sequence>
461         <xs:any namespace="##other" processContents="lax" minOccurs="0"
462 maxOccurs="unbounded"/>
463       </xs:sequence>
464       <xs:anyAttribute namespace="##any" processContents="lax"/>
465     </xs:complexType>
466   </xs:element>
467   <xs:element name="SequenceSTR">
468     <xs:complexType>
469       <xs:sequence/>
470       <xs:anyAttribute namespace="##any" processContents="lax"/>
471     </xs:complexType>
472   </xs:element>
473   <xs:element name="SequenceTransportSecurity">
474     <xs:complexType>
475       <xs:sequence/>
476       <xs:anyAttribute namespace="##any" processContents="lax"/>
477     </xs:complexType>
478   </xs:element>
479   <xs:element name="DeliveryAssurance">
480     <xs:complexType>
481       <xs:sequence>
482         <xs:any namespace="##any" processContents="lax" minOccurs="0"
483 maxOccurs="unbounded"/>
484       </xs:sequence>
485     </xs:complexType>
486   </xs:element>
487   <xs:element name="ExactlyOnce">
488     <xs:complexType>
489       <xs:sequence/>
490     </xs:complexType>
491   </xs:element>
492   <xs:element name="AtLeastOnce">
493     <xs:complexType>
494       <xs:sequence/>
495     </xs:complexType>
496   </xs:element>
497   <xs:element name="AtMostOnce">
498     <xs:complexType>
499       <xs:sequence/>
500     </xs:complexType>
```

```
501 </xs:element>
502 <xs:element name="InOrder">
503   <xs:complexType>
504     <xs:sequence/>
505   </xs:complexType>
506 </xs:element>
507 </xs:schema>
```

---

## 508 Appendix B. Acknowledgments

509 This document is based on initial contribution to OASIS WS-RX Technical Committee by the following  
510 authors:

511	Stefan Batres-Editor, Microsoft	523	David Langworthy, Microsoft
512	Ruslan Bilursets, BEA	524	Amelia Lewis, TIBCO Software
513	Don Box, Microsoft	525	Rodney Limprecht, Microsoft
514	Luis Felipe Cabrera, Microsoft	526	Steve Lucco, Microsoft
515	Derek Collison, TIBCO Software	527	Don Mullen, TIBCO Software
516	Donald Ferguson, IBM	528	Anthony Nadalin, IBM
517	Christopher Ferris, IBM	529	Mark Nottingham, BEA
518	Tom Freund, IBM	530	David Orchard, BEA
519	Mary Ann Hondo, IBM	531	Shivajee Samdarshi, TIBCO Software
520	John Ibbotson, IBM	532	John Shewchuk, Microsoft
521	Lei Jin, BEA	533	Tony Storey, IBM
522	Chris Kaler, Microsoft		

534 The following individuals have provided invaluable input into the initial contribution:

535	Keith Ballinger, Microsoft	546	Frank Leymann, IBM
536	Allen Brown, Microsoft	547	Martin Nally, IBM
537	Michael Conner, IBM	548	Peter Niblett, IBM
538	Francisco Curbera, IBM	549	Jeffrey Schlimmer, Microsoft
539	Steve Graham, IBM	550	Chris Sharp, IBM
540	Pat Helland, Microsoft	551	James Snell, IBM
541	Rick Hill, Microsoft	552	Keith Stobie, Microsoft
542	Scott Hinkelman, IBM	553	Satish Thatte, Microsoft
543	Tim Holloway, IBM	554	Stephen Todd, IBM
544	Efim Hudis, Microsoft	555	Sanjiva Weerawarana, IBM
545	Johannes Klein, Microsoft	556	Roger Wolter, Microsoft

557 The following individuals were members of the committee during the development of this specification:

558	Abbie Barbir, Nortel	580	Alastair Green, Choreology
559	Charlton Barreto, Adobe	581	Mike Grogan, Sun
560	Stefan Batres, Microsoft	582	Ondrej Hrebicek, Microsoft
561	Hamid Ben Malek, Fujitsu	583	Kazunori Iwasa, Fujitsu
562	Andreas Bjarlestam, Ericsson	584	Chamikara Jayalath, WSO2
563	Toufic Boubez, Layer 7	585	Lei Jin, BEA
564	Doug Bunting, Sun	586	Ian Jones, BTplc
565	Lloyd Burch, Novell	587	Anish Karmarkar, Oracle
566	Steve Carter, Novell	588	Paul Knight, Nortel
567	Martin Chapman, Oracle	589	Dan Leshchiner, Tibco
568	Dave Chappell, Sonic	590	Mark Little, JBoss
569	Paul Cotton, Microsoft	591	Lily Liu, webMethods
570	Glen Daniels, Sonic	592	Matt Lovett, IBM
571	Doug Davis, IBM	593	Ashok Malhotra, Oracle
572	Blake Dournaee, Intel	594	Jonathan Marsh, Microsoft
573	Jacques Durand, Fujitsu	595	Daniel Millwood, IBM
574	Colleen Evans, Microsoft	596	Jeff Mischkinsky, Oracle
575	Christopher Ferris, IBM	597	Nilo Mitra, Ericsson
576	Paul Fremantle, WSO2	598	Peter Niblett, IBM
577	Robert Freund, Hitachi	599	Duane Nickull, Adobe
578	Peter Furniss, Erebor	600	Eisaku Nishiyama, Hitachi
579	Marc Goodner, Microsoft	601	Dave Orchard, BEA



602	Chouthri Palanisamy, NEC	610	Shivajee Samdarshi, Tibco
603	Sanjay Patil, SAP	611	Vladimir Videlov, SAP
604	Gilbert Pilz, BEA	612	Claus von Riegen, SAP
605	Martin Raeppe, SAP	613	Pete Wenzel, Sun
606	Eric Rajkovic, Oracle	614	Steve Winkler, SAP
607	Stefan Rossmann, SAP	615	Ümit Yalçınalp, SAP
608	Tom Rutt, Fujitsu	616	Nobuyuki Yamamoto, Hitachi
609	Rich Salz, IBM		
617			