

Liberty Architecture Implementation Guidelines

Draft Version 1.1-06

5 November 2002

Document identifier: draft-liberty-architecture-implementation-guidelines-06

Notice

- 32 Copyright © 2002 ActivCard; American Express Travel Related Services; America Online, Inc.; Bank of
- 33 America; Bell Canada; Cingular Wireless; Cisco Systems, Inc.; Citigroup; Communicator, Inc.; Consignia;
- Deloitte & Touche LLP; EarthLink, Inc.; Electronic Data Systems, Inc.; Entrust, Inc.; Ericsson; Fidelity
- 35 Investments; France Telecom; Gemplus; General Motors; Hewlett-Packard Company; i2 Technologies, Inc.;
- 36 Intuit Inc.; MasterCard International; NEC Corporation; Netegrity; NeuStar; Nextel Communications; Nippon
- 37 Telegraph and Telephone Company; Nokia Corporation; Novell, Inc.; NTT DoCoMo, Inc.; OneName
- Corporation; Openwave Systems Inc.; PricewaterhouseCoopers LLP; Register.com; RSA Security Inc; Sabre
- 39 Holdings Corporation; SAP AG; SchlumbergerSema; SK Telecom; Sony Corporation; Sun Microsystems,
- 40 Inc.; United Airlines; VeriSign, Inc.; Visa International; Vodafone Group Plc; Wave Systems. All rights
- 41 reserved.
- This specification document has been prepared by Sponsors of the Liberty Alliance. Permission is hereby
- granted to use the document solely for the purpose of implementing the Specification. No rights are granted to
- 44 prepare derivative works of this Specification. Entities seeking permission to reproduce portions of this
- document for other uses must contact the Liberty Alliance to determine whether an appropriate license for
- such use is available.
- 47 Implementation of the Specifications may involve the use of one or more of the following United States
- 48 Patents claimed by AOL Time Warner, Inc.: No.5,774,670, No.6,134,592, No.5,826,242, No. 5,825,890, and
- 49 No.5,671,279. The Sponsors of the Specification take no position concerning the evidence, validity or scope
- of the claimed subject matter of the aforementioned patents. Implementation of certain elements of this
- 51 Specification may also require licenses under third party intellectual property rights other than those identified
- above, including without limitation, patent rights. The Sponsors of the Specification are not and shall not be
- held responsible in any manner for identifying or failing to identify any or all such intellectual property rights
- that may be involved in the implementation of the Specification.
- 55 This Specification is provided "AS IS", and no participant in the Liberty Alliance makes any warranty
- of any kind, express or implied, including any implied warranties of merchantability, non-infringement
- or third party intellectual property rights, and fitness for a particular purpose.
- 58 Liberty Alliance Project
- 59 Licensing Administrator
- 60 c/o IEEE-ISTO
- 61 445 Hoes Lane, P.O. Box 1331
- 62 Piscataway, NJ 08855-1331, USA

Liberty Architecture Implementation Guidelines

63 Editors

- Lena Kannappan, France Telecom, <u>lena.kannappan@rd.francetelecom.com</u>
- Matthieu Lachance, OpenWave, <u>matthieu.lachance@openwave.com</u>
- John Kemp, IEEE-ISTO

67 Contributors

ActivCard Netegrity
American Express Travel Related Services NeuStar

America Online, Inc. Nextel Communications

Bank of America Nippon Telegraph and Telephone Company

Bell Canada Nokia Corporation

Cingular Wireless Novell, Inc.

Cisco Systems, Inc.

NTT DoCoMo, Inc.

OneName Corporation

Communicator, Inc.

Openwave Systems Inc.

Consignia

PricewaterhouseCoopers LLP

Deloitte & Touche LLP Register.com
EarthLink, Inc. RSA Security Inc

Electronic Data Systems, Inc.

Sabre Holdings Corporation

Entrust, Inc. SAP AG

Ericsson SchlumbergerSema

Fidelity Investments SK Telecom

France Telecom Sony Corporation

Gemplus Sun Microsystems, Inc.

General Motors

Hewlett-Packard Company

i2 Technologies, Inc.

Intuit Inc.

Vodafone Group Plc

MasterCard International

Wave Systems

NEC Corporation

68 69

70

Document History

Rev	Date	By Whom	Description
00	02-Apr-02	Lena Kannappan	Initial outline
01	12-Apr-02	Lena Kannappan	Introduced new Columns and Tables to separate ZIC-UA and LECP requirements
02	26-Apr-02	Matthieu Lachance Lena Kannappan	 Renamed the document from Static Conformance Requirements to Liberty Architecture Implementation Guidelines document as it no longer consists of Mandatory or Optional requirements for identity provider or SP or LECP. Restructured the document to reflect that the document is service or deployment focused

vider and SP profiles were added. entity provider, SP and LECP were
ests #1051, and #1061
to indicate the recent section number xt specifications.
evious Document History (May 09 th). , 3.5 and 3.6 to reflect changes to tions ver 06.
Architecture Overview document for otes associated with implementations. o references to the "DoFederate" the sections for IDP and SP guidelines diffied to address CR#1162: Register include IDP and SP initiation of
or CR #1162

Draft Version 1.1-06

Liberty Alliance Project: Liberty Architecture Implementation Guidelines

72

73

Table of Contents

74	1 Int	roduction	6
75	2 Re	commended Liberty Architecture Implementation Guidelines	6
76	2.1	Identity Provider Implementation Guidelines	6
77	2.2	Service Provider Implementation Guidelines	
78	2.3	LECP Implementation Guidelines	
79	3 Lil	berty Architecture Specifications Checklist	
80	3.1	Liberty Profiles and Bindings Requirements — Identity Provider	
81	3.2	Liberty Profiles and Bindings Requirements — Service Provider	
82	3.3	Liberty Profiles and Bindings Requirements — LECP	12
83	3.4	Authentication Context Requirements — Identity Provider	
84	3.5	Authentication Context Requirements — Service Provider	
85	3.6	Authentication Context Requirements — LECP	
86	4 Re	ferences	
87			

1 Introduction

88

100

101

102

103

110

119120

- This document defines the recommended implementation guidelines and checklists for the Liberty
- architecture focused on deployments for the service-providing entities: service providers, identity
- providers, and Liberty-enabled clients or proxies (LECPs). It is intended to provide recommended
- 92 implementation guidelines to Liberty component developers to help them decide what they need to
- 93 implement to meet their business needs. Because Liberty Phase 1 does not provide formal
- ompliance, this document does not contain any conformance requirements only
- 95 recommendations. A recommended profile tailored according to the high-level Liberty features is
- 96 provided for different Liberty service-providing entities. Implementers facing specific needs can
- 97 decide to implement what they need and claim support for each specific feature separately.
- The document also provides a checklist of requirements based on the following Liberty architecture
- 99 specification categories that implementers can use to advertise their supported feature set:
 - Functionality in the Liberty protocols and schemas described
 - Bindings and profiles defined for each Liberty protocol type (specific interactions between identity providers, service providers, and LECPs)
 - The authentication request and reply context-specific information
- Definitions for Liberty-specific terms can be found in [LibertyGloss]. Note: Phrases and numbers in
- brackets [] refer to other documents; details of these references can be found in Section 4 (at the end
- of this document).
- Policy/Security and Technical notes related to implementations are covered by Liberty Architecture
- Overview document associated with this Implementation Guidelines document specified by
- 109 [LibertyArchOverview].

2 Recommended Liberty Architecture Implementation Guidelines

- The recommended implementation guidelines for identity providers, service providers, and LECPs
- are listed in the tables in 2.1 through 2.3. The guidelines refer to front-channel-based and back-
- channel-based mechanisms. Front channel is described as a communication channel where HTTP
- redirect-, GET-, and POST-based request and response protocol messages between the identity
- provider and the service provider flow through the Web browser. *Back channel* is a SOAP/HTTP-
- based direct communication channel between the identity provider and the service provider. A
- service provider with SOAP client support is considered to be a "back-channel-capable SP" whereas
- a "basic SP" is not back-channel-capable.

2.1 Identity Provider Implementation Guidelines

Liberty Feature	Recommendations
Single Sign-On	It is strongly recommended that identity providers support the LECP single sign-on profile to ensure forward compatibility. The LECP profile is intended for future clients of all kinds (thin and thick) as well as existing wireless thin clients (WML, HDML, etc) when used with a LEP.
	Identity providers that want to support existing HTML client environments should implement the browser artifact and the browser POST single sign-on profiles.

Liberty Feature	Recommendations
	To support existing WML client in environments that do not contain any LEP, identity providers should support the WML single sign-on profile.
Identity Federation	Identity providers that want to support permanent identity linking between service providers and identity providers (beyond the stateless single sign-on association) should support the <federate> element of the <authnrequest> for all the supported single sign-on profiles.</authnrequest></federate>
Federation Termination Notification	Identity providers that support identity federation should also support the Federation Termination Notification Protocol. When supported, both service-provider-initiated and identity-provider-initiated federation termination notification should be supported. Liberty offers two federation termination notification mechanisms:
	Front channel, or HTTP-redirect-based
	Back channel, or SOAP-based
	As a minimum, identity providers should support the front- channel-based mechanism. Identity providers that want to support back-channel-capable SPs should implement both mechanisms.
Name Registration	The Name Registration Protocol allows the service provider to use its own opaque handle to identify the Principal when communicating with the identity provider (rather than using the identity provider's opaque handle generated during federation). This protocol also allows the identity provider to register a new name identifier with the service provider at any time after federation.
	When supported, both service-provider-initiated and identity-provider-initiated Name Registration should be supported.
	Liberty offers two Name Registration mechanisms:
	• Front channel, or HTTP-redirect-based
	Back channel, or SOAP-based
	At a minimum, identity providers should support the front- channel-based mechanism. Identity providers that want to support back-channel-capable SPs should implement both mechanisms.
Single Logout	The Single Logout Protocol allows logging out a Principal from all its active sessions to service providers, linked to an identity provider. Identity providers keeping trace of the Principal's service provider sessions should implement this feature. When supported, both service-provider-initiated and identity-provider-initiated single logout should be supported.
	Liberty offers two single logout mechanisms:
	Front channel, or HTTP-redirect-based
	Back channel, or SOAP-based
	As a minimum, identity providers supporting this feature should support the front-channel-based mechanism. Identity providers that want to support back-channel-capable SPs should implement both mechanisms.
Identity Provider Introduction	Identity providers that want to support more than a single circle of trust simultaneously should support the Identity Provider Introduction Protocol.

Draft Version 1.1-06

Liberty Architecture Implementation Guidelines

2.2 Service Provider Implementation Guidelines

- 123 In general service providers are divided in two categories: the back-channel-capable SPs and the
- basic SPs (that are not back-channel-capable).

Liberty Alliance Project:Liberty Architecture Implementation Guidelines

125

Liberty Feature	Recommendations
Single Sign-On	It is strongly recommended that service providers support the LECP single sign-on profile to ensure forward compatibility. The LECP profile is intended for future clients of all kinds (thin and thick) as well as existing wireless thin clients (WML, HDML, etc) when used with a LEP.
	Service providers that want to support existing HTML client environments should implement the browser artifact and the browser POST single sign-on profiles.
	To support existing WML client in environments that do not contain any LEP, service providers should support the WML single sign-on profile.
Identity Federation	Service providers that want to support permanent identity linking between service providers and identity providers (beyond the stateless single sign-on association) should support the <federate> element of the <authnrequest> for all the supported single sign-on profiles.</authnrequest></federate>
Federation Termination Notification	Service providers that support identity federation should also support the Federation Termination Notification Protocol. When supported, both service-provider-initiated and identity-provider-initiated federation termination notification should be supported.
	Service providers should support either the front-channel or back- channel federation termination notification mechanisms depending on their respective capabilities although nothing prevents them from supporting both mechanisms if desired.
Name Registration	The Name Registration Protocol allows the service provider to use its own opaque handle to identify the Principal when communicating with the identity provider (rather than using the identity provider's opaque handle generated during federation). This protocol also allows the service provider to register a new name identifier with the identity provider at any time after federation.
	Service providers should support either the front-channel or back- channel Name Registration mechanisms depending on their respective capabilities although nothing prevents them from supporting both mechanisms if desired.
Single Logout	The Single Logout Protocol allows logging out a Principal from all its active sessions to service providers, linked to an identity provider. When supported, both service-provider-initiated and identity-provider-initiated single logout should be supported.
	Service providers should support either the front-channel or back- channel single logout mechanisms depending on their respective capabilities although nothing prevents them from supporting both mechanisms if desired.
Identity Provider Introduction	Service providers that want to support networks with more than a single circle of trust simultaneously should support the Identity Provider Introduction Protocol.

126

2.3 LECP Implementation Guidelines

128

Liberty Architecture Implementation Guidelines

Liberty Feature	Recommendations
Single Sign-On	Support for LECP single sign-on profile.

129

130

3 Liberty Architecture Specifications Checklist

3.1 Liberty Profiles and Bindings Requirements — Identity Provider

]	3	2

Req ID#	Description	Ref	Y/N
IDP-FED-1	Identity Federation	Section 3.2.1 [LibertyBindProf]	
IDP-SSO-1	Single Sign-On using Browser Artifact	Section 3.2.2 [LibertyBindProf]	
IDP-SSO-2	Single Sign-On using Browser POST	Section 3.2.3 [LibertyBindProf]	
IDP-SSO-3	Single Sign-On using WML POST	Section 3.2.4 [LibertyBindProf]	
IDP-SSO-4	Single Sign-On using LECP	Section 3.2.5 [LibertyBindProf]	
IDP-REG-1	Register Name Identifier — Front Channel	Section 3.3 [LibertyBindProf]	
IDP-REG-2	Register Name Identifier — Back Channel	Section 3.3 [LibertyBindProf]	
IDP-REG-3	Register Name Identifier (Identity Provider initiated) — Front Channel	Section 3.3.1.1 [LibertyBindProf]	
IDP-REG-4	Register Name Identifier (Identity Provider initiated) — Back Channel	Section 3.3.1.2 [LibertyBindProf]	
IDP-REG-5	Register Name Identifier (Service Provider initiated) — Front Channel	Section 3.3.2.1 [LibertyBindProf]	
IDP-REG-6	Register Name Identifier (Service Provider initiated) — Back Channel	Section 3.3.2.2 [LibertyBindProf]	
IDP-FED-2	Identity Federation Termination — Front Channel	Section 3.4 [LibertyBindProf]	
IDP-FED-3	Identity Federation Termination — Back Channel	Section 3.4 [LibertyBindProf]	
IDP-FED-4	Federation Termination Notification (Identity Provider Initiated) — Front Channel	Section 3.4.1.1 [LibertyBindProf]	
IDP-FED-5	Federation Termination Notification (Identity Provider Initiated) — Back Channel	Section 3.4.1.2 [LibertyBindProf]	
IDP-FED-6	Federation Termination Notification (Service Provider Initiated) — Front Channel	Section 3.4.2.1 [LibertyBindProf]	
IDP-FED-7	Federation Termination Notification (Service Provider Initiated) — Back Channel	Section 3.4.2.2 [LibertyBindProf]	
IDP-SLO-1	Single Logout	Section 3.5 [LibertyBindProf]	
IDP-SLO-2	Single Logout Initiated by Identity Provider: Redirect	Section 3.5.1.1 [LibertyBindProf]	

Liberty Architecture Implementation Guidelines

Req ID#	Description	Ref	Y/N
IDP-SLO-3	Single Logout Initiated by Identity Provider: SOAP	Section 3.5.1.2 [LibertyBindProf]	
IDP-SLO-4	Single Logout Initiated by Service Provider: Redirect	Section 3.5.2.1 [LibertyBindProf]	
IDP-SLO-5	Single Logout Initiated by Service Provider: SOAP	Section 3.5.2.2 [LibertyBindProf]	
IDP-INT-1	Identity Provider Introduction	Section 3.6 [LibertyBindProf]	
IDP-COM-1	HTTP Connection over SSL3.0 or TLS1.0 [RFC2246], WTLS	[SSLv3], [RFC2246], [WTLS]	
IDP-COM-2	Support for Minimum URL length of 256 bytes	[RFC2965]	
IDP-COM-3	Support for Session Cookies	[RFC2965]	

133

3.2 Liberty Profiles and Bindings Requirements — Service Provider

135

Req ID#	Description	Ref	Y/N
SP-FED-1	Identity Federation	Section 3.2.1 [LibertyBindProf]	
SP-SSO-1	Single Sign-On using Browser Artifact	Section 3.2.2 [LibertyBindProf]	
SP-SSO-2	Single Sign-On using Browser POST	Section 3.2.3 [LibertyBindProf]	
SP-SSO-3	Single Sign-On using WML	Section 3.2.4 [LibertyBindProf]	
SP-SSO-4	Single Sign-On using LECP	Section 3.2.5 [LibertyBindProf]	
SP-REG-1	Register Name Identifier — Front Channel	Section 3.3 [LibertyBindProf]	
SP-REG-2	Register Name Identifier — Back Channel	Section 3.3 [LibertyBindProf]	
SP-REG-3	Register Name Identifier (Identity Provider initiated) — Front Channel	Section 3.3.1.1 [LibertyBindProf]	
SP-REG-4	Register Name Identifier (Identity Provider initiated) — Back Channel	Section 3.3.1.2 [LibertyBindProf]	
SP-REG-5	Register Name Identifier (Service Provider initiated) — Front Channel	Section 3.3.2.1 [LibertyBindProf]	
SP-REG-6	Register Name Identifier (Service Provider initiated) — Back Channel	Section 3.3.2.2 [LibertyBindProf]	
SP-FED-2	Identity Federation Termination — Front Channel	Section 3.4 [LibertyBindProf]	
SP-FED-3	Identity Federation Termination — Back Channel	Section 3.4 [LibertyBindProf]	
SP-FED-4	Federation Termination Notification (Identity Provider Initiated) — Front Channel	Section 3.4.1.1 [LibertyBindProf]	
SP-FED-5	Federation Termination Notification (Identity Provider Initiated) — Back Channel	Section 3.4.1.2 [LibertyBindProf]	

Liberty Architecture Implementation Guidelines

Req ID#	Description	Ref	Y/N
SP-FED-6	Federation Termination Notification (Service Provider Initiated) — Front Channel	Section 3.4.2.1 [LibertyBindProf]	
SP-FED-7	Federation Termination Notification (Service Provider Initiated) — Back Channel	Section 3.4.2.2 [LibertyBindProf]	
SP-SLO-1	Single Logout	Section 3.5 [LibertyBindProf]	
SP-SLO-2	Single Logout Initiated by Identity Provider: Redirect	Section 3.5.1.1 [LibertyBindProf]	
SP-SLO-3	Single Logout Initiated by Identity Provider: SOAP	Section 3.5.1.2 [LibertyBindProf]	
SP-SLO-4	Single Logout Initiated by Service Provider: Redirect	Section 3.5.2.1 [LibertyBindProf]	
SP-SLO-5	Single Logout Initiated by Service Provider: SOAP	Section 3.5.2.2 [LibertyBindProf]	
SP-INT-1	Identity Provider Introduction	Section 3.6 [LibertyBindProf]	
SP-COM-1	HTTP Connection over SSL3.0 or TLS1.0 [RFC2246], WTLS	[SSLv3], [RFC2246], [WTLS]	
SP-COM-2	Support for Minimum URL Length of 256 bytes	[RFC2965]	
SP-COM-3	Support for Session Cookies	[RFC2965]	

136

3.3 Liberty Profiles and Bindings Requirements — LECP

137138

Req ID#	Description	Ref	Y/N
LECP-SSO-1	Single Sign-On using LECP	Section 3.2.5 [LibertyBindProf]	
LECP-COM-1	Support for Minimum URL Length of 256 bytes	[RFC2965]	
LECP-COM-2	Support for Session Cookies	[RFC2965]	

139

3.4 Authentication Context Requirements — Identity Provider

Req ID#	Description	Ref	Y/N
IDP-AUTHN-01	MobileContract	Section 5.1.1 [LibertyAuthnContext]	
IDP-AUTHN-02	MobileDigitalID	Section 5.1.2 [LibertyAuthnContext]	
IDP-AUTHN-03	MobileUnregistered	Section 5.1.3 [LibertyAuthnContext]	
IDP-AUTHN-04	Password	Section 5.1.4 [LibertyAuthnContext]	
IDP-AUTHN-05	Password-ProtectedTransport	Section 5.1.5 [LibertyAuthnContext]	
IDP-AUTHN-06	Previous-Session	Section 5.1.6	

Liberty Architecture Implementation Guidelines

Req ID#	Description	Ref	Y/N
		[LibertyAuthnContext]	
IDP-AUTHN-07	Smartcard	Section 5.1.7 [LibertyAuthnContext]	
IDP-AUTHN-08	Smartcard-PKI	Section 5.1.8 [LibertyAuthnContext]	
IDP-AUTHN-09	Software-PKI	Section 5.1.9 [LibertyAuthnContext]	
IDP-AUTHN-10	Time-Sync-Token	Section 5.1.10 [LibertyAuthnContext]	

142

3.5 Authentication Context Requirements — Service Provider

144

143

Req ID#	Description	Ref	Y/N
SP-AUTHN-01	MobileContract	Section 5.1.1 [LibertyAuthnContext]	
SP-AUTHN-02	MobileDigitalID	Section 5.1.2 [LibertyAuthnContext]	
SP-AUTHN-03	MobileUnregistered	Section 5.1.3 [LibertyAuthnContext]	
SP-AUTHN-04	Password	Section 5.1.4 [LibertyAuthnContext]	
SP-AUTHN-05	Password-ProtectedTransport	Section 5.1.5 [LibertyAuthnContext]	
SP-AUTHN-06	Previous-Session	Section 5.1.6 [LibertyAuthnContext]	
SP-AUTHN-07	Smartcard	Section 5.1.7 [LibertyAuthnContext]	
SP-AUTHN-08	Smartcard-PKI	Section 5.1.8 [LibertyAuthnContext]	
SP-AUTHN-09	Software-PKI	Section 5.1.9 [LibertyAuthnContext]	
SP-AUTHN-10	Time-Sync-Token	Section 5.1.10 [LibertyAuthnContext]	

145

3.6 Authentication Context Requirements — LECP

Req ID#	Description	Ref	Y/N
LECP-AUTHN-01	MobileContract	Section 5.1.1 [LibertyAuthnContext]	
LECP-AUTHN-02	MobileDigitalID	Section 5.1.2 [LibertyAuthnContext]	
LECP-AUTHN-03	MobileUnregistered	Section 5.1.3 [LibertyAuthnContext]	
LECP-AUTHN-04	Password	Section 5.1.4	

Liberty Alliance Project: Liberty Architecture Implementation Guidelines

Req ID#	Description	Ref	Y/N
		[LibertyAuthnContext]	
LECP-AUTHN-05	Password-ProtectedTransport	Section 5.1.5 [LibertyAuthnContext]	
LECP-AUTHN-06	Previous-Session	Section 5.1.6 [LibertyAuthnContext]	
LECP-AUTHN-07	Smartcard	Section 5.1.7 [LibertyAuthnContext]	
LECP-AUTHN-08	Smartcard-PKI	Section 5.1.8 [LibertyAuthnContext]	
LECP-AUTHN-09	Software-PKI	Section 5.1.9 [LibertyAuthnContext]	
LECP-AUTHN-10	Time-Sync-Token	Section 5.1.10 [LibertyAuthnContext]	

148

4 References

149	4 References	
150 151 152	[LibertyArchOverview]	J. Hodges, "Liberty Architecture Overview.", http://projectliberty.org/specs/liberty-architecture-overview-v1.0.pdf , October 2002
153 154 155	[LibertyAuthnContext]	P. Madsen, "Liberty Authentication Context Specification.", http://projectliberty.org/specs/liberty-architecture-authentication-context-v1.0.pdf , October 2002
156 157 158	[LibertyBindProf]	J. Rouault, "Liberty Bindings and Profiles Specification.", http://projectliberty.org/specs/liberty-architecture-bindings-profiles-v1.0.pdf , October 2002
159 160	[LibertyGloss]	H. Mauldin, "Liberty Glossary", http://projectliberty.org/specs/liberty-tech-glossary-v1.0.pdf , October 2002.
161 162 163	[LibertyProtSchema]	J. Beatty, "Liberty Protocols and Schemas Specification," http://projectliberty.org/specs/liberty-architecture-protocols-schemas-v1.0.pdf , October 2002.
164 165	[RFC2246]	T. Dierks, C. Allen, "The TLS Protocol Version 1.0," http://www.ietf.org/rfc/rfc2246.txt , January 1999.
166 167	[RFC2965]	D. Cristol, L. Montulli, "HTTP State Management Mechanism," http://www.ietf.org/rfc/rfc2965.txt , October 2000.
168 169 170 171	[SAMLBind]	Mishra, Prateek, et al., "Bindings and Profiles for the OASIS Security Assertion Markup Language (SAML)," http://www.oasis-open.org/committees/security/docs/draft-sstc-bindings-model-10.doc , OASIS, 10 January 2002.
172 173 174 175	[SAMLCore]	Hallam-Baker, P., et al., "Assertions and Protocol for the OASIS Security Assertion Markup Language (SAML)," http://www.oasis-open.org/committees/security/docs/draft-sstc-core-21.pdf , OASIS, December 2001.
176 177 178	[SOAP1.1]	D. Box et al., "Simple Object Access Protocol (SOAP) 1.1," http://www.w3.org/TR/SOAP , World Wide Web Consortium Note, May 2000.

Draft Version 1.1-06

Liberty Alliance Project: Liberty Architecture Implementation Guidelines

179	[SSLv3]	A. Frier et al, "The SSL Protocol Version 3.0,"
180		http://www.mozilla.org/projects/security/pki/nss/ssl/draft302.txt,
181		18 November 1996.
182	[WML1.3]	"Wireless Application Protocol Wireless Markup Language
183		Specification Version 1.3," Wireless Application Protocol Forum, Ltd.,
184		http://www.wapforum.org/, 19 February 2000.
185	[WTLS]	"Wireless Transport Layer Security,"
186		http://www1.wapforum.org/tech/documents/WAP-261 102-
187		WTLS-20011027-a.pdf.
188	[XMLSig]	D. Eastlake et al., "XML-Signature Syntax and Processing,"
189		http://www.w3.org/TR/xmldsig-core/, World Wide Web Consortium.

Liberty Alliance Project: Confidential15