

Activity	ActivityType extends SuperType	Details about an activity or process that occurs. An activity may encompass a period of time and multiple events.
ActivityAbstracter.Organization	OrganizationType extends SuperType	A person or an organization that abstracted a particular set of information about an activity.
ActivityAbstracter.Person	PersonType extends SuperType	A person or an organization that abstracted a particular set of information about an activity.
ActivityApprovalPerson	PersonType extends SuperType	A person who reviewed, signed off, or otherwise approved the information as a whole.
ActivityAssistingPerson	PersonType extends SuperType	A person assisting with an activity function such as an arrest.
ActivityClearer.Organization	OrganizationType extends SuperType	A person or an organization that cleared a particular activity.
ActivityClearer.Person	PersonType extends SuperType	A person or an organization that cleared a particular activity.
ActivityCollectedEvidence	EvidenceType extends SuperType	Evidence actually collected as part of an activity
ActivityCommentText	TextType	A note or comment about an activity.
ActivityComplainantAttorney	PersonType extends SuperType	The complainant's attorney in a court case.
ActivityComplainantPerson	PersonType extends SuperType	The complainant in a court case or activity.
ActivityCompletedIndicator	j-xsd:boolean	True if an activity or process was completed; false otherwise.
ActivityCourt	CourtType extends OrganizationType	The court associated with an activity.
ActivityCrimeCase	CaseType extends ActivityType	A reference to the originating case agency number (OCA) or case file associated with an activity.
ActivityCrimePotentialCharge	ChargeType extends SuperType	An association that is part of the justification for a field interview activity, e.g., the reason for talking with a person or a possible crime.
ActivityDate	j-xsd:date	A date of an activity that occurs at a singular point in time or a start date of an activity that occurs over a period of time.
ActivityDefenseAttorney	PersonType extends SuperType	A defense attorney in a court case.

ActivityDescriptionText	TextType	A description or narrative of the activity or process that occurred.
ActivityDetainedLocation	LocationType extends SuperType	A location at which a person was detained due to an activity, e.g., nonviolent protesters detained at RFK stadium or the location where detained for a booking.
ActivityDispatcher	PersonType extends SuperType	A person assigning people or units to respond to an activity or location.
ActivityDispatchLocation	LocationType extends SuperType	A location in a call for service-type activity to which units are dispatched. This may differ from the reported Location for the activity, which is the origin of the call.
ActivityDisposition	DocumentType extends SuperType	A hard-copy documenting the disposition of a case or a charge.
ActivityDistrictAttorney	PersonType extends SuperType	A district attorney (DA) associated with a case.
ActivityDocket	DocumentType extends SuperType	A court number or docket number associated with an activity within a court case.
ActivityDocument	WarrantType extends CourtOrderType	A document relating to an activity, such as a warrant or a booking slip.
ActivityDocumentIssuerOrganization	OrganizationType extends SuperType	An agency issuing any legal document. This is typically associated with a warrant-type activity.
ActivityDocumentServer.Organization	OrganizationType extends SuperType	A person or organization responsible for service of a legal document, e.g., a warrant or a restraining order.
ActivityDocumentServer.Person	PersonType extends SuperType	A person or organization responsible for service of a legal document, e.g., a warrant or a restraining order.
ActivityDocumentValidator.Organization	OrganizationType extends SuperType	A person or organization to contact to validate a document, such as a warrant.
ActivityDocumentValidator.Person	PersonType extends SuperType	A person or organization to contact to validate a document, such as a warrant.
ActivityEndDate	j-xsd:date	An end or completion date of an activity that occurs over a duration of time.
ActivityEndTime	j-xsd:time	An end or completion time of an activity that occurs over a period of time.
ActivityEvidenceLedger	DocumentType extends SuperType	A ledger containing the written record of evidence associated with an activity, e.g., narcotic, money, storage.
ActivityID	IDType extends SuperType	An identifier that uniquely refers to an activity or process that occurred.

ActivityInformant	PersonType extends SuperType	A person providing information associated with the activity.
ActivityInitiatingInstrument	DocumentType extends SuperType	A document that officially initiated a process or court case.
ActivityInvestigator	PersonType extends SuperType	A person investigating an activity.
ActivityIssuingJudge	PersonType extends SuperType	A judge that issues the warrant or court order.
ActivityItemObtainer	PersonType extends SuperType	A person who obtained the item in question.
ActivityLabReceipt	DocumentType extends SuperType	A written lab receipt for evidence associated with the activity.
ActivityNarrativeDocument	DocumentType extends SuperType	Comments entered as a narrative for incident objects.
ActivityOfficial.Enforcement	EnforcementOfficialType extends PersonType	An official associated with an activity
ActivityOfficial.Judicial	JudicialOfficialType	An official associated with an activity
ActivityOriginatingDocument	DocumentType extends SuperType	A document that started or originated the activity.
ActivityOwner	PersonType extends SuperType	An owner of a property item such as a vehicle associated with the activity. Should not be used if multiple vehicles appear in the activity, with different owners.
ActivityPhoneOperator	PersonType extends SuperType	A telephone operator associated with an activity. Generally used for a CallForService-type activity.
ActivityPreviousActivity	ActivityType extends SuperType	A previous activity associated with the current activity.
ActivityPreviousCase	CaseType extends ActivityType	A previous case associated with the current activity.
ActivityPreviousCourt	CourtType extends OrganizationType	The court previously associated with an activity. This is associated with a court case activity.
ActivityPreviousIncident	IncidentType extends ActivityType	A previous incident associated with the current activity.
ActivityPrimaryOrganization	OrganizationType extends SuperType	The organization primarily associated with the activity.
ActivityPrimaryWorker	PersonType extends SuperType	The primary worker supporting a juvenile.
ActivityReasonText	TextType	A reason why an activity or process occurred.

ActivityRegistration	PropertyRegistrationType extends SuperType	A registration associated with an activity.
ActivityReleaser	PersonType extends SuperType	A person who released either information, property, or a person in an activity.
ActivityReporter	PersonType extends SuperType	A person who reported or observed an incident or an activity.
ActivityReportingOrganization	OrganizationType extends SuperType	The organization for which units responded to an incident.
ActivityRequestedEvidence	EvidenceType extends SuperType	Evidence that has been requested to be collected, as part of an activity.
ActivityResponsibleOrganization	OrganizationType extends SuperType	The public-safety agency responsible for the activity. For Parole, this is the parole agency. For Pawn, this is the agency monitoring pawnshops.
ActivityResultDate	j-xsd:date	A date that a result of an activity or process occurred.
ActivityResultText	TextType	A result or outcome of an activity.
ActivityResultTime	j-xsd:time	A time that a result of an activity or process occurred.
ActivitySecondaryServiceAgency	OrganizationType extends SuperType	A secondary agency serving a warrant or other legal document. Not listed by the court as the primary service agency.
ActivitySeizedProperty	PropertyType extends SuperType	Property or money that was seized in an associated activity.
ActivitySeverestInjury	InjuryType extends SuperType	The most severe injury involved in the activity.
ActivityStatus	StatusType extends SuperType	Details about a status of an activity or process.
ActivitySupervisingOrganization	OrganizationType extends SuperType	An agency or other organization supervising a person, e.g., an inmate, parolee, probationer, or juvenile.
ActivitySupplementalDocument	DocumentType extends SuperType	Additional documents relating to an activity.
ActivitySuspect	SubjectType extends PersonType	A suspect associated with an activity.
ActivityTime	j-xsd:time	A time of an activity that occurs at a singular point in time or a start time of an activity that occurs over a period of time.
ActivityTypeText	TextType	A type of activity or process that occurred.

ActivityUnknownAffiliate	PersonType extends SuperType	A person attached in a Records Management System (RMS) to an activity whose involvement cannot be determined.
ActivityUpdateIndicator	j-xsd:boolean	True if details about an activity is an update to previous activity details received.
ActivityUsedForce	ForceType extends ActivityType	The force, tool, or weapon used in an incident activity.
ActivityVehicleOperator	PersonType extends SuperType	The person operating the vehicle associated with an activity. This context may also be used between Vehicle and Person for complex activities.
ActivityVictim	VictimType extends SuperType	The victim or person that was the target of an activity. Note that a Target object indicates the property or other non-person entity that is the target of an incident.
ActivityWitness	WitnessType extends PersonType	A person who saw something connected with the activity, or a person testifying in court.
Actor.Organization	OrganizationType extends SuperType	A legal person in the court system. This is either a person, organization, or property item.
Actor.Person	PersonType extends SuperType	A legal person in the court system. This is either a person, organization, or property item.
Actor.Property	PropertyType extends SuperType	A legal person in the court system. This is either a person, organization, or property item.
Address	AddressType extends SuperType	A postal location to which paper mail can be directed.
AddressComponentDescriptionText	TextType	A description of a miscellaneous address component.
AddressComponentText	TextType	A value of the miscellaneous address component.
AddressFullText	TextType	A complete address to be used when the address components cannot be broken down into the JXDD components.
AddressGrid	AddressGridType extends SuperType	Details about a specific geographic area of a law enforcement agency's jurisdiction.
AddressGridID	IDType extends SuperType	A unique identifier of an address grid.
AddressGridText	TextType	A relationship between an address and a law enforcement agency's grid.
AddressMailDeliveryUnitText	TextType	A complete Post Office box number or other mail delivery point for a location, e.g., "PO BOX 12345"

AddressOther	AddressComponentType extends SuperType	An undefined address component to be labeled and tracked.
AddressPrivateMailboxText	TextType	Identifies a private mailbox within a company. Sometimes referred to as a Mail stop Code.
AddressRecipientName	TextType	A person, organization, or other recipient associated with an address to whom paper mail may be sent.
AddressRegionFullText	TextType	A single reference to a city, state, and postal code. This is customarily the third line in an address.
AddressRouteName	TextType	The name and number of a postal route.
Affiliate	AffiliateType extends SuperType	Details about a person or organization that has a membership-like relationship or association with an organization.
AffiliateDescriptionText	TextType	A description of the relationship or association one party has with another party.
AffiliateName	TextType	A name of a person, organization or actor that has a relationship or association with another person organization or actor.
AffiliateParty.Organization	OrganizationType extends SuperType	A person or organization that has a relationship with another party.
AffiliateParty.Person	PersonType extends SuperType	A person or organization that has a relationship with another party.
AffiliateRoleText	TextType	A part or function one party performs for another party.
AffiliateStartDate	j-xsd:date	A date an affiliation began.
AffiliateTypeText	TextType	A type of relationship between two parties. For an organization, this may be a parent company, child company, spin-off, division, subdivision.
AgeMeasure	AgeMeasureType extends MeasureType	A representation of an age.
Agency	OrganizationType extends SuperType	An division of a governmental or international body.
Aircraft	AirCRAFTType extends VehicleBasicsType	Details about a mode of transportation capable of flying in the air.
AircraftAirportID	IDType extends SuperType	An identifying number of an airport at which an aircraft lands or is kept. Sometimes referred to as an airport code.
AircraftAirportName	TextType	A name of an airport at which an aircraft lands or is kept.
AircraftEngineQuantity	j-xsd:nonNegativeInteger	A number of engines on an aircraft.
AircraftFuselageColorCode	j-ncic:VCOType	A code identifying a color of a fuselage of an aircraft.

AircraftFuselageColorText	TextType	A color of a fuselage of an aircraft.
AircraftMakeCode	j-ncic:VMAType	A code identifying a manufacturer of an aircraft.
AircraftModelCode	j-ncic:VMOType	A code identifying a specific design or type of vehicle made by a manufacturer.
AircraftStyleCode	j-ncic:VSTType	A code identifying a style of a vehicle.
AircraftTailID	IDType	An identifier of an aircraft. Sometimes referred to as a tail number.
AircraftWingColorCode	extends SuperType	A code identifying a color of the wings of an aircraft.
AircraftWingColorText	j-ncic:VCOType	A color of the wings of an aircraft.
AircraftYearDate	TextType	A year which is assigned to a vehicle by the manufacturer.
Alert	j-xsd:gYear	Details about an alert used to notify agencies and public systems of an emergency.
AlertAudienceDescriptionText	AlertType	A description of the target audience of an alert.
AlertAudioURLID	extends ActivityType	A link to a digital audio file that is associated with an alert.
AlertCertaintyCode	TextType	A code identifying a likeliness of an occurrence of an event that raised an alert.
AlertCertaintyText	IDType	A likeliness of occurrence of an event that raised an alert.
AlertContactInformation	extends SuperType	Details about contact information for follow-up and confirmation.
AlertContactText	j-cap:AlertCertaintyCodeType	Contact information for follow-up and confirmation associated with an alert.
AlertEffectiveDate	TextType	A date the alert information takes effect.
AlertEffectiveTime	ContactInformationType	A time the alert information takes effect.
AlertEventCategoryCode	extends SuperType	A code identifying the category of the event that raised an alert.
AlertEventCategoryText	TextType	A category of the event that raised an alert.
AlertEventDescriptionText	TextType	An extended description of an event that raised an alert.
AlertEventTypeText	TextType	A specific type of event that occurred that raised an alert.
AlertExpiresDate	j-xsd:date	A date on which the alert is no longer valid.
AlertExpiresTime	j-xsd:time	A time at which the alert is no longer valid.
AlertHeadlineText	TextType	A headline or title for an alert.
AlertImageURLID	IDType	A link to a digital image file that is associated with an alert.
AlertInformationURLID	extends SuperType	A link to additional information about an alert or event.
	IDType	
	extends SuperType	

AlertInstructionText	TextType	A recommended action to be taken by recipients in response to an alert.
AlertOnsetDuration	j-xsd:duration	A duration until the expected beginning of an event that raised an alert.
AlertParameterCodeText	TextType	A technical parameter associated with an event that raised an alert.
AlertSenderDescriptionText	TextType	A name or description of the alert originator.
AlertSeverityCode	j-cap:AlertSeverityCodeType	A code identifying a severity level of an event that raised an alert.
AlertSeverityText	TextType	A severity level of an event that raised an alert.
AlertTargetCodeText	TextType	A system-specific code for message targeting.
AlertUrgencyCode	j-cap:AlertUrgencyCodeType	A code identifying an urgency of an event that raised an alert.
AlertUrgencyText	TextType	An urgency level of an event that raised an alert.
AmendedSentence	SentenceType extends ActivityType	A new sentence term and conditions that replace a previous sentence.
Amount	AmountType extends decimal	A representation of an amount of money.
AppellateCase	AppellateCaseType extends CaseType	Details about a single case heard by the Court of Appeals (Intermediate Court of Appeal) or Supreme Court (The Court of Last Resort). This case does not retry the original case but determines whether the original case was tried properly and the defendant received a fair trial.
AppellateCaseBrief	DocumentType extends SuperType	A document written by prosecution or defense summarizing why a lower court acted correctly or incorrectly.
AppellateCaseDecision	AppellateCaseDecisionType extends SuperType	A statement by a judge or court of a decision reached in regard to an appeal. This may be an opinion or an order.
AppellateCaseDecisionDate	j-xsd:date	A date that an issuing judge signs an Opinion or issues an Order.
AppellateCaseDecisionDescriptionText	TextType	A description of an appellate case decision.
AppellateCaseDecisionID	IDType extends SuperType	An identifier of an appellate case decision.
AppellateCaseDecisionIssuingJudge	JudicialOfficialType	A judge that issues, orders, or authors an appellate case decision.
AppellateCaseDecisionName	TextType	A name of an opinion or order that is a result of an appellate case decision.

AppellateCaseDecisionOpinionIndicator	j-xsd:boolean	True if an appellate case decision refers to an opinion issued; false if it refers to an order issued.
AppellateCaseDecisionPrecedenceIndicator	j-xsd:boolean	True if an appellate case decision opinion or order is worthy of setting an example or justification for a later decision; false otherwise.
AppellateCaseDecisionReliefEffectiveDate	j-xsd:date	A date relief is to be made to a person as stated in an appellate case decision.
AppellateCaseDecisionReliefIndicator	j-xsd:boolean	True if an appellate case decision states any relief assistance be provided to a defendant; false otherwise.
AppellateCaseDecisionText	TextType	A decision of the appellate court about a case. For example, Reaffirmation, Dismissal, Order Opinion, etc.
AppellateCaseDecisionTypeText	TextType	A type of appellate case decision made, e.g., opinion, order.
AppellateCaseJudgePanel	JudgePanelType	A panel of judges presiding over an appellate case. Normally there are three appellate judges, but there may be the entire membership of the Court of Appeals or Supreme Court.
AppellateCaseNotice	AppellateCaseNoticeType extends DocumentType	A request filed with an appellate court to start an appellate case. Sometimes referred to as a Notice of Appeal.
AppellateCaseNoticeDefendantActor.Organization	OrganizationType extends SuperType	A person, organization, or property that was originally tried in a case.
AppellateCaseNoticeDefendantActor.Person	PersonType extends SuperType	A person, organization, or property that was originally tried in a case.
AppellateCaseNoticeDefendantActor.Property	PropertyType extends SuperType	A person, organization, or property that was originally tried in a case.
AppellateCaseNoticeDefendingAgency	OrganizationType extends SuperType	A firm reported in an appellate case notice that originally defended a case.
AppellateCaseNoticeFilingCourt	CourtType extends OrganizationType	An appellate court where a notice of appeal is filed in hopes of being reviewed.
AppellateCaseNoticeOriginalCourt	CourtType extends OrganizationType	A court where a case was originally tried.
AppellateCaseNoticeProsecutingAgency	OrganizationType extends SuperType	A firm reported in an appellate case notice that originally tried a case.
AppellateCaseNoticeProsecutingAttorney	JudicialOfficialType	An attorney reported in an appellate case notice that originally tried a case.
AppellateCaseNoticeReasonText	TextType	A statement explaining the reason for an appeal.

AppellateCaseOriginalCase	CaseType extends ActivityType	An original case that is being retried in an appellate court.
AppellateCaseRelatedCase	CaseType extends ActivityType	A case related to a case being tried in an appellate court.
AppellateCaseSanction	SanctionType extends ActivityType	A sanction ordered for a subject by a judge or a supervising agency as a result of a disposition of a charge.
Area	AreaType extends SuperType	Details about the boundaries of a geographic area of location.
AreaCircularRegion	CircularRegionType extends SuperType	A circular area described by the center and the radius of the circle.
AreaCircularText	TextType	A description of a circular area.
AreaDescriptionText	TextType	A description of an area.
AreaGeographicCodeText	TextType	Any local or map-specific geographically-based code to describe an area.
AreaPolygonGeographicCoordinate	GeographicCoordinateType extends SuperType	A coordinate of a point or vertex on a polygon.
AreaPolygonText	TextType	A description of a geographic polygon.
Arrest	ArrestType extends ActivityType	Details about the apprehension of a subject by a peace official based on an observed or a reported violation of a law or ordinance, an outstanding arrest warrant, or probable cause information.
ArrestAgency	OrganizationType extends SuperType	An agency which employs the arresting official.
ArrestAgencyRecordID	IDType extends SuperType	A records management system number of the originating case agency for an arrest. This may be the booking number or the Records Management System number. Sometimes referred to as Originating Case Agency (OCA) number.
ArrestApprehensionDetentionOrder	CourtOrderType extends ActivityType	An order issued by a judge or the Department of Corrections to arrest a subject for technical violation of probation, parole, supervised release or institution status.
ArrestArraignmentDate	j-xsd:date	A date a subject is due to appear in court after an arrest to answer the charges filed.
ArrestArraignmentTime	j-xsd:time	A time a subject is due to appear in court after an arrest to answer the charges filed.
ArrestBailRecommendationText	TextType	A bail amount on a schedule recommended according to the offense(s).

ArrestBloodAlcoholContentNumberText	TextType	A blood-alcohol percentage reading from a Blood Alcohol Test (BAC Test). A blank value represents "not tested".
ArrestCharge	ChargeType extends SuperType	A formal allegation of a violation of a statute and/or ordinance in association with an arrest.
ArrestIntoxicantInvolvedIndicator	j-xsd:boolean	True if drugs or alcohol were involved in an arrest; false otherwise.
ArrestInvolvedOrganization	OrganizationType extends SuperType	An organization associated with an arrest.
ArrestInvolvedProperty	PropertyType extends SuperType	A piece of property associated with an arrest.
ArrestInvolvedWeapon	PropertyType extends SuperType	A description of a weapon associated with an arrested subject.
ArrestLocation	LocationType extends SuperType	A location where a subject was arrested.
ArrestOfficial	EnforcementOfficialType extends PersonType	A peace official who makes an arrest.
ArrestProbableCauseText	TextType	An observed or reported violation of a law or ordinance, which can be a sufficient cause to arrest a subject.
ArrestRelease	ReleaseType extends ActivityType	Details about a release of a subject from an arrest.
ArrestResistedIndicator	j-xsd:boolean	True if a subject resisted arrest; false otherwise.
ArrestSequenceID	IDType extends SuperType	A sequential number assigned to the arrest of a subject.
ArrestSubject	SubjectType extends PersonType	A person who is arrested.
ArrestSubjectCountCode	j-nibrs:MultipleArresteeSegmentsCod	A code identifying whether or not to count or score an arrested subject in a system to avoid duplicate counts in the event that the subject may be a part of multiple arrests.
ArrestSubjectCustodyTransfer	CustodyTransferType extends ActivityType	A transfer of custody or transportation of a subject from one peace official or location to another.
ArrestSubjectRightsReadIndicator	j-xsd:boolean	True if a person's legal rights (Miranda Rights) were read to a subject during an arrest; false otherwise.
ArrestSubjectRightsReadResponseText	TextType	A subject's response after legal rights were read, e.g., invoked, waived, confessed, requested attorney.
ArrestSummonsIndicator	j-xsd:boolean	True if an arrest occurred due to a summons; false otherwise.

ArrestTypeCode	j-nibrs:ArrestTypeCodeType	A code identifying a type of arrest that occurred.
ArrestWarrant	WarrantType	A court authorized order which commands a peace official to arrest a subject and bring that subject before the court.
Assessment	extends CourtOrderType AssessmentType extends ActivityType	Details about an evaluation or an assessment of a subject. For example, gambling, psychological, chemical dependency, psycho-sexual, etc. Evaluations are frequently done in the context of pre-plea and pre-sentencing investigations (PSI).
AssessmentAdministrator.Organization	OrganizationType extends SuperType	An agency or person performing an assessment and evaluating a subject.
AssessmentAdministrator.Person	PersonType extends SuperType	An agency or person performing an assessment and evaluating a subject.
AssessmentBillRecipient.Organization	OrganizationType extends SuperType	An agency or person billed for an assessment.
AssessmentBillRecipient.Person	PersonType extends SuperType	An agency or person billed for an assessment.
AssessmentFee	ObligationType extends SuperType	An amount of money charged to conduct an assessment.
AssessmentProgram	ProgramType extends SupervisionType	A program a subject attends in which an assessment is made.
AssessmentRecommendationText	TextType	A recommendation or result of the an assessment.
AssessmentReferral	ReferralType extends ActivityType	An order or direction from a person or organization to a subject to undergo an assessment.
AssessmentScoreText	TextType	An evaluation score of an assessment.
AssessmentSubject	SubjectType extends PersonType	A person required to undergo an assessment.
AssessmentSupervisor.Organization	OrganizationType extends SuperType	A supervising agency or person that reviews the way an assessment is carried out.
AssessmentSupervisor.Person	PersonType extends SuperType	A supervising agency or person that reviews the way an assessment is carried out.
Attorney	JudicialOfficialType	A person admitted to practice law in his or her respective state and authorized to perform both civil and criminal legal functions for clients. May include, but not limited to: Prosecuting attorney, public defender, attorney general, defense attorney.

Bail	BailType extends ActivityType	Details about a commitment made (and possibly secured by cash or property) to secure the release of a subject being held in custody and suspected of a crime. Bail is designed to provide some kind of guarantee that a subject will reappear to answer the charges in court at some later date.
BailConditionDescriptionText	TextType	A condition that must be met in order for a subject to post bail.
BailHearingDate	j-xsd:date	A date of a court hearing to determine the bail to be set.
BailPostedAmount	AmountType extends decimal	An amount of bail payed.
BailPostedBond	BondType extends ActivityType	A bond that was posted for bail.
BailPostedDate	j-xsd:date	A date a subject posts or secures bail.
BailRequirementText	TextType	A description of the bail requirement set at a court hearing.
BailRevokedDate	j-xsd:date	A date bail is revoked.
BailSetAmountText	TextType	An amount of bail set for defendant.
BailSetCourt	CourtType extends OrganizationType	A court that assigns a bail to a subject.
BailSubject	SubjectType extends PersonType	A person who is assigned bail.
Binary	BinaryType extends SuperType	A digital representation of an object encoded in a binary format.
BinaryCaptureDate	j-xsd:date	A date on which the data represented by the binary object is captured, e.g., an image taken or an audio recorded.
BinaryCaptureOrganization	OrganizationType extends SuperType	An organization which captured or created a binary.
BinaryCapturePerson	PersonType extends SuperType	A person who captured or created a binary.
BinaryCaptureTime	j-xsd:time	A time at which the data represented by the binary object is captured, e.g., an image taken or an audio recorded.
BinaryDescriptionText	TextType	A textual description of a binary object.
BinaryFormatText	TextType	A format of a binary object, e.g., "image/jpeg".
BinaryFormatTypeText	TextType	A format type of a binary object, e.g., "MIME".
BinaryID	IDType extends SuperType	An identifying number or string for the encoded data.

BinaryObject.Base64	j-xsd:base64Binary	A binary encoding of data, e.g., a binary encoding of a picture, photo, image, graphic, sound, or video.
BinaryObject.Hex	j-xsd:hexBinary	A binary encoding of data, e.g., a binary encoding of a picture, photo, image, graphic, sound, or video.
BinaryReferenceID	IDType extends SuperType	Identifies a url or file reference of the binary object.
BinarySizeValue	j-xsd:integer	A size of a binary object in kilobytes.
BinaryTypeText	TextType	A type of binary object that is encoded, e.g., mug shot, driver license picture, audio confession.
Biometric	BiometricType extends SuperType	Information used to measurable a biological or behavioral characteristic, which can reliably recognize the identity, or verify the claimed identity, of a person.
BiometricAccuracyDescriptionText	TextType	A description of the believed accuracy of a biometric identification.
BiometricBinary	BinaryType extends SuperType	A binary representation of a biometric sample.
BiometricCaptureDate	j-xsd:date	A date a biometric sample was collected.
BiometricCaptureDescriptionText	TextType	A description of how a biometric sample was collected.
BiometricCaptureOrganization	OrganizationType extends SuperType	An organization that collected a biometric sample.
BiometricCapturePerson	PersonType extends SuperType	A person that collected a biometric sample.
BiometricCaptureSourceText	TextType	A source or location from which a biometric sample was collected.
BiometricCaptureTime	j-xsd:time	A time a biometric sample was collected.
BiometricDescriptionText	TextType	A description of a biometric.
BiometricEncodingMethodText	TextType	A method used to encode a biometric.
BiometricID	IDType extends SuperType	An identifier used to uniquely refer to a biometric.
BiometricImage	ImageType extends BinaryType	A picture of a biometric sample.
BiometricLabAnalysisText	TextType	An analysis of a biometric sample.
BiometricRepositoryDescriptionText	TextType	A description of the storage of a biometric sample.
BiometricRepositoryOrganization	OrganizationType extends SuperType	An organization that is responsible for the storage of a biometric sample.
BiometricStatus	StatusType extends SuperType	A status of a biometric, e.g., tested, scheduled.

BiometricTestDate	j-xsd:date	A date a biometric sample was tested.
BiometricTestDescriptionText	TextType	A description of how a biometric sample was tested.
BiometricTestMethodText	TextType	A method used to test a biometric sample.
BiometricTestOrganization	OrganizationType extends SuperType	An organization that tested a biometric sample.
BiometricTestPerson	PersonType extends SuperType	A person who tested a biometric sample.
BiometricTestTime	j-xsd:time	A time a biometric sample was tested.
BiometricValueText	TextType	A textual representation of the value of a biometric.
Boat	BoatType extends VehicleBasicsType	Details about a vessel for transport by water, constructed to provide buoyancy by excluding water and shaped to give stability and permit propulsion.
BoatColorCode	j-ncic:BCOType	A code identifying the color of a vessel.
BoatHullID	IDType extends SuperType	An identifier found on a vessel's hull.
BoatHullMaterialCode	j-ncic:HULType	A code identifying a primary construction material of a vessel's hull.
BoatHullMaterialText	TextType	A primary construction material of a vessel's hull.
BoatHullShapeCode	j-ncic:HSPTType	A code identifying a shape and configuration of a hull on a vessel.
BoatHullShapeText	TextType	A hull shape and configuration on a vessel.
BoatMakeCode	j-ncic:BMAType	A code identifying the manufacturer of a vessel.
BoatPropulsionCode	j-ncic:PROType	A code identifying a mode of propulsion of a vessel.
BoatPropulsionText	TextType	A mode of propulsion of a vessel.
BoatRegistrationID	IDType extends SuperType	An identifier assigned to a vessel by the coast guard or another vessel licensing organization.
BoatTrailerMakeCode	j-ncic:BTMAType	A code identifying a make of a boat trailer.
BoatTrailerMakeName	TextType	A make of a boat trailer.
BoatTypeCode	j-ncic:BTYType	A code identifying the type of a vessel.
Bond	BondType extends ActivityType	Details about an agreement between a bondsman and a subject in which a bondsman pays the subject's bail or portion of the bail in exchange for certain conditions, including the payment of a certain amount of money and the reappearance of the subject in court on the required date.
BondAmount	AmountType extends decimal	Amount of bond

BondConditionDescriptionText	TextType	A description of a condition or requirement for a subject attached to a bond.
BondIssuer.Organization	OrganizationType extends SuperType	A person or organization who issues a bond. Sometimes referred to as a bondsman.
BondIssuer.Person	PersonType extends SuperType	A person or organization who issues a bond. Sometimes referred to as a bondsman.
BondPaymentDescriptionText	TextType	A description of what a subject pays for a bond.
BondRevokeDate	j-xsd:date	A date a bond is revoked.
BondSuretyName	TextType	A name of a person or organization who has agreed to be responsible for a subject.
BondTerminationDate	j-xsd:date	A date a bond no longer is in effect.
BondTerminationTypeText	TextType	A way a bond is no longer in effect.
Booking	BookingType extends ActivityType	Details about an administrative step taken after an arrested subject is brought to a police station or detention facility, which involves entry of the subject's name and other relevant facts on the police "blotter", and which may also include photographing, fingerprinting, and the like.
BookingAdditionalChargesIndicator	j-xsd:boolean	True if a subject has more charges for which to be booked; false otherwise.
BookingAgency	OrganizationType extends SuperType	An organization which processes a booking.
BookingAgencyRecordID	IDType extends SuperType	A booking identifier of the originating case agency. This identifier may be the booking number or the Originating Agency Report (Incident) number or a combination of both. Also known as the Originating Case Agency (OCA) number.
BookingArraignmentDate	j-xsd:date	A date a subject is due to appear in court to answer the charges filed.
BookingArraignmentTime	j-xsd:time	A time a subject is due to appear in court to answer the charges filed.
BookingCourtCaseID	IDType extends SuperType	An identifier for the cause of a booking. Sometimes referred to as a warrant or commitment number.
BookingDepositedProperty	PropertyType extends SuperType	A piece of property a subject gives to an official for safe keeping during a booking.
BookingDetentionFacility	FacilityType extends OrganizationType	A state, county or city detention facility where a subject is detained as a result of booking.

BookingDocumentControlID	IDType extends SuperType	A number assigned by a booking system to identify a unique booking event within a specific jail. This may be manually tracked if there is no booking system. It also may not be unique.
BookingEmployee	EnforcementOfficialType extends PersonType	An official who processes a subject for booking, e.g., takes photographs, fingerprints, enters relevant information into a register.
BookingFacility	FacilityType extends OrganizationType	A police station or a detention facility where a booking occurs.
BookingFileID	IDType extends SuperType	A records management system identification number for the Incident that precipitated the booking of the subject.
BookingRelease	ReleaseType extends ActivityType	Details about a release of a subject from booking or from booking detention.
BookingReleaseCorrectionsAnalyst	EnforcementOfficialType extends PersonType	A corrections pre-trial screening official.
BookingReportingDistrictText	TextType	A district of a booking agency.
BookingRetainedProperty	PropertyType extends SuperType	A piece of property a subject keeps during booking.
BookingSealedIndicator	j-xsd:boolean	True if the information regarding a booking is to remain sealed and confidential; false otherwise.
BookingSearchOfficial	EnforcementOfficialType extends PersonType	An official who searches a subject during a booking.
BookingSeizedProperty	PropertyType extends SuperType	A piece of property taken from a subject by an official during a booking. Includes a vehicle a subject may have.
BookingSubject	SubjectType extends PersonType	A person who is booked.
BookingSubjectCustodyTransfer	CustodyTransferType extends ActivityType	A transfer of custody or transportation of a subject from one booking detention facility to another.
BookingTelephoneCall	BookingTelephoneCallType extends SuperType	Details about a telephone call (number) a subject makes while being booked or detained from an arrest.
BookingTelephoneCallDate	j-xsd:date	A date a subject makes a telephone call while being booked or detained from a booking.
BookingTelephoneCallSupervisingOfficial	EnforcementOfficialType extends PersonType	A peace official who supervises a subject making a telephone call.
BookingTelephoneCallTime	j-xsd:time	A time a subject makes a telephone call while being booked or detained from a booking.

BookingTransportOfficial	EnforcementOfficialType extends PersonType	An official who moves a subject to a detention facility.
BranderID	IDType extends SuperType	A code to uniquely identify a brander (i.e., an entity applying a brand to a vehicle), which could be a state, insurance carrier, junk yard, or salvage yard. States use the US Postal State Codes. Insurance Carriers use the NAIC codes (the NAIC codes are the same as the NICB codes).
BranderTypeCode	j-ansi_d20:BranderTypeCodeType	A code to identify the type of brander (e.g., state, insurance carrier, junk yard, or salvage yard).
BuildingFullText	TextType	A complete reference that identifies a building.
BuildingName	TextType	A name of a building, e.g., "Electronic Research Building"
BuildingNumberText	TextType	A number or text associated with a building, e.g., 115C.
BuildingSubUnitText	TextType	A department, group, division, or other subcomponent of a building.
CanadianProvinceCode	j-can:CanadianProvinceCodeType	A code identifying a province of Canada.
CapabilityCategoryText	TextType	A general classification or categorization of a capability, e.g. training, physical, trait.
CapabilityDescriptionText	TextType	A description of a person's capability.
CapabilityIsLimitationIndicator	j-xsd:boolean	True if a capability implies an inability to do something, false otherwise. This indicator applies only to physical capabilities.
CapabilityTypeText	TextType	A type of capability within a particular class of capabilities, e.g. risk to others, sex offender.

Case	CaseType extends ActivityType	An aggregation of information, in any format, that describes a set of related activities and occurrences. The domain or discipline defines the limits of the information included in a specific kind of case. Case is not limited to any particular discipline or domain, and can relate a wide range of areas: a situation requiring investigation or action (as by the police); the object of investigation or consideration; an instance of disease or injury; an instance that directs attention to a situation or exhibits it in action; a set of circumstances or a state of affairs; a situation; a question or problem; a matter; an action or a law suit or just grounds for an action; the facts or evidence offered in support of a claim; a set of reasons or supporting facts; a person being assisted, treated, or studied, as by a physician, lawyer, or social worker.
CaseAmendedCharge	ChargeType extends SuperType	A charge different than the original charge a person is being tried for in a court of law.
CaseCapiasDate	j-xsd:date	A date where subject proceeds directly to court, without being able to post bond. Similar to a Failure to Appear
CaseCategoryText	TextType	A category type of a court case, e.g. criminal, civil, juvenile, family.
CaseCharge	ChargeType extends SuperType	A charge or accusation a person is being tried for in a court of law.
CaseClassification	CaseClassificationType extends SuperType	A classification or categorization of a case.
CaseContinuanceDate	j-xsd:date	A date a court case is set to resume after being postponed.
CaseConvictionReportingRequirements	CaseConvictionReportingRequirementsType extends SuperType	Details about the requirements placed on a person convicted in a case to report to a supervising agency.
CaseCourt	CourtType extends OrganizationType	A court of law in which the case is being tried.
CaseCourtEvent	CourtEventType extends ActivityType	A court occurrence. It generally refers to an appearance (Appearance, Arraignment, Findings, Sentencing, etc.) but may include clerical events such as filing an affidavit or cash register events.

CaseDefendantParty.Organization	OrganizationType extends SuperType	A person, organization, or property being charged or sued in a court of law. Sometimes referred to as the defendant.
CaseDefendantParty.Person	PersonType extends SuperType	A person, organization, or property being charged or sued in a court of law. Sometimes referred to as the defendant.
CaseDefendantParty.Property	PropertyType extends SuperType	A person, organization, or property being charged or sued in a court of law. Sometimes referred to as the defendant.
CaseDefendantQuantityText	TextType	A number of defendants being tried at once for a case.
CaseDefendantSelfRepresentationIndicator	j-xsd:boolean	True if a defendant waived the right to have a defense attorney and is representing him or her self; false otherwise.
CaseDefenseAttorney	CaseOfficialType extends JudicialOfficialType	An attorney who defends a case.
CaseDetails	CaseDetailsType extends SuperType	Additional information about a case.
CaseDisposition	CaseDispositionType extends SuperType	An outcome or processing of a case.
CaseDispositionDecision	CaseDispositionDecisionType extends SuperType	Details about a case disposition occurring as a result of some decision.
CaseDispositionDecisionText	TextType	The literal language of a decision.
CaseDispositionDecisionTypeText	TextType	A type of decision made.
CaseDispositionFinalDate	j-xsd:date	A date that all charges in a case were disposed.
CaseDocketID	IDType extends SuperType	A number used to identify a case docket.
CaseDomesticViolenceIndicator	j-xsd:boolean	True if the case involves domestic violence; false otherwise.
CaseDrivingImpairedIndicator	j-xsd:boolean	True if the case involves a person who was driving with the presence of illegal or unprescribed prescription drugs in his or her system; false otherwise.
CaseDrivingIntoxicatedIndicator	j-xsd:boolean	True if a case involves a person who was driving with blood alcohol level that is higher than the law allows; false otherwise.
CaseExhibit	ExhibitType extends SuperType	An item admitted in court as evidence.
CaseFiling	SubmissionType extends ActivityType	A submission from a prosecutor that initiates a court case.
CaseHearing	CourtEventType extends ActivityType	An appearance before a judicial official conducted in person, by telephone, or by video.

CaseInformationAdmissibleIndicator	j-xsd:boolean	True if new trial information may be entered from an appellate ruling/decision; false otherwise.
CaseInformationAdmissibleText	TextType	A piece of new trial information that may be admissible in court.
CaseInformationUnadmissibleText	TextType	A piece of new trial information that is not admissible in court.
CaseInitiatingParty.Organization	OrganizationType extends SuperType	A person, organization, or property that brings charges or a suit against another in a court of law. Can be either a victim in a criminal case or a plaintiff in a civil case.
CaseInitiatingParty.Person	PersonType extends SuperType	A person, organization, or property that brings charges or a suit against another in a court of law. Can be either a victim in a criminal case or a plaintiff in a civil case.
CaseInitiatingParty.Property	PropertyType extends SuperType	A person, organization, or property that brings charges or a suit against another in a court of law. Can be either a victim in a criminal case or a plaintiff in a civil case.
CaseJudge	CaseOfficialType extends JudicialOfficialType	A judicial official assigned to a case.
CaseJuror	JurorType	An empanelled juror or an alternate juror.
CaseLineageCase	CaseType extends ActivityType	A description of a case at a previous stage.
CaseOfficial	CaseOfficialType extends JudicialOfficialType	Details about a justice official's involvement in a court case.
CaseOfficialCaseID	IDType extends SuperType	A unique identifier a justice official uses to identify a case.
CaseOfficialCaseStatusText	TextType	A status of a justice official's case.
CaseOfficialEndDate	j-xsd:date	A date a justice official left a case or a date a case ended.
CaseOfficialRoleDescriptionText	TextType	A description of the role a justice official played in a court case.
CaseOfficialRoleText	TextType	A role a justice official played in a court case.
CaseOfficialStartDate	j-xsd:date	A date a justice official became involved in a case.
CaseOfficialTerminationIndicator	j-xsd:boolean	True if a justice official left a case before its conclusion, either by choice or for official reasons; false otherwise.
CaseOfficialTerminationReasonText	TextType	A reason a justice official left a case before its conclusion.
CaseOriginalCourt	CourtType extends OrganizationType	A court that originally heard or tried a case before it was transferred or appealed.
CaseOtherActor.Organization	OrganizationType extends SuperType	A miscellaneous person, organization, or property involved in a court case.

CaseOtherActor.Person	PersonType extends SuperType	A miscellaneous person, organization, or property involved in a court case.
CaseOtherActor.Property	PropertyType extends SuperType	A miscellaneous person, organization, or property involved in a court case.
CaseOtherID	IDType extends SuperType	A miscellaneous identifier for a case.
CaseOtherOfficial	CaseOfficialType extends JudicialOfficialType	A miscellaneous person or organization involved in a court case.
CaseParticipants	CaseParticipantsType extends SuperType	Details about the participants involved in a court case
CasePendingCourtEvent	CourtEventType extends ActivityType	A court event or activity that is postponed or pending.
CaseProceedingTypeText	TextType	A type of case proceeding, e.g., hearing, trial, arraignment.
CaseProsecutionAttorney	CaseOfficialType extends JudicialOfficialType	An attorney who prosecutes a case.
CaseProtectionOrderIndicator	j-xsd:boolean	True if a Domestic Violence Protection Order or Antiharassment Order is filed with the Judgment and Sentence; false otherwise.
CaseRelatedCase	CaseType extends ActivityType	Details about a related case.
CaseResolutionText	TextType	A result of a case.
CaseRespondentParty.Organization	OrganizationType extends SuperType	The person, organization, or property in a court case that is required to answer a petition for a court order or writ requiring the respondent to take some action, halt an activity or obey a court's direction. In such matters the moving party (the one filing the petition) is usually called the "petitioner." Thus, the respondent is equivalent to a defendant in a lawsuit. On an appeal, the party who must respond to an appeal by the losing party in the trial court (called "appellant") in the appeals court. The accused in a domestic violence case or civil action; a person responding to a Request or Petition for Protection filed by a petitioner.

CaseRespondentParty.Person	PersonType extends SuperType	The person, organization, or property in a court case that is required to answer a petition for a court order or writ requiring the respondent to take some action, halt an activity or obey a court's direction. In such matters the moving party (the one filing the petition) is usually called the "petitioner." Thus, the respondent is equivalent to a defendant in a lawsuit. On an appeal, the party who must respond to an appeal by the losing party in the trial court (called "appellant") in the appeals court. The accused in a domestic violence case or civil action; a person responding to a Request or Petition for Protection filed by a petitioner.
CaseRespondentParty.Property	PropertyType extends SuperType	The person, organization, or property in a court case that is required to answer a petition for a court order or writ requiring the respondent to take some action, halt an activity or obey a court's direction. In such matters the moving party (the one filing the petition) is usually called the "petitioner." Thus, the respondent is equivalent to a defendant in a lawsuit. On an appeal, the party who must respond to an appeal by the losing party in the trial court (called "appellant") in the appeals court. The accused in a domestic violence case or civil action; a person responding to a Request or Petition for Protection filed by a petitioner.
CaseRestrictionDate	j-xsd:date	A date a restriction is placed on a person by a court order.
CaseRestrictionText	TextType	A restriction imposed upon a party, e.g., a restraining order.
CaseSecurityText	TextType	A level of case security required from low to high
CaseSeverityText	TextType	A severity of a case, e.g., felony, misdemeanor, infraction.
CaseStatus	StatusType extends SuperType	A status of a case.
CaseSubtypeText	j-xsd:string	Second level of case category classification, e.g. employment to further define a civil case, or homicide to further define a felony case.
CaseTerminationStageText	TextType	A stage of termination for a case.
CaseTerminationTypeText	TextType	A type of termination for a case.
CaseTitleText	TextType	An official name of a case.

CaseTrackingID	IDType extends SuperType	A number used to track a case.
CaseTrial	CourtEventType extends ActivityType	A type of hearing during which the final disposition of a case is determined.
CaseTypeText	TextType	Identifies the type of case being considered, e.g., law enforcement, prosecution, court, public safety, department of human services, department of health.
CaseVerdictGivenIndicator	j-xsd:boolean	True if a verdict is given by judge or jury; false otherwise.
CaseVictimNotProsecutingIndicator	j-xsd:boolean	True if a victim is not or was not willing to prosecute; false otherwise.
CaseWitness	WitnessType extends PersonType	The person/entity who has information relating to the activity or who testifies in court.
CaseYearDate	j-xsd:gYear	A year a case is tried.
Caveat	TextType	Details about a warning, caution, qualifier, or explanation, generally about an offender or suspect.
CaveatIssuingAuthorityName	TextType	A name of a person or organization which issued a caveat.
CaveatReferenceDate	j-xsd:date	A date a caveat was issued.
CaveatText	TextType	A warning, caution, qualifier, or explanation.
Charge	ChargeType extends SuperType	Details about a formal allegation that a specific person has committed a specific offense.
ChargeAccidentRelatedIndicator	j-xsd:boolean	True if a charge is related to a traffic accident; false otherwise.
ChargeApplicabilityText	TextType	A degree of involvement a person is being charged with committing in an offense. Sometimes referred to as A/C/S, InchoateCharge. Example: Solicitation; Conspiracy; Attempt; Accessory Before the Fact.
ChargeArrestReasonIndicator	j-xsd:boolean	True if a charge is the reason a person was arrested; false otherwise.
ChargeCategoryDescriptionText	TextType	A description of a crime category.
ChargeClassification	ChargeClassificationType extends SuperType	Details that further describes and classifies a charge.
ChargeCountQuantity	j-xsd:nonNegativeInteger	A number of times a person is charged with committing the same crime.
ChargeDegreeText	TextType	A degree of a charge, e.g., first degree, second degree.
ChargeDescriptionText	TextType	A plain language description of a charge.
ChargeDisposition	ChargeDispositionType extends SuperType	Details about the results or processing of a charge.

ChargeDispositionCondition	ConditionType extends ActivityType	A requirement which, when met, represents compliance with a pre-disposition condition. For example: curfew, no contact with victim, condition of release, etc.
ChargeDispositionDate	j-xsd:date	A date of a disposition of a charge.
ChargeDispositionDescriptionText	TextType	A description of the result of processing a charge. For an arrest charge, this may be a law enforcement agency action, such as custody only, turned over to another agency, referred or not referred for prosecution. For a court case charge, this may be dismissal, or any penalties, sanctions, or sentence assessed as a result of a finding or negotiated resolution in the case.
ChargeDispositionOtherText	TextType	Additional information beyond, or separate from the ChargeDispositionDescriptionText about a charge. It may contain information about the processing of a charge rather than just the outcome.
ChargeDispositionPlea	PleaType extends ActivityType	An answer which a defendant in an action at law makes in response to a charge. Adult Examples: Guilty, Not Guilty. Juvenile Examples: Admit, Deny.
ChargeDispositionReasonText	TextType	A reason for disposing of a charge via dismissal, discharge, etc.
ChargeDispositionSanction	SanctionType extends ActivityType	A penalty ordered for a subject by a judge or a supervising agency as a result of a disposition of a charge.
ChargeDispositionVerdict	VerdictType extends ActivityType	A finding by a judge or jury of that nature of a person allegedly committing an offense.
ChargeEmploymentRelatedIndicator	j-xsd:boolean	True if a charge is related to a person's employment; false otherwise.
ChargeEnhancingAllegationCharge	ChargeType extends SuperType	A formal allegation, contained in at least one charging instrument, that a defendant has violated a statute and/or ordinance in association with an incident.
ChargeEnhancingFactor	ChargeEnhancingFactorType extends SuperType	Details about a factor or reason that makes a charge more serious (e.g., armed, against the elderly, hate crime)
ChargeEnhancingFactorDescriptionText	TextType	A description of a factor or reason that makes a charge more serious.
ChargeEnhancingFactorReferenceDate	j-xsd:date	A reference date for an enhancing charge factor or reason.
ChargeEnhancingFactorStatusText	TextType	A status of a factor or reason that makes a charge more serious.
ChargeEnhancingFactorText	TextType	A factor or reason that makes a charge more serious.

ChargeEnhancingPriorConviction	ConvictionType extends ActivityType	Details about a prior conviction. A usage of this may be for a three strikes you are out rule.
ChargeFelonyIndicator	j-xsd:boolean	True if a charge refers to a felony offense; false otherwise. Sometimes referred to as Severity Level.
ChargeFiler.Organization	OrganizationType extends SuperType	A person or organization which filed a current charge.
ChargeFiler.Person	PersonType extends SuperType	A person or organization which filed a current charge.
ChargeFilingDate	j-xsd:date	A date a charge was filed.
ChargeHighestIndicator	j-xsd:boolean	True if a charge is the most serious charge within a group of charges; false otherwise.
ChargeID	IDType extends SuperType	A unique identifying number assigned to a particular charge by an arresting agency, prosecuting attorney, or a court for case management purposes.
ChargeInstrument	DocumentType extends SuperType	An official document filed to formally accuse a person of committing a specific offense.
ChargeLegalDescriptionText	TextType	The legal or formal description of a charge.
ChargeLocalCode	NonStandardCodeType extends SuperType	A local statute or ordinance that identifies an offense.
ChargeMACRDispositionText	TextType	Charge disposition as reported to the Monthly Arrest and Citation Register.
ChargeMACRIndicationLevelText	TextType	An indication of the level or seriousness of the charge, as reported to the Monthly Arrest and Citation Register
ChargeMACRJuvvenileLevelText	TextType	An indication of the level or seriousness of a juvenile charge, as reported to the Monthly Arrest and Citation Register
ChargeMACRStatusText	TextType	A status of a charge, as reported to the Monthly Arrest and Citation Register
ChargeModificationInstrument	DocumentType extends SuperType	An official document filed to modify a charge against a person.
ChargeModifier.Organization	OrganizationType extends SuperType	An organization or person that modified the original charge.
ChargeModifier.Person	PersonType extends SuperType	An organization or person that modified the original charge.
ChargeNarrative	DocumentType extends SuperType	A document associated with a charge.

ChargeNCICCode	j-ncic:OFFType	A code that identifies an offense within the National Crime Information Center (NCIC) system.
ChargeOriginator.Organization	OrganizationType extends SuperType	An agency, organization, or person (e.g., attorney) that originally filed a charge or a related predecessor charge if the charge was changed later by prosecution or the court. This originating party is often an arresting agency but may be different if a charge was added during booking or if cases are consolidated.
ChargeOriginator.Person	PersonType extends SuperType	An agency, organization, or person (e.g., attorney) that originally filed a charge or a related predecessor charge if the charge was changed later by prosecution or the court. This originating party is often an arresting agency but may be different if a charge was added during booking or if cases are consolidated.
ChargeQualifierText	TextType	Additional information that clarifies a charge.
ChargeRecommendedBailAmount	AmountType extends decimal	A bail amount on a schedule recommended according to the charge.
ChargeReducingFactorText	TextType	A factor which may make a charge less serious or limit the penalty (e.g., violations observed by photo-radar stations in some states)
ChargeReporting	ChargeReportingType extends SuperType	Information that is sent to local, state, or federal repositories describing the nature of a charge in terms of official codes, terms, and fields.
ChargeSanction	SanctionType extends ActivityType	A sanction given to a person convicted of a charge.
ChargeSentence	SentenceType extends ActivityType	A sentence given to a person convicted of a charge.
ChargeSentenceRangeText	TextType	A standard sentence range a person charged with an offense potentially faces if convicted.
ChargeSequenceID	IDType extends SuperType	A sequentially assigned number for charge tracking purposes (for example, the first charge under the arrest might be assigned Charge Sequence ID 1, the second 2, and so forth).
ChargeSeriousViolentIndicator	j-xsd:boolean	True if a charge filed refers to a serious or violent offense; false otherwise.
ChargeSeverityLevel	SeverityLevelType extends SuperType	A severity level of a charge.

ChargeSeverityText	TextType	A level of severity of a charge, e.g., Felony; Misdemeanor; Petty Misdemeanor; Other; Unknown.
ChargeSpecialAllegationText	TextType	A factor that has enhanced a charge, making it a more serious offense.
ChargeStatus	StatusType extends SuperType	A state of a charge.
ChargeStatute	StatuteType extends SuperType	A unique identifier of a law, rule, or ordinance within a jurisdiction that a person is accused of violating.
ChargeSubject	SubjectType extends PersonType	A person accused of committing a specific offense.
ChargeText	TextType	The text of a charge.
ChargeTrackingID	IDType extends SuperType	A unique identifying number assigned to an entire set of charges for an arrest. Different numbers may appear in the set if cases have been consolidated.
ChargeUCRCode	j-ucr:OffenseCodeType	A code that identifies an offense within the Uniform Crime Report (UCR) system.
ChargeUCRCrimeTypeText	TextType	A Uniform Crime Report (UCR) type or classification of a crime associated with a charge.
ChargeVerdict	VerdictType extends ActivityType	Details describing if a person was found guilty or innocent of a charge.
ChargeVictim	VictimType extends SuperType	A person or entity who is the victim of an offense designated by the charge.
CircularRegionCenterCoordinate	GeographicCoordinateType extends SuperType	A coordinate of the center of a circular region.
CircularRegionRadiusLengthMeasure	LengthMeasureType extends MeasureType	A length of a radius of a circular area.
Citation	CitationType extends ActivityType	Details about an official summons to appear in court or pay a fine given to a subject from a peace official due to a subjects violation or infraction of a law.
CitationAgency	OrganizationType extends SuperType	An organization for whom the citation issuing official is employed.
CitationDismissalConditionIndicator	j-xsd:boolean	True if a citation can be dismissed if certain conditions are met; false otherwise.
CitationDismissalConditionText	TextType	A condition to be met that can make a citation eligible for dismissal.

CitationFineAmount	AmountType extends decimal	An amount of money to be paid by the subject receiving the citation if the subject chooses not to dispute the citation in court.
CitationIssuedLocation	LocationType extends SuperType	A place where a citation is given to a subject.
CitationIssuingOfficial	EnforcementOfficialType extends PersonType	A peace official who gives a citation to a subject.
CitationSubject	SubjectType extends PersonType	A person who violates a law and receives a citation.
CitationViolation	IncidentType extends ActivityType	An activity that is a violation of a law or ordinance that results in a subject being given a citation.
Classification	ClassificationType extends SuperType	A restriction imposed on information on documents or data that are only available to certain authorized people.
ClassificationAgencyName	TextType	A name of the agency which classified the information.
ClassificationDerivationText	TextType	A source where a classification was derived from.
ClassificationEffectiveDate	j-xsd:date	A date the classification became effective.
ClassificationInstructionText	TextType	An instruction related to classifying information as such.
ClassificationNonUSText	TextType	A word that describes the highest non-United States classification of a document.
ClassificationPersonName	TextType	A name of the person who classified the information.
ClassificationReasonText	TextType	A reason why the classification was made as such.
ClassificationReviewAgencyName	TextType	A name of the agency set to review or has reviewed the classification.
ClassificationReviewDate	j-xsd:date	A date a classification is to be or has been reviewed.
ClassificationReviewPersonName	TextType	A name of a person set to review or who has reviewed the classification.
ClassificationTerminationActualDate	j-xsd:date	A date the classification actually terminated.
ClassificationTerminationSetDate	j-xsd:date	A date the classification is set to terminate.
ClassificationText	TextType	A classification of information. Includes confidential, secret, top secret, no markings.
ClassificationUSCode	j-dod_exec-12958:SecurityClassificati	A code used to describe the highest classification of a United States document, e.g., top secret.
ClothingCategoryText	TextType	A general category of clothing, e.g., shirt, pants.
ClothingColorText	TextType	A color of an article of clothing.
ClothingDescriptionText	TextType	A description of an article of clothing.
ClothingStyleText	TextType	A style of an article of clothing.

CommercialStructure	StructureType extends PropertyType	A structure used for business purposes.
CommercialVehicle	CommercialVehicleType extends VehicleType	Details about a class of vehicle that includes motor vehicles with a gross vehicle weight rating of 26,001 pounds or more.
Condition	ConditionType extends ActivityType	Details about a requirement which, when met, represents compliance with a pre-disposition condition. For example: curfew, no contact with victim, condition of release, etc.
ConditionalRelease	ConditionalReleaseType extends ReleaseType	Details about a release of a person or item from confinement, holding, or obligation, that is dependent upon certain conditions being met.
ConditionalReleaseCondition	ConditionType extends ActivityType	A requirement or prerequisite for release. A restriction, modification, or qualification of a term or terms of release. (Ex. no contact with victim; do not leave jurisdiction of court, etc.)
ConditionalReleaseOppositionText	TextType	A reason against releasing a person.
ConditionalReleaseProjectedDate	j-xsd:date	An expected date of conditional release. This date may change over time.
ConditionalReleaseRevokedDate	j-xsd:date	A date a conditional release was revoked due to a person's failure in meeting required conditions or for other reasons.
ConditionalReleaseRevokedReasonText	TextType	A reason why a conditional release was revoked.
ConditionalReleaseSupportText	TextType	A reason in support of releasing a person.
ConditionDisciplinaryAction	DisciplinaryActionType extends ActivityType	A corrective action such as attending counseling or entering a risk reduction facility that is specified as part of a condition as stated in the imposed sentence.
ConditionGroup	ConditionGroupType extends ActivityType	Details about a set of conditions assigned to a person.
ConditionGroupID	IDType extends SuperType	An identifier of a group of conditions to which this condition belongs.
ConditionGroupParentID	IDType extends SuperType	ID of the parent condition group to which this group belongs.
ConditionMandatoryIndicator	j-xsd:boolean	True if a condition is strictly required; false otherwise.
ConditionSetDate	j-xsd:date	A date a condition was set.
ConditionViolatedIndicator	j-xsd:boolean	True if a condition has been violated; false otherwise.
ConditionViolationDate	j-xsd:date	A date a condition was violated.
ConditionViolationText	TextType	A violation of a condition.

ContactEmailID	IDType extends SuperType	An email address of a person or organization.
ContactFacsimileNumber	TelephoneNumberType extends SuperType	A facsimile number of a person or organization. Sometimes referred to as a FAX or fax number.
ContactInformation	ContactInformationType extends SuperType	Details about how to contact a person or an organization.
ContactInformationDescriptionText	TextType	A general description of contact information.
ContactMailingAddress	AddressType extends SuperType	A mailing address of a person or organization.
ContactMobileTelephoneNumber	TelephoneNumberType extends SuperType	A mobile phone or cell phone number of a person.
ContactOrganization	OrganizationType extends SuperType	An organization at the site of the contact. Example: the organization that "owns" the physical telephone being called.
ContactOtherID	IDType extends SuperType	An additional method of contact, e.g., Internet Relay Chat (IRC), AOL Instant Messenger.
ContactPagerNumber	TelephoneNumberType extends SuperType	A pager number of a person.
ContactPerson	PersonType extends SuperType	A person with the given contact information.
ContactPersonDescriptionText	TextType	A description of the title or function of a person with this contact information, e.g., Director of Public Relations, mother.
ContactRadio	ContactRadioType extends SuperType	A radio contact information of a person.
ContactRadioCallSignID	IDType extends SuperType	A term used to identify a person using this radio. Sometimes referred to as a handle or call letters, e.g., "Whiskey 52".
ContactRadioChannelText	TextType	A radio channel or frequency within the band.
ContactRadioTypeText	TextType	A wavelength or band of a radio, e.g., AM, FM, CB, FRS, GRS, military, etc.
ContactResponder	PersonType extends SuperType	A person who is actually at the "other end" of the contact. Used when the address is for a third party who is supposed to find the contactee (a secretary, for example).
ContactTelephoneNumber	TelephoneNumberType extends SuperType	A telephone number of a person or organization.

ContactWebsiteID	IDType extends SuperType	A website address of a person or organization.
Conviction	ConvictionType extends ActivityType	Details about a judgment, based either on the verdict of a jury or judicial official or the guilty plea of a defendant, that the defendant is guilty.
ConvictionCharge	ChargeType extends SuperType	A charge for which a person was convicted.
ConvictionCountQuantity	j-xsd:nonNegativeInteger	A total number of charges a person has been found guilty of with reference to charging document.
ConvictionCourt	CourtType extends OrganizationType	A court in which a conviction was issued.
ConvictionLocatorReferenceID	IDType extends SuperType	A reference number for the organization that keeps the conviction records.
ConvictionOffense	IncidentType extends ActivityType	An offense that a person has been found guilty of committing.
ConvictionPlea	PleaType extends ActivityType	A final plea a person offered in response to the charges filed.
ConvictionReportingProfessionName	TextType	A name of the profession or occupation of an arrested professional.
ConvictionReportingRequirementText	TextType	A description of when the court is required to file a special report, e.g. when complaint is filed, at conviction.
ConvictionSanction	SanctionType extends ActivityType	A penalty imposed upon a person having been found guilty of a crime.
ConvictionSentence	SentenceType extends ActivityType	A sentence imposed upon a person having been found guilty of a crime.
ConvictionSubject	SubjectType extends PersonType	A person who was found guilty of a crime.
ConvictionVerdict	VerdictType extends ActivityType	A guilty verdict of a judge or jury.
CorrectionalFacility	FacilityType extends OrganizationType	A facility that both detains and provides instruction and training in trade and vocational activities to subjects charged or convicted of a crime.
Corrections	SupervisionType extends ActivityType	An involvement of an agency or facility with the custody, confinement, supervision, or treatment of alleged or adjudicated offenders.
Court	CourtType extends OrganizationType	Details about a court or a unit of a court responsible for trying justice proceedings.

CourtActivity	CourtActivityType extends ActivityType	Details about a court-related action associated with a court case event. There must be at least one activity for each event. For example: ordering bail, pleading of not guilty, filing an affidavit. An activity may have conditions attached to it. An activity takes place on the date of the event to which it pertains.
CourtActivityCondition	ConditionType extends ActivityType	A condition related or attached to a court activity.
CourtActivityCourtOrder	CourtOrderType extends ActivityType	A direction of a judge not included in a judgment, which determines some point or directs some step in proceedings.
CourtActivityScheduleDay	ScheduleDayType extends ActivityType	A schedule on which a court activity is to occur.
CourtActivitySupervisingAgency	OrganizationType extends SuperType	A supervising agency associated with a court activity result, especially for reporting purposes. For example, for pre-plea and pre-sentencing investigations.
CourtAdministrativeUnitText	TextType	A unit within a court system responsible for record maintenance.
CourtAppearance	CourtAppearanceType extends SuperType	Details about an appearance required of a party in a court of law on a certain date.
CourtAppearanceActor.Organization	OrganizationType extends SuperType	A person, organization, or property required to appear in court.
CourtAppearanceActor.Person	PersonType extends SuperType	A person, organization, or property required to appear in court.
CourtAppearanceActor.Property	PropertyType extends SuperType	A person, organization, or property required to appear in court.
CourtAppearanceCase	CaseType extends ActivityType	A case for which a party must appear in court.
CourtAppearanceCourt	CourtType extends OrganizationType	A court in which a party is required to appear.
CourtAppearanceDate	j-xsd:date	A date on which a party must appear in court.
CourtAppearanceReasonText	TextType	A reason a party is required to appear in court.
CourtAppearanceTime	j-xsd:time	A time at which a party must appear in court.
CourtAppearanceTypeText	TextType	A type of appearance a party is required to make in court, e.g., sentencing, bail.

CourtCharge	ChargeType extends SuperType	A charge a person is tried for in court. May be different from or the same as its predecessor arrest and prosecution charges.
CourtDivisionText	TextType	An area of case processing and the law governing specific types of matters before the court and governed by distinct court rule and processes, e.g., criminal, juvenile, family, civil, etc.
CourtEvent	CourtEventType extends ActivityType	Details about a court occurrence. An event generally refers to an appearance (Appearance, Arraignment, Findings, Sentencing, etc.) but may include clerical events such as filing an affidavit or cash register events.
CourtEventActivity	CourtActivityType extends ActivityType	A court-related action associated with a court case event. There must be at least one activity for each event. For example: ordering bail, pleading of not guilty, filing an affidavit. An activity may have conditions attached to it.
CourtEventAppearance	CourtAppearanceType extends SuperType	An appearance in court required of a party
CourtEventCase	CaseType extends ActivityType	A case associated with a court event.
CourtEventCourt	CourtType extends OrganizationType	A court in which a court event occurs.
CourtEventJudge	JudicialOfficialType	A judge associated with a court event.
CourtEventMotion	CourtActivityType extends ActivityType	A request made to a court for a ruling or an order.
CourtEventSchedule	ScheduleDayType extends ActivityType	Details about the days for which a court event is scheduled.
CourtEventSequenceID	IDType extends SuperType	A unique identifier for a court case event record.
CourtName	TextType	A name of a unit of a court.
CourtOrder	CourtOrderType extends ActivityType	Details about a direction of a judge not included in a judgement, which determines some point or directs some step in proceedings.
CourtOrderCondition	ConditionType extends ActivityType	A condition described in a court order that is to be followed by a subject.
CourtOrderDesignatedLocation	LocationType extends SuperType	A location to which a court order applies.

CourtOrderDesignatedOrganization	OrganizationType extends SuperType	An organization to which a court order applies.
CourtOrderDesignatedProperty	PropertyType extends SuperType	A property item to which a court order applies.
CourtOrderDesignatedSubject	SubjectType extends PersonType	A person to which a court order applies. The subject could be a Protected Party, the recipient of a Summons or Subpoena, the subject of a Warrant, etc.
CourtOrderEnforcementAgency	OrganizationType extends SuperType	An agency responsible for enforcing a court order.
CourtOrderIssuingCourt	CourtType extends OrganizationType	A court that issued a court order.
CourtOrderIssuingDate	j-xsd:date	A date a court order was issued by a judicial official.
CourtOrderIssuingJudicialOfficial	JudicialOfficialType	A judge or other judicial official that issued a court order.
CourtOrderJurisdiction	JurisdictionType	An area in which a court order can be enforced.
CourtOrderRecallDate	j-xsd:date	A date a court order was recalled or rescinded.
CourtOrderRecallReasonText	TextType	A reason a court order was recalled or rescinded.
CourtOrderRequestActor.Organization	OrganizationType extends SuperType	A person or organization which requested a court order.
CourtOrderRequestActor.Person	PersonType extends SuperType	A person or organization which requested a court order.
CourtOrderRequestActor.Property	PropertyType extends SuperType	A person or organization which requested a court order.
CourtOrderRequestDate	j-xsd:date	A date a court order was requested.
CourtOrderRequestReasonText	TextType	A reason why a court order was requested.
CourtOrderServiceAttemptedDate	j-xsd:date	A date a court order was attempted but unable to be delivered.
CourtOrderServiceCautionText	TextType	A caution, warning, or risk advisement given as an alert to an official servicing a court order.
CourtOrderServiceDate	j-xsd:date	A date a court order was delivered.
CourtOrderServiceDescriptionText	TextType	A description of how a court order was delivered.
CourtOrderServiceOfficial.Enforcement	EnforcementOfficialType extends PersonType	An official who delivered a court order.
CourtOrderServiceOfficial.Judicial	JudicialOfficialType	An official who delivered a court order.
CourtOrderServiceReceivedDate	j-xsd:date	A date a service agency received a court order to deliver.
CourtOrderServiceRestrictionText	TextType	A restriction or limitation on how a court order can be delivered.

CourtOrderSignatureMethodText	TextType	A method used to obtain a signature on a court order. For example, Telephonic, Fax, etc.
CourtOrderSpecialInstructionText	TextType	A description of inclusions and/or constraints of a court order. Like extradition limitation or whether an arrest or a search warrant may be served at a subject's residence between sunrise and sunset only (nightcap indicator), etc.
CourtOrderStatus	StatusType extends SuperType	A state of a court order.
CourtOrderSupervisingAgency	OrganizationType extends SuperType	An agency responsible for evaluating, investigating, supervising and/or setting conditions for a subject incarcerated, on probation, conditional release, supervised release, parole, or otherwise under the jurisdiction of the court, the Department of Corrections, or a Community Corrections Act county.
CourtSupervisingAgency	OrganizationType extends SuperType	A supervising agency that performs court services for a court unit.
CourtTypeCode	j-ansi d20:CourTypeCodeType	A type of court, e.g., district court, appellate court, state superior court.
CriminalOrganization	CriminalOrganizationType extends OrganizationType	Details about an organization that is formed to or intentionally conducts illegal activities.
CriminalOrganizationCautionText	TextType	A caution or warning associated with a criminal organization.
CriminalOrganizationMembershipHighQuantityText	TextType	A high estimate of the number of people in an organization.
CriminalOrganizationMembershipInitiationText	TextType	A description of the requirement or result of a person becoming a member of a criminal organization.
CriminalOrganizationMembershipLowQuantityText	TextType	A low estimate of the number of people in an organization.
CriminalOrganizationNCICID	IDType extends SuperType	An identifier assigned to a criminal organization. Sometimes referred to as an NCIC code, VGTOF code.
CriminalOrganizationObjectiveText	TextType	An objective or purpose of the criminal organization.
CriminalOrganizationTraitDetails	CriminalTraitDetailsType extends SuperType	A description of characteristic traits and identifiers of a criminal organization.
CriminalTraitAction	EventType extends SuperType	Details about a characteristic action associated with criminal activity by a person or a criminal organization.
CriminalTraitActivityDescriptionText	TextType	A description of a type of crime a criminal organization or person usually commits.
CriminalTraitColorText	TextType	A color associated with criminal activity.

CriminalTraitCommunicationDescriptionText	TextType	A description of the types of communication used by a criminal organization or person.
CriminalTraitDescriptionText	TextType	A description of criminal characteristics, e.g., a trait, pattern, or trademark
CriminalTraitDetails	CriminalTraitDetailsType extends SuperType	Details about criminal characteristics associated with a person or a criminal organization.
CriminalTraitDressText	TextType	Identifying dress or clothing associated with a criminal organization or person.
CriminalTraitEthnicityCode	j-nibrs:EthnicityCodeType	Identifies an ethnic or cultural background associated with a criminal organization.
CriminalTraitEthnicityText	TextType	An ethnic or cultural background associated with a criminal organization.
CriminalTraitGraffitiDescriptionText	TextType	A description of criminal artwork (often spray-painted images) associated with a criminal organization or person.
CriminalTraitGraffitiImage	ImageType extends BinaryType	An image of criminal artwork (often spray-painted images).
CriminalTraitHandSignalText	TextType	An identifying hand signal associated with a criminal organization or person.
CriminalTraitModusOperandiText	TextType	A usual way in which a criminal organization or person acts or operates.
CriminalTraitTargetDescriptionText	TextType	A description of the type of recipient of criminal activity usually chosen by a criminal organization or person. This could describe a person, organization, location, or property.
CriminalTraitTattooDescriptionText	TextType	A description of a tattoo associated with a criminal organization or person.
CriminalTraitTattooImage	ImageType extends BinaryType	An image of a tattoo associated with a criminal organization or person.
CriminalTraitTurfText	TextType	A description of a location a criminal organization or person often frequents or considers to have control over. Sometimes referred to as haunts, hangouts.
CrossStreet	CrossStreetType extends SuperType	Details about an intersecting street near a location.
CrossStreetDescriptionText	TextType	A description of an intersecting street.
CrossStreetRelativeLocation	RelativeLocationType extends SuperType	Details about a location with respect to a cross street.

CustodyTransfer	CustodyTransferType extends ActivityType	A transfer of custody or transportation of a subject or property from one enforcement party to another.
CustodyTransferActionText	TextType	An action taken in the transfer of custody.
CustodyTransferLocation	LocationType extends SuperType	A location where transfer of custody occurs.
CustodyTransferProperty	PropertyType extends SuperType	A piece of property which is being transferred from one custody to another.
CustodyTransferReceivingEnforcementAgency	OrganizationType extends SuperType	An enforcement agency that receives custody of a subject or property.
CustodyTransferReceivingEnforcementFacility	FacilityType extends OrganizationType	An enforcement facility that receives custody of a subject or property.
CustodyTransferReceivingEnforcementOfficial	EnforcementOfficialType extends PersonType	A peace official that receives custody of a subject or property.
CustodyTransferReleasingEnforcementAgency	OrganizationType extends SuperType	An enforcement agency that releases custody of a subject or property.
CustodyTransferReleasingEnforcementFacility	FacilityType extends OrganizationType	An enforcement facility that releases custody of a subject or property.
CustodyTransferReleasingEnforcementOfficial	EnforcementOfficialType extends PersonType	A peace official that releases custody of a subject or property.
CustodyTransferSubject	SubjectType extends PersonType	A person who is being transferred from one custody to another.
DecalColorText	TextType	A color of a vehicle registration decal. Sometimes referred to as the sticker color.
DecalID	IDType extends SuperType	An identifier assigned to a registration decal sticker in a given year. Sometimes referred to as a decal number.
DecalMonthDate	j-xsd:gMonth	A month as shown on the registration decal issued, e.g., JAN, FEB, MAR, etc.
DecalPeriodCode	j-ansi_d20:DecalPeriodCodeType	A code that describes the lifespan of a decal on a vehicle license plate.
DecalPeriodText	TextType	A lifespan of a decal on a vehicle license plate.
DecalYearDate	j-xsd:gYear	A year as shown on the registration decal issued, e.g., 1995, 1996, 1997, etc.
Detention	SupervisionType extends ActivityType	A mandatory confined supervision of a person.
DetentionFacility	FacilityType extends OrganizationType	A facility that carries out the confinement of a subject charged or convicted of a crime.

DisciplinaryAction	DisciplinaryActionType extends ActivityType	Details about an activity assigned to a person that is meant to be self-improving or restititional.
DisciplinaryActionAssigner.Organization	OrganizationType extends SuperType	A person or an organization which assigned a corrective action to a person.
DisciplinaryActionAssigner.Person	PersonType extends SuperType	A person or an organization which assigned a corrective action to a person.
DisciplinaryActionCommunityService	ActivityType extends SuperType	Community service a person is recommended or required to perform as a correctional action.
DisciplinaryActionCounseling	ActivityType extends SuperType	Counseling a person is recommended or required to attend as a correctional action.
DisciplinaryActionEnforcer.Organization	OrganizationType extends SuperType	A person or an organization responsible for making sure a person performs a corrective activity assigned.
DisciplinaryActionEnforcer.Person	PersonType extends SuperType	A person or an organization responsible for making sure a person performs a corrective activity assigned.
DisciplinaryActionFacility	FacilityType extends OrganizationType	A facility a person is assigned to for a corrective action. May be a risk reduction facility, a diversion facility.
DisciplinaryActionFee	ObligationType extends SuperType	A monetary fine assigned to a person or organization.
DisciplinaryActionProgram	ProgramType extends SupervisionType	A risk reduction, rehabilitation, diversion, or other type program a person is recommended or required to attend as a correctional action.
DisciplinaryActionRestitution	ObligationType extends SuperType	A restitution or compensation a person is required to pay another person.
DisciplinaryActionSanction	SanctionType extends ActivityType	A sanction or penalty ordered for a subject by a judge or a supervising agency as a result of a disposition of a charge.
DisciplinaryActionSubject	SubjectType extends PersonType	A person who is assigned a corrective action.
Disposition	DispositionType extends SuperType	A result or outcome that is the product of handling, processing, or finalizing a charge, case, activity or entity. Includes law enforcement, prosecutorial, and court dispositions.
DispositionDate	j-xsd:date	A date a disposition occurred.
DispositionDescriptionText	TextType	A description of a disposition.
DispositionInstrument	DocumentType extends SuperType	An official document filed to formally document the disposition of a specific Charge.
DispositionReasonText	TextType	A reason why an outcome occurred.

DispositionReportedAuthorityText	TextType	A name of an authority to which a disposition was reported.
DispositionText	TextType	A result or outcome that occurred after processing an activity or entity.
DispositionTypeText	TextType	A type of disposition.
DiversionProgram	ProgramType extends SupervisionType	A program designed to help a person give up a criminal lifestyle.
DNAImage	ImageType extends BinaryType	An image of a DNA strand.
DNALocus	DNALocusType extends SuperType	Location specific information regarding a person's DNA.
DNALocusTypeText	TextType	The location within a strand of DNA that a value was determined.
DNALocusValue	TextType	The value string for a DNA locus.
Document	DocumentType extends SuperType	Details about inherent and frequently used characteristics of a document. Format or media is irrelevant in defining a document, however they are characteristics of a document. Documents are considered unique resources.
DocumentAbstractText	TextType	A summary of the content of the resource.
DocumentAlternativeTitleText	TextType	Any form of the title used as a substitute or alternative to the formal title of the resource.
DocumentApplicationName	ApplicationNameType extends SuperType	A name of the application used to create the document.
DocumentApprovedIndicator	j-xsd:boolean	True if a document has been approved; false otherwise.
DocumentAuthor.Organization	OrganizationType extends SuperType	A person or organization primarily responsible for creating the intellectual content of the resource, e.g., author for written documents, artist, photographer or illustrator for visual resources.
DocumentAuthor.Person	PersonType extends SuperType	A person or organization primarily responsible for creating the intellectual content of the resource, e.g., author for written documents, artist, photographer or illustrator for visual resources.
DocumentBinary	BinaryType extends SuperType	The binary encoding of the content of a document.
DocumentCategoryDescriptionText	TextType	A description of the category of information in a document.
DocumentCategoryID	IDType extends SuperType	An identifier of a category of information in a document.

DocumentCategoryName	TextType	A category of information in a document.
DocumentCommentText	TextType	A general comment about a document.
DocumentContentTableText	TextType	A subunit of the content of the resource usually containing a list of the information content of the resource.
DocumentContributor.Organization	OrganizationType extends SuperType	An entity responsible for making contributions to the content of the resource. May include a person, organization, or service.
DocumentContributor.Person	PersonType extends SuperType	An entity responsible for making contributions to the content of the resource. May include a person, organization, or service.
DocumentControlMetadata	DocumentControlMetadataType extends SuperType	Details about the control and management of a document.
DocumentCopyrightIndicator	j-xsd:boolean	True if a document is copyrighted; false otherwise. Copyrighted products cannot be reproduced and/or distributed without the express written permission of the copyright owner. This prohibition is binding on individuals and corporations, as well as the United States government.
DocumentCountryCode.iso3166Alpha2	j-iso_3166:CountryAlpha2CodeType	A country or countries being discussed in a document.
DocumentCountryCode.iso3166Alpha3	j-iso_3166:CountryAlpha3CodeType	A country or countries being discussed in a document.
DocumentCountryCode.fips10-4	j-fips_10-4:CountryCodeType	A country or countries being discussed in a document.
DocumentCountryCode.iso3166Numeric	j-iso_3166:CountryNumericCodeType	A country or countries being discussed in a document.
DocumentCoverageText.Address	AddressType extends SuperType	An extent or scope of the content of the resource. May include a spatial location, temporal period, or a jurisdiction.
DocumentCoverageText.Date	j-xsd:date	An extent or scope of the content of the resource. May include a spatial location, temporal period, or a jurisdiction.
DocumentCoverageText.Text	TextType	An extent or scope of the content of the resource. May include a spatial location, temporal period, or a jurisdiction.
DocumentCoverageText.Time	j-xsd:time	An extent or scope of the content of the resource. May include a spatial location, temporal period, or a jurisdiction.
DocumentCreationDate	j-xsd:date	A date of the creation of the resource.
DocumentCreator.Organization	OrganizationType extends SuperType	An entity primarily responsible for making the content of the resource.

DocumentCreator.Person	PersonType extends SuperType	An entity primarily responsible for making the content of the resource.
DocumentCutDate	j-xsd:date	A cutoff date for information in a document. Sometimes referred to as Information Cutoff Date, ICOD.
DocumentDescriptionText	TextType	A brief account of the content of a resource. May include but not limited to an abstract, table of contents, graphical, or free-text account of the content.
DocumentDescriptiveMetadata	DocumentDescriptiveMetadataType extends SuperType	Details about general document descriptors.
DocumentDispositionAuthorityName	TextType	A name of an authority designated to handle or process information in a document.
DocumentDispositionInstructionText	TextType	An instruction on how to handle or process information in a document.
DocumentDisputedIndicator	j-xsd:boolean	True if the accuracy of a document is disputed; false otherwise.
DocumentDisputedReasonCodeText	TextType	A local code indicating a reason why the accuracy of a document is being disputed.
DocumentDisputedReasonText	TextType	A reason why the accuracy of a document is being disputed.
DocumentEffectiveDate	j-xsd:date	A date the information in a document becomes valid.
DocumentEnteredBy	PersonType extends SuperType	The person who made a particular entry into the referenced document.
DocumentExpirationDate	j-xsd:date	A date a document should be removed from a registry or index.
DocumentFileControlID	IDType extends SuperType	A number assigned to a document that identifies the location of a file is located within a file control system.
DocumentFiledDate	j-xsd:date	A date a document was filed.
DocumentFiledTime	j-xsd:time	The time that the a document is officially filed. The circumstance of the official time is dictated by local policy and procedure, therefore the time recorded reflects the application of this policy.
DocumentFileExtensionText	TextType	A file extension of an electronic copy of a document.
DocumentFileName	TextType	A file name of an electronic copy of a document.
DocumentFormatText	TextType	The specific structural format of the binary object or file, e.g., "image/jpeg", "text/plain".

DocumentFormatTypeText	TextType	The classification system used to define the specific format of the binary object or file, e.g., "MIME", "DIME".
DocumentGroupID	IDType extends SuperType	An identifier of a group to which a document belongs.
DocumentID	IDType extends SuperType	A unique and unambiguous reference to the resource within a given context.
DocumentIntelligenceTypeCode	j-dod_jcs-pub2.0:DocumentIntelligenc	A nature or genre of the resource. Type is specified as an intelligence discipline, e.g., HUMINT, IMINT.
DocumentKeywordText	TextType	A keyword or words that describe the overall content of the document, or the main topic of discussion.
DocumentLanguageCode.iso639-2b	j-iso_639-2b:LanguageCodeType	A language of the intellectual content of the resource.
DocumentLanguageCode.iso639-2t	j-iso_639-2t:LanguageCodeType	A language of the intellectual content of the resource.
DocumentLastModifiedDate	j-xsd:date	The date that a document was last updated.
DocumentLocation	LocationType extends SuperType	Details about the location of a physical document.
DocumentLocationURI	IDType extends SuperType	A URI (Uniform Resource Identifier) for the referenced document which may indicate the HTTP or Intelink address.
DocumentMangementCyclePeriodText	TextType	A review or update cycle period for a document.
DocumentMediaTypeText	TextType	A physical device on which a document is stored.
DocumentMediumText	TextType	The makeup of the material or physical carrier of the resource.
DocumentOtherAddresseeName	TextType	A name of additional addressees.
DocumentOtherMetadataField	MetadataFieldType extends SuperType	A user-defined document metadata field.
DocumentPermanentRecordIndicator	j-xsd:boolean	True if a document is to be kept as a permanent record; false otherwise.
DocumentPostDate	j-xsd:date	A date a document is posted to Intelink.
DocumentPrivacyActIndicator	j-xsd:boolean	True if a document is categorized as containing personal information subject to protection by the Privacy Act; false otherwise.
DocumentPublicationDate	j-xsd:date	A date of the first public dissemination of the content in any media.
DocumentReceivedDate	j-xsd:date	A date a transmitted document was received.
DocumentRelatedResourceText	TextType	A reference to a related resource.
DocumentRelationText	TextType	Another document related to this document instance.

DocumentRightsText	TextType	Rights held in and over the resource. Rights are the constraints applied to assure the protection of privacy or intellectual property, and any special restrictions, limitations or warning on using a shared resource.
DocumentSecurityMetadata	SecurityMetadataType extends SuperType	Details about security and classification information of a document.
DocumentSequenceID	IDType extends SuperType	An identifier that determines the document order in a set or related documents.
DocumentSource.Organization	OrganizationType extends SuperType	A person or organization that was the source of a document.
DocumentSource.Person	PersonType extends SuperType	A person or organization that was the source of a document.
DocumentSourceText	TextType	A reference to a source from which the present resource is derived.
DocumentStatus	StatusType extends SuperType	Indicates the document's status, e.g., approved, submitted, awaiting revision.
DocumentSubject.Organization	OrganizationType extends SuperType	A person or organization that is a target or intended recipient of a document.
DocumentSubject.Person	PersonType extends SuperType	A person or organization that is a target or intended recipient of a document.
DocumentSubjectCodeText	TextType	A code that identifies the subject code systems used and the appropriate subject code assigned to the document. Example subject code systems: be, ifc, nsa, state.
DocumentSubjectText	TextType	A subject that is typically expressed as keywords, phrases, or classification codes that describe a topic of the resource.
DocumentSubmitter.Organization	OrganizationType extends SuperType	An entity responsible for making the resource available. May include a person, organization or service.
DocumentSubmitter.Person	PersonType extends SuperType	An entity responsible for making the resource available. May include a person, organization or service.
DocumentSummaryText	TextType	A short description of the document subject, contents, and any "bottom line" point the document is trying to convey.
DocumentSupplementalMarkingText	TextType	A marking made on a document.
DocumentTitleText	TextType	A name given to a resource, typically a name by which it is formally known.

DocumentTypeText	TextType	A nature or genre of the content of the resource. Includes terms describing general categories, functions, or genres. To describe the physical or digital manifestation of the resource use the Format property.
DocumentVitalIndicator	j-xsd:boolean	True if a document is categorized as a vital record by the originating agency; false otherwise. A vital record is that information that is needed to restore an enterprise to full operation following a catastrophe, or for records essential to protect the legal and financial rights of the government or the individual directly affected by its activities.
DriverAuthorization	DriverAuthorizationType extends SuperType	Details about an authorization issued to a driver granting driving privileges.
DriverAuthorizationEndorsementCode	j-ansi_d20:DrivingEndorsementCode	A code identifying the endorsement on a driver license or driver license permit which authorizes the operation of specified types of vehicles carrying specified loads. Endorsements are specific to classifications of a driver license.
DriverAuthorizationEndorsementText	TextType	The endorsement on a drivers license or driver license permit which authorizes the operation of specified types of vehicles carrying specified loads. Endorsements are specific to classifications of a driver license.
DriverAuthorizationExpirationDate	j-xsd:date	The date after which a driver license or driver license permit is no longer valid.
DriverAuthorizationID	IDType extends SuperType	Details about a driver license identifier or driver license permit identifier, including the number and state.
DriverAuthorizationIssueDate	j-xsd:date	The date when a driver license or driver license permit is issued or renewed.
DriverAuthorizationPerson	PersonType extends SuperType	The person to which a driver license or driver license permit is assigned.
DriverAuthorizationRestriction	DrivingRestrictionType extends SuperType	A restriction on a driver license or driver license permit.
DriverConviction	DriverConvictionType extends ConvictionType	Details about a judge or jury finding a person guilty or a person pleading guilty in relation to a traffic offense.
DriverConvictionCitation	CitationType extends ActivityType	The citation received by a person that resulted in a conviction.

DriverConvictionCMVCode	j-ansi_d20:CMVCodeType	A code identifying whether a person was driving a commercial motor vehicle (CMV) in an incident that resulted in a conviction.
DriverConvictionCMVText	TextType	An indication of whether a person was driving a commercial motor vehicle (CMV) in an incident that resulted in a conviction.
DriverConvictionHazMatCode	j-ansi_d20:HazMatCodeType	A code identifying whether a person was carrying hazardous materials (HazMat) in a vehicle that was involved in an incident, resulting in a conviction.
DriverConvictionHazMatText	TextType	An indication of whether a person was carrying hazardous materials (HazMat) in a vehicle that was involved in an incident, resulting in a conviction.
DriverConvictionOffenseCode	j-ansi_d20:DrivingOffenseCodeType	The offense code a driver was convicted of in relation to a driving incident. Also known as ACD.
DriverConvictionOffenseDescriptionText	TextType	Additional details about an ACD defined offense. Typically used on speeding and alcohol related offenses to convey the measured values.
DriverConvictionOffenseText	TextType	A specific offense or charge for which the party has been found guilty. There may be multiple charges associated with a specific activity or action. This specifies to which of the charges the conviction applies.
DriverHistoryAccidentQuantity	j-xsd:nonNegativeInteger	A number of accidents in which a driver has been involved.
DriverHistoryConvictionQuantity	j-xsd:nonNegativeInteger	A number of times that a driver has been convicted.
DriverHistorySummary	DriverHistorySummaryType extends SuperType	Summary details about a driver's history
DriverHistoryWithdrawalQuantity	j-xsd:nonNegativeInteger	A number of times that a driver has had their driving privileges withdrawn.
DriverLicense	DriverLicenseType extends SuperType	Details about a license issued to a person granting driving privileges.
DriverLicenseCommercialClassCode	j-ansi_d20:DriverLicenseClassCodeT	A code identifying the type of commercial vehicle that a licensed driver has been examined on and approved to operate. This field represents the highest-level classification for a particular Driver Privilege Type (e.g., commercial license or non-commercial license).

DriverLicenseCommercialClassText	TextType	A type of commercial vehicle that a licensed driver has been examined on and approved to operate. This field represents the highest-level classification for a particular Driver Privilege Type (e.g., commercial license or non-commercial license).
DriverLicenseCommercialStatusCode	j-ansi_d20:DrivingStatusCodeType	A code identifying the current status of an individual's Commercial privilege type.
DriverLicenseCommercialStatusText	TextType	A current status of an individual's Commercial privilege type.
DriverLicenseConviction	ConvictionType extends ActivityType	A conviction which affects a drivers license.
DriverLicenseIssuedPerson	PersonType extends SuperType	A person to which a driving license is issued.
DriverLicenseNonCommercialClassText	TextType	A type of non-commercial vehicle that a licensed driver has been examined on and approved to operate. This field represents the highest-level classification for a particular Driver Privilege Type. Non-commercial classes are defined by each state.
DriverLicenseNonCommercialStatusCode	j-ansi_d20:DrivingStatusCodeType	A code identifying the current status of an individual's non-commercial (base) privilege type.
DriverLicenseNonCommercialStatusText	TextType	A current status of an individual's non-commercial privilege (base) type.
DriverLicensePermit	DriverLicensePermitType extends DriverAuthorizationType	Details about a driver license permit issued to a driver granting conditional or limited driving privileges.
DriverLicensePermitClassificationText	TextType	A type of commercial or non-commercial vehicle that a licensed driver has been examined on and approved to operate subject to a permit. This field represents the highest level classification for a particular driver privilege type (e.g., commercial vs. non-commercial).
DriverLicensePermitQuantity	j-xsd:integer	A number of driver permits issued on a license.
DriverLicensePermitStatusCode	j-ansi_d20:DrivingStatusCodeType	A code identifying the current status of an individual's driver license permit.
DriverLicenseWithdrawal	DriverLicenseWithdrawalType extends ActivityType	Details regarding a driver license withdrawal.
DriverLicenseWithdrawalActionCode	j-ansi_d20:DriverLicenseWithdrawalA	A code identifying a type of driver license withdrawal action that was taken.

DriverLicenseWithdrawalBasisCode	j-ansi_d20:DriverLicenseWithdrawalB	A code identifying a basis for the withdrawal action for a driver.
DriverLicenseWithdrawalCode	j-ansi_d20:DrivingOffenseCodeType	A code identifying a reason for the withdrawal
DriverLicenseWithdrawalDueProcessStatusCode	j-ansi_d20:DriverLicenseWithdrawalD	A code identifying a due process status of a withdrawal action
DriverLicenseWithdrawalEffectiveDate	j-xsd:date	A date on which a driver license withdrawal becomes effective.
DriverLicenseWithdrawalEligibilityCode	j-ansi_d20:DriverLicenseWithdrawalE	A code indicating when a driver is eligible to apply for reinstatement of those driving privileges withdrawn.
DriverLicenseWithdrawalEligibilityDate	j-xsd:date	A date on or after which a driver is eligible to apply for reinstatement of those driving privileges withdrawn.
DriverLicenseWithdrawalExtentCode	j-ansi_d20:DriverLicenseWithdrawalE	A code identifying a particular withdrawal extent. A withdrawal extent identifies the portion of driving privileges being withdrawn, such as the Commercial Privilege Type, or non-Commercial (Base) Privilege Type, or a specific Permit.
DriverLicenseWithdrawalIssuingAuthorityCode	j-ansi_d20:JurisdictionAuthorityCode	A code identifying a jurisdiction which withdrew driving privileges for a driver.
DriverLicenseWithdrawalIssuingAuthorityText	TextType	A jurisdiction which withdrew driving privileges for a driver
DriverLicenseWithdrawalLocatorReferenceID	TextType	A reference number for the organization that keeps the withdrawal records.
DriverLicenseWithdrawalPendingIndicator	j-xsd:boolean	True if a current licensing jurisdiction has an action pending that, if carried to completion, will cause a withdrawal of a specified driver privilege type; false otherwise.
DriverLicenseWithdrawalReasonReferenceCode	TextType	A native state (legislative) code that specifies a withdrawal reason for future reference by the original State of Conviction.
DriverLicenseWithdrawalReinstatementDate	j-xsd:date	A date that the licensing privilege of an individual driver (which has been previously withdrawn) is reinstated.
DrivingAccidentSeverityCode	j-ansi_d20:AccidentSeverityCodeType	A code identifying a severity level of an accident, based on the most intense injury to any person or, if none were injured, so designating.
DrivingAccidentSeverityText	TextType	A severity level of an accident, based on the most intense injury to any person or, if none were injured, so designating.

DrivingIncident	DrivingIncidentType extends IncidentType	Details about an incident involving a vehicle, e.g., a traffic accident, speeding, reckless driving.
DrivingIncidentCMVCode	j-ansi_d20:CMVCodeType	A code identifying whether the incident occurred while the driver was operating a commercial vehicle.
DrivingIncidentCMVText	TextType	A determination of whether the incident occurred while the driver was operating a commercial vehicle.
DrivingIncidentCollisionIndicator	j-xsd:boolean	True if a driving incident involved a collision with another vehicle, person, or object; false otherwise.
DrivingIncidentDriverOwnershipIndicator	j-xsd:boolean	True if a driver owns the vehicle being driven in an incident; false otherwise.
DrivingIncidentFemalePassengerQuantityText	TextType	A number of females in a vehicle excluding the driver when an incident occurred.
DrivingIncidentHazMatCode	j-ansi_d20:HazMatCodeType	A code determining whether the incident occurred while the driver was operating a commercial vehicle that was carrying hazardous materials (that required a placard).
DrivingIncidentHazMatText	TextType	A determination of whether the incident occurred while the driver was operating a commercial vehicle that was carrying hazardous materials (that required a placard).
DrivingIncidentJurisdiction	JurisdictionType	A jurisdiction in which an incident occurred.
DrivingIncidentLaserDetectionIndicator	j-xsd:boolean	True if a laser was involved in the detection of an incident; false otherwise.
DrivingIncidentLegalSpeedRate	SpeedRateType extends RateType	A legally designated speed limit in the area where an incident occurred.
DrivingIncidentLocatorReferenceID	IDType extends SuperType	A reference number for the organization that keeps the incident report.
DrivingIncidentMalePassengerQuantityText	TextType	A number of males in a vehicle excluding the driver when an incident occurred.
DrivingIncidentMobilePhoneIndicator	j-xsd:boolean	True if a mobile phone being used was involved in an incident; false otherwise.
DrivingIncidentPassenger	PersonType extends SuperType	A person in a vehicle excluding the driver when an incident occurred.
DrivingIncidentPassengerDescriptionText	TextType	A description of the people in a vehicle excluding the driver during the time of an incident.
DrivingIncidentPassengerQuantityText	TextType	A number of people in a vehicle excluding the driver when an incident occurred.
DrivingIncidentRadarDetectionIndicator	j-xsd:boolean	True if radar was involved in the detection of an incident; false otherwise.

DrivingIncidentRecordedSpeedRate.Range	RangeVehicleSpeedMeasureType extends RangeMeasureType	A speed a vehicle was moving at when an incident occurred.
DrivingIncidentRecordedSpeedRate	SpeedRateType extends RateType	A speed a vehicle was moving at when an incident occurred.
DrivingIncidentRoadDescriptionText	TextType	A description of the road conditions during the time of an incident.
DrivingIncidentRoadTypeText	TextType	A type of road where an incident occurred, e.g., highway, interstate, rural road.
DrivingIncidentTrafficDescriptionText	TextType	A description of the traffic conditions during the time of an incident.
DrivingIncidentWeatherDescriptionText	TextType	A description of the weather during the time of an incident.
DrivingJurisdictionAuthorityCode	j-ansi_d20:JurisdictionAuthorityCode	A federal or state organization, such as a department of motor vehicles (DMV), with jurisdiction over a person's driving privileges.
DrivingRestriction	DrivingRestrictionType extends SuperType	Details about a restriction applicable to a driver permit or license.
DrivingRestrictionCode	j-ansi_d20:DrivingRestrictionCodeType	A code identifying the category of a driving restriction.
DrivingRestrictionDescriptionText	TextType	An explanation of the nature of a restriction
DrivingRestrictionEndDate	j-xsd:date	A date on which a special restriction ends.
DrivingRestrictionText	TextType	A category of a driving restriction.
Drug	DrugType extends PropertyType	Details about a legal or illegal substance that can be used as medicine or a narcotic. Possible effects from its use include addiction, habituation, a marked change in consciousness, sickness, and/or death. Examples include crack cocaine, marijuana, heroin, glue, prescription drugs, etc.
DrugCompositionDescriptionText	TextType	A description of the composition of a drug substance.
DrugContainerDescriptionText	TextType	A description of a container used to hold a drug, e.g., plastic bag
DrugFoundDescriptionText	TextType	A description of where a drug or some container of drugs was found, e.g., glove box, subject's pockets.
DrugQuantityMeasure	DrugMeasurementType extends MeasureType	An amount of a drug being described.
DrugSubstanceFormText	TextType	A form in which a drug appears, e.g., powdery substance, pill.
DrugTypeCode	j-nibrs:DrugTypeCodeType	A code that identifies a type of drug.

EmergencyContactInformation	ContactInformationType extends SuperType	Information identified by the person on whom to contact in case of an emergency and how to contact them.
Employment	EmploymentType extends SuperType	Details about the employment of a person.
EmploymentAssignedUnit.EnforcementUnit	EnforcementUnitType extends OrganizationType	The unit commonly used by the person in a particular position.
EmploymentAssignedUnit.Organization	OrganizationType extends SuperType	The unit commonly used by the person in a particular position.
EmploymentContactInformation	ContactInformationType extends SuperType	Information on how to contact a person at their work place.
EmploymentDepartmentName	TextType	A department or command associated with a job position.
EmploymentEarningsRate	RateType extends MeasureType	The monetary compensation (salary or wage) a person receives for working.
EmploymentEmployee	PersonType extends SuperType	The person associated with a particular period of employment.
EmploymentEmployer.Organization	OrganizationType extends SuperType	A person or organization within which the subject of the employment worked.
EmploymentEmployer.Person	PersonType extends SuperType	A person or organization within which the subject of the employment worked.
EmploymentEmployerName	TextType	A name of an employer. This could be an organization name, a person's name, unemployed, or self employed.
EmploymentEndDate	j-xsd:date	A date a person left an employment position.
EmploymentEndReasonText	TextType	A reason a person no longer works at a job, e.g., fired for being intoxicated at work, quit, downsized.
EmploymentLocation	LocationType extends SuperType	A location where a person works.
EmploymentOccupationCode	j-census:OccupationCodeType	A code that identifies a specific type of employment or occupation.
EmploymentOccupationText	TextType	A specific type of employment or occupation.
EmploymentOccupationTypeCode	j-census:OccupationTypeCodeType	A code that identifies a general category or type of employment.
EmploymentOccupationTypeText	TextType	A general category or type of employment.
EmploymentPersonID	IDType extends SuperType	Information about an employment identifier assigned to a person, e.g., badge number, employeeID.
EmploymentPositionName	TextType	A job description title of an employed person.
EmploymentRankText	TextType	A rank, status, or promotion level of a person within an employment organization.

EmploymentShiftText	TextType	The hours or time frame associated with a person's position, e.g., day shift, night shift, 8am-5pm.
EmploymentStartDate	j-xsd:date	A date a person was hired for an employment position.
EmploymentStatus	StatusType extends SuperType	A status of the capacity in which a person is working, e.g., part time, full time, sick leave, terminated.
EmploymentSupervisor	PersonType extends SuperType	A person or organization for whom the subject of the employment worked.
EnforcementOfficial	EnforcementOfficialType extends PersonType	A person involved in the enforcement of law. This generally refers to a person designated by a public authority to keep the peace and arrest persons guilty or suspected of crime. May include, but not limited to: police, sheriff, marshal, federal authorities, military.
EnforcementOfficialBadgeID	IDType extends SuperType	An identifier used to refer to an enforcement official.
EnforcementOfficialPOSTLicenseID	IDType extends SuperType	A Peace official Standards and Training identifier.
EnforcementOfficialTypeText	TextType	A type of enforcement official, e.g., Detective, Investigator, etc.
EnforcementOfficialUnavailableSchedule	ScheduleDayType extends ActivityType	Dates and times an enforcement official is unavailable for scheduling.
EnforcementOfficialUnit	EnforcementUnitType extends OrganizationType	An enforcement unit to which an enforcement officer is assigned, e.g., patrol, detective, narcotic.
EnforcementUnit	EnforcementUnitType extends OrganizationType	Details about a unit of an agency responsible for enforcing the law and maintaining peace.
EnforcementUnitBeatID	IDType extends SuperType	A local area for which an enforcement unit is responsible.
EnforcementUnitID	IDType extends SuperType	An identifier of an enforcement unit.
EnforcementUnitName	TextType	A name of an enforcement unit.
EnforcementUnitNumberID	IDType extends SuperType	A number that identifies an enforcement unit.
EnforcementUnitSectionID	IDType extends SuperType	A section of an enforcement unit.
EnginePowerDisplacement	EnginePowerDisplacementType extends SuperType	The amount of power or displacement of a vehicle or boat.
Event	EventType extends SuperType	Details about a singular occurrence or something that happened at a point of time.

EventDate	j-xsd:date	A date on which an event occurred.
EventDescriptionText	TextType	A description of an event or occurrence.
EventName	TextType	A name of an event that occurred.
EventStatus	StatusType extends SuperType	A status or state of affairs of an event or occurrence.
EventTime	j-xsd:time	A time at which an event occurred.
EventTypeText	TextType	A type or classification of an event that occurred.
Evidence	EvidenceType extends SuperType	Details about an item legally received by or submitted to an agency for use in ascertaining the truth of a matter. This includes items such as test reports, fingerprints, body parts, etc. and items considered "physical evidence."
EvidenceAmount	AmountType extends decimal	An estimated or actual monetary value of a piece of evidence.
EvidenceCollector	PersonType extends SuperType	A person who collected a particular piece of evidence.
EvidenceCustodyTransfer	CustodyTransferType extends ActivityType	A transfer of custody of evidence from one agency to another.
EvidenceDocumentBinary	BinaryType extends SuperType	An evidentiary document encoded in binary, such as a mp3 file, WAV file, tiff image, relating to the evidence.
EvidenceItem.Binary	BinaryType extends SuperType	A piece of evidence.
EvidenceItem.Biometric	BiometricType extends SuperType	A piece of evidence.
EvidenceItem.Property	PropertyType extends SuperType	A piece of evidence.
EvidenceKit	KitType extends SuperType	A kit used to collect evidence.
EvidenceNumberID	IDType extends SuperType	A number that identifies a piece of evidence.
EvidenceOtherID	IDType extends SuperType	Identifies an item associated with evidence not explicitly referenced
EvidencePreviousLocation	LocationType extends SuperType	A previous location of a piece of evidence.
EvidenceQuantityText	TextType	A number of individual items that represent a piece of evidence.

EvidenceReceiptID	IDType extends SuperType	An identifier for a receipt issued for collection, analysis, and movement of Evidence.
EvidenceReturnedIndicator	j-xsd:boolean	True if a piece of evidence was returned to its owner; false otherwise.
EvidenceReturnRecipient.Organization	OrganizationType extends SuperType	A person, agency, or other organization to which a particular piece of property was returned
EvidenceReturnRecipient.Person	PersonType extends SuperType	A person, agency, or other organization to which a particular piece of property was returned
EvidenceTakenFrom.Organization	OrganizationType extends SuperType	A person or an organization from which a particular piece of evidence was taken or seized from, e.g., an organization from which a computer was seized.
EvidenceTakenFrom.Person	PersonType extends SuperType	A person or an organization from which a particular piece of evidence was taken or seized from, e.g., an organization from which a computer was seized.
EvidenceTakenLocation	LocationType extends SuperType	A location where a particular piece of evidence was taken, collected, or removed.
Exhibit	ExhibitType extends SuperType	Details about an item introduced as evidence in a hearing or a trial.
ExhibitAcceptingAgency	OrganizationType extends SuperType	An agency that accepts evidence into the judicial process.
ExhibitAdmittedIndicator	j-xsd:boolean	True if an exhibit was admitted in trial; false otherwise.
ExhibitEvidence	EvidenceType extends SuperType	An exhibit item.
ExhibitID	IDType extends SuperType	An identifying number of an exhibit.
ExhibitRemainingProofIndicator	j-xsd:boolean	True if an exhibit that has not been admitted as evidence will remain with the court as an offer of proof in the event of an appeal; false otherwise.
ExhibitStatusText	TextType	A description of the status of an exhibit, e.g., offered, withdrawn, admitted, refused.
Facility	FacilityType extends OrganizationType	Details about an organization that carries out some form of enforcement or reformatory activities for its members. This may be detention, corrections, supervision, a rehabilitation, risk reduction, or diversion program, or another type of function designed to reform a member of society.

FacilityCapacityDescriptionText	TextType	A description of the number of people a facility can house at a time.
FacilityCapacityQuantity	j-xsd:nonNegativeInteger	A number of people a facility can house at one time.
FacilityCaseLoadQuantity	j-xsd:nonNegativeInteger	A number of people a facility is currently servicing.
FacilityID	IDType extends SuperType	A unique NCIC or other identifier assigned to a reform-related organization. Sometimes referred to as a KAG number for detention facilities.
FacilityJuvenileIndicator	j-xsd:boolean	True if a facility has the ability to accept people under the legal age of an adult; false otherwise.
FacilityMemberTypeText	TextType	A type of occupant or member a facility manages. This may be adult, juvenile, addict.
FacilityOperatingAgency	OrganizationType extends SuperType	An organization that operates the facility.
FacilitySecurityLevelText	TextType	A level of security an organization operates at, e.g., minimum, medium, maximum, none.
FacilitySupervisingAgency	OrganizationType extends SuperType	A supervising agency that operates or oversees the facility.
Fee	ObligationType extends SuperType	Details about a monetary amount charged for a service, product, or restitution or the monetary amount assessed as court case fees.
Felony	IncidentType extends ActivityType	A crime which is punishable by death or imprisonment in a state facility.
FinalPlea	PleaType extends ActivityType	A final plea offered by a defendant in relation to a charge that was accepted by the court.
FinancialObligation	FinancialObligationType extends ObligationType	A monetary obligation, e.g., fee, fine, support, restitution, damages, court costs.
FinancialObligationDueAmount	AmountType extends decimal	An amount of a payment obligation that has not been made.
FinancialObligationExemptionAmount	AmountType extends decimal	A total or partial amount of a payment obligation no longer required of a person.
FinancialObligationPaidAmount	AmountType extends decimal	An amount of a payment obligation that has been made.
FinancialObligationTotalAmount	AmountType extends decimal	A total amount of money to be charged or paid to meet a financial obligation, such as a fee or restitution.
Fingerprint	FingerprintType extends BiometricType	A representation or an encoding of the identifying characteristics of a persons fingerprints.

FingerprintClassificationCode	j-ncic:FPCType	A code identifying a specific classification of a persons fingerprint.
FingerprintClassificationText	TextType	A specific classification of a persons fingerprint. If the classification represents a radial or ulmar loop pattern, then the classification is two numeric characters.
FingerprintFingerCode	j-ncic:FPCFingerType	A code identifying a finger of a person that has been printed or has attempted to have been printed, e.g., right thumb, left index.
FingerprintFingerText	TextType	A finger of a person that has been printed or has attempted to have been printed, e.g., right thumb, left index.
FingerprintPatternCode	j-ncic:FPCPatternType	A code identifying a general pattern of a persons fingerprint.
FingerprintPatternText	TextType	A general pattern of a persons fingerprint.
Firearm	FirearmType extends PropertyType	Details about any weapon, including a starter gun, which will or is designed to or may readily be converted to expel a projectile by air, carbon dioxide, or the action of an explosive.
FirearmAutomaticIndicator	j-xsd:boolean	True if firearm is an automatic weapon and can be fired in quick succession; false otherwise.
FirearmBarrellLengthMeasure	LengthMeasureType extends MeasureType	A measurement of a barrel length of a firearm.
FirearmCaliberCode	j-ncic:CALType	A code identifying a caliber of a firearm.
FirearmCaliberText	TextType	A caliber of a firearm.
FirearmFinishCode	j-ncic:GUNColorFinishType	A code identifying a finish of a firearm.
FirearmFinishText	TextType	A finish of a firearm.
FirearmGaugeText	TextType	A gauge of a firearm, particularly a shotgun.
FirearmGripText	TextType	A grip of a firearm.
FirearmMakeCode	j-ncic:MAKType	A code identifying the manufacturer of a firearm.
FirearmTypeCode	j-ncic:TYPType	A code identifying a type of firearm.
FirearmTypeDescriptionCode	j-ncic:TYPDescriptionType	A code identifying a description or further classification of a firearm.
FirearmTypeDescriptionText	TextType	A description or further classification of a firearm.
Force	ForceType extends ActivityType	Details about force used, whether physical or aided by a tool or weapon. Sometimes referred to as ForceToolWeapon.

ForcePhysicalDescriptionText	TextType	A description of the physical force a person used against another person.
ForceSubject	SubjectType extends PersonType	A person who used force against another.
ForceTakenAsEvidence	EvidenceType extends SuperType	The evidence taken in an incident when specifically a tool or weapon was used.
ForceToolProperty	PropertyType extends SuperType	A tool used to apply force to a person.
ForceTypeCode	j-nibrs:ForceTypeCodeType	A code identifying a type of force used, which may be physical or aided by a weapon or tool.
ForceTypeText	TextType	A type of force used, which may be physical or aided by a weapon or tool.
ForceUser.Organization	OrganizationType extends SuperType	Indicates that a particular force/tool/weapon was used by a specific organization.
ForceUser.Person	PersonType extends SuperType	Indicates that a particular force/tool/weapon was used by a specific organization.
ForceVictim	VictimType extends SuperType	A person who was a victim of force.
ForceWeaponProperty	PropertyType extends SuperType	A weapon used to apply force to a person.
GeographicCoordinate	GeographicCoordinateType extends SuperType	Details about identifying a location based on latitude and longitude.
GeographicCoordinateLatitude	LatitudeCoordinateType extends SuperType	A circle around the Earth parallel to the Equator. Values range from -90 degrees (inclusive) at the South Pole to +90 degrees (inclusive) at the North Pole. The value is 0 at the Equator.
GeographicCoordinateLongitude	LongitudeCoordinateType extends SuperType	A meridian that is perpendicular to the Equator. Values range from -180 degrees (inclusive) at the International Date Line to +180 (exclusive) just west of the International Date Line. The value is 0 at the Prime Meridian.
GeographicCoordinateSystemID	IDType extends SuperType	An identification of the coordinate system used.
GeographicDatumID	IDType extends SuperType	An identification of the spatial reference system used.
Highway	HighwayType extends SuperType	Details about a major public road.
HighwayFullText	TextType	A complete reference to a highway.

HighwayID	IDType extends SuperType	An identifier of a highway, e.g., "SR-78"
HighwayName	TextType	A name of a highway, e.g., "Stone Mountain Parkway"
HighwayPositionText	TextType	A designation of a specific place on a highway. Sometimes referred to as a mile marker, mile post, exit number.
HomeContactInformation	ContactInformationType extends SuperType	Information on how to contact a person at their home residence.
ID	TextType	A value that identifies an entity within the identifier domain.
IDEffectiveDate	j-xsd:date	A date an identifier becomes effective. This may or may not be the issue date.
IDExpirationDate	j-xsd:date	A date an identifier is no longer valid.
IDIssuingAuthorityText	TextType	A name, identifier, or code of an organization or person that has authority over an identifier.
IDJurisdictionCode	j-ncic:RESType	A code identifying an area or region, e.g., state or country, in which an identifier is unique.
IDJurisdictionText	TextType	An area or region, e.g., state or country, in which an identifier is unique.
IDObject	IDType extends SuperType	Information that identifies an entity.
IDSourceText	TextType	The locale or organization from which an identification originates.
IDStatus	StatusType extends SuperType	A condition or state of an identifier, e.g., valid, expired.
IDTypeCodeSourceText	TextType	A source of the identifiers type code.
IDTypeCodeText	TextType	A textual code representing the type of identifier assigned.
IDTypeCodeVersionText	TextType	A source version of the identifiers type code.
IDTypeDescriptionText	TextType	A description of a type of identifier.
IDTypeText	TextType	A type of identifier assigned.
Image	ImageType extends BinaryType	Details about a representation of an image encoded for XML.
ImageCreatedOrganization	OrganizationType extends SuperType	An organization that created an image.
ImageFacialText	TextType	A facial adornment or hair piece that appears in an image.
ImageHeightValue	j-xsd:integer	A height of image in pixel
ImageJuvenileIndicator	j-xsd:boolean	True if an image is of a juvenile; false otherwise.

ImageLocation	LocationType extends SuperType	A physical location where an image is stored.
ImageOperator	PersonType extends SuperType	A person who took an image.
ImagePoseCode	j-nonauth:ImagePoseCodeType	A code identifying an angle of a person's face in a photograph.
ImagePoseText	TextType	An angle of a person's face in a photograph.
ImageTypeCode	j-ncic:IMTType	A type of image that that has been taken, e.g., mug shot, fingerprint.
ImageWidthValue	j-xsd:integer	A width of image in pixels
Incarceration	SupervisionType extends ActivityType	A mandatory confined supervision of a person.
Incident	IncidentType extends ActivityType	Details about a criminal or non-criminal activity that occurred.
IncidentArrest	ArrestType extends ActivityType	An arrest made because of an incident.
IncidentArrestMadeIndicator	j-xsd:boolean	True if an arrest was made due to the incident; false otherwise.
IncidentAssistingOfficial	EnforcementOfficialType extends PersonType	A peace official that assisted in processing an incident.
IncidentCategory	IncidentCategoryType extends SuperType	Details that describe a general category or classification of an incident.
IncidentCategoryTypeCode	j-nibrs:CriminalActivityTypeCodeType	A code that identifies a type of incident that occurred.
IncidentCategoryTypeText	TextType	A general category of an incident that occurred, e.g., assault, burglary, theft.
IncidentCriminalIndicator	j-xsd:boolean	True if an incident that occurred is criminal; false if an incident is non-criminal.
IncidentDamagedProperty	PropertyType extends SuperType	A property item that was damaged in an incident.
IncidentDayPeriodText	TextType	A period of a day an incident occurred. For example: morning, late night, afternoon, etc.
IncidentEntryPoint	PassagePointType extends ActivityType	A point of entry to a location or structure used in an incident.
IncidentEvent	EventType extends SuperType	Details about an action or occurrence associated with an incident, e.g., Victim was seen walking to his car at 11:30pm.

IncidentEvidence	EvidenceType extends SuperType	An item seized by an official for later use in ascertaining the true nature of an incident.
IncidentEvidenceHeldIndicator	j-xsd:boolean	True if evidence was held due to this incident; false otherwise.
IncidentExceptionalClearanceCode	j-nibrs:IncidentExceptionalClearanceCode	A code that identifies a reason why an incident has been cleared exceptionally, e.g., the identity of at least one subject has been determined, sufficient probable cause has been developed, the exact location of the subject is known so an arrest could be made, and there are reasons outside of law enforcement which prevent the arrest of the subject.
IncidentExceptionalClearanceText	TextType	A reason why an incident has been cleared exceptionally, e.g., the identity of at least one subject has been determined, sufficient probable cause has been developed, the exact location of the subject is known so an arrest could be made, and there are reasons outside of law enforcement which prevent the arrest of the subject.
IncidentExceptionClearanceDate	j-xsd:date	A date an incident was cleared exceptionally.
IncidentExitPoint	PassagePointType extends ActivityType	A point of exit to a location or structure used in an incident.
IncidentFactor	IncidentFactorType extends SuperType	Details about a factor involved that has an effect on an incident. Example: narcotics, computer, radar, domestic violence, employment, bias, injury, hazmat, CMV.
IncidentFactorCode.nibrsAggravatedAssaultHomicide	j-nibrs:AggravatedAssaultHomicideFactorCode	A unique code that identifies a circumstance of factor in an incident.
IncidentFactorCode.nibrsBiasMotivation	j-nibrs:IncidentBiasMotivationCodeType	A unique code that identifies a circumstance of factor in an incident.
IncidentFactorCode	j-nibrs:IncidentFactorCodeType	A unique code that identifies a circumstance of factor in an incident.
IncidentFactorCode.nibrsJustifiableHomicide	j-nibrs:JustifiableHomicideFactorsCode	A unique code that identifies a circumstance of factor in an incident.
IncidentFactorDescriptionText	TextType	A description of a circumstance or factor involved in an incident.
IncidentFactorKnownIndicator	j-xsd:boolean	True if a factor in an incident is known to be true; false if it is suspected, estimated, or otherwise.
IncidentFactorSubtypeText	TextType	A specific detail or aspect of an incident factor or circumstance.

IncidentFactorText	TextType	A circumstance or factor in an incident, e.g., argument, narcotics, domestic violence.
IncidentForce	ForceType extends ActivityType	Details about a force used in an incident, whether physical or aided by a tool or weapon.
IncidentForceInvolvedIndicator	j-xsd:boolean	True if force was used in an incident; false otherwise. Applies to any incident category.
IncidentForm	IncidentFormType extends SuperType	Details about an electronic or paper form to be completed by a response unit and submitted to record the details of an incident and of a response to an incident.
IncidentFormComment	TextType	A note or comment about a form associated with an incident.
IncidentFormName	TextType	A name of an incident report form.
IncidentFormSubmittedIndicator	j-xsd:boolean	True if a form has been submitted; false otherwise.
IncidentInjuryLevelText	TextType	An indication of the severity level of an injury received during an incident, e.g., major, minor, none, noncriminal.
IncidentInvolvedProperty	PropertyType extends SuperType	A property item that was somehow involved in an incident but not damaged, stolen, or seized. This may include a vehicle a subject was driving.
IncidentInvolvedStructure	StructureType extends PropertyType	A structure that was involved in an incident.
IncidentJurisdictionalOrganization	OrganizationType extends SuperType	An organization or agency who has jurisdiction over an incident.
IncidentLevelCode	j-mn_off:OffenseLevelCodeType	A code identifying a level of an incident, e.g., felony.
IncidentLevelText	TextType	A level of an incident, e.g., felony.
IncidentLocation	LocationType extends SuperType	A location where an incident occurred.
IncidentMethodDescriptionText	TextType	A description of the method used to carry out on incident. Sometimes referred to as MO, modus operandi.
IncidentMinorInvolvedIndicator	j-xsd:boolean	True if an incident involved or employed a person under the legal age of an adult; false otherwise.
IncidentNonPropertyItemText	TextType	An item that was stolen. Includes only items not included in property, e.g., services.
IncidentObservationText	TextType	An observation made by an official of an incident occurring.
IncidentOfficialPresentIndicator	j-xsd:boolean	True if an official was present when an incident occurred; false otherwise.

IncidentPrintsRequestedIndicator	j-xsd:boolean	True if a request was made to gather fingerprints; false otherwise.
IncidentPropertyDisposition	PropertyDispositionType extends ActivityType	Details about what happened to a property item after an incident.
IncidentRecoveredProperty	PropertyType extends SuperType	A property item that was found or recovered in an incident.
IncidentRecoveredVehicleQuantity	QuantityType extends NumericType	A number of motor vehicle recovered from an incident.
IncidentReportedNarrative	DocumentType extends SuperType	A textual narrative of an incident by an investigative official.
IncidentReportingOfficial	EnforcementOfficialType extends PersonType	A peace official that submitted an incident report in an incident.
IncidentResponse	IncidentResponseType extends ActivityType	Details about a response to an incident by an official unit.
IncidentResponseOfficial	EnforcementOfficialType extends PersonType	A peace official that responded to an incident.
IncidentResponseOrganization	OrganizationType extends SuperType	An organization or agency that responded to an incident.
IncidentSeizedProperty	PropertyType extends SuperType	A property item that was removed by an official in an incident.
IncidentServiceCall	ServiceCallType extends ActivityType	An identifier issued by an organization to track calls for service or an observation by an organization employee.
IncidentSourceText	TextType	An item or location from which something was stolen. Includes only items and locations not included in property and location type, e.g., shipment, military, telecommunication system, etc.
IncidentStolenProperty	PropertyType extends SuperType	A property item that was stolen in an incident.
IncidentStolenVehicleQuantity	QuantityType extends NumericType	A number of motor vehicles stolen in an incident.
IncidentStructuresEnteredQuantity	QuantityType extends NumericType	A number of structures or premises entered by the subject during an incident.
IncidentSubject	SubjectType extends PersonType	A person whose actions caused an incident.
IncidentSubjectOrganization	OrganizationType extends SuperType	An organization (possibly a criminal organization) whose actions caused an incident.

IncidentSubjectWeapon	PropertyType extends SuperType	A weapon used or possessed by a subject in an incident.
IncidentSupervisingOfficial	EnforcementOfficialType extends PersonType	An enforcement supervisor responsible for, or present at, an incident.
IncidentSurroundingLocation	LocationType extends SuperType	An area surrounding a location where an incident occurred.
IncidentTarget	TargetType extends SuperType	An entity that was an intended recipient of a subject's actions involved in an incident.
IncidentTrafficAccidentInvolvedIndicator	j-xsd:boolean	True if an incident involved a traffic accident; false otherwise.
IncidentVictim	VictimType extends SuperType	A person that was negatively affected in an incident.
IncidentViolatedStatute	ViolatedStatuteType extends StatuteType	Details about a statute, rule, or ordinance that was violated in an incident.
IncidentWeaponInvolvedIndicator	j-xsd:boolean	True if a weapon was used in an incident; false otherwise.
IncidentWitness	WitnessType extends PersonType	A person who observed or has knowledge of an incident.
Infraction	IncidentType extends ActivityType	An offense punishable by a fine or other penalty, but not by incarceration.
InjuryCauser.Force	ForceType extends ActivityType	A force, tool, weapon, or person that caused an injury.
InjuryCauser.Person	PersonType extends SuperType	A force, tool, weapon, or person that caused an injury.
InjuryDate	j-xsd:date	A date on which an injury occurred.
InjuryDescriptionText	TextType	A description of an injury.
InjuryLocationText	TextType	A location of an injury on a person's body.
InjurySeverityText	TextType	A level of severity of an injury.
InjuryTime	j-xsd:time	A time at which an injury occurred.
InjuryTreater.Organization	OrganizationType extends SuperType	A person or organization that treated an injury.
InjuryTreater.Person	PersonType extends SuperType	A person or organization that treated an injury.
InjuryTreatmentEndDate	j-xsd:date	A date on which treatment for an injury concluded.
InjuryTreatmentStartDate	j-xsd:date	A date on which treatment for an injury began.
InjuryTreatmentText	TextType	A treatment given to an injury.
InjuryTypeCode	j-nibrs:InjuryTypeCodeType	A code identifying a general category of harm or injury.
InjuryTypeText	TextType	A general category of harm or injury.

Insurance	InsuranceType extends SuperType	Details about a coverage by contract whereby one party agrees to indemnify or guarantee another against loss by a specified contingent event or peril.
InsuranceActiveIndicator	j-xsd:boolean	True if an insurance policy is active; false otherwise.
InsuranceCancelationDate	j-xsd:date	A date an insurance policy was or will be cancelled.
InsuranceCarrierID	IDType extends SuperType	An identifier code assigned by the National Association of Insurance Carriers (NAIC) for a business involved in underwriting automobile insurance.
InsuranceCarrierName	TextType	A business name of the company maintaining insurance on a vehicle.
InsuranceCertifiedDate	j-xsd:date	A date a driver with a future proof requirement was certified as having the necessary automobile liability coverage
InsuranceCoverageTypeCode	j-ansi_d20:InsuranceCoverageTypeC	A code describing the category of coverage provided by the insurance policy.
InsuranceCoverageTypeText	TextType	A category of coverage provided by the insurance policy.
InsuranceCoveredProperty	PropertyType extends SuperType	A property item such as a vehicle that an insurance policy covers.
InsuranceEffectiveDate	j-xsd:date	A date the insured party's policy coverage starts.
InsuranceEndDate	j-xsd:date	A date the insured party's policy coverage ends
InsurancePersonalIndicator	j-xsd:boolean	True if an insurance coverage is for a personal use; false if it is for commercial or corporate use.
InsurancePolicyID	IDType extends SuperType	An identifier assigned to the insurance policy by the insurance carrier. Sometimes referred to as the Policy Number.
IntellectualProperty	IntellectualPropertyType extends PropertyType	Details about an intellectual property item such as information, patents, trademarks, and copyrighted material.
IntellectualPropertyBusinessAreaText	TextType	An area in which a piece of intellectual property is used or would be useful, e.g., information technology.
IntellectualPropertyCreationDate	j-xsd:date	A date that a piece of intellectual property came into existence.
IntellectualPropertyCreationEventText	TextType	An event that led to the creation of the intellectual property, e.g., when system "X" became operational
IntellectualPropertyRegistrationDate	j-xsd:date	A date when intellectual property rights began for the registered owner (e.g., registration date of copyright)
IntellectualPropertyRegistrationID	IDType extends SuperType	An identifier of a piece of intellectual property, e.g., Patent Registration No.

IntellectualPropertyTerminationDate	j-xsd:date	A date when intellectual property is destroyed and/or property or registration rights cease to exist.
IntellectualPropertyTerminationEventText	TextType	An event that led to the destruction of a piece of intellectual property and/or the termination of registration rights.
IntoxicationAlcoholInvolvedIndicator	j-xsd:boolean	True if an intoxicant discovered was alcohol; false otherwise.
IntoxicationDrugInvolvedIndicator	j-xsd:boolean	True if an intoxicant discovered was a drug; false otherwise.
IntoxicationIntoxicantTypeCode	j-nibrs:DrugTypeCodeType	A code assigned to a substance by which a person is intoxicated.
IntoxicationIntoxicantTypeText	TextType	A type of substance by which a person is intoxicated.
IntoxicationLevelText	TextType	A description of the degree a person is intoxicated or under the influence of a substance.
IntoxicationOverLimitIndicator	j-xsd:boolean	True if the amount of drugs or alcohol in a person's system is over the legal limit; false otherwise.
IntoxicationTestAdministrator	PersonType extends SuperType	A person who administers a test to another person to determine the presence and/or amount of drug or alcohol intoxicants in a persons system.
IntoxicationTestDate	j-xsd:date	The date that a test for intoxication was conducted.
IntoxicationTestDescriptionText	TextType	A description of the intoxication test that yielded the described results.
IntoxicationTestTime	j-xsd:time	The time that a test for intoxication was conducted.
IntoxicationTestTypeText	TextType	A type of test performed to determine a person's intoxication.
IsAssociatedWith	SuperType	A general relationship that indicates two object instances are linked but the meaning of the relationship is unknown.
Jewelry	JewelryType	Details about adornments, such as bracelets and necklaces, made out of metals and gems or imitations.
JewelryCaratText	TextType	A measurement of the fineness of gold in a piece of jewelry.
JewelryMetalText	TextType	A metal that makes up part of a piece of jewelry, e.g., gold.
JewelryStone	JewelryStoneType	A stone or gem from a piece of jewelry.
JewelryStoneCaratText	TextType	A measurement of the weight of a jewelry stone in carats.
JewelryStoneColorText	TextType	A color of jewelry stone.

JewelryStoneCutText	TextType	The cut of a jewelry stone, e.g., marquise, square, round, trillium.
JewelryStoneQuantity	j-xsd:nonNegativeInteger	A number of a type of stone found on a piece of jewelry.
JewelryStoneTypeText	TextType	A type of jewelry gem or imitation gem.
JewelryTypeCode	j-ncic:JWTType	A code identifying a type of jewelry.
Judge	JudicialOfficialType	An official who hears and decides a case or who rules over a case proceeding.
JudgePanel	JudgePanelType	Details about a group of federal or state appellate court judges needed to decide a case.
JudgePanelID	IDType extends SuperType	A unique identifier of a judge panel.
JudgePanelRequiredQuantity	j-xsd:nonNegativeInteger	A number of panel judges required to make a decision
JudgePanelTotalQuantity	j-xsd:nonNegativeInteger	A total number of judges that sit on a judge's panel.
JudicialOfficial	JudicialOfficialType	A person involved in a judicial area of government. May include, but not limited to: magistrate, all types of judges and justices, court clerks, and attorneys.
JudicialOfficialBarID	IDType extends SuperType	An identifier assigned to a judicial official after meeting the requirement to practice law in a region. Includes information about the issuing authority.
JudicialOfficialBarMembership	JudicialOfficialBarMembershipType	Details about a legal capacity in which a judicial official is able to practice law.
JudicialOfficialBarStatus	StatusType extends SuperType	A status of a judicial officials bar membership.
JudicialOfficialCourt	CourtType extends OrganizationType	A court unit to which a judicial official is assigned.
JudicialOfficialFirm	OrganizationType extends SuperType	An agency at which a judicial official works.
JudicialOfficialPanelID	IDType extends SuperType	An identifier or name of a panel or group to which a judicial official is assigned. Sometimes referred to as judges panel.
JudicialOfficialRegistrationID	IDType extends SuperType	An identifier assigned to a judicial official after registering within a state or region.
JudicialOfficialTypeText	TextType	A type of judicial official, e.g., Judge, Attorney, DA, etc.
Jurisdiction	JurisdictionType	Details about the geo-political area in which an organization, person, or object has a specific range of authority.

JurisdictionDescriptionText	TextType	A description of an area an organization or person has some kind of authoritative capacity or responsibility over.
JurisdictionDistrictText	TextType	A district in a jurisdiction.
JurisdictionID	IDType	A name or number of a district in a jurisdiction.
JurisdictionRestrictionText	extends SuperType	A restriction or limitation of a jurisdiction.
JurisdictionText	TextType	An area in which an organization or person has some kind of authoritative capacity or responsibility over.
JurisdictionTitle	TextType	A title issued by a jurisdiction.
Juror	PropertyTitleType extends SuperType JurorType	A person who serves on a jury and listens to a case to determine the guilt or innocence of a person accused of a crime. This person is a member of a jury, including special or alternate jurors.
JurorDismissedDate	j-xsd:date	A date a juror was dismissed from jury service.
JurorDismissedIndicator	j-xsd:boolean	True if a juror has been dismissed; false otherwise.
JurorDismissedReasonText	TextType	A reason why a juror was dismissed or excused, e.g., dismissed by prosecution, excused for health reasons.
JurorForemanIndicator	j-xsd:boolean	True if a juror has been appointed as juror leader; false otherwise.
JurorID	IDType	A juror number that identifies a juror within a panel on which he or she is serving
JurorPanelID	extends SuperType IDType	Identifies the panel on which a juror is serving.
JurorPrimaryIndicator	extends SuperType j-xsd:boolean	True if a person is a primary indicator; false if a person in an alternate juror.
KitID	IDType	An identifier of a kit.
KitTypeText	extends SuperType TextType	A type of kit.
LatitudeDegreeValue	LatitudeDegreeType extends SuperType	A value that specifies the degree of a latitude. The value comes from a restricted range between -90 (inclusive) and +90 (inclusive).
LatitudeMinuteValue	AngularMinuteType extends SuperType	A value that specifies a minute of a degree. The value comes from a restricted range of 0 (inclusive) to 60 (exclusive).

LatitudeSecondValue	AngularSecondType extends SuperType	A value that specifies a second of a minute. The value comes from a restricted range of 0 (inclusive) to 60 (exclusive).
LengthMeasure	LengthMeasureType extends MeasureType	A representation of the measurement of a length.
Lessee	LesseeType extends SuperType	Details about a party (individual or business) which has a contract (lease) to use a vehicle.
LesseeJurisdictionAuthorityCode	j-ansi_d20:JurisdictionAuthorityCode1	A code identifying an authority that has jurisdiction over a lease.
LesseeJurisdictionAuthorityText	TextType	An authority that has jurisdiction over a lease.
LesseeParty.Organization	OrganizationType extends SuperType	A person or a business which has a contact (lease) to use a vehicle.
LesseeParty.Person	PersonType extends SuperType	A person or a business which has a contact (lease) to use a vehicle.
Lessor.Organization	OrganizationType extends SuperType	One who conveys vehicles by way of a lease.
Lessor.Person	PersonType extends SuperType	One who conveys vehicles by way of a lease.
Lien	LienType extends SuperType	Details about a legal encumbrance placed on property, such as a vehicle. Historically, liens have been reflected on title documents. Thus, title documents are used to record liens in a way that is visible across jurisdictions.
LienAmount	AmountType extends decimal	A monetary amount representing a legal encumbrance placed on a property.
LienDate	j-xsd:date	A date a lien was placed on property.
LienHolder.Organization	OrganizationType extends SuperType	A person or organization who holds a lien on (has a security interest in) a property item.
LienHolder.Person	PersonType extends SuperType	A person or organization who holds a lien on (has a security interest in) a property item.
LienHolderEntity	LienHolderType extends SuperType	A person or organization who holds a lien on (has a security interest in) a property item.
LienReleaseDate	j-xsd:date	A date a legal encumbrance is removed from property.
LienReleaseReasonCode	j-ansi_d20:LienReleaseReasonCode1	A code that identifies a reason a legal encumbrance is removed from property.
LienReleaseReasonText	TextType	A reason a legal encumbrance is removed from property.
LienTime	j-xsd:time	A time a lien was placed on property.

Locale	LocaleType extends SuperType	Details about a geo-political area.
LocaleCensusBlockID	IDType extends SuperType	A census block number for a locale
LocaleCensusTractID	IDType extends SuperType	A census tract number for a locale
LocaleCommunityName	TextType	A name of a specific community within a region.
LocaleDescriptionText	TextType	A description of the place of a location.
LocaleDistrictName	TextType	A name of a district (an area of land defined for administrative or official purposes).
LocaleEmergencyServicesCityName	TextType	A name of a city containing the emergency services department associated with a region.
LocaleFireJurisdictionID	IDType extends SuperType	An identification of the fire jurisdiction associated with a region.
LocaleJudicialDistrictCodeText	TextType	A local code for a judicial district within a region.
LocaleJudicialDistrictName	TextType	A name of the judicial district within a region.
LocaleNeighborhoodName	TextType	A name of a neighborhood within a region.
LocalePoliceBeatText	TextType	An identification of a police beat that encompasses a location.
LocalePoliceGridText	TextType	A police grid coordinate associated with a region.
LocalePoliceJurisdictionID	IDType extends SuperType	An identification of a police jurisdiction that encompasses a location.
LocaleRegionName	TextType	A name of a region.
LocaleSubdivisionName	TextType	A name of a subdivision within a region.
LocaleZoneName	TextType	A name of the zone for a region.
Location	LocationType extends SuperType	Details about a physical location.
LocationAddress	AddressType extends SuperType	Details about a postal address for a location.
LocationAddressGrid	AddressGridType extends SuperType	Details about a specific geographic area of a Law Enforcement Agency's jurisdiction within a location.
LocationArea	AreaType extends SuperType	Details about the boundaries of a geographic area of location.
LocationBuilding	BuildingType extends SuperType	Details about a building at a location.
LocationCityName	TextType	A name of a city or town.

LocationContactInformation	ContactInformationType extends SuperType	Details about contact information for a location.
LocationContainsOrganization	OrganizationType extends SuperType	Indicates that a particular location contains the indicated organization. For example, the locale might be a neighborhood that contains a particular watch organization; a municipal complex might contain the Sherrifs organization.
LocationCountryCode.iso3166Alpha2	i-iso_3166:CountryAlpha2CodeType	A code that identifies a country, territory, or dependency.
LocationCountryCode.iso3166Alpha3	i-iso_3166:CountryAlpha3CodeType	A code that identifies a country, territory, or dependency.
LocationCountryCode.fips10-4	i-fips_10-4:CountryCodeType	A code that identifies a country, territory, or dependency.
LocationCountryCode.iso3166Numeric	i-iso_3166:CountryNumericCodeType	A code that identifies a country, territory, or dependency.
LocationCountryName	TextType	A name of a country.
LocationCountyCode	i-fips_6-4:USCountyCodeType	A code identifying a county, parish, or vicinage.
LocationCountyName	TextType	A name of a county, parish, or vicinage.
LocationCrossStreet	CrossStreetType extends SuperType	Details about a cross street or intersecting street near a location.
LocationDescriptionText	TextType	A description of a location.
LocationElevation	ElevationType extends MeasureType	Details about a height or elevation of a location.
LocationEmergencyServices	OrganizationType extends SuperType	The emergency services department or agency associated with a particular location
LocationGeographicCoordinate	GeographicCoordinateType extends SuperType	Details about the latitude and longitude of a location.
LocationHighway	HighwayType extends SuperType	Details about a major public road at a location.
LocationLandmarkText	TextType	A name or description of a distinguishing physical feature at a location.
LocationLocale	LocaleType extends SuperType	Details about a geo-political area location.
LocationMapLocation	MapLocationType extends SuperType	Details about a location identified by map coordinates.
LocationMGRSCoordinate	MGRSCoordinateType extends UTMCoordinateType	Details about a coordinate from the Military Grid Reference System (MGRS). This coordinate represents a location with a Universal Transverse Mercator (UTM) coordinate and a unique military grid square.
LocationName	TextType	A name of a location.

LocationNeighbor	PersonType extends SuperType	The associate lives in the general neighborhood of the location.
LocationPoliceDepartment	OrganizationType extends SuperType	The police department associated with a particular location.
LocationPostalCodeExtensionID	IDType extends SuperType	An extension of a zip code or postal code.
LocationPostalCodeID	IDType extends SuperType	A zip code or postal code.
LocationRangeDescriptionText	TextType	A description of the boundary or range of a location.
LocationRelativeLocation	RelativeLocationType extends SuperType	Details about a location relative to another location.
LocationSecondaryUnitText	TextType	A piece of information used to identify a particular unit within a specific location. Examples of this could be an apartment number or a suite number.
LocationStateCode.CanadianProvince	j-can:CanadianProvinceCodeType	A code identifying a state.
LocationStateCode.fips10-4International	j-fips_10-4:InternationalStateCodeType	A code identifying a state.
LocationStateCode.ncicLIS	j-ncic:LISType	A code identifying a state.
LocationStateCode.ncicLSTA	j-ncic:LSTAType	A code identifying a state.
LocationStateCode.ncicRES	j-ncic:RESType	A code identifying a state.
LocationStateCode.USPostalService	j-usps:USStateCodeType	A code identifying a state.
LocationStateCode.fips5-2Alpha	j-fips_5-2:USStateCodeType	A code identifying a state.
LocationStateCode.fips5-2Numeric	j-fips_5-2:USStateNumericCodeType	A code identifying a state.
LocationStateName	TextType	A name of a state, commonwealth, province, or other subregion of a country.
LocationStreet	StreetType extends SuperType	Details about a street.
LocationSurroundingAreaDescriptionText	TextType	A description of an area surrounding a location.
LocationTypeCode	j-nibrs:LocationTypeCodeType	A code identifying a functional description of a location, e.g., residence, school, agency, park.
LocationTypeText	TextType	A functional description of a location, e.g., residence, school, agency, park.
LocationUTMCoordinate	UTMCoordinateType extends SuperType	Details about a coordinate from the Universal Transverse Mercator (UTM) Coordinate System. This coordinate represents a location as with a grid zone, an easting value, and a northing value.

LongitudeDegreeValue	LongitudeDegreeType extends SuperType	A value that specifies the degree of a longitude. The value comes from a restricted range between -180 (inclusive) and +180 (exclusive).
LongitudeMinuteValue	AngularMinuteType extends SuperType	A value that specifies a minute of a degree. The value comes from a restricted range of 0 (inclusive) to 60 (exclusive).
LongitudeSecondValue	AngularSecondType extends SuperType	A value that specifies a second of a minute. The value comes from a restricted range of 0 (inclusive) to 60 (exclusive).
LowerBound	TextType	An allowable lower bound on a numeric point estimate.
MapCoordinateFullText	TextType	A complete coordinate of a point on a map.
MapDate	j-xsd:date	A date a map was current or copyrighted.
MapElevationCoordinateText	TextType	A point's height or elevation on a map. Sometimes referred to as a z-coordinate.
MapHorizontalCoordinateText	TextType	A point's horizontal location on a map. Sometimes referred to as an x-coordinate.
MapLocation	MapLocationType extends SuperType	Details about a location specified by map or grid coordinates.
MapLocationDescriptionText	TextType	A complete description of a map location.
MapName	TextType	A name of a map.
MapPageID	IDType extends SuperType	A page number of a map.
MapQuadrantText	TextType	A quadrant or square in a map.
MapVersionID	IDType extends SuperType	A version of a map.
MapVerticalCoordinateText	TextType	A point's vertical location on a map. Sometimes referred to as a y-coordinate.
Measure	MeasureType extends SuperType	A representation of a measurement.
MedicalConditionCauseText	TextType	A name or description of a medication, drug, food, allergen, or other cause that can initiate an onset of a medical condition.
MedicalConditionDescriptionText	TextType	A description of a medical condition.
MedicalConditionPresentIndicator	j-xsd:boolean	True if a medical condition currently exists; false otherwise.
MedicalConditionSeverityText	TextType	A degree to which a medical condition is affecting a person.

MedicalConditionText	TextType	A medical condition.
MetadataFieldName	TextType	A name of a user-defined document metadata field.
MetadataFieldValueText	TextType	A value of a user-defined document metadata field.
MGRSCoordinate	MGRSCoordinateType extends UTMCoordinateType	A coordinate from the Military Grid Reference System (MGRS) Coordinate System. The MGRS Coordinate System qualifies a Universal Transverse Mercator (UTM) Coordinate System by including a reference to a military grid square.
MGRSCoordinateID	IDType extends SuperType	A complete Military Grid Reference System (MGRS) coordinate value. This value is a concatenation of a UTM Grid Zone, a MGRS square identifier, a UTM Easting Value (in meters), and a UTM Northing value (in meters).
MGRSCoordinateSquareID	IDType extends SuperType	A unique identifier of a Military Grid Reference System (MGRS) square.
MilitaryBranchName	TextType	A name of a military branch in which a person served.
MilitaryDischargeDate	j-xsd:date	A date a person was discharged from military service.
MilitaryDischargeTypeCode	j-ut_offender:MilitaryDischargeTypeC	A code identifying a type of discharge a person received from military service.
MilitaryDischargeTypeText	TextType	A type of discharge a person received from military service.
MilitaryExemptionDescriptionText	TextType	A description of why a person was excused from military service, e.g., overage, disability.
MilitaryExperienceIndicator	j-xsd:boolean	True if a person has some form of military experience; false otherwise.
MilitaryReleaseDate	j-xsd:date	A date a person was released from military service.
MilitaryReleaseTypeText	TextType	A type of release a person received from military service.
MilitaryServiceActiveIndicator	j-xsd:boolean	True if a person is currently serving in the military; false otherwise.
MilitaryServiceTimeMeasure	TimeMeasureType extends MeasureType	An amount of time a person spent in military service.
MilitaryStatus	StatusType extends SuperType	A status of a person in the military, e.g., active, retired, discharged.
Misdemeanor	IncidentType extends ActivityType	A crime punishable by imprisonment in a county jail for up to one year.
MissingPerson	MissingPersonType extends PersonType	Details about a person whose whereabouts are unknown.

MissingPersonCircumstanceCode	j-ncic:MPCType	A code identifying a circumstance surrounding the disappearance of a person.
MissingPersonCircumstanceText	TextType	A circumstance surrounding the disappearance of a person.
MissingPersonDeclarationDate	j-xsd:date	A date a person was declared or legally assumed to be missing.
MissingPersonDeclarationPerson	PersonType extends SuperType	A person who declared another person to be missing.
MissingPersonDeclarationTime	j-xsd:time	A time a person was declared or legally assumed to be missing.
MissingPersonDisappearanceTypeCode	j-ncic:MNPType	A code identifying the type of disappearance of a missing person.
MissingPersonDisappearanceTypeText	TextType	A type of disappearance of a missing person.
MissingPersonFoundDate	j-xsd:date	A date a missing person was found.
MissingPersonFoundIndicator	j-xsd:boolean	True if a missing person has been found; false otherwise.
MissingPersonFoundLocation	LocationType extends SuperType	A location where a missing person was found.
MissingPersonFoundTime	j-xsd:time	A time a missing person was found.
MissingPersonID	IDType extends SuperType	A number or string identifying a missing person.
MissingPersonLastSeenDate	j-xsd:date	A date a missing person was last seen before disappearing.
MissingPersonLastSeenLocation	LocationType extends SuperType	A place a missing person was last seen before disappearing.
MissingPersonLastSeenTime	j-xsd:time	A time a missing person was last seen before disappearing.
MissingPersonLastSeenWitness	WitnessType extends PersonType	A person who last saw a missing person.
MissingPersonStatus	StatusType extends SuperType	A status of a missing person.
NonStandardCode	TextType	A code value.
NonStandardCodeDetails	NonStandardCodeType extends SuperType	A representation for a code not defined or referred to by the JDD standard. This is to be used ONLY when a standard code mechanism is unavailable.
NonStandardCodeSourceName	TextType	The source from which a code value was obtained.
NonStandardCodeValueDescriptionText	TextType	A description of a code value.

NonStandardCodeVersionText	TextType	The version of the source from which a code value was obtained.
Numeric	NumericType extends decimal	A type representing a numeric value.
Obligation	ObligationType extends SuperType	An amount of money or time to be paid as part of a required obligation.
ObligationCompleteIndicator	j-xsd:boolean	True if a payment obligation has been completely fulfilled; false otherwise.
ObligationComplianceIndicator	j-xsd:boolean	True if a payer is in compliance with the requirements of a payment obligation, e.g., no overdue or outstanding amounts.
ObligationDueDate	j-xsd:date	A date by which a payment must be made.
ObligationDueTime	j-xsd:time	A time by which a payment obligation must be made.
ObligationEndDate	j-xsd:date	A final or end date of a payment obligation.
ObligationEndTime	j-xsd:time	A final or end time of a payment obligation.
ObligationExemption	ObligationExemptionType extends SuperType	A waiving or dismissal of a payment obligation.
ObligationExemptionDescriptionText	TextType	A description of the partial or total exemption of a person from a payment obligation.
ObligationExemptionIndicator	j-xsd:boolean	True if a payment obligation has been waived or dismissed; false otherwise.
ObligationPaidDate	j-xsd:date	A date a payment obligation was made.
ObligationPaidTime	j-xsd:time	A time a payment obligation was made.
ObligationPeriodText	TextType	An interval or period a payment obligation is required to be made, e.g., weekly, monthly, yearly.
ObligationProgressDescriptionText	TextType	A description of the amount of progress that has been made on a payment obligation.
ObligationRecipient.Organization	OrganizationType extends SuperType	A person or organization to whom a payment obligation must be fulfilled.
ObligationRecipient.Person	PersonType extends SuperType	A person or organization to whom a payment obligation must be fulfilled.
ObligationRequirementDescriptionText	TextType	A description of the payment requirements, e.g., an amount of money or time in service due.
ObligationStartDate	j-xsd:date	A date on which a payment obligation began.
ObligationStartTime	j-xsd:time	A time at which a payment obligation began.

ObligationSubject.Organization	OrganizationType extends SuperType	A person or organization which must pay an amount of money or time in some activity to fulfill a payment requirement.
ObligationSubject.Person	PersonType extends SuperType	A person or organization which must pay an amount of money or time in some activity to fulfill a payment requirement.
ObligationTypeText	TextType	A type or category of obligation, e.g., fee, fine, support, restitution, community service, damages, court costs.
Offense	IncidentType extends ActivityType	An act or a course of action which may constitute a violation of a criminal statute, ordinance or rule that occurred during an incident.
OfferedPlea	PleaType extends ActivityType	An original plea offered by a defendant in relation to a charge.
Organization	OrganizationType extends SuperType	Details about a unit which conducts some sort of business or operations.
OrganizationAbbreviationText	TextType	An abbreviation, acronym, or code for an organization name, e.g., FBI, NCIC.
OrganizationActivityText	TextType	An activity that an organization is known or thought to be involved with, e.g., law enforcement, supervision.
OrganizationAffiliate	AffiliateType extends SuperType	A person or organization that has some relationship or association with an organization.
OrganizationBranchName	TextType	A name or number of the chapter or branch an organization is known by within a larger group of organizations.
OrganizationDayContact	ContactInformationType extends SuperType	The contact information that is valid during daytime hours.
OrganizationDescriptionText	TextType	A description of an organization
OrganizationDoingBusinessAsName	TextType	A name an organization uses for conducting business. Sometimes referred to as a DBA.
OrganizationEmergencyContact	ContactInformationType extends SuperType	The contact information should be used to contact the person during an emergency only.
OrganizationEmploymentHistory	EmploymentType extends SuperType	An employment history or an employee of an organization or company.
OrganizationEstablishedDate	j-xsd:date	A date an organization was started.
OrganizationEveningContact	ContactInformationType extends SuperType	The contact information that is valid during evening (early night) hours.

OrganizationGovernmentLevelCode	j-ncic:ORIGovernmentLevelType	A code that identifies a governmental level of an organization: local, county, state, federal, or nongovernmental.
OrganizationID	IDType extends SuperType	An identifier of an organization based on the type of organization it is, e.g., for a school, this would be a school identifier, for a lien holder, this would be a lien holder identifier, for a court, this would be a court identifier.
OrganizationIncorporatedIndicator	j-xsd:boolean	True if an organization is incorporated (e.g., corporation); false otherwise (e.g., proprietorship or partnership).
OrganizationJurisdiction	JurisdictionType	An area of service or jurisdiction an organization has over a region.
OrganizationLocalID	IDType extends SuperType	An identifier assigned on a local level to an organization.
OrganizationLocation	LocationType extends SuperType	A location of an organization.
OrganizationMember	AffiliateType extends SuperType	A person or organization that has joined an organization.
OrganizationName	TextType	A name of an organization.
OrganizationNightContact	ContactInformationType extends SuperType	The contact information that is valid during night hours.
OrganizationOccupiedStructure	StructureType extends PropertyType	Indicates that the named organization occupies at least part of the structure.
OrganizationORIID	IDType extends SuperType	A unique identifier assigned to a justice-related organization by the federal government. Sometimes referred to as ORI, ORI code, Originating Agency Code.
OrganizationOtherID	IDType extends SuperType	A generic identifier assigned to an organization.
OrganizationParent.Affiliate	AffiliateType extends SuperType	A person or organization that owns, controls, or operates the organization.
OrganizationParent.Organization	OrganizationType extends SuperType	A person or organization that owns, controls, or operates the organization.
OrganizationPrimaryContact	ContactInformationType extends SuperType	The preferred contact for an individual. Use this designation only when more specific ones (e.g. home or work) are not available.
OrganizationPrincipalOfficial	PersonType extends SuperType	A chief or high ranking executive of an organization.
OrganizationStatusText	TextType	An overall status of an organization, e.g., active/inactive/...

OrganizationSubsidiary	AffiliateType extends SuperType	A person or organization that is owned, controlled, or operated by the organization.
OrganizationSubunitName	TextType	A name of a subdivision of a high-level division of an organization, e.g., division.
OrganizationTaxID	IDType extends SuperType	A federal tax identifier assigned to an organization. Sometimes referred to as a Federal Employer Identification Number, FEIN, an Employer Identification Number, or an EIN.
OrganizationTerminationDate	j-xsd:date	A date an organization went out of business.
OrganizationTypeCode.ncicORIAgency	j-ncic:ORIAgencyType	A code that identifies the functional type of an organization.
OrganizationTypeCode.ncicTYPO	j-ncic:TYPOType	A code that identifies the functional type of an organization.
OrganizationTypeText	TextType	A general functional type of an organization
OrganizationUnitName	TextType	A name of a high-level division of an organization, e.g., department, agency.
OrganizationUnspecifiedContact	ContactInformationType extends SuperType	The contact information should be used to contact the person under unspecified circumstances.
Parole	SupervisionType extends ActivityType	An added period of control following release from prison.
PartialContent	PartialContentType extends SuperType	A regular expression that accurately describes what part(s) of the content are known or certain and what part(s) are unknown. Uses syntax for "xsd:pattern" facet.
PassagePoint	PassagePointType extends ActivityType	Details about a point of entry or exit to a location or structure.
PassagePointDescriptionText	TextType	A description of an entry or exit point.
PassagePointMethodCode	j-nibrs:MethodOfEntryType	A code identifying a method used to enter or exit through a passage point.
PassagePointMethodText	TextType	A method used to enter or exit through a passage point.
PassagePointSecurityTypeText	TextType	A type of security system or mechanism installed at a point of entry or exit.
PassagePointText	TextType	A point of entry or exit to a location or structure.
PassagePointTypeText	TextType	A type of entry or exit point to a location or structure, e.g., door, window, gate.
Percentage	PercentageType extends SuperType	A fraction or ratio with 100 understood as the denominator. Values are between 0 and 1, inclusive.

Person	PersonType extends SuperType	Describes inherent and frequently associated characteristics of a person.
PersonAccentText	TextType	A description of an accent that a person speaks with.
PersonAccompliceActivity	ActivityType extends SuperType	An activity with which a subject has some relation or degree of involvement
PersonAccompliceWithSubject	SubjectType extends PersonType	A person who is an accomplice with a subject person.
PersonAcquaintance	PersonType extends SuperType	The associate is an acquaintance of the subject.
PersonAdoptedChild	PersonType extends SuperType	A person who is an adopted child of the person.
PersonAdoptiveParent	PersonType extends SuperType	A person who is an adoptive parent of the person.
PersonAffiliationOrganization	OrganizationType extends SuperType	Other organization a person is affiliated with
PersonAFISID	IDType extends SuperType	A number issued by a local agency (county) Automated Fingerprint Identification System (AFIS) based on submitted fingerprints.
PersonAgeDescriptionText	TextType	A description of the age of a person.
PersonAgeMeasure	AgeMeasureType extends MeasureType	A measurement of the age of a person.
PersonAgeMeasure.Range	RangeAgeMeasureType extends RangeMeasureType	A measurement of the age of a person.
PersonAlias	PersonType extends SuperType	A name and set of personal demographics describing the same person using alternative descriptors, e.g., an AKA.
PersonAlternateName	PersonNameType extends SuperType	An alternate name used by a person. Sometimes referred to as an AKA.
PersonAssignedIDDetails	PersonAssignedIDDetailsType extends SuperType	A set of details about identifications issued to a person.
PersonAssignmentUnit.EnforcementUnit	EnforcementUnitType extends OrganizationType	The unit assigned to or associated with a person.
PersonAssignmentUnit.Organization	OrganizationType extends SuperType	The unit assigned to or associated with a person.
PersonAuthorityFigure	PersonType extends SuperType	Indicates that the Subject had a trusted position of authority over associate subject (i.e. priest, teacher, boy scout leader, counselor, therapist, etc.)

PersonBabysittee	PersonType extends SuperType	The person being watched by the babysitter.
PersonBabysitter	PersonType extends SuperType	The person performing the babysitting.
PersonBiologicalChild	PersonType extends SuperType	A person who is a biological child of the person.
PersonBiologicalParent	PersonType extends SuperType	A person who is the biological parent of the person.
PersonBiometricDetails	PersonBiometricDetailsType extends SuperType	A set of details about measurable biological or behavioral characteristics, which can reliably recognize the identity, or verify the claimed identity, of a person.
PersonBirthDate	j-xsd:date	A date a person was born.
PersonBirthLocation	LocationType extends SuperType	Details about a place where a person was born.
PersonBirthPlaceCode	j-ncic:POBType	A code identifying the state or country of a person's birth.
PersonBloodTypeCode	j-ncic:BLTType	A code identifying a person's type of blood, e.g., A positive, O negative.
PersonBloodTypeText	TextType	A person's type of blood, e.g., A positive, O negative.
PersonBodyOdor	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's body odor.
PersonBuildText	TextType	A person's physique or shape.
PersonCapability	CapabilityType extends SuperType	Describes a skill, knowledge, physical or emotional trait of a person. Capability implies either a potential ability or an inability for doing something.
PersonCharge	ChargeType extends SuperType	A sequence of charges against a person. This context generally includes an index
PersonChild	PersonType extends SuperType	A person who is a child of the person.
PersonCircumcisionIndicator	TextType	True if a person is circumcised; false otherwise.
PersonCitizenshipCode.iso3166Alpha2	j-iso_3166:CountryAlpha2CodeType	A code identifying a country that assigns rights, duties, and privileges to a person due to the person's birth or naturalization in that country.
PersonCitizenshipCode.iso3166Alpha3	j-iso_3166:CountryAlpha3CodeType	A code identifying a country that assigns rights, duties, and privileges to a person due to the person's birth or naturalization in that country.

PersonCitizenshipCode.fips10-4	j-fips_10-4:CountryCodeType	A code identifying a country that assigns rights, duties, and privileges to a person due to the person's birth or naturalization in that country.
PersonCitizenshipCode.iso3166Numeric	j-iso_3166:CountryNumericCodeType	A code identifying a country that assigns rights, duties, and privileges to a person due to the person's birth or naturalization in that country.
PersonCitizenshipText	TextType	A country that assigns rights, duties, and privileges to a person due to the person's birth or naturalization in that country.
PersonClothing	ClothingType extends SuperType	Details about an article of clothing worn by a person.
PersonCohabitant	PersonType extends SuperType	The associate shares a common residence with the subject
PersonCommonLawSpouse	PersonType extends SuperType	The associate is a common-law spouse of the subject.
PersonComplexionText	TextType	An appearance of a person's skin, e.g., clear, freckled, wrinkled.
PersonDayContact	ContactInformationType extends SuperType	The contact information should be used during daylight hours only.
PersonDeathDate	j-xsd:date	A date a person died or was declared legally dead.
PersonDental	PersonDentalType extends SuperType	Details about the dental characteristics of a person.
PersonDentalCharacteristicGeneralCode	j-ncic:DCHGeneralType	A code identifying a person's general dental characteristics.
PersonDentalCharacteristicGeneralText	TextType	A person's general dental characteristics.
PersonDentalCharacteristicOtherCode	j-ncic:DCHOtherType	A code identifying a person's other dental characteristics.
PersonDentalCharacteristicOtherText	TextType	A person's other dental characteristics.
PersonDentalCharacteristicRemovableAppliances	j-ncic:DCHRemovableAppliancesType	A code identifying a person's removable dental appliance.
PersonDentalCharacteristicRemovableAppliancesText	TextType	A person's removable dental appliance.
PersonDentalCharacteristicRestorationCariesCode	j-ncic:DCHRestorationCariesType	A code identifying a person's dental restoration or caries.
PersonDentalCharacteristicRestorationCariesText	TextType	A person's dental restoration or caries.
PersonDentalCharacteristicStatusCode	j-ncic:DCHStatusType	A code identifying a status of a person's dental characteristics.
PersonDentalCharacteristicStatusText	TextType	A status of a person's dental characteristics.
PersonDentalCharacteristicText	TextType	A visible problem or characteristic of a person's teeth.
PersonDependentQuantity	QuantityType extends NumericType	A number of people dependent upon a person as their primary means of support.

PersonDescriptionText	TextType	A general description of a person.
PersonDetainedLocation.Location	LocationType extends SuperType	The location or structure at which a person is or was detained.
PersonDetainedLocation.Structure	StructureType extends PropertyType	The location or structure at which a person is or was detained.
PersonDigitalImage	ImageType extends BinaryType	A photograph or image of a person in a digital format.
PersonDigitizedSignatureImage	ImageType extends BinaryType	An image of a person's handwritten signature.
PersonDisguiseDescriptionText	TextType	A description of something misleading that a person wears, e.g., wig, mask, uniform.
PersonDNA	DNAType extends BiometricType	A representation or an encoding of the identifying characteristics of a person's DNA.
PersonDomesticPartner	PersonType extends SuperType	The associate is the domestic partner of the subject.
PersonDriverLicenseID	DrivingJurisdictionAuthorityIDType extends IDType	Information about an identifier used to refer to a specific person who has obtained a driver's license. Sometimes referred to as driver license number, dINumber.
PersonDriversLicense	DriverLicenseType extends SuperType	A driver's license.
PersonDrivingIncident	DrivingIncidentType extends IncidentType	A driving accident in which a person is involved.
PersonDrivingInsuranceCoverageTypeText	TextType	A type of insurance coverage a driver of a vehicle has.
PersonDrivingInsuranceStatusText	TextType	The status of a person's driving insurance, e.g., insured, not insured.
PersonEarShape	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's ear shape.
PersonEducationLevelText	TextType	The highest level of education a person has obtained.
PersonEmergencyContact	ContactInformationType extends SuperType	The contact information should be used to contact the person during an emergency only.
PersonEmploymentHistory	EmploymentType extends SuperType	Details about an employment record of a person.
PersonEthnicityCode	j-nibrs:EthnicityCodeType	A code identifying a person's cultural lineage.
PersonEthnicityText	TextType	A person's cultural lineage.
PersonEveningContact	ContactInformationType extends SuperType	The contact information should be used during evening hours (early night) only.
PersonEyeColorCode	j-ncic:EYEType	A code identifying the color of a person's eyes.

PersonEyeColorText	TextType	The color of a person's eyes.
PersonEyewearDescriptionText	TextType	A description of glasses or other eyewear a person wears.
PersonFacialFeatures	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's facial features.
PersonFamilyRelation	PersonType extends SuperType	The associate and the subject are members of the same family, but the precise relationship is not clear or not noted.
PersonFBIID	IDType extends SuperType	A number issued by the FBI's Automated Fingerprint Identification System (AFIS) based on submitted fingerprints.
PersonFingerGeometry	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's finger geometry.
PersonFingerprintSet	FingerprintSetType extends BiometricType	A representation or an encoding of the identifying characteristics of a set of a persons fingerprints.
PersonFirearmSalesDisqualifiedIndicator	j-xsd:boolean	True if a person is prohibited from purchasing firearms; false otherwise.
PersonFootPrint	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's footprint.
PersonFosterChild	PersonType extends SuperType	The associate is a legal foster parent of the subject
PersonFosterParent	PersonType extends SuperType	The associate is a legal foster child of the subject
PersonFullName	PersonNameTextType extends TextType	A complete name of a person.
PersonGait	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's gait.
PersonGangAffiliation	OrganizationType extends SuperType	A gang a person is affiliated with
PersonGeneralAppearanceDescriptionText	TextType	A general description of the way a person looks and is presented.
PersonGeneralLedgerID	IDType extends SuperType	A general-ledger account number associated with a person.
PersonGivenName	PersonNameTextType extends TextType	A first name of a person.
PersonGuardian	PersonType extends SuperType	A person who is a legal guardian of the person.

PersonGuardianRecipient	PersonType extends SuperType	A person who is under the legal guardianship of the person.
PersonHairAppearanceText	TextType	A description of the way a person's hair looks.
PersonHairColorCode	j-ncic:HAIType	A code identifying the color of a person's hair.
PersonHairColorText	TextType	The color of a person's hair.
PersonHairFacialText	TextType	A type of facial hair a person has.
PersonHairLengthText	TextType	A length of hair of a person.
PersonHairStyleText	TextType	A style of a person's hair.
PersonHairTypeText	TextType	A person's type of hair, e.g., fine, straight, curly.
PersonHandednessText	TextType	A hand a person is more adept with using, e.g., left, right, ambidextrous.
PersonHandGeometry	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's hand geometry.
PersonHeightDescriptionText	TextType	A description of the height of a person.
PersonHeightMeasure	PersonHeightMeasureType extends MeasureType	A measurement of the height of a person.
PersonHeightMeasure.Range	RangePersonHeightMeasureType extends RangeMeasureType	A measurement of the height of a person.
PersonHumanResourcesID	IDType extends SuperType	A human resources id or assigned number for a person, such as a badge number.
PersonIDTypeCode	j-ncic:MNUType	A code the identifies a type of identifier assigned to a person.
PersonInjury	InjuryType extends SuperType	Details about an injury a person has received.
PersonIntoxication	IntoxicationType extends SuperType	Details about the measurable alcoholic and/or drug intoxication level of a person.
PersonIrisFeatures	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's iris features.
PersonIssuedTitle.PropertyRegistration	PropertyRegistrationType extends SuperType	A title which has been issued to a person.
PersonIssuedTitle.PropertyTitle	PropertyTitleType extends SuperType	A title which has been issued to a person.
PersonJewelryDescriptionText	TextType	A description of jewelry a person wears.
PersonKeystrokeDynamics	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's keystroke dynamics.
PersonLanguageEnglishIndicator	j-xsd:boolean	True if a person understands and speaks English; false otherwise.

PersonLearningDisabilityText	TextType	A learning disability of a person.
PersonLicenseID	IDType extends SuperType	A string that identifies a license, certification, or registration of a person for some purpose; may be granted to certify professional occupation or skill, e.g., medical license, pilot license, professional engineer.
PersonLipMovement	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's lip movement.
PersonLivingIndicator	j-xsd:boolean	True if a person is alive, false if a person is dead. This may be useful if death date is not known.
PersonMaidenName	PersonNameTextType extends TextType	An original surname of a person before changed by marriage.
PersonMaritalStatusText	TextType	A marital status of a person, e.g., married, divorced, single, separated.
PersonMarriagePartner	PersonType extends SuperType	The associate is legally married to the subject.
PersonMedicalCondition	MedicalConditionType extends SuperType	Details about a specific medical condition a person has or experiences.
PersonMedicalDescriptionText	TextType	A description of the overall health of a person.
PersonMedicalDetails	PersonMedicalDetailsType extends SuperType	A set of details about the medical condition of a person.
PersonMedicalFileIndicator	j-xsd:boolean	True if a state or province medical history file is known to exist for a person; false otherwise. The presence of a file dose not necessarily indicate that there is a medical issue that impacts a person's driving ability.
PersonMedicationRequiredText	TextType	A medication and dosage required for a person.
PersonMentalStateText	TextType	A mental state of a person.
PersonMiddleName	PersonNameTextType extends TextType	A middle name of a person.
PersonMilitarySummary	MilitarySummaryType extends SuperType	Summary details about the service of a person in the military.
PersonModusOperandi	ActivityType extends SuperType	A methodology of action, particularly a criminal action, known to be routinely associated with a persons crimes.
PersonMoodDescriptionText	TextType	A description of a person's mood or emotions.
PersonName	PersonNameType extends SuperType	A name by which a person is known.
PersonNameInitialsText	TextType	A first letter of a person's given, possibly middle, and last names.

PersonNameSoundexText	TextType	A name encoding such that similar sounding names with different spellings appear the same.
PersonNationalID	IDType extends SuperType	A general ID that identifies a person within a country but is not based on fingerprint.
PersonNationalityCode.iso3166Alpha2	j-iso_3166:CountryAlpha2CodeType	A code identifying the country in which a person was born.
PersonNationalityCode.iso3166Alpha3	j-iso_3166:CountryAlpha3CodeType	A code identifying the country in which a person was born.
PersonNationalityCode.fips10-4	j-fips_10-4:CountryCodeType	A code identifying the country in which a person was born.
PersonNationalityCode.iso3166Numeric	j-iso_3166:CountryNumericCodeType	A code identifying the country in which a person was born.
PersonNationalityText	TextType	The country in which a person was born.
PersonNeighbor	PersonType extends SuperType	The associate is a neighbor of the subject.
PersonNightContact	ContactInformationType extends SuperType	The contact information should be used during night hours only. If there is no evening contact, this information may be used during the evening as well.
PersonOtherID	PersonOtherIDType extends IDType	Information about an identifier with a type that is not explicitly defined in the standard that refers to a person within a certain domain, e.g., state ID cards or other non-license and non-fingerprint based IDs.
PersonPalmPrint	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's palm print.
PersonParent	PersonType extends SuperType	The associated person is a parent of the main person. Use this context when a more specific relationship is not relevant or not important
PersonPhysicalDetails	PersonPhysicalDetailsType extends SuperType	A set of details about the physical appearance of a person.
PersonPhysicalDisabilityText	TextType	A physical disability of a person.
PersonPhysicalFeature	PhysicalFeatureType extends SuperType	Details about a physical feature of a person. Includes scars, marks, and tattoos.
PersonPrefixName	TextType	A title or honorific used by a person, e.g., Dr., Judge, General, Ms.
PersonPrimaryLanguageCode.iso639-2t	j-iso_639-2t:LanguageCodeType	A code identifying a language that a person is most comfortable using.
PersonPrimaryLanguageCode.iso639-2b	j-iso_639-2b:LanguageCodeType	A code identifying a language that a person is most comfortable using.
PersonPrimaryLanguageText	TextType	A language that a person is most comfortable using.
PersonPrimaryWorker	PersonType extends SuperType	A primary social worker or other overseer assigned to a person that is not a caregiver.

PersonRaceCode	j-ncic:RACType	A code identifying the race of a person.
PersonRaceText	TextType	A classification of a person based on factors such as geographical locations and genetics.
PersonReferralWorker	PersonType extends SuperType	Employee of State assigned to the particular juvenile
PersonRegisteredOffenderIndicator	j-xsd:boolean	True if a person is required to register as an offender; false otherwise.
PersonReligionText	TextType	A religion to which a person subscribes or believes. Describes the overall category of a person's spiritual beliefs.
PersonResidentCode	j-nibrs:ResidentCodeType	A code identifying a type of residence a person has in an area such as a city, town, or community.
PersonResidentText	TextType	A type or description of a persons residence, e.g., local, resident, non-resident.
PersonRetina	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's retina.
PersonSaliva	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's saliva.
PersonSecondaryLanguageCode.iso639-2t	j-iso_639-2t:LanguageCodeType	A code identifying a language that a person has some knowledge of and can speak or understand to some degree.
PersonSecondaryLanguageCode.iso639-2b	j-iso_639-2b:LanguageCodeType	A code identifying a language that a person has some knowledge of and can speak or understand to some degree.
PersonSecondaryLanguageText	TextType	A language that a person has some knowledge of and can speak or understand to some degree.
PersonSemen	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's semen.
PersonSexCode	j-ncic:SEXTYPE	A code identifying the gender or sex of a person.
PersonSexText	TextType	The gender or sex of a person.
PersonSexualOrientationText	TextType	Describes a target gender of a person's sexual interest.
PersonSkinToneCode	j-ncic:SKNType	A code identifying a color or tone of a person's skin
PersonSkinToneText	TextType	A color or tone of a person's skin.
PersonSocialDetails	PersonSocialDetailsType extends SuperType	A set of details about the social characteristics of a person.

PersonSocialFriend	PersonType extends SuperType	The associate is a friend of the subject, in a social setting. This includes relationships such as "boy friend" and "girl friend".
PersonSpeechDescriptionText	TextType	A description of any impediments that affect a person's speech, e.g., stutter, cleft palate.
PersonSpeechPattern	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's speech pattern.
PersonSpouse	PersonType extends SuperType	The associate is a spouse of the subject. Used when the legal status of the relationship (marriage, common-law) is not known.
PersonSSNID	IDType extends SuperType	A 9-digit numeric identifier assigned to a living person by the U.S. Social Security Administration. A social security number of a person. Sometimes referred to as a SSN.
PersonStateID	IDType extends SuperType	A number issued by a state Automated Fingerprint Identification System (AFIS) based on submitted fingerprints. Sometimes referred to as a State ID number or a SID.
PersonStranger	PersonType extends SuperType	The associate has no known or admitted knowledge of the subject
PersonSuffixName	TextType	A component that is appended after the family name that distinguishes members of a family with the same given, middle, and last name, e.g., Jr, Sr, III, or otherwise qualifies the name (e.g., MD, LLD, PhD).
PersonSurName	PersonNameTextType extends TextType	A last name or family name of a person.
PersonTaxID	IDType extends SuperType	An identifier used to refer to a specific person within the tax system of a country. Within the U.S., this identifier may also be a persons social security number (SSN) or another identifier.
PersonTemporaryAssignmentUnit	OrganizationType extends SuperType	The organizational unit to which a person is assigned, specifically a temporary assignment.
PersonThermalFacelImage	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's thermal face image.
PersonThermalHandImage	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's thermal hand image.
PersonThermalImage	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's thermal image.

PersonUnspecifiedContact	ContactInformationType extends SuperType	The contact information should be used to contact the person under unspecified circumstances.
PersonUrine	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's urine.
PersonUSCitizenIndicator	j-xsd:boolean	True if a person is a citizen of the United States; false otherwise.
PersonVeinPattern	BiometricType extends SuperType	A representation or an encoding of the identifying characteristics of a person's vein pattern.
PersonVendorID	IDType extends SuperType	Vendor number for a person
PersonVisionPrescriptionText	TextType	A prescription a person needs for corrective lenses or contacts.
PersonWasCommonLawSpouse	PersonType extends SuperType	The associate was at one time the common-law spouse of the subject but has legally separated or divorced.
PersonWasDomesticPartner	PersonType extends SuperType	The associate was at one time the domestic partner of the subject but has dissolved the relationship.
PersonWasMarriedTo	PersonType extends SuperType	The associate was at one time married to the subject but has legally divorced.
PersonWasSpouse	PersonType extends SuperType	The associate was at one time a spouse of the subject but has divorced or otherwise legally severed the relationship. Used when the legal status of the relationship (marriage, common-law) is not known.
PersonWeightDescriptionText	TextType	A description of the weight of a person.
PersonWeightMeasure	PersonWeightMeasureType extends MeasureType	A measurement of the weight of a person.
PersonWeightMeasure.Range	RangePersonWeightMeasureType extends RangeMeasureType	A measurement of the weight of a person.
PersonWorkContact	ContactInformationType extends SuperType	The contact information should be used when the person is expected to be or might be at work.
PersonWorkLocation.Location	LocationType extends SuperType	The work address or structure of a person. This association is used when the person's employer is not known. If the employer is known, use an Organization which in turn has a Location.
PersonWorkLocation.Structure	StructureType extends PropertyType	The work address or structure of a person. This association is used when the person's employer is not known. If the employer is known, use an Organization which in turn has a Location.

PersonXRayImage	ImageType extends BinaryType	An X-Ray image of a person or part of a person.
PhysicalFeatureCategoryText	TextType	A general classification or categorization of a physical feature, e.g., scar, mark, tattoo, missing limb.
PhysicalFeatureDescriptionText	TextType	A description of a physical feature.
PhysicalFeatureImage	ImageType extends BinaryType	A digital image of a physical feature, e.g., tattoo.
PhysicalFeatureLocationText	TextType	A location of a physical feature on a person's body.
PhysicalFeatureTypeCode	j-ncic:SMTType	A code identifying a type of physical feature.
PhysicalFeatureTypeText	TextType	A type of physical feature within a category, e.g., for a tattoo type, this could be animal, flag.
Plea	PleaType extends ActivityType	Details about an answer which a defendant in an action at law makes to the State's charges, e.g., Guilty, Not Guilty, for adult, Admit, Deny for juvenile.
PleaDescriptionText	TextType	A description of a plea.
PleaGuiltyIndicator	j-xsd:boolean	True if a person admits guilt in relation to a charge; false otherwise.
PleaNegotiatedIndicator	j-xsd:boolean	True if a plea is negotiated with the prosecution; false otherwise.
PleaNoContestIndicator	j-xsd:boolean	True if a person is willing to accept the consequences of a charge without admitting guilt or innocence; false otherwise.
PleaRecommendationText	TextType	A recommended plea agreement for violent, most serious, or armed offenses.
PleaTypeCode	j-ut_offender:PleaTypeCodeType	A code to indicate a type of plea.
PreviousSentence	SentenceType extends ActivityType	An old sentence term and conditions that have since been replaced by an amended sentence.
PrimaryContactInformation	ContactInformationType extends SuperType	Information on a preferred or primary contact mechanism.
Probation	SupervisionType extends ActivityType	A judicial requirement that a person fulfill certain conditions of behavior in lieu of jail time.
Program	ProgramType extends SupervisionType	Details about projects, programs, or services designed to reduce a person's likelihood for committing crimes or to improve their understanding of laws and consequences.
ProgramAction	EventType extends SuperType	An project or service of a program.

ProgramAdministrator.Organization	OrganizationType extends SuperType	A person or organization that runs a program.
ProgramAdministrator.Person	PersonType extends SuperType	A person or organization that runs a program.
ProgramCapacityText	j-xsd:integer	A maximum number of people that can be enrolled in a program at a time..
ProgramCondition	ConditionType extends ActivityType	A condition that must be met in order for a person to remain in a program.
ProgramFacility	FacilityType extends OrganizationType	A place where a program is located.
ProgramPubliclyRunIndicator	j-xsd:boolean	True if a program is run in the public sector; false if the program is run privately.
ProgramPurposeText	TextType	A purpose or reason for a program.
ProgramReferral	ReferralType extends ActivityType	A direction from a person or organization to a subject to attend a program.
ProgramRelease	ReleaseType extends ActivityType	Details about how a subject left a program. Could describe program completion, removal.
ProgramResidentialIndicator	j-xsd:boolean	True if a subject is to reside at a program's facility during the duration of a program; false otherwise.
ProgramSubject	SubjectType extends PersonType	A person who attends a program.
ProgramSupervisedIndicator	j-xsd:boolean	True if a subject will be officially supervised during the duration of a program; false otherwise.
ProgramSupervisor.Organization	OrganizationType extends SuperType	A person or organization that makes sure a program runs according to standards.
ProgramSupervisor.Person	PersonType extends SuperType	A person or organization that makes sure a program runs according to standards.
Progress	ProgressType extends ActivityType	Details about a tracking of progression or changes made in an assigned activity.
ProgressComplianceIndicator	j-xsd:boolean	True if a reported progress is acceptable according to the terms set; false otherwise.
ProgressComplianceText	TextType	A description of the compliance or non-compliance of a person with an activity.
ProgressPaymentAmountText	TextType	A description of the amount of payment a person has made against a fee, fine, restitution, surcharge, etc.
ProgressTimeAmountText	TextType	A description of the amount of time a person has spent making progress in an activity.

Property	PropertyType extends SuperType	A tangible or intangible item that can be owned or used.
PropertyActionText	TextType	An action that was taken against a property item.
PropertyAgeMeasure	AgeMeasureType extends MeasureType	An age of a property item.
PropertyAssignedIDDetails	PropertyAssignedIDDetailsType extends SuperType	Information about a set of identifiers assigned to a property item.
PropertyBarCodeID	IDType extends SuperType	A bar code assigned to a property item.
PropertyBinary	BinaryType extends SuperType	A binary representation of a property item, e.g., encoded video or audio file.
PropertyBrandName	TextType	A trademark or distinctive name that identifies a manufacturer of a property item.
PropertyCategoryCode.nibrsPropertyCategory	j-nibrs:PropertyCategoryCodeType	A code identifying a category or classification of a property item.
PropertyCategoryCode.ncicTYP	j-ncic:TYPArticleCategoryType	A code identifying a category or classification of a property item.
PropertyCategoryText	TextType	A category or classification of a property item.
PropertyColorDescriptionText	TextType	A description of the overall color of a property item.
PropertyConditionText	TextType	A state or appearance of a property item, e.g., new, used, damaged.
PropertyContainedInStructure	StructureType extends PropertyType	The structure in which a property item is currently in or on.
PropertyCurrentResaleValue	PropertyValue PropertyValueType extends SuperType	A current monetary value or worth of a property item for which it could be sold.
PropertyDealerID	IDType extends SuperType	An identifier assigned to a property item by a dealer.
PropertyDescriptionText	TextType	A description of a property item.
PropertyDetail	PropertyDetailType extends SuperType	Details about a feature or characteristic of a property item.
PropertyDetailCode	j-ncic:TYPAType	A code identifying a feature or characteristic of a property item.
PropertyDetailDescription	TextType	A description of a feature or characteristic of a property item.
PropertyDetailText	TextType	A feature or characteristic of a property item.
PropertyDisposition	PropertyDispositionType extends ActivityType	Details about what has happened to a property item.

PropertyDispositionCode	j-nibrs:PropertyLossCodeType	A code that identifies what happened to a property item, e.g., towed, released, seized, unrecoverable, missing, stolen.
PropertyDispositionLocation	LocationType extends SuperType	A location of a property item after it has been processed.
PropertyDispositionProperty	PropertyType extends SuperType	A description of the property item being processed.
PropertyFederalID	IDType extends SuperType	A federal identifying number assigned to a property item.
PropertyHeightMeasure	LengthMeasureType extends MeasureType	An overall height of a property item.
PropertyHoldingOrganization	OrganizationType extends SuperType	An organization that currently is in possession of a property item.
PropertyImage	ImageType extends BinaryType	An encoding of a digital picture of a property item.
PropertyLengthMeasure	LengthMeasureType extends MeasureType	An overall length of a property item as measured from the front to the rear.
PropertyLocation	LocationType extends SuperType	Details about the location of a property item.
PropertyMakeName	TextType	A name of the manufacturer that produced a property item.
PropertyMissingValue	PropertyValueType extends SuperType	A monetary value or worth of a property item that is lost, stolen, being held, or is otherwise missing.
PropertyModelName	TextType	A specific design or type of product made by a manufacturer.
PropertyMovingOrganization	OrganizationType extends SuperType	An organization that moved a property item, e.g., a towing company.
PropertyNCICID	IDType extends SuperType	A unique identifier assigned to a property item by the FBI National Crime Information Center.
PropertyOtherID	IDType extends SuperType	A miscellaneous identification number for a property item.
PropertyOtherValue	PropertyValueType extends SuperType	An additional monetary value of a property item.
PropertyOwner.Organization	OrganizationType extends SuperType	Details about a person or organization which own a property item.
PropertyOwner.Person	PersonType extends SuperType	Details about a person or organization which own a property item.

PropertyOwnerAppliedID	IDType extends SuperType	Information about a name or number applied to a property item by the owner. This may be an engraving on the property item or may be used to identify a fleets equipment number.
PropertyOwnerPurchasedValue	PropertyValue extends SuperType	An amount of money a current owner paid to purchase a property item.
PropertyPhysicalDetails	PropertyPhysicalDetailsType extends SuperType	Details about a property items physical structures such as make, model, length, and color.
PropertyPossessionDescriptionText	TextType	A description of how or why a party other than the owner came to possess a property item.
PropertyPossessor.Organization	OrganizationType extends SuperType	Details about a person or organization other than the owner that has possession of a property item. Can also refer to a towing company for a vehicle.
PropertyPossessor.Person	PersonType extends SuperType	Details about a person or organization other than the owner that has possession of a property item. Can also refer to a towing company for a vehicle.
PropertyQuantity	QuantityType extends NumericType	A count or number of similar pieces or units that make up a property item, e.g. to indicate three bags of drugs were found, set PropertyQuantity=3 and quantityUnitText=bags.
PropertyReceiptID	IDType extends SuperType	An identifier issued to a property item when taken into custody by a justice official or organization.
PropertyRecoveredValue	PropertyValue extends SuperType	A monetary value or worth of a property item that has been returned to an owner or possessor after having been missing.
PropertyRegistration	PropertyRegistrationType extends SuperType	Details about registering a property item with an authority.
PropertySeizedLocation	LocationType extends SuperType	The location where property was seized.
PropertySeizer.Organization	OrganizationType extends SuperType	The person or organization who seized a property item.
PropertySeizer.Person	PersonType extends SuperType	The person or organization who seized a property item.
PropertySeizure	PropertySeizureType extends ActivityType	Details about a removal of property from the possession of a person or organization and placed in custody of the justice system.
PropertySeizureDisposition	DispositionType extends SuperType	Details about how a property item was processed or handled after being seized.

PropertySeizureMethodText	TextType	A method by which a property item was removed from a person's possession and taken into custody.
PropertySeizureOwningPerson	PersonType extends SuperType	A person who owns a property item that was seized.
PropertySeizurePossessingPerson	PersonType extends SuperType	A person who had possession of a property item when it was seized.
PropertySeizureProperty	PropertyType extends SuperType	A property item that was seized.
PropertySeizurePropertyHoldingOrganization	OrganizationType extends SuperType	An organization that holds or stores a property item that has been seized.
PropertySeizureReleaseConditionText	TextType	A condition that, if met, will allow a seized property item to be released back to its owner.
PropertySeizureSeizingEnforcementOfficial	EnforcementOfficialType extends PersonType	A peace official that seized a property item.
PropertySeizureWarrant	WarrantType extends CourtOrderType	A warrant that was required to remove property from a person's possession.
PropertySerialID	IDType extends SuperType	An identifying number inscribed on or attached to a part, collection of parts, or complete unit by the manufacturer.
PropertySizeDescriptionText	TextType	A description of the size or physical dimension of a property item.
PropertyStateID	IDType extends SuperType	A state-assigned identification to a property item.
PropertyStatus	StatusType extends SuperType	A status of a property item. Describes if the property is being held, is stolen, missing, recovered, damaged, no change.
PropertyStyleText	TextType	A style of a property item.
PropertyTitle	PropertyTitleType extends SuperType	Details about property ownership and purchase.
PropertyTitleHolder.Organization	OrganizationType extends SuperType	A person or organization who holds the actual title on a property item, e.g., a bank may hold a vehicle title.
PropertyTitleHolder.Person	PersonType extends SuperType	A person or organization who holds the actual title on a property item, e.g., a bank may hold a vehicle title.
PropertyTotalDamageValue	PropertyValueType extends SuperType	A monetary value or worth of damage that occurred to a property item.
PropertyTypeCode.nibrsArresteeWeapon	j-nibrs:ArresteeWeaponCodeType	A code that identifies a type of property.
PropertyTypeCode	j-ncic:TYPAType	A code that identifies a type of property.
PropertyTypeText	TextType	A type of property.

PropertyUsageText	TextType	A description of how a property item is used.
PropertyValue	PropertyValueType extends SuperType	Details about an estimation, account, or appraisal of a property item's actual monetary value.
PropertyValueAmount	AmountType extends decimal	A monetary value of a property item.
PropertyValueAssigningMethodText	TextType	A method used in assigning a value to a property item, e.g., fair market value, estimate, reported, appraised value.
PropertyValueAssigningOrganization	OrganizationType extends SuperType	An organization that assigns a value to a property item.
PropertyValueAssigningPerson	PersonType extends SuperType	A person that assigns a value to a property item.
PropertyValueDate	j-xsd:date	A date a value of a property item was assigned or became effective.
PropertyValueDescriptionText	TextType	A description of a monetary value of a property item.
PropertyValueDetails	PropertyValueDetailsType extends SuperType	Details about the value of a property item.
PropertyValueTaxIncludedIndicator	j-xsd:boolean	True if taxes were included in the property value; false otherwise.
PropertyVisibleID	IDType extends SuperType	A license number or other visible identifier. For a vehicle, this is the plate number. For a boat, this is the registration number visible on the outside of the hull. For aircraft, this is the aircraft registration number visible on the tail or the rear of the fuselage.
PropertyWeaponIndicator	j-xsd:boolean	True if a property item is a weapon, e.g., firearm or knife; false otherwise.
PropertyWeaponUsageIndicator	j-xsd:boolean	True if a property item not traditionally thought of as a weapon was used as such, e.g., a vehicle used to hit a person; false otherwise.
PropertyWeaponUseText	TextType	A way a property item was used as a weapon.
PropertyWeightMeasure	WeightMeasureType extends MeasureType	A measurement of the weight of a property item.
PropertyWidthMeasure	LengthMeasureType extends MeasureType	An overall width of a property item as measure from side to side.
PropertyYearDate	j-xsd:gYear	The model year of a property item.
ProsecutionCharge	ChargeType extends SuperType	A charge filed by a prosecuting attorney. May be different from or the same as the original arrest charge.

ProtectionOrder	ProtectionOrderType extends CourtOrderType	A civil order, issued by a court, protecting one individual from another.
ProtectionOrderConditionCode	j-ncic:PCOType	A code identifying a specific type of protection order.
ProtectionOrderRestrictedPerson	PersonType extends SuperType	A person that a subject is restricted from having any contact with as defined in a protection order.
Quantity	QuantityType extends NumericType	A representation of a quantity.
RangeMaximumMeasure	MeasureType extends SuperType	A maximum measure value on a range measure.
RangeMeasure	RangeMeasureType extends SuperType	A minimum - maximum range between two measured values.
RangeMinimumMeasure	MeasureType extends SuperType	A minimum measure value on a range measure.
Rate	RateType extends MeasureType	A representation of the measurement of a rate.
RealEstate	RealEstateType extends PropertyType	Details about a piece of real estate.
RealEstateAcreageText	TextType	An amount of land measured in acres.
RealEstateAttachedStructure	StructureType extends PropertyType	A structure attached or affixed to real estate.
RealEstateBoundaryDescriptionText	TextType	A description of the boundary or real property limits.
RecurringObligation	RecurringObligationType extends ObligationType	A recurring payment obligation that must be met on a periodical basis.
Referral	ReferralType extends ActivityType	Details about a directing of a person to a relevant service or product.
ReferralActivity	ActivityType extends SuperType	An activity or service a person is directed to attend or perform.
ReferralCourtOrder	CourtOrderType extends ActivityType	A court order that issues a referral for a person.
ReferralDesignation.Organization	OrganizationType extends SuperType	A person or agency to which a person has been referred.
ReferralDesignation.Person	PersonType extends SuperType	A person or agency to which a person has been referred.
ReferralIssuer.Organization	OrganizationType extends SuperType	A person or organization who directs a person to a relevant service or product.
ReferralIssuer.Person	PersonType extends SuperType	A person or organization who directs a person to a relevant service or product.

ReferralMandatoryIndicator	j-xsd:boolean	True if a referral is required; false if a referral is optional.
ReferralProperty	PropertyType extends SuperType	A product or property item to which a person has been directed.
ReferralSubject	SubjectType extends PersonType	A person who is being directed to a relevant service or product.
ReferralSupervisor.Organization	OrganizationType extends SuperType	A person or organization who is responsible for ensuring that a person follows a referral.
ReferralSupervisor.Person	PersonType extends SuperType	A person or organization who is responsible for ensuring that a person follows a referral.
RegisterAction	RegisterActionType extends SuperType	A history of action for a case.
RegisterActionDate	j-xsd:date	A date an action took place in a register of actions.
RegisterActionDescriptionText	TextType	A description of something that happened in a case in a register of actions entry.
RegisterActionJudge	CaseOfficialType extends JudicialOfficialType	An associated judge in a register of actions.
RegisterActionTime	j-xsd:time	A time an action took place in a register of actions.
RegisterActionTitle	TextType	A title or type of register of actions entry.
RegisteredOffender	RegisteredOffenderType extends PersonType	Details about a person that is required to register their residential information with a local law enforcement agency due to having been convicted of a certain type of crime.
RegisteredOffenderConviction	ConvictionType extends ActivityType	A conviction that led to a person's status as a registered offender.
RegisteredOffenderCourtOrder	CourtOrderType extends ActivityType	A court order mandating a person register as an offender.
RegisteredOffenderDescription	TextType	A description of a registered offense for which a person must register.
RegisteredOffenderEndDate	j-xsd:date	A date a person no longer must register as an offender.
RegisteredOffenderEntryDate	j-xsd:date	A date a person initially registered as an offender.
RegisteredOffenderID	IDType extends SuperType	Identification information identifying a person as a certain kind of registered offender.
RegisteredOffenderReportingCriteriaText	TextType	Requirements placed on a registered offender to report to a supervising agency.
RegisteredOffenderReportingProfessionName	TextType	The name of the profession a registered offender must report, e.g., doctor.
RegisteredOffenderStartDate	j-xsd:date	A date a person must be registering as an offender.

RegisteredOffenderTypeText	TextType	An offense for which a person must register as being an offender, e.g. sex. felon.
RegisteredSexOffender	RegisteredOffenderType extends PersonType	A person who is required to register as a sexual offender.
RegisterOfActions	RegisterOfActionsType extends SuperType	A history of actions for a case. May include things such as information about filings, hearings, manually entered notes, and any historical changes in the case. Also known as a case docket sheet, ROA.
RegistrationAuthorityName	TextType	A name of an authority, person, or organization which issued a property registration.
RegistrationDuplicateQuantity	j-xsd:nonNegativeInteger	A number of times proof of property registration is issued with no change in information by the issuing authority. This number may be more than one because a proof may have been lost. This can be used to track duplicates or replacements.
RegistrationEffectiveDate	j-xsd:date	A date the current registration becomes effective. This may or may not be the original registration date.
RegistrationExpirationDate	j-xsd:date	A date the current registration expires.
RegistrationFee	ObligationType extends SuperType	An amount of money required to register a property item.
RegistrationID	IDType extends SuperType	A number or text used to uniquely identify a registration certificate or document. Sometimes referred to as a Registration Serial Number.
RegistrationJurisdictionCode.CanadianProvince	j-can:CanadianProvinceCodeType	A code identifying a state or other jurisdictional unit where a property registration was issued.
RegistrationJurisdictionCode.fips10-4International	j-fips_10-4:InternationalStateCodeType	A code identifying a state or other jurisdictional unit where a property registration was issued.
RegistrationJurisdictionCode.ANSID20Jurisdiction	j-ansi_d20:JurisdictionAuthorityCodeType	A code identifying a state or other jurisdictional unit where a property registration was issued.
RegistrationJurisdictionCode.ncicLIS	j-ncic:LISType	A code identifying a state or other jurisdictional unit where a property registration was issued.
RegistrationJurisdictionCode.ncicLSTA	j-ncic:LSTAType	A code identifying a state or other jurisdictional unit where a property registration was issued.
RegistrationJurisdictionCode.ncicRES	j-ncic:RESType	A code identifying a state or other jurisdictional unit where a property registration was issued.
RegistrationJurisdictionCode.USPostalService	j-usps:USStateCodeType	A code identifying a state or other jurisdictional unit where a property registration was issued.

RegistrationJurisdictionCode.fips5-2Alpha	j-fips_5-2:USStateCodeType	A code identifying a state or other jurisdictional unit where a property registration was issued.
RegistrationJurisdictionCode.fips5-2Numeric	j-fips_5-2:USStateNumericCodeType	A code identifying a state or other jurisdictional unit where a property registration was issued.
RegistrationJurisdictionName	TextType	A name of a state or other jurisdictional area from which a property registration was issued.
RegistrationOutsideJurisdictionIndicator	j-xsd:boolean	True if a property item is found to be registered outside of an agency's immediate jurisdiction when processed, e.g., out-of-state driver's license; false otherwise.
RegistrationParty.Organization	OrganizationType extends SuperType	A person or organization to whom a registration is issued.
RegistrationParty.Person	PersonType extends SuperType	A person or organization to whom a registration is issued.
RegistrationProperty	PropertyType extends SuperType	A property item that is registered, such as a vehicle.
RegistrationStatus	StatusType extends SuperType	A status of a registration.
RehabilitationProgram	ProgramType extends SupervisionType	A program designed to improve a person physically. This may include drug rehabilitation, physical rehabilitation, or occupational rehabilitation.
RelativeLocation	RelativeLocationType extends SuperType	Details about how to reach a location relative to a starting point.
RelativeLocationDescriptionText	TextType	A complete description of how to reach a location from a starting point, e.g., "Drive 1 mile north of the Big Chicken"
RelativeLocationDirectionCode	DirectionCodeType extends SuperType	A code identifying a compass direction of the location from a reference point.
RelativeLocationDirectionText	TextType	A relative compass direction of a location or movement from a reference point, e.g., north, north-north-east, S, SW, WNW.
RelativeLocationDistanceText	TextType	A description of the distance of a location from a starting point, e.g., 1 mile.
RelativeLocationHeadingValue	RelativeLocationHeadingType extends SuperType	The compass heading of a direction from a reference location. The range is from 0 (inclusive) to 360 (exclusive).
RelativeLocationReferencePoint	LocationType extends SuperType	Details about a starting point used to reach a location. Can include details about the name, address, contact information, type, and other information.

Release	ReleaseType extends ActivityType	Details about a release or freeing of a person or property item from confinement, holding, or an obligation.
ReleaseFromLocation	LocationType extends SuperType	A location from which a person is released.
ReleaseIssuer.Organization	OrganizationType extends SuperType	A justice official or organization which authorizes a release.
ReleaseIssuer.Person	PersonType extends SuperType	A justice official or organization which authorizes a release.
ReleaseProperty	PropertyType extends SuperType	A property item which is released from holding.
ReleaseRecipient.Organization	OrganizationType extends SuperType	A person, justice official, or organization that receives custody or supervisory authority of a released person or object, e.g., a probation official, half-way house.
ReleaseRecipient.Person	PersonType extends SuperType	A person, justice official, or organization that receives custody or supervisory authority of a released person or object, e.g., a probation official, half-way house.
ReleaseSubject	SubjectType extends PersonType	A person who is released from confinement or an obligation.
ReleaseSupervisor.Organization	OrganizationType extends SuperType	A justice official or organization which currently has custody over a subject or property item.
ReleaseSupervisor.Person	PersonType extends SuperType	A justice official or organization which currently has custody over a subject or property item.
ReleaseToLocation	LocationType extends SuperType	A location to which a person is released.
Residence	ResidenceType extends LocationType	Details about the place in which a person lives.
ResidenceDescriptionText	TextType	A general description of a place in which a person lives.
ResidenceEndDate	j-xsd:date	A date a person stopped living at a residence.
ResidenceOccupancyTypeText	TextType	A person's type of occupancy of a residence, e.g., owns, rents.
ResidencePaymentAmount	AmountType extends decimal	An amount of money a person pays each payment period to live at a place of residence. This may include a mortgage payment amount or a rent amount.
ResidencePaymentPeriodText	TextType	An interval or period for which a person is required to make regular residence payments.
ResidenceStartDate	j-xsd:date	A date a person began living at a residence.

ResidenceTypeText	TextType	A type of place at which a person lives, e.g., house, apartment, homeless.
ResidentialStructure	StructureType extends PropertyType	A structure in which a person or persons live.
RiskReductionFacility	FacilityType extends OrganizationType	A facility other than a detention or correctional facility a subject may be remanded to as part of a condition set by a court or supervising agency. For example, Boot Camp, Halfway House, etc.
RiskReductionProgram	ProgramType extends SupervisionType	A program designed to lower the chance that a person does something illegal or unhealthy or is exposed to situations that may tempt illegal or unhealthy behavior.
SameAs	SuperType	A general equivalence between two object instances (they refer to the same thing).
Sanction	SanctionType extends ActivityType	Details about a sanction or penalty ordered for a subject by a judge or a supervising agency as a result of a disposition of a charge.
SanctionAdultSentenceIndicator	j-xsd:boolean	True if a sanction for an extended jurisdiction juvenile is part of an adult or a juvenile sentence; false otherwise.
SanctionCreditedObligation	ObligationType extends SuperType	An amount of money or time requirement of a sanction already paid.
SanctionCreditedTerm	TermType extends ActivityType	An amount of time of a sanction already completed.
SanctionDisciplinaryAction	DisciplinaryActionType extends ActivityType	A correction action that is assigned as part of a sanction. This may be enrolling in a risk reduction facility or program, for example.
SanctionFrequencyText	TextType	A frequency with which a sanction is to be met.
SanctionGroupingText	TextType	A way of grouping multiple sanctions. For example, consecutive, concurrent, combined, merged, etc.
SanctionIssuingAgency	OrganizationType extends SuperType	A court that sets a sanction.
SanctionJurisdictionalAgency	OrganizationType extends SuperType	A court that has jurisdiction over a sanction.
SanctionProgress	ProgressType extends ActivityType	A tracking of changes in a subject's progress toward fulfillment of the terms of a sanction.
SanctionRelatedChargeDispositionText	TextType	A final version of a disposed Charge. This may be the same or another Charge as the one to which the related Sanction applies.

SanctionRelatedSanctionID	IDType extends SuperType	A sanction identifier from related court case.
SanctionSentenceDefinitionIndicator	j-xsd:boolean	True if a sanction "defines" a sentence; false otherwise. For adults, any sanction of type fine, incarceration or restitution defines a sentence. For juveniles, any sanction may define a sentence.
SanctionSetDate	j-xsd:date	A date a sanction was set or ordered.
SanctionSetObligation	ObligationType extends SuperType	An amount of money or time requirement of a sanction that has been set.
SanctionSetTerm	TermType extends ActivityType	An amount of time of a sanction that has been set.
SanctionStayedObligation	ObligationType extends SuperType	An amount of money or time requirement of a sanction that is temporarily suspended.
SanctionStayedTerm	TermType extends ActivityType	An amount of time of a sanction that is temporarily suspended.
SanctionSuspendedObligation	ObligationType extends SuperType	An amount of money or time requirement of a sanction that is no longer required to be paid.
SanctionSuspendedTerm	TermType extends ActivityType	An amount of time of a sanction that is no longer required to be completed.
SanctionTypeText	TextType	A type of sanction, e.g., incarceration, fine, restitution, probation, community service, etc.
ScheduleActivityText	TextType	An activity scheduled for a day or time.
ScheduleDate	j-xsd:date	A date that is scheduled.
ScheduleDay	ScheduleDayType extends ActivityType	Details about a schedule on a day.
ScheduleDayEndTime	j-xsd:time	An ending time of a day on a schedule.
ScheduleDayStartTime	j-xsd:time	A start time of a day on a schedule.
SchedulePerson	PersonType extends SuperType	A person with the given schedule.
SearchWarrant	WarrantType extends CourtOrderType	An order signed by a judge authorizing a search of a place or a vehicle. The search warrant is issued for an address where things which may be evidence are to be found.
Security	SecurityType extends PropertyType	Details about a financial instrument such as cash, stock(s) or bond(s).
SecurityClassificationCurrent	ClassificationType extends SuperType	Details about the current classification of information.

SecurityClassificationDowngrade	ClassificationType extends SuperType	Details about downgrading the level of classification of information.
SecurityClassificationInitial	ClassificationType extends SuperType	Details about the original classification of information.
SecurityClassificationUpgrade	ClassificationType extends SuperType	Details about upgrading the level of classification of information.
SecurityCollectionEndDate	j-xsd:date	A date when the ability for a security owner to collect returns from a security expires.
SecurityCollectionStartDate	j-xsd:date	A date when a security owner may collect returns from a security.
SecurityControlText	TextType	A SCI control system or systems that may be applicable to a document, e.g., SI, TK, NONE.
SecurityDateSeriesCode	j-ncic:SDTType	A code identifying a security date or series year.
SecurityDateSeriesText	TextType	A security date or series year.
SecurityDeclassification	ClassificationType extends SuperType	Details about the declassification of information.
SecurityDenominationCode	j-ncic:DENType	A code identifying a value within a series of values reflecting the worth of a security note.
SecurityDenominationText	TextType	A value within a series of values reflecting the worth of a security note.
SecurityDisseminationText	TextType	Dissemination control markings as designated by CAPCO Classification Markings Register, e.g., NOFORN, ORCON, FOUO, SETTEE.
SecurityFGICode	j-iso_3166:CountryAlpha3CodeType	A code that identifies foreign government distribution information included in a United States controlled document.
SecurityFGIText	TextType	Foreign government distribution information or country codes included in a United States controlled document, e.g., "FGI, AUS, DEU", "FGI, DEU, GBR, NATO", "FGI".
SecurityForeignReleasabilityText	TextType	The foreign releasability of information.
SecurityIssuer.Organization	OrganizationType extends SuperType	A bank, agency, or other authority which issued a security to a person.
SecurityIssuer.Person	PersonType extends SuperType	A bank, agency, or other authority which issued a security to a person.
SecurityLevelCode	j-dod:SecurityLevelCodeType	A code identifying a level of security of information, e.g., personal, supplier proprietary.

SecurityLevelText	TextType	A level of security of information, e.g., personal, supplier proprietary.
SecurityMetadata	SecurityMetadataType extends SuperType	Describes security information and classification on information.
SecurityNonICMarkingsText	TextType	Non-Intelligence Community markings authorized for use by entities outside of the Intelligence Community as designated by CAPCO Classification Markings Register., e.g., SPECAT, SIOP-ESI, SENSITIVE INFORMATION, LIMDIS.
SecurityTypeCode	j-ncic:TYPSType	A code identifying a type of security.
Sentence	SentenceType extends ActivityType	Details about a punishment resulting from conviction of charges in a court case.
SentenceAggravatedIndicator	j-xsd:boolean	True if aggravating factors were considered during sentencing.
SentenceCharge	ChargeType extends SuperType	A specific charge in a court case resulting in a sentence.
SentenceCondition	ConditionType extends ActivityType	A description and duration of a sentence component.
SentenceConfinementCreditDayQuantity	QuantityType extends NumericType	Total presentencing days served credited towards sentence term.
SentenceConfinementCreditIndicator	j-xsd:boolean	True if any days served preceding the sentence will be applied to the sentence duration.
SentenceDeferredIndicator	j-xsd:boolean	True if the sentence has been deferred.
SentenceDeferredTerm	TermType extends ActivityType	Details about the deferred term.
SentenceDescriptionText	TextType	A description of the sentence being imposed, e.g., probation, incarceration, public service.
SentenceDetails	SentenceDetailsType extends SuperType	A specific description of the requirements of a sentence.
SentenceGroupingText	TextType	An order to how a sentence must be served, e.g., consecutively, concurrently, or both.
SentenceIssuer.Organization	OrganizationType extends SuperType	A person, court or other organization which issued a sentence.
SentenceIssuer.Person	PersonType extends SuperType	A person, court or other organization which issued a sentence.
SentenceModification	SentenceModificationType extends ActivityType	Details about a change made to a sentence.

SentenceModificationAggravatedIndicator	j-xsd:boolean	True if a sentence modification results in a harsher sentence than the original one; false otherwise.
SentenceModificationCharge	ChargeType extends SuperType	A charge for which the sentence was originally set.
SentenceModificationConfinementCreditDayText	j-xsd:integer	An amount of time a person is credited with spending in confinement.
SentenceModificationConfinementCreditIndicator	j-xsd:boolean	True if an offender has credit for already being confined; false otherwise.
SentenceModificationDismissalIndicator	j-xsd:boolean	True if a modification made to a sentence results in the charges being dismissed; false otherwise.
SentenceModificationDismissalRemainingCase	CaseType extends ActivityType	A case that a person is being tried for that is dismissed by a sentence modification.
SentenceModificationDismissalRemainingQuantity	j-xsd:nonNegativeInteger	A number of times a person charged with the same crime has been dismissed by a sentence modification.
SentenceModificationMitigatedIndicator	j-xsd:boolean	True if a sentence modification results in a lesser sentence than the original one; false otherwise.
SentenceModificationOriginalTerm	TermType extends ActivityType	An original length of a sentence.
SentenceModificationParoleIndicator	j-xsd:boolean	True if a modification made to a sentence results in the parole of the offender; false otherwise.
SentenceModificationParoleTerm	TermType extends ActivityType	A portion of a sentence that an offender is to spend on parole.
SentenceModificationProbation	SupervisionType extends ActivityType	A modification made to a sentence that results in the probation of the offender.
SentenceModificationProbationIndicator	j-xsd:boolean	True if a modification made to a sentence results in the probation of the offender; false otherwise.
SentenceModificationRestitutionIndicator	j-xsd:boolean	True if a modification made to a sentence results in the offender being assigned a restitution; false otherwise.
SentenceModificationSuspendedIndicator	j-xsd:boolean	True if a sentence modification results in a portion of a sentence being suspended; false otherwise.
SentenceModificationSuspendedTerm	TermType extends ActivityType	A portion of a sentence that is being suspended.
SentenceRegisterSexOffenderIndicator	j-xsd:boolean	True if sex offender registration is required.
SentenceSeverityLevel	SeverityLevelType extends SuperType	A severity level of a sentence.
SentenceSubject	SubjectType extends PersonType	A person who is being sentenced. Sometimes referred to as an offender.

SentenceSuspendedIndicator	j-xsd:boolean	True if the sentence has been suspended.
SentenceSuspendedTerm	TermType extends ActivityType	Details about the suspended term.
SentenceTerm	TermType extends ActivityType	A duration of a sentence. Specified as either a specific term in days-months-years or as a minimum - maximum range.
SentencingGuideline	SentencingGuidelineType extends SuperType	A sentencing guideline used for determining a sanction.
SentencingGuidelineChargeSeverityLevelText	TextType	A sentencing guideline severity level assigned to a charge by a judge or supervising agency.
SentencingGuidelineDepartureReasonText	TextType	A reason a judge departs from a sentencing guideline.
SentencingGuidelineDepartureTypeText	TextType	A type of departure from sentencing guidelines represented by a sentence for a charge. For example, disposition, duration.
SentencingGuidelineMonthsMaximumText	TextType	A maximum sentence, in months, called for by sentencing guidelines.
SentencingGuidelineMonthsMinimumText	TextType	A minimum sentence in months, outlined by sentencing guidelines, which can be imposed by a judge without indicating a reason for departure.
SentencingGuidelineRecommendationMonthsText	TextType	A recommended sentence, in months, called for by sentencing guidelines.
ServiceCall	ServiceCallType extends ActivityType	Details about a call for service received from a person alerting an authority of a situation.
ServiceCallArrivedDate	j-xsd:date	A date a response unit arrived at the scene designated by a call for service.
ServiceCallArrivedTime	j-xsd:time	A time a response unit arrived at the scene designated by a call for service.
ServiceCallAssignedUnit	OrganizationType extends SuperType	A response unit responsible for handling a call for service.
ServiceCallAssistingUnit	OrganizationType extends SuperType	A unit that assists the assigned response unit in handling a call for service.
ServiceCallClearanceText	TextType	A description that identifies the incident conditions or status when a response unit cleared or left the scene designated by a call for service.
ServiceCallClearedDate	j-xsd:date	A date when a response unit cleared or left the scene designated by a call for service.

ServiceCallClearedTime	j-xsd:time	A time when a response unit cleared or left the scene designated by a call for service.
ServiceCallDispatchedDate	j-xsd:date	A date a service call was received by a dispatcher.
ServiceCallDispatchedOfficial	EnforcementOfficialType extends PersonType	An official assigned specifically to handle a call for service.
ServiceCallDispatchedTime	j-xsd:time	A time a service call was received by a dispatcher.
ServiceCallDispatcher	PersonType extends SuperType	A person who determines the course of action to be taken in response to a call for service and sends out appropriate response units as necessary.
ServiceCallMechanismText	TextType	A way in which a call for service is received, e.g., 911, regular phone line, in person, mail, radio, visual, teletype.
ServiceCallOperator	PersonType extends SuperType	A person who receives a call for service.
ServiceCallOriginator	PersonType extends SuperType	A person who places a call for service.
ServiceCallResponseLocation	LocationType extends SuperType	A location where a response unit should be sent to handle a call for service.
ServiceCallResponsePerson	PersonType extends SuperType	A person who needs the assistance of a response unit from a call for service.
SeverityLevel	SeverityLevelType extends SuperType	Details about a sentencing guideline severity level assigned to a charge by a judge or supervising agency.
SeverityLevelAssignedDate	j-xsd:date	A date on which the severity level was assigned.
SeverityLevelAssignedJudge	JudicialOfficialType	A higher court judge assigned the severity level to the referenced charge.
SeverityLevelCriminalHistoryScoreText	TextType	A criminal history score that is assigned.
SeverityLevelDescriptionText	TextType	A narrative account of a severity level assigned to a charge.
SeverityLevelID	IDType extends SuperType	A unique identifier of a Severity Level. Valid values are: I, II, III, IV, V, VI, VII, VIII, IX, and X.
SeverityLevelIssuingAgency	OrganizationType extends SuperType	A supervising agency that assigned a severity level to a referenced charge.
Status	StatusType extends SuperType	A set of details about the condition or status of a person, activity, or object.
StatusDate	j-xsd:date	A date a status was set, effective, or reported.
StatusDescriptionText	TextType	A description of a condition or state of something or someone.

StatusIssuerID	IDType extends SuperType	An identifier of a person or organization which assigns a status.
StatusIssuerText	TextType	A name or code of a person or organization which assigns a status.
StatusText	TextType	A condition or state of something or someone.
StatusTime	j-xsd:time	A time a status was set, effective, or reported.
Statute	StatuteType extends SuperType	Details about a unique identifier of a law, rule, or ordinance within a jurisdiction.
StatuteCodeID	IDType extends SuperType	An identifier of a set of laws for a particular jurisdiction. Sometimes referred to as a code book, legal code, native state code, or law.
StatuteCodeSectionID	IDType extends SuperType	An identifier of a section or category within a code book.
StatuteCommentText	TextType	An additional note or comment about a statute.
StatuteDescriptionText	TextType	A description of a statute.
StatuteEnactmentDate	j-xsd:date	A date a statute was enacted and came into effect.
StatuteJurisdiction	JurisdictionType	Details about an area in which a statute applies, e.g., city, state, country.
StatuteKeywordText	TextType	A brief description of a Statute which makes use of "catchwords." This can be used as an aid in finding a correct Statute.
StatuteLevelText	TextType	A level of crime a statute applies to, e.g., Misdemeanor, Gross Misdemeanor, Felony.
StatuteOffenseCode	j-ucr:OffenseCodeType	A code that identifies a criminal offense within a code book. Sometimes referred to as offense code, ordinance number.
StatuteOffenseCode.Minnesota	j-mn_off:OffenseCodeType	A code that identifies a criminal offense within a code book. Sometimes referred to as offense code, ordinance number.
StatuteOffenseEnhancibleIndicator	j-xsd:boolean	True if a statute refers to an offense that may be made more serious due to circumstances related to the incident; false otherwise.
StatuteOffenseID	IDType extends SuperType	A number or code that identifies a criminal offense within a code book. Sometimes referred to as offense code, ordinance number.
StatuteRepealDate	j-xsd:date	A date a statute was repealed and no longer applied.

StatuteStatus	StatusType extends SuperType	A current status of a statute. Includes Repealed, Renumbered, Redefined, etc.
StatuteText	TextType	The full text of a statute or law.
StatuteTypeCode	j-mn_off:StatuteTypeCodeType	A code identifying a type of statute, e.g., Criminal, Procedure.
StatuteTypeText	TextType	A type of statute, e.g., Criminal, Procedure.
Street	StreetType extends SuperType	Details about an intersecting street.
StreetExtensionText	TextType	Any additional parts of a street name that follows the street type and post directional.
StreetFullText	TextType	A complete street reference, e.g., "123 Main Street NW".
StreetName	TextType	A name of a street.
StreetNumberText	TextType	A number that identifies a particular unit or location within a street.
StreetPostdirectionalText	TextType	A direction that appears after a street name.
StreetPredirectionalText	TextType	A direction that appears before a street name.
StreetTypeText	TextType	A type of street, e.g., Street, Boulevard, Avenue, Highway, etc.
Structure	StructureType extends PropertyType	Details about a building or construction.
StructureCommercialIndicator	j-xsd:boolean	True if structure is commercial; false is a structure is residential.
StructureContainsProperty	PropertyType extends SuperType	The structure currently has the indicated property item in or on it.
StructureGarageForVehicle	VehicleType extends VehicleBasicsType	Indicates that the vehicle is currently or routinely garaged in the structure.
StructureLocation	LocationType extends SuperType	A specific location of a structure.
StructureOccupant.Organization	OrganizationType extends SuperType	Indicates that the structure is occupied, at least in part, by the indicated organization or person.
StructureOccupant.Person	PersonType extends SuperType	Indicates that the structure is occupied, at least in part, by the indicated organization or person.
StructureOrganization	OrganizationType extends SuperType	An organization that uses a structure.
StructureResident	PersonType extends SuperType	Indicates that the person is one of the residents of the indicated structure.

StructureWorker	PersonType extends SuperType	Indicates that the person works in the indicated structure.
SubExhibit	ExhibitType extends SuperType	A part or portion of an exhibit.
Subject	SubjectType extends PersonType	A person who is involved or suspected of being involved in an incident or criminal activity. This person may be the focus of an investigation or legal process, but is not necessarily the sole or primary focus. A weapon a subject is carrying.
SubjectArmedWeapon	PropertyType extends SuperType	A weapon a subject is carrying.
SubjectCautionInformationCaveat	TextType	Details regarding cautionary messages about an individual.
SubjectCautionInformationCode	j-ncic:CMCType	A code identifying cautionary information about a subject.
SubjectCriminalOrganizationInvolvementCode	j-ncic:ECRTType	A code identifying a subject's involvement in a criminal organization such as a gang or terrorist group.
SubjectCriminalTraitDetails	CriminalTraitDetailsType extends SuperType	A set of identifying characteristics a subject has with regard to illegal activity.
SubjectDetainmentLocation	LocationType extends SuperType	The specific address of the facility associated with the incarceration. This association is used when there is a specific address for the facility.
SubjectDisciplinaryAction	DisciplinaryActionType extends ActivityType	A disciplinary action which a subject is undergoing.
SubjectID	IDType extends SuperType	An assigned number or string that identifies a subject.
SubjectInvolvementCriminalOrganization	CriminalOrganizationType extends OrganizationType	A criminal organization with which a subject is known or suspected of being involved.
SubjectInvolvementPerson	PersonType extends SuperType	A person with whom a subject is known or suspected of being involved.
SubjectOffenderNoticeCaveat	TextType	Details about other cautions/caveats/notices related to an offender.
SubjectStatus	StatusType extends SuperType	A general status of a subject, e.g., arrested, charged, paroled.
SubjectSupervision	SupervisionType extends ActivityType	An incarceration, detention, or other form of supervision a subject is currently undergoing.
SubjectWarrantTypeDescriptionText	TextType	A description of a warrant out for a subject's arrest.
Submission	SubmissionType extends ActivityType	Details about a submission of a document to a recipient.

SubmissionDocument	DocumentType extends SuperType	A document that is submitted.
SubmissionFee	ObligationType extends SuperType	A fee or price required to submit a document.
SubmissionReceivedDate	j-xsd:date	A date the receiving party received the document.
SubmissionReceivedTime	j-xsd:time	A time the receiving party received the document.
SubmissionReceiver.Organization	OrganizationType extends SuperType	A person or organization which receives a document.
SubmissionReceiver.Person	PersonType extends SuperType	A person or organization which receives a document.
SubmissionSubmittedDate	j-xsd:date	A date a document left the control of the submitting party.
SubmissionSubmittedTime	j-xsd:time	A time a document left the control of the submitting party.
SubmissionSubmitter.Organization	OrganizationType extends SuperType	A person or organization which submits a document.
SubmissionSubmitter.Person	PersonType extends SuperType	A person or organization which submits a document.
Summons	CourtOrderType extends ActivityType	A written notification warning a person to appear in court at a specific date and time.
SuperObject	SuperType	The root object in the inheritance hierarchy.
Supervision	SupervisionType extends ActivityType	Details about an act of officially overseeing, supervising, or keeping track in some capacity of a person. Supervision may or may not involve incarceration, conditions, and treatment.
SupervisionAgency	OrganizationType extends SuperType	An agency responsible for supervising a subject.
SupervisionAreaID	IDType extends SuperType	An identification of an area or block within a supervision facility a subject is assigned.
SupervisionAssessment	AssessmentType extends ActivityType	An assessment of a person in or entering supervision.
SupervisionAssignedTerm	TermType extends ActivityType	Details about the duration of time a person has been assigned to be under supervision.
SupervisionBedID	IDType extends SuperType	An identification of a bed within a supervision facility cell a subject is assigned.
SupervisionBoardActionDocument	DocumentType extends SuperType	A form specifying an action to take that is filed by the board of a supervisory agency. Sometimes referred to as board action form, baf.

SupervisionCautionText	TextType	A warning, caution, or risk associated with supervising a person.
SupervisionCellID	IDType extends SuperType	An identification of a cell housing within a supervision facility a subject is assigned.
SupervisionClassificationDate	j-xsd:date	A date a person under supervision is classified.
SupervisionCondition	ConditionType extends ActivityType	A condition that must be met for a person to remain in supervision.
SupervisionConditionalRelease	ConditionalReleaseType extends ReleaseType	A provisional release of a subject that requires defined conditions to be met to prevent the supervision from being reinstated.
SupervisionCurrentIndicator	j-xsd:boolean	True if a subject is currently under supervision; false otherwise.
SupervisionCustodyStatus	StatusType extends SuperType	A status of the custody of a person under supervision.
SupervisionCustodyTransfer	CustodyTransferType extends ActivityType	A transfer of a subject from the supervision of one facility, agency, or official to the supervision of another.
SupervisionDisciplinaryAction	DisciplinaryActionType extends ActivityType	A self-improving or restitutorial activity that must or may be performed by a person under supervision.
SupervisionFacility	FacilityType extends OrganizationType	A facility at which a subject is being supervised.
SupervisionFee	ObligationType extends SuperType	A description of a charge assigned to a person under supervision.
SupervisionFelonyOffenseIndicator	j-xsd:boolean	True if a subject is incarcerated for a felony offense; false if a person is incarcerated for a misdemeanor.
SupervisionGoodDaysCreditText	TextType	A number a days a subject is credited spending with good behavior under supervision.
SupervisionIntensiveIndicator	j-xsd:boolean	True if a subject requires more effort in supervising than normal; false otherwise.
SupervisionIsolationIndicator	j-xsd:boolean	True if a subject should be kept apart from other members being supervised; false otherwise.
SupervisionJurisdiction	JurisdictionType	An area or location within which a person must remain in while under supervision.
SupervisionLevelCode	j-ut_offender:SupervisionLevelCodeT	A code that identifies the basic level of supervision required by a person: intensive, normal, minimal, none.
SupervisionLevelText	TextType	A level of supervision required by a person.
SupervisionMandatoryIndicator	j-xsd:boolean	True if a supervision of a person is required; false if a supervision is optional.

SupervisionModifiedTerm	TermType extends ActivityType	Modified or changed details about the duration of time a person is assigned to spend under supervision.
SupervisionOfficial	EnforcementOfficialType extends PersonType	An official who is responsible for supervising a subject.
SupervisionOtherLocation	LocationType extends SuperType	A location other than a facility at which a person under supervision is located.
SupervisionReinstatementDate	j-xsd:date	A date that a supervision is reinstated.
SupervisionRelease	ReleaseType extends ActivityType	A complete and unrestricted release of a subject from a supervision.
SupervisionRestriction	SupervisionRestrictionType extends ActivityType	Details about a restriction on a supervised person.
SupervisionRestrictionBehaviorText	TextType	A behavior a supervised person is restricted from doing, e.g., no drugs or alcohol.
SupervisionRestrictionCode	j-ut_offender:SupervisionRestrictionC	A code identifying a supervision restriction.
SupervisionRestrictionLocation	LocationType extends SuperType	A location a supervised person is restricted from going to, e.g., a restricted address.
SupervisionRestrictionPerson	PersonType extends SuperType	A person a supervised person is restricted from involvement, e.g., a no-contact person.
SupervisionSelfImposedIndicator	j-xsd:boolean	True if a person voluntarily agreed to supervision; false otherwise.
SupervisionServedTerm	TermType extends ActivityType	Details about the duration of time a person has actually spent under supervision.
SupervisionSubject	SubjectType extends PersonType	A person who is being supervised.
SupervisionSubjectResponsibilityText	TextType	A job or responsibility a subject holds within a supervision facility.
SupervisionSubjectStatus	StatusType extends SuperType	A status of a person under supervision.
SupervisionViolationText	TextType	A violation of a condition or rule of a person while under supervision.
SupervisionVisitation	VisitationType extends ActivityType	A visit from a person to a subject.
Suspect	SubjectType extends PersonType	A person suspected of illegal activity.
Target	TargetType extends SuperType	Details about a target or object against which an action is taken.

TargetDescriptionText	TextType	A description of a target or object for which an action taken.
TargetLocation	LocationType extends SuperType	A location that is a target of an action.
TargetName	TextType	A name of a target or object for which an action is taken.
TargetOrganization	OrganizationType extends SuperType	An organization that is a target of an action.
TargetPerson	PersonType extends SuperType	A person that is a target of an action.
TargetProperty	PropertyType extends SuperType	A property item that is a target of an action.
TargetReasonText	TextType	An explanation of why a target was chosen for action.
TargetTypeText	TextType	A type of target or object for which an action is taken.
TelephoneAreaCodeID	j-xsd:string	A dialing code for a state or province for phone numbers in the USA, Canada, Mexico, and the Caribbean.
TelephoneCityCodeID	j-xsd:string	A dialing code for a city.
TelephoneCountryCodeID	j-xsd:string	An international dialing code for a country.
TelephoneExchangeID	j-xsd:string	The first three digits of a base telephone number. Usually represents a central telephone switch.
TelephoneNumber	TelephoneNumberType extends SuperType	Details about a number to be dialed to reach a contact.
TelephoneNumberCommentText	TextType	An additional comment about a telephone number.
TelephoneNumberFullID	j-xsd:string	A full length telephone identifier to be used when a number cannot be broken down into its subcomponents.
TelephoneSubscriberID	j-xsd:string	The last four digits of a base telephone number. Identifies the individual circuit within an exchange.
TelephoneSuffixID	j-xsd:string	Additional numbers to be entered to direct a call to the appropriate place. Includes extensions, answering system navigation codes, and PINs.
Term	TermType extends ActivityType	Details about a duration length specified as either a specific term in days-months-years or as a minimum - maximum range.
TermDuration	j-xsd:duration	A specific range or duration of a term.
TermMaximumDuration	j-xsd:duration	A maximum range or duration for a term.
TermMinimumDuration	j-xsd:duration	A minimum range or duration for a term.
Text	TextType	A representation of a string value.

TimeMeasure	TimeMeasureType extends MeasureType	A representation of the measurement of an amount of time.
TimeObligation	TimeObligationType extends ObligationType	An obligation or requirement on a person's time, which may be associated with a disciplinary action, e.g., community service.
TimeObligationDueDuration	j-xsd:duration	An amount of time of a time obligation that has not been spent.
TimeObligationPaidDuration	j-xsd:duration	An amount of time that has been spent to fulfill a time obligation.
TimeObligationTotalDuration	j-xsd:duration	A total amount of time that must be spend in order to meet an obligation, e.g., community service.
TitleDuplicateQuantity	j-xsd:nonNegativeInteger	A total number of title documents issued where the titling information is unchanged (may be called duplicate or replacement, depending on the state) by the current titling jurisdiction (e.g., because a title was lost).
TitleID	IDType extends SuperType	A number used to uniquely identify a certificate of title to a property item. Assigned by a titling jurisdiction authority.
TitleIssueDate	j-xsd:date	A date on which a jurisdictions titling authority issued a title to the owner of the property item.
TitleIssuingAuthorityName	TextType	An authority which issued a title.
TitleLienIndicator	j-xsd:boolean	True if a lien exists on the titled property or vehicle. A value of true indicates the property item can be used as a payment to the owners debtors.
TitleParty.Organization	OrganizationType extends SuperType	A person or organization to whom a title is issued.
TitleParty.Person	PersonType extends SuperType	A person or organization to whom a title is issued.
TitleProperty	PropertyType extends SuperType	A property item such as a vehicle for which a title is issued.
TitleReplacesTitle	PropertyTitleType extends SuperType	A title issued as a replacement to another title.
TitleStatusCode	j-ansi_d20:TitleStatusCodeType	A code identifying a most recent known status recorded for a title.
TitleStatusText	TextType	A most recent known status recorded for a title.
TitleTypeText	TextType	A type of title issued.
TowingCompany	OrganizationType extends SuperType	A company that tows vehicles. Sometimes referred to as wreckers.

UpperBound	TextType	An allowable upper bound on a numeric point estimate.
UTMCoordinate	UTMCoordinateType extends SuperType	A coordinate from the Universal Transverse Mercator (UTM) Coordinate System, which is a projected rectangular coordinate system that divides the world into 60 north and south zones, each zone six degrees wide.
UTMCoordinateID	IDType extends SuperType	A complete Universal Transverse Mercator coordinate value. The value is specified as the concatenation of UTMGridZoneID, UTMGridZoneSquareID, UTMEastingValue, and UTMNorthingValue.
UTMDatumID	IDType extends SuperType	Identifies a datum standard for the coordinates. The datum standard identifies the spatial reference system - the set of numbers that represent the size and shape of the Earth.
UTMEastingValue	j-xsd:integer	A distance east within a UTM zone. The precision of the value is based on the number of digits. Has the same number of digits as UTMNorthingValue.
UTMGridZoneID	IDType extends SuperType	A unique alphanumeric identifier of a UTM grid zone. Also known as Grid Zone Designator, GZD.
UTMGridZoneSquareID	IDType extends SuperType	A two-letter pair that identifies a specific 100,000 meter squared region within a UTM grid zone.
UTMNorthingValue	j-xsd:integer	A distance north within a UTM zone. The precision of the value is based on the number of digits. Has the same number of digits as UTMEastingValue.
Vehicle	VehicleType extends VehicleBasicsType	Details about a motor-driven conveyance designed to carry its operator, passengers, and cargo, including trailers, and excepting boats.
VehicleAxleQuantity	j-xsd:nonNegativeInteger	A count of common axles of rotation of one or more wheels of a vehicle, whether power driven or freely rotating.
VehicleBasics	VehicleBasicsType extends PropertyType	Details about a vehicle, boat, aircraft, or other object used to provide a physical mode of transportation
VehicleBrand	VehicleBrandType extends SuperType	A brand issued to a vehicle.
VehicleBrandCode	j-ansi_d20:BrandCodeType	A code providing information about the brand applied to the title or odometer.
VehicleBrandDamagePercentageTypeCode	j-ansi_d20:BrandDamagePercentage	An indicator of whether the Percentage of Damage is the actual value applied to a specific vehicle or is the threshold level applied by a state.

VehicleBrandDamagePercentageTypeText	TextType	An indicator of whether the Percentage of Damage is the actual value applied to a specific vehicle or is the threshold level applied by a state.
VehicleBrandDate	j-xsd:date	A date a brand was applied or obtained. If the brander applying the brand is a titling jurisdiction, this field represents the date the brand was applied. Otherwise (the brander is either an insurance carrier, junk yard, or salvage yard), this field represents the date obtained.
VehicleBrander	VehicleBranderType extends OrganizationType	An organization that brands a vehicle.
VehicleBrandSalvagePercentage	PercentageType extends SuperType	A percentage of damage (in terms of the extent that the fair salvage value plus the cost of repairing the vehicle for legal operation exceeds the fair market value of the vehicle prior to the incident causing the damage) a vehicle must sustain to be branded as 'Salvage'.
VehicleBrandText	TextType	A brand applied to the vehicle title or odometer.
VehicleBrandVehicleDispositionCode	j-ansi_d20:BrandVehicleDispositionCode	A code identifying the disposition of the vehicle as documented by the junk yard or salvage yard.
VehicleBrandVehicleDispositionText	TextType	A disposition of the vehicle as documented by the junk yard or salvage yard.
VehicleBrandVehicleSourceName	TextType	A name of the individual or organization from whom the (insurance carrier, junk yard or salvage yard) brander obtained the vehicle.
VehicleCargoText	TextType	Goods or cargo that is transported by a vehicle.
VehicleColorInteriorText	TextType	A color of the interior of a vehicle.
VehicleColorPrimaryCode	j-ncic:VCOType	A code identifying a single, upper-most, front-most, or majority color of a vehicle.
VehicleColorPrimaryText	TextType	A single, upper-most, front-most, or majority color of a vehicle.
VehicleColorSecondaryCode	j-ncic:VCOType	A code identifying the lower-most or rear-most color of a two-tone vehicle or the lesser color of a multi-colored vehicle.
VehicleColorSecondaryText	TextType	A lower-most or rear-most color of a two-tone vehicle or a lesser color of a multi-colored vehicle.
VehicleCurrentWeightMeasure	WeightMeasureType extends MeasureType	An observed, estimated, or measured weight of the conveyance.
VehicleDoorQuantity	j-xsd:nonNegativeInteger	A number of doors of a vehicle.

VehicleEmissionInspection	VehicleEmissionInspectionType extends VehicleInspectionType	Details about an inspection of a vehicle that tests if the emissions exceed the legal limit.
VehicleEmissionInspectionQuantity	j-xsd:nonNegativeInteger	A number of times a vehicle goes through an emissions inspection.
VehicleEngineCylinderQuantity	j-xsd:nonNegativeInteger	A count of the cylinders contained in the engine of a vehicle. If the vehicle has a rotary engine, a value of '99' is used.
VehicleEngineDisplacementMeasure	VehicleEngineDisplacementMeasureType extends MeasureType	The engine displacement of a vehicle.
VehicleEngineHorsepowerQuantity	j-xsd:integer	The engine horsepower of a vehicle.
VehicleEngineID	IDType extends SuperType	An identifier stamped on an engine by a manufacturer.
VehicleEnginePowerDisplacementText	EnginePowerDisplacementType extends SuperType	An engine power or displacement of a vehicle.
VehicleEngineQuantity	j-xsd:nonNegativeInteger	A number of engines on a vehicle.
VehicleFirstSoldYearDate	j-xsd:gYear	A calendar year in which a vehicle was first sold.
VehicleFuelTypeCode	j-ansi_d20:VehicleFuelTypeCodeType	A code that identifies a type of fuel or motive power used to propel a vehicle.
VehicleFuelTypeText	TextType	A type of fuel or motive power used to propel a vehicle.
VehicleGarage	StructureType extends PropertyType	Indicates that the vehicle is currently or routinely garaged in the indicated structure.
VehicleGarageIndicator	j-xsd:boolean	True if a vehicle is normally stored in a garage; false otherwise.
VehicleGrossLadenSumWeightMeasure	WeightMeasureType extends MeasureType	A sum of values specified by the manufacturer(s) for a truck tractor or trailer for the units that make up a combination. In the absence of a value specified by the manufacturer, an estimate of the gross vehicle weight of a fully loaded unit may be submitted.
VehicleGrossLadenUnitWeightMeasure	WeightMeasureType extends MeasureType	A value specified by the manufacturer for a single unit truck, truck tractor, or trailer. In the absence of a value specified by the manufacturer, an estimate of the gross vehicle weight of a fully loaded unit may be submitted.

VehicleID	DrivingJurisdictionAuthorityIDType extends IDType	A unique combination of alphanumeric characters that identifies a specific vehicle. A vehicle identification number is normally imprinted by the manufacturer and attached to the vehicle in specific locations, but is occasionally assigned by titling or registration agencies. Sometimes referred to as a VIN, VIN number.
VehicleInspection	VehicleInspectionType extends ActivityType	Details about an Inspection refers to a safety, emissions, or type of inspection which may be required by a DMV prerequisite to vehicle registration. Inspection data is recorded by a DMV.
VehicleInspectionAddress	AddressType extends SuperType	Address details for an inspection facility.
VehicleInspectionEmissionCertificationID	IDType extends SuperType	A unique identifier that appears on an emissions certificate, e.g., inspection smog certificate.
VehicleInspectionEmissionPassIndicator	j-xsd:boolean	True if the emission readings of a vehicle passed an emission inspection; false if the readings failed the inspection.
VehicleInspectionInspectorID	IDType extends SuperType	A jurisdiction-assigned code identifying the person or station that performed the emissions inspection.
VehicleInspectionJurisdictionAuthorityCode	j-ansi_d20:JurisdictionAuthorityCode1	A code of the authority which has jurisdiction over the location where the inspection is performed.
VehicleInspectionJurisdictionAuthorityText	TextType	A name of the authority which has jurisdiction over the location where the inspection is performed.
VehicleInspectionSafetyPassIndicator	j-xsd:boolean	True if a vehicle passed a safety inspection; false if the vehicle failed the safety inspection.
VehicleInspectionSmogCertificateCode	j-ansi_d20:SmogCertificateCodeType	A code that specifies whether or not the vehicle has a current smog certificate
VehicleInspectionStationID	IDType extends SuperType	A station number performing the inspection.
VehicleInspectionTestTypeText	TextType	A type of test used to conduct an inspection.
VehicleInvoiceDate	j-xsd:date	A date on which the vehicle was invoiced by the manufacturer to the purchaser.
VehicleInvoiceID	IDType extends SuperType	A manufacturer-assigned number affixed to the paperwork when the manufacturer ships the vehicle.
VehicleLeaseIndicator	j-xsd:boolean	True if a vehicle is leased; false otherwise.
VehicleLicensePlateID	IDType extends SuperType	License plate associated with a vehicle

VehicleMakeCode	j-ncic:VMAType	A code identifying the manufacturer of a vehicle.
VehicleMaximumLoadWeightMeasure	WeightMeasureType extends MeasureType	A maximum load weight intended for the vehicle to transport, assigned at the point of manufacture. It is normally known as the Gross Vehicle Weight Rating (GVWR). It is applied to pickups, single unit trucks and trailers.
VehicleModelCode	j-ncic:VMOType	A code identifying the specific design or type of vehicle made by a manufacturer. Sometimes referred to as the series model.
VehicleModelCodeText	TextType	A code denoting a family of vehicles within a vehicle make which has a degree of similarity in construction, such as body, chassis, etc. The field does not necessarily contain a standard code; it may contain a value provided by the originator (the manufacturer) of the field.
VehicleModelYearDate	j-xsd:gYear	A year which is assigned to a vehicle by the manufacturer.
VehicleMSRPAmount	AmountType extends decimal	A manufacturer's suggested retail price of a vehicle. Includes the manufacturer-installed standard equipment and suggested delivery and handling, excluding transportation, state, and local taxes.
VehicleOdometerReadingMeasure	OdometerReadingMeasureType extends MeasureType	A reading of a vehicle odometer to the nearest mile or kilometer.
VehicleOwnershipTypeText	TextType	A type of ownership of a vehicle, e.g., owned, rented, financed.
VehiclePaperMCOIssuedIndicator	j-xsd:boolean	True if a paper copy of the manufacturers certificate of origin was sent from the manufacturer to the purchaser of the vehicle; false otherwise.
VehiclePart	PropertyType extends SuperType	Details about a part or component of a vehicle.
VehiclePartBrandCode	j-ncic:BRAType	A code identifying a brand name or manufacturer name of a vehicle part.
VehiclePartBrandName	TextType	A brand name or manufacturer name of a vehicle part.
VehiclePartCategoryCode	j-ncic:CATType	A code identifying a category of a vehicle part.
VehiclePartCategoryText	TextType	A category of a vehicle part.
VehiclePartDescriptionText	TextType	A description of a vehicle part.
VehiclePartID	IDType extends SuperType	An identifier assigned to a vehicle part.

VehiclePassengerSafeQuantity	j-xsd:integer	The total safe passenger capacity in a vehicle, accounting for both number of seats and standing room.
VehicleRegistration	VehicleRegistrationType extends PropertyRegistrationType	Details about a registration of a vehicle.
VehicleRegistrationDecal	DecalType extends SuperType	Details about a sticker attached to a permanent registration plate on a vehicle when it is renewed for the current year.
VehicleRegistrationGrossWeightMeasure	WeightMeasureType extends MeasureType	An unladen weight of a vehicle (e.g., single-unit truck, truck combination) plus the weight of the maximum load for which vehicle registration fees have been paid within a particular jurisdiction.
VehicleRegistrationLocation	LocationType extends SuperType	A location where a vehicle is registered.
VehicleRegistrationPermenantIndicator	j-xsd:boolean	True if a registration for a vehicle is permanent; false if a registration is temporary.
VehicleRegistrationPlateBackgroundText	TextType	A background image and/or colors of a vehicle license plate.
VehicleRegistrationPlateColorCode	j-ansi_d20:RegistrationPlateColorCode	A code identifying a color of a vehicle registration plate or license plate.
VehicleRegistrationPlateColorText	TextType	A color of a vehicle registration plate or license plate.
VehicleRegistrationPlateID	IDType extends SuperType	A number on a metal plate fixed to a vehicle. The purpose of a license plate number is to identify uniquely each vehicle in a state.
VehicleRegistrationPlateTypeCode	j-ncic:LITType	A code identifying a type of registration plate or license plate of a vehicle.
VehicleRegistrationPlateTypeText	TextType	A type of registration plate or license plate of a vehicle.
VehicleRegistrationStatus	StatusType extends SuperType	A status of a vehicle registration.
VehicleRegistrationStatusCode	j-ansi_d20:RegistrationStatusCodeType	A code identifying the most recent activity recorded for a registration.
VehicleRegistrationStatusDetailCode	j-ansi_d20:RegistrationStatusDetailCode	A code describing additional details about a registration status.
VehicleRegistrationStatusDetailText	TextType	Additional details about a registration status.
VehicleRentalIndicator	j-xsd:boolean	True if a vehicle is rented; false otherwise.
VehicleSafetyInspection	VehicleSafetyInspectionType extends VehicleInspectionType	Details about an inspection of the safety of a vehicle.

VehicleSalesTaxPercentage	PercentageType extends SuperType	A tax rate as a percentage used for computing the sales tax on the purchase of a vehicle or vessel.
VehicleSeatingQuantity	j-xsd:nonNegativeInteger	A number of seats available for passengers (including the operator) in a vehicle.
VehicleShipDate	j-xsd:date	A date on which the vehicle was shipped by the manufacturer to the purchaser.
VehicleStyleCode	j-ncic:VSTType	A code identifying the style of a vehicle.
VehicleTaxableAmount	AmountType extends decimal	A monetary amount used as the tax basis for a vehicle
VehicleTitle	VehicleTitleType extends PropertyTitleType	Details about the ownership and purchase of a vehicle.
VehicleTitleDocumentTypeCode	j-ansi_d20:VehicleTitleDocumentType	A code that identifies the type or kind of an individual title document.
VehicleTitlePurchaseDate	j-xsd:date	A date a current owner purchased a vehicle.
VehicleTitlePurchasePriceAmount	AmountType extends decimal	A price a current owner paid to purchase a vehicle.
VehicleTitleSalesTaxAmount	AmountType extends decimal	A sales tax charged on a purchase of a vehicle.
VehicleTitleSalesTaxPercentage	PercentageType extends SuperType	A tax rate used for computing sales tax on a vehicle.
VehicleTitleTaxableValue	PropertyValueType extends SuperType	A dollar value used to compute the taxes on a vehicle.
VehicleTowedIndicator	j-xsd:boolean	True if vehicle is towed; false otherwise.
VehicleTower	OrganizationType extends SuperType	An organization (towing company) that tows a vehicle.
VehicleTransmissionTypeCode	j-ansi_d20:VehicleTransmissionType	A code identifying a type of transmission unit in a vehicle.
VehicleTransmissionTypeText	TextType	A type of transmission unit in a vehicle
VehicleUnladenWeightMeasure	WeightMeasureType extends MeasureType	A weight of the vehicle fully equipped for service, not including the weight of the payload (e.g., empty weight). The unladen weight is Sometimes referred to as the scale weight.
VehicleUseCode	j-ansi_d20:VehicleUseCodeType	A code identifying a way a vehicle is used.
VehicleUseText	TextType	A way a vehicle is used.
VehicleVINAText	TextType	A combination of vehicle make and model, derived from Polk's VINA software.
VehicleWantedIndicator	j-xsd:boolean	True if a vehicle is being searched for by law enforcement; false otherwise.

Verdict	VerdictType extends ActivityType	Details about a finding related to a charge. For example, Guilty, Not Guilty, or Not Guilty By Reason Of Insanity Or Mental Illness for adults or Proven Delinquent or Not Proven Delinquent for juveniles.
VerdictDate	j-xsd:date	A date a verdict was given.
VerdictDescriptionText	TextType	A description of a verdict. For example, Guilty, Not Guilty, Proven Delinquent, Not Proven Delinquent, etc.
VerdictDispositionDate	j-xsd:date	A date of a verdict disposition.
VerdictDispositionName	TextType	A name of a disposition of a verdict. For example, Judgement, Pardon, Expunge, etc.
VerdictIssuingCourt	CourtType extends OrganizationType	A court which issued a verdict.
VerdictIssuingJudge	JudicialOfficialType	A judge which issued a verdict.
VerdictIssuingJudgeIndicator	j-xsd:boolean	True if a verdict was issued by a judge or a jury; false otherwise.
VerdictSubject	SubjectType extends PersonType	A person who received a verdict.
Victim.Organization	OrganizationType extends SuperType	Details about a person, organization, or other entity who suffers injury, loss, or death as a result of an incident. This is the object of a crime or tort.
Victim.Person	PersonType extends SuperType	Details about a person, organization, or other entity who suffers injury, loss, or death as a result of an incident. This is the object of a crime or tort.
Victim.Property	PropertyType extends SuperType	Details about a person, organization, or other entity who suffers injury, loss, or death as a result of an incident. This is the object of a crime or tort.
VictimAffectedProperty	PropertyType extends SuperType	Details about a victims property that was stolen or damaged.
VictimDispositionText	TextType	Describes what happens to the victim after the incident, e.g., went home, went to the hospital.
VictimEntity	VictimType extends SuperType	Details about a person, organization, or other entity who suffers injury, loss, or death as a result of an incident. This is the object of a crime or tort.
VictimID	IDType extends SuperType	A number or string identifying a victim.
VictimInjury	InjuryType extends SuperType	Details about an injury received by a victim due to an incident.

VictimMedicalTreatmentRequiredIndicator	j-xsd:boolean	True if a victim needed medical treatment after an incident.
VictimOffenseChargeCode	j-ucr:OffenseCodeType	A code identifying a charge representing an offense committed against a person.
VictimOffenseChargeText	TextType	A charge representing an offense committed against a person.
VictimSeeksProsecutionIndicator	j-xsd:boolean	True if a victim wants the alleged suspect prosecuted in a court of law.
VictimTypeCode	j-nibrs:VictimTypeCodeType	A code identifying a type of victim an offense was committed against.
VictimTypeText	TextType	A type of victim an offense was committed against.
Violation	IncidentType extends ActivityType	A non-conformance with a rule, law, or condition.
Visitation	VisitationType extends ActivityType	Details about a record of a person visiting a person under restricted access. This could be a family member visiting an incarcerated person, a non-custodial parent visiting a child.
VisitationPurposeText	TextType	A purpose or reason for a visit.
VisitationRestrictedAccessPerson	PersonType extends SuperType	A person under restricted access who receives a visit.
VisitationRestrictedAccessReasonText	TextType	A reason why a person is under restricted access to a visitor.
VisitationSupervisingOfficial.Enforcement	EnforcementOfficialType extends PersonType	An official who supervised a visit.
VisitationSupervisingOfficial.Judicial	JudicialOfficialType	An official who supervised a visit.
VisitationVisitor	PersonType extends SuperType	A person who visits a person under restricted access.
VisitationVisitorRelationshipText	TextType	A relationship of a visitor to a restricted access person.
Warrant	WarrantType extends CourtOrderType	An authorization for an enforcement official to perform a specified action such as arresting a person or searching a residence.
WarrantAppearanceBail	BailType extends ActivityType	Details about a monetary condition placed on a person to ensure appearance in court.
WarrantAppearanceBailForfeitText	TextType	A reason an appearance bond was forfeited in connection to a warrant.
WarrantExtraditionLimitationCode	j-ncic:EXLType	A code identifying the type of limitation placed on the extradition of a subject from an area outside the immediate jurisdiction of the issuing court.

WarrantExtraditionLimitationText	TextType	Limitations place on the extradition of a subject from an area outside the immediate jurisdiction of the issuing court.
WarrantExtraditionStateName	TextType	A state an arrest warrant specifies that a subject is to be extradited from.
WarrantFurtherProcessingText	TextType	An area a warrant went to for further processing or service, e.g., marshal, federal.
WarrantLevelText	TextType	An offense level associated with a warrant to be served, e.g., Felony or Misdemeanor.
WarrantProbableCauseText	TextType	A justification for securing a warrant.
WeightMeasure	WeightMeasureType extends MeasureType	A representation of the measurement of a weight.
Witness	WitnessType extends PersonType	Details about a person who has observed an incident. A person whose declaration under oath or affirmation is received or designated to be offered as evidence for any purpose.
WitnessAccountDescriptionText	TextType	A description or narrative of an incident as reported by the witness.
WitnessDate	j-xsd:date	A date a witness observed an incident.
WitnessID	IDType extends SuperType	A number or string identifying a witness.
WitnessLocationDescriptionText	TextType	A description of a location from which the witness observed an incident.
WitnessReportVerifiedIndicator	j-xsd:boolean	True if a witness's story has been corroborated or validated; false otherwise.
WitnessSpecialConditionText	TextType	A special condition a witness requires to testify.
WitnessTime	j-xsd:time	A time a witness observed an incident.
WitnessWillTestifyIndicator	j-xsd:boolean	True if a witness is willing to testify; false otherwise.